MILITARY SPECIFICATION SHEET

CAPACITORS, FIXED, ELECTROLYTIC (NONSOLID ELECTROLYTE), TANTALUM, (POLARIZED, SINTERED SLUG) - 85°C (VOLTAGE DERATED TO 125°C), STYLES CL66 AND CL67

This amendment forms a part of Military Specification Sheet MIL-C-3965/24A, dated 26 August 1970, and is mandatory for use by all Departments and Agencies of the Department of Defense.

Page 7

Marking requirement: Delete and substitute:

"Marking (except case size T1): in accordance with MIL-C-3965. T1 case size, mark as follows:

EXAMPLE:

CL66BB } - Type designation.
300JPG }
12345 - Source code.
7015 (TM) - Date code and trademark.

Polarity - Series of plus (+) symbols encircling positive end (see figure 1)."

Following marking requirement, insert:

"Voltage groups (85°C rated voltage):

I - - - - -	6 to 15v incl
II - - - - -	25 to 75v incl
III - - - - -	100 and 125v"

Custodians:
Army - EL
Navy - EC
Air Force - 80

Review activities:
Army - EL, MU
Navy - SH, EC
Air Force - 11, 17, 80
DSA - ES

User activities:
Army -
Navy - AS, MC, OS
Air Force - 19

Preparing activity:
Air Force - 80

Agent:
DSA - ES

(Project 5910-1014)

☆ U. S. GOVERNMENT PRINTING OFFICE: 1970-433-693/3308

FSC 5910

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:03Z
Check the source to verify that this is the current version before use.