INCH-POUND

MIL-PRF-1/1773D
18 November 2015
SUPERSEDING
MIL-PRF-1/1773C
w/AMENDMENT 1
9 August 2011

PERFORMANCE SPECIFICATION SHEET

ELECTRON TUBE, MAGNETRON
TYPE DOD-042

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the electron tube described herein shall consist of this document and MIL-PRF-1.

DESCRIPTION: Coaxial fixed frequency, 9,375 MHz ± 30 MHz, pulse type, 65-kw rated peak-power output, integral permanent magnet, air cooled.

ABSOLUTE RATINGS:

Parameter: Unit:	Ef V	If A	tk sec	tpc µs	rrv kv/µs	Pi W	ib a	VSWR	Alt ft
Maximum Minimum	14 ----	10 (surge) ----	---- 90	5.5 0.4	187 54	240 ----	19 11	1.5:1 ----	10,000 ----

ABSOLUTE RATINGS:

Parameter: Unit:	Anode T ºC	Cathode bushing T ºC	Storage ambient T ºC
Maximum Minimum	150 ---- (See note 17)	175 -55 (See note 15)	+85 -55

PHYSICAL CHARACTERISTICS:

Dimensions: Experience has shown that magnetron tubes conforming to outline drawing dimensions of figures 1, 1A, 2, 2A, 3, 3A, 4, and 4A satisfy form, fit and function interface requirements for installation within user APN-59 application systems. With qualifying activity approval alternative dimensions for selected non-interface critical requirements are permissible.

Weight: 6 pounds (approximate).

TEST CONDITIONS:

Parameter: Unit: Tolerance:	Ef V ---- 2/	tpc µs ±10%	Du ---- ----	rrv kv/µs ±10%	Ib mA dc ----
Test 1: Test 2: Test 3: Test 4: Test 5:	9.1 9.1 7.9 7.9 7.9	0.4 0.4 5.0 5.0 5.0	0.00065 0.00065 0.001 0.001 0.001	170 170 110 110 60	9.8 ---- 15 ---- ----

GENERAL:

Qualification - Required.

This specification sheet utilizes an accept on zero defect sampling plan in accordance with MIL-PRF-1, table III.

Service-life guarantee - Service-life guarantee of 2000 Hours shall be required for tube operating time.

Marking - Tubes sold under service-life guarantee shall be marked with contract number and with the number of operating (2000 hours) guaranteed.

AMSC N/A

FSC 5960

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:34Z
Check the source to verify that this is the current version before use.

TABLE I. Testing and inspection.

Inspection	Method MIL-STD-1311	Notes	Test	Conditions	Symbol	Limits		Unit
						Min	Max	
Qualification inspection								
Life test	----	7/ 13/	----	VSWR = 1.5:1 (min) with phase varying through a minimum of 0.5 λ approximately every 15 minutes	----	2,000	----	Hours
Life-test end points:								
Power levels	4250	1/	3		Po	56	----	W
Frequency	----	----	3		F	9,345	9,405	MHz
Spectrum	4308	3/ 4/ 9/	3		BW	----	2.5/tpc	MHz
Spectrum	4308	3/ 4/ 9/	3		Ratio	8	----	dB
Pulse stability	4315	9/ 9/	1 3		MP MP	---- ----	2.0 2.0	% %
	--							
Shelf life endpoints Vibration, mechanical	1032	10/	1	10 G; f = 50 Hz to 500 Hz; varied over complete range in not less than 5 minutes at uniform rate.	ΔF	----	± 0.5	MHz
Direct-interelectrode capacitance	4266	----	----	Measured between cathode terminal and mounting plate.	Cin	9	14	pF
Barometric pressure, Reduced	4028	8/	3	Pressure = 55 mm Hg absolute	----	----	----	----
Conformance Inspection, part 1								
Heater or filament current, nonoperating	4289	----	----	Ef = 12.6 V; tk = 180 seconds (min)	If	2.0	2.4	A
Pressurizing	4003	----	----	40 to 45 psia, input and output assemblies.	----	----	----	----
Power levels	4250	1/ 1/	1 3		Po Po	44 65	---- ----	W W
Spectrum	4308	3/ 4/ 11/ 3/ 4/ 12/	2 4		BW BW	---- ----	2.0/tpc 2.5/tpc	MHz MHz
Spectrum	4308	3/ 4/ 11/ 3/ 4/ 12/	2 4		Ratio Ratio	10 8	---- ----	dB dB
Pulse voltage	4306	----	3		epy	14.7	14.9	kv

See notes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:34Z
Check the source to verify that this is the current version before use.

TABLE I. Testing and inspection - Continued.

Inspection	Method MIL-STD-1311	Notes	Test	Conditions	Symbol	Limits		Unit
						Min	Max	
Conformance inspection, part 1 - Continued								
Pulse stability	4315	---- 6/	1 3		MP MP	---- ----	0.25 0.25	% %
Frequency pulling figure	4310	----	1		ΔF	----	5	MHz
Frequency	----	Note 17 on figures 1 thru 4A	3	Anode T at reference point = +100ºC ±10ºC	F	9,345	9,405	MHz
Frequency pushing Figure	4311	----	3	ib = 12 a to 15 a	ΔF/Δib	----	0.1	MHz/a
Conformance inspection, part 2								
Vibration	----	10/	----	Ef = 12.6 V; 15 G; F = 60 Hz; duration 15 minutes; no heater cathode shorts during test	----	----	----	----
Pulse stability	4315	---- ----	3 5		MP MP	---- ----	0.5 0.25	% %

See notes at end of table

1/ The tube heater shall be protected against arcing by the use of a capacitor that places a minimum capacitance of 4,000 pF across the heater directly at the input terminals.

2/ A tk of 180 seconds (minimum) with an Ef of 12.6 volts is required before test.

3/ The tube shall be operated into a transmission line with a VSWR of 1.5:1 adjusted in phase to produce maximum spectrum degradation.

4/ A suitable spectrum shall be considered one in which the major lobe has a shape such that its slope does not change sign more than once for power levels greater than the specified dB below its peak.

5/ An airflow of 15 cfm at approximately 760 mm Hg shall be directed on the cooling fins from an orifice of 2.5 inches (63.5 mm) x1.188 inches (30.18 mm). The temperature rise shall be measured at that point on the anode block as shown on figure 1 (see figures 1 through 4A, note 17).

6/ This test shall be the first one performed after 48 hours of holding period.

7/ Air cooling shall be adjusted so that the anode block runs at +150ºC, or at the maximum temperature it will reach in the absence of cooling, whichever is lower. This shall be adjusted during the test condition 3 portions of the qualification inspection and the intermittent life test cycles.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:34Z
Check the source to verify that this is the current version before use.

TABLE I. Testing and inspection - Continued.

8/ The tube shall be operated in a transmission line with a load VSWR of 1.5:1 and a variable phase. At specified pressure, there shall be no evidence of breakdown at the input or output assemblies.

9/ If during life test the tube does not meet the specified limits, it shall be recycled for an additional five cycles. At such time, the test shall be repeated. Should the tube fail the second test, it shall be considered unsatisfactory.

10/ Direction of vibration shall be in a plane perpendicular to the axis of the cathode.

11/ Measurements shall be made at 11 a and 19 a.

12/ Measurements shall be made at 12 a and 19 a.

13/ Qualification inspection life test shall be conducted with the following cycle:

Condition	Ib	Ef	Duration
Standby	----	12.6 V	3 minutes
Test 1	9.8 mA	9.1 V	15 minutes
Test 3	15.0 mA	7.9 V	30 minutes
Off	----	0	12 minutes

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:34Z
Check the source to verify that this is the current version before use.




FIGURE 1. Outline drawing of electron tube type DOD-042 (front view).

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:34Z
Check the source to verify that this is the current version before use.




FIGURE 1A. Alternate outline drawing of electron tube type DOD-042 (front view).

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:34Z
Check the source to verify that this is the current version before use.




FIGURE 2. Outline drawing of electron tube type DOD-042 (detail enlarged).

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:34Z
Check the source to verify that this is the current version before use.




FIGURE 2A. Alternate outline drawing of electron tube type DOD-042 (detail enlarged).

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:34Z
Check the source to verify that this is the current version before use.

Figure	Ltr	Dimensions				Notes
		Inches		Millimeters		
Conformance inspection, part 1						
		Min	Max	Min	Max	
1, 1A	O	1.250	1.280	31.75	32.51	5
1, 1A	R	.732	.742	18.59	18.85	
1, 1A	T	1.470	1.478	37.34	37.54	
1, 1A	Z	.594	.656	15.09	16.66	
1, 1A	AD	1.348	1.356	32.24	34.44	
1	AE	.671	.681	17.04	17.30	
1, 1A	AL	2.094	2.219	53.19	56.36	
2, 2A	BC	.115	.135	2.92	3.43	11
2, 2A	BD	.610	.650	15.49	16.51	
2, 2A	BF	.125	.187	3.18	4.75	
2, 2A	BG	.164	.174	4.17	4.42	
2, 2A	BH	.234	.266	5.94	6.76	
2, 2A	BJ	.532	.545	13.51	13.84	
2, 2A	BK	.825	.838	20.96	21.29	
1, 1A	BM	1.386	1.426	35.20	36.22	
Conformance inspection, part 2						
1, 1A	A	----	5.938	----	150.83	
1, 1A	B	----	3.156	----	80.16	
1, 1A	M	---	4.250	----	107.95	
1, 1A	N	----	1.688	----	42.88	
1	U	----	1.438	----	36.53	
1, 1A	AM	1.250	----	31.75	----	
2	BE	.125	----	3.18	----	
1	BN	----	2.938	----	74.63	
2, 2A	BT	.750	----	19.05	----	
2, 2A	BU	.516	----	13.11	----	
2, 2A	BV	----	.200	----	5.08	
1, 1A	P	---	1.830	---	46.48	
1, 1A	AF	---	1.830	---	46.48	
Reference dimensions						
1, 1A	X	0.497		12.62		
1 1A	Y	1.625 1.516		41.28 38.51		
1, 1A	AJ	.164-32 UNC-2B				
1, 1A	AK	1.156		29.36		
1, 1A	AN	1.265		32.13		4
2 2A	AZ	1.125 1.100		28.58 27.94		
2 2A	BA	0.750 0.772		19.05 19.61		
2 2A	BX	1.000 1.125		25.40 28.57		15

FIGURES 1, 1A, 2, and 2A. Outline drawing of electron tube type DOD-042.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:34Z
Check the source to verify that this is the current version before use.




FIGURE 3. Outline drawing of electron tube type DOD-042 (bottom view).

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:34Z
Check the source to verify that this is the current version before use.




FIGURE 3A. Alternate outline drawing of electron tube type DOD-042 (bottom view).

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:34Z
Check the source to verify that this is the current version before use.

Figure	Ltr	Dimensions				Notes
		Inches		Millimeters		
Conformance inspection, part 1						
		Min	Max	Min	Max	
3, 3A	AP	.990	1.040	25.15	26.42	5
3, 3A	AV	2.771	2.791	70.38	70.89	
3, 3A	AO	2.521	2.541	64.03	64.54	
Conformance inspection, part 2						
3, 3A	C	----	3.625	----	92.08	
3, 3A	AR	----	.594	----	15.09	
3, 3A	AS	----	.422	----	10.72	
3, 3A	AX	1.875	----	47.62	----	6
3, 3A	AY	----	3.483	----	87.33	
3, 3A	BB	----	3.203	----	81.36	
Reference dimensions						
3, 3A	AQ	.375		9.52		
3, 3A	AU	1.391		35.33		4
3, 3A	CD	.411		10.44		5

FIGURES 3 and 3A. Outline drawing of electron tube type DOD-042 (bottom view).

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:34Z
Check the source to verify that this is the current version before use.




FIGURE 4. Outline drawing of electron tube type DOD-042 (top view).

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:34Z
Check the source to verify that this is the current version before use.




FIGURE 4A. Alternate outline drawing of electron tube type DOD-042 (top view).

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:34Z
Check the source to verify that this is the current version before use.

Figure	Ltr	Dimensions				Notes
		Inches		Millimeters		
Conformance inspection, part 1						
		Min	Max	Min	Max	
4	BS	1.334	1.438	33.88	36.53	
4, 4A	BL	.276	.286	7.01	7.26	
Conformance inspection, part 2						
4	BP	---	2.875	---	73.02	
4	BQ	---	.625	---	15.88	
4, 4A	BR	.031R	---	0.79	---	
Reference dimensions						
Nominal						
4, 4A	K	.500		12.70		
4, 4A	L	.250		6.35		
4	BW	.138-32 UNC-2A				

NOTES:

1. If these tests have been previously performed by the tube manufacturer, and if the material, manufacturing process, and test requirements are the same as when the tests were performed, the subject test(s) need not be performed.
2. All metal surfaces shall be corrosion resistant for the lifetime of the magnetron. Surface finishes may be used on metals except on surfaces designated S and D. Surface finishes shall prevent galvanic corrosion and prevent electrical contact (directly or through moist conductive media) between dissimilar metals. Surface finishes shall themselves meet and enable the magnetron to meet all interface and performance requirements. Surface S shall consist of or be plated with material providing electrical conductivity and corrosion resistance equivalent to that of gold, silver, nickel or bright alloy plating. If nickel plating is required, it is recommended that it be used only when other platings cannot meet performance requirements. Surface S plating shall meet and enable the magnetron to meet all interface and performance requirements.
3. Hermetic connections may be made to surface D.
4. Axis of cathode terminal shall occupy specified location within .047 inch (1.19 mm) radius. Note 7 shall apply.
5. Limits include angular and lateral deviations.
6. Diameter AX shall meet interface requirements for flatness and parallelism to reference plane A within .010 inch (0.25 mm) over the extent of AX. Surface flatness and parallelism shall enable the interface to meet hermetic seal requirements and enable the magnetron to meet all performance requirements.
7. Diameter Y shall meet interface requirements for flatness of .005 inch (0.13 mm) over the extent of Y. Surface flatness shall enable the interface to meet hermetic seal requirements and enable the magnetron to meet all performance requirements.
8. To satisfy system interface mating requirements, any portion of the magnetron assembly which extends below reference plane A shall be within .625 inch (15.88 mm) radius of the specified axis of input. Input concentricity is an essential interface requirement.
9. See note 10. Warning: In handling and mounting the magnetron care shall be exercised to prevent demagnetization. Neither ferromagnetic materials nor energized magnets shall be brought within two inches of the magnetron or its magnet.
10. Manufacturers code designation and tube serial number shall appear within this area.
11. Clamping shall be confined to this area.
12. Heater terminal and cathode terminal shall be concentric within .010 inch (0.25 mm).
13. Protective covers shall be provided with tubes.
14. Reference planes A, B, and C are mutually perpendicular.
15. Reference point for cathode temperature measurements. Located on the diameter, dimension BX.
16. Materials or their surface plating shall satisfy thermal coefficient of expansion compatibility requirements with ceramic materials they contact and shall be corrosion resistant for the life of the magnetron. Surface plating shall provide electrical conductivity and corrosion resistance equivalent to gold, silver or nickel plate over the full extent of input connector penetration. If nickel plating is required, it is recommended that it be used only when other platings cannot meet performance requirements. Surface plating shall meet and enable the magnetron to meet all interface and performance requirements.
17. Reference point for anode temperature measurements. Located on body near output section. (see 5/)
18. Magnet lugs, when included, shall satisfy interface mating requirements such that extremity of magnet lugs shall coincide with reference plane C within .094 inch (2.39 mm).
19. For vibration tests, planes of vibration shall be reference planes A, B, and C.

FIGURES 1 THROUGH 4A. Outline drawing of electron tube type DOD-042.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:34Z
Check the source to verify that this is the current version before use.

Referenced documents. In addition to MIL-PRF-1, this document references the following:
MIL-STD-1311

The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA-CC

Preparing activity:
DLA - CC

(Project 5960-2016-002)

Review activities:
Army - CR4
Navy - AS, CG, OS, SH
Air Force - 84, 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:34Z
Check the source to verify that this is the current version before use.