MIL-C-52765D(ME)
AMENDMENT 1
5 August 1987

MILITARY SPECIFICATION

CAMOUFLAGE SCREENING SUPPORT SYSTEMS

This amendment forms a part of MIL-C-52765D(ME), dated 15 August 1985, and is approved for use within the USA Belvoir Research, Development, and Engineering Center, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 11

4.5.2.1.3.2.2, line 7, delete "All components shall be assembled in their normal way of operation" and substitute "All components shall remain assembled in their normal way of operation at the moment of impact."

Add the following new paragraph:

"4.5.2.1.3.2.3 Single pole slant drop. A type I aluminum support pole shall be dropped three times onto a 3/4-inch steel plate in such a manner that the sleeve end (female) of the support pole strikes the steel plate at approximately a 45-degree angle. The pole shall be dropped from such a height that the sleeve end of the pole falls at least 4 feet. The pole shall not be guided in that the pole shall be unrestrained when it strikes the steel plate. The pole shall be rotated 120 degrees between each drop. Nonconformance with 3.4.3.2 shall constitute failure of this test."

Custodian:
Army - ME

Preparing activity:
Army - ME

Project 1080-A070

AMSC N/A FSC 1080
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:32Z
Check the source to verify that this is the current version before use.