MILITARY SPECIFICATION

GENERATOR SETS, GASOLINE ENGINE DRIVEN, 0.5KW THRU 10KW,

60 HERTZ, 400 HERTZ AND 28 VOLT DIRECT CURRENT,

TYPE I (TACTICAL), CLASS 2 (UTILITY)

GENERAL SPECIFICATION FOR

This supplement forms a part of military specification MIL-G-52732B dated 27 September 1985.

Specification Sheet	Size	Mode	Model Number	NSN
MIL-G-52732/1	0.5	III (60 Hz)	MEP-014A	6115-00-923-4469
MIL-G-52732/2	0.5	II (400 Hz)	MEP-019A	6115-00-940-7862
MIL-G-52732/3	0.5	IV (28 VDC)	MEP-024A	6115-00-940-7867
MIL-G-52732/4	1.5	III (60 Hz)	MEP-015A	6115-00-889-1446
MIL-G-52732/5	1.5	IV (28 VDC)	MEP-025A	6115-00-017-8236
MIL-G-52732/6	3	III (60 Hz)	MEP-016A	6115-00-017-8237
MIL-G-52732/7	3	II (400 Hz)	MEP-021A	6115-00-017-8238
MIL-G-52732/8	3	IV (28 VDC)	MEP-026A	6115-00-017-8239
MIL-G-52732/9	5	III (60 Hz)	MEP-017A	6115-00-017-8240
MIL-G-52732/10	5	II (400 Hz)	MEP-022A	6115-00-017-8241
MIL-G-52732/11	10	III (60 Hz)	MEP-018A	6115-00-889-1447
MIL-G-52732/12	10	II (400 Hz)	MEP-023A	6115-00-926-0843

Preparing activity:
Army - ME

Project 6115-0236

FSC 6115

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:31Z
Check the source to verify that this is the current version before use.