FED SUP CLASS
5340

FAST PIN




TABLE I. DASH NUMBERS AND DIMENSIONS.

DASH NUMBER	NOMINAL SIZE A	WIDTH B	PAD LENGTH C	PAD WIDTH D	THICKNESS MIN T	NUMBER OF SCREW HOLES	1/ SIZE OF SCREWS (REF)
LIGHT							
2	3.00	1.09	2.25	.75	.065	6	#6 X 3/4
HEAVY							
12	4.00	1.31	2.87	.87	.072	6	#8 X 3/4
14	6.00	1.56	3.50	1.25	.087	7	#9 X 7/8
EXTRA HEAVY							
22	8.00	2.62	5.50	2.12	.125	9	#12 X 1-1/2
24	10.00	3.50	7.00	2.25	.139	9	#14 X 1-1/2
26	12.00	4.00	7.75	2.75	.156	10	#16 X 1-1/2
28	16.00	4.25	7.75	2.75	.156	11	#16 X 1-1/2

1/ SEE NOTE 1

(B) ENTIRE STANDARD REVISED

APPROVED 24 FEB 61 REVISED (B) 21 DEC 87

P.A.	INTERNATIONAL INTEREST	TITLE	MILITARY STANDARD
ARMY – AR Other Cust NAVY – YD AIR FORCE-99		HINGE, TEE	MS27970
PROCUREMENT SPECIFICATION ANSI A156.20	SUPERSEDES SHDX1, SHDX2, MQ126A, MQ126B		PAGE 1 OF 2

DD FORM 672-1 (COORDINATED)

5340-1724

USER ACTIVITIES:

REVIEWER ACTIVITIES:
NAVY – SH
AIR FORCE – 82
DLA – IS

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

AMSC N/A

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T16:54Z
Check the source to verify that this is the current version before use.

FED SUP CLASS
5340

REQUIREMENTS:

1. MATERIAL:

   BODY: STEEL, IN ACCORDANCE WITH ASTM A506 LOW CARBON, COLD ROLLED.

   PIN: BRASS, IN ACCORDANCE WITH QQ-B-626, COMPOSITION 11, HARD OR CORROSION-RESISTANT STEEL, IN ACCORDANCE WITH ASTM A666.

2. PROTECTIVE COATING: ZINC COATED, IN ACCORDANCE WITH ASTM B633 Fe/Zn13, TYPE II OR MIL-C-81562, TYPE II, CLASS 2.

3. PART NUMBER: THE MS PART NUMBER CONSISTS OF THE MS NUMBER, PLUS THE DASH NUMBER TAKEN FROM TABLE I.

   EXAMPLE: MS27970-2

   DASH NUMBER

   BASIC MS NUMBER

   MS27970-2 - INDICATES HINGE, TEE, STEEL, NOMINAL SIZE 3.00, WIDTH B, 1.09, LENGTH, 2.25, WIDTH D, .75, THICKNESS.

NOTES:

1. SCREWS: HINGES ARE FURNISHED WITH WOOD SCREWS. THE SIZES SPECIFIED ARE THOSE NORMALLY FURNISHED BY THE SUPPLIER.
2. TOLERANCE: SLIGHT VARIATION IN DIMENSIONS TO CONFORM TO MANUFACTURER'S PATTERNS IS PERMISSIBLE.
3. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.
4. IN THE EVENT OF A CONFLICT BETWEEN THE TEXT OF THIS STANDARD AND THE REFERENCES CITED HEREIN, THE TEXT OF THIS STANDARD SHALL TAKE PRECEDENCE.
5. REFERENCED GOVERNMENT (OR NON-GOVERNMENT) DOCUMENTS OF THE ISSUE LISTED IN THAT ISSUE OF THE DEPARTMENT OF DEFENSE INDEX OF SPECIFICATIONS AND STANDARDS (DODISS) SPECIFIED IN THE SOLICITATION, FORM A PART OF THIS STANDARD TO THE EXTENT SPECIFIED HEREIN.

APPROVED 24 FEB 61 REVISED (B) FOR CHANGES SEE PAGES 1 AND 2

USER ACTIVITIES:

REVIEWER ACTIVITIES:
NAVY – SH
AIR FORCE – 82
DLA – IS

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

PA	INTERNATIONAL INTEREST	TITLE	MILITARY STANDARD
ARMY – AR Other Cust NAVY – YD AIR FORCE-99		HINGE, TEE	MS27970
PROCUREMENT SPECIFICATION ANSI A156.20	SUPERSEDES SHDX1, SHDX2, MQ126A, MQ126B		PAGE 2 OF 2

DD FORM 1 MAY 1 672-1 (COORDINATED) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE 5340-1724

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T16:54Z
Check the source to verify that this is the current version before use.