
MILITARY SPECIFICATION SHEET

SEAL RING, COPPER, METRIC

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the seal described herein shall consist of this specification and the latest issue of DOD-S-70338.



NOTES:

1. All Dimensions are in Millimeters.

FIGURE 1. SEAL RING, COPPER, METRIC.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:24Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

1. Material: Copper shall be as specified in DOD-S-70338.

2. Part number: The part number consists of the letter "D" the basic number of this specification sheet and a dash number taken from Table I.

Example: D70338/1-01
- 01 — Dash number
- D70338/1 — Specification sheet number

D70338/1-01 indicates - Seal Ring, Copper, Metric
3.5 x 6 Nominal size;
3.7 Inside Diameter; 5.9
Outside Diameter; Height 1

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:24Z
Check the source to verify that this is the current version before use.

TABLE I. Dasn numbers and dimensions.

Dash Number	Nominal Size	ØA +0.3 0	ØB 0 -0.2	H Height	R Radius	Recommended for use with 1/		Weight 2/
						External Thread Size	Internal Thread Size	
01	3.5 X 6	3.7	5.9	1.0 ±0.2	4.0 ±0.6		M8X1	0.13
02	4 X 8	4.2	7.9					0.27
03	5 X 7.5	5.2	7.4				M10X1	0.18
04	5.5 X 8	5.7	7.9				M10X1	0.19
05	6.5 X 9.5	6.7	9.4				M12X1.5	0.27
06	8 X 11.5	8.2	11.4			M8X1	M14X1.5	0.38
07	8 X 12	8.2	11.9			M8X1		0.45
08	10 X 13.5	10.2	13.4			M10X1	M16X1.5	0.48
09	10 X 14	10.2	13.9			M10X1		0.54
10	12 X 15.5	12.2	15.4	1.5 ±0.2	4.0 ±0.6	M12X1.5	M18X1.5	0.83
11	12 X 16	12.2	15.9			M12X1.5		0.99
12	14 X 18	14.2	17.9			M14X1.5		1.12
13	15 X 19	15.2	18.9				M22X1.5	1.19
14	16 X 20	16.2	19.9			M16X1.5		1.26
15	17 X 21	17.2	20.9				M24X1.5	1.34
16	18 X 22	18.2	21.9			M18X1.5	M26X1.5	1.40
17	20 X 24	20.2	23.9			M20X1.5	M27X2	1.54
18	21 X 26	21.2	25.9				M30X2	2.06
19	22 X 27	22.2	26.9			M22X1.5	M30X1.5 M30X2	2.17
20	23 X 28	23.3	27.9	2.0 ±0.3	6.0 ±0.9			3.12
21	24 X 29	24.3	28.9			M24X1.5	M33X2	3.25

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:24Z
Check the source to verify that this is the current version before use.

TABLE I. Dash numbers and dimensions - Continued.

Dash Number	Nominal Size	ØA +0.3 0	ØB 0 -0.2	H Height	R Radius	Recommended for use with 1/		Weight 2/
						External Thread Size	Internal Thread Size	
22	25 X 30	25.3	29.9				M33X1.5	3.36
23	26 X 31	26.3	30.9			M26X1.5		3.45
24	26 X 32	26.3	31.9			M26X1.5	M36X2	4.10
25	27 X 32	27.3	31.9			M27X2	M36X2	3.60
26	28 X 33	28.3	32.9				M36X2	3.71
27	30 X 36	30.3	35.9			M30X1.5 M30X2	M39X2 M42X2	4.69
28	32 X 38	32.3	37.9				M42X2	4.94
29	33 X 39	33.3	38.9			M33X2	M42X1.5 M42X2 M45X2	5.29
30	35 X 41	35.3	40.9				M45X2	5.38
31	36 X 42	36.3	41.9	2.0 ±0.3	6.0 ±0.9	M36X1.5 M36X2	M45X1.5 M45X2 M48X2	5.71
32	38 X 44	38.3	43.9			M38X1.5	M48X2	6.05
33	39 X 46	39.3	45.9			M39X2		7.06
34	40 X 47	40.3	46.9				M52X2	7.40
35	42 X 49	42.3	48.9			M42X1.5 M42X2	M52X1.5 M52X2	7.62
36	44 X 51	44.3	50.9					7.95
37	45 X 52	45.3	51.9			M45X1.5 M45X2		8.10
38	48 X 55	48.3	54.9			M48X1.5 M48X2		8.55
39	50 X 57	50.3	56.9					8.87

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:24Z
Check the source to verify that this is the current version before use.

TABLE I. Dash numbers and dimensions - Continued.

Dash Number	Nominal Size	∅A +0.5 0	∅B 0 -0.3	H Height	R Radius	Recommended for use with 1/ External Thread Size	Recommended for use with 1/ Internal Thread Size	Weight 2/
40	52 X 60	52.5	59.8			M52X1.5 M52X2		12.90
41	54 X 62	54.5	61.8					13.20
42	55 X 63	55.5	62.8					13.50
43	56 X 64	56.5	63.8			M56X2		13.80
44	58 X 66	58.5	65.8					14.30
45	60 X 68	60.5	67.8			M60X2		14.60
46	64 X 72	64.5	71.8			M64X2		15.60
47	65 X 74	65.5	73.8			M65X2		18.00
48	70 X 79	70.5	78.8					19.50
49	75 X 84	75.5	83.8					21.50
50	78 X 88	78.5	87.8	2.5 ±0.4	10 ±1	M78X2		24.60
51	80 X 90	80.7	89.8					25.20
52	85 X 95	85.7	94.8					25.90
53	90 X 100	90.7	99.8					27.60
54	95 X 105	95.7	104.8					28.90
55	100 X 110	100.7	109.8					30.10
56	105 X 115	105.7	114.8					31.60
57	110 X 120	110.7	119.8					33.10
58	115 X 125	115.7	124.8					34.80
59	120 X 130	120.7	129.8					36.00
60	125 X 135	125.7	134.8					37.40

1/ Empty blocks in the "recommended for use with" column indicate that, for the nominal size, no thread is applicable.

2/ Weight = Kg/1000 pieces; calculated using a density of 8.9 Kg/dm^3 for copper.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:24Z
Check the source to verify that this is the current version before use.

Custodians:
Army - AR
Navy - SH
Air Force - 99

Review activities:
Army - MI, MR
Navy - OS
Air Force - 82
DLA - IS

User activities:
Army - AT, AV, GL, ME
Navy - AS, YD
Air Force - 68

Civil agencies coordinating activities:
GSA - FSS

Preparing activity:
Army - AR

Agent :
DLA - IS

(Project 5330-0686)

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:24Z
Check the source to verify that this is the current version before use.