MILITARY SPECIFICATION

CASE SECTION, BALLISTIC, REAR, TRAINING

1. SCOPE

1.1 This specification covers requirements, quality assurance provisions, and the preparation for delivery criteria for one type of case section, entitled Case Section, Ballistic, Rear, Training, which is utilized for personnel training on the Honest John warhead section.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-1169	- Packaging, Packing and Marking for Shipment of Inert Ammunition Components.

DRAWINGS

ORDNANCE CORPS

8813618	- Ring, Adapter.
8821952	- Case Section, Ballistic, Rear, Training.
EL-8842311	- Equipment List.

PROCESS SPECIFICATION

PICATINNY ARSENAL

RPS-R-116	- Riveting, General Specification for.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The case section shall comply with all requirements specified on the drawing (dwg) 8821952, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3.3 Static load. The case section assembly shall be capable of supporting a 960 pound static load without evidence of cracking, distortion or other physical damage when tested as specified in 4.3.1.

3.4 Riveting. Riveting shall be as specified in RPS-R-116.

3.5 Workmanship.

3.5.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.5.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.5.3 Burrs. Parts shall be free from burrs.

3.5.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.5.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

4.2 Quality conformance inspection.

4.2.1 Lot formation.

4.2.1.1 Production lot. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision.

4.2.1.2 Inspection lot. A lot or batch and its formation, size, and presentation is described in MIL-STD-105, Section 5. Accordingly, a lot shall mean an inspection lot and a batch shall mean an inspection batch for the purpose of this specification. The manner in which each inspection lot or batch is to be presented and identified by the contractor, shall be designated or approved by the Government representative.

4.2.2 Product inspection examination. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table (see Table I and Table II), and inspected for all characteristics in the applicable classification. Any characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Table I
Major Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

Table II
Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-9	all	14-16	12	28-33	16	77-121	20
10	9	17-18	13	34-41	17	122-273	21
11	10	19-22	14	42-54	18	over 273	22
12-13	11	23-27	15	55-76	19		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

4.2.2.1 Classification of characteristics (see 3.2). Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.2.2.1.1 Ring, adapter (see dwg 8813618 covering a detail of dwg 8821952).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Incorrect bolt circle diameter (both flanges)	Gage
102.	Perpendicularity of flange surfaces	Gage
Minor:		
201.	Marking missing, incorrect or unidentifiable	Visual
202.	Evidence of poor workmanship (see 3.5)	Visual

4.2.2.1.2 Case section, ballistics, rear, training (see dwg 8821952).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Bolt circle not concentric to skin surface	Gage
102.	Rivets loose or cracked (see 3.4)	Visual/Manual
103.	Insert loose or missing	Visual/Manual
Minor:		
201.	Markings missing, incorrect or unidentifiable	Visual
202.	Evidence of poor workmanship (see 3.5)	Visual

4.2.2.1.3 Preparation for delivery (see 5).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Preservation, packaging and packing not in accordance with MIL-STD-1169	Visual
102.	Marking not in accordance with MIL-STD-1169	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

Minor:

201. Evidence of poor workmanship (see 3.5).....Visual

4.2.3 Testing. The following test shall be performed:

Test	Test Classification
a. Static load	Major

This test is not considered destructive.

4.2.3.1 Static load. Each case section shall be tested in accordance with 4.3.1. If any item fails to comply with 3.3, the item shall be rejected and removed from the lot.

4.2.4 Acceptance inspection equipment.

4.2.4.1 Major characteristics and tests. Inspection and testing shall be performed with the acceptance inspection equipment, operating instructions, and calibration instructions specified on the Equipment Lists (EL) (see EL-8842311). When either of the conditions listed below exist, the contractor shall design required equipment or specify suitable commercial equipment and obtain approval prior to use on the contract.

a. Any deviation from equipment or procedures specified on the EL is desired (see 6.3).
b. The code "CD" is listed in the "Part or Identifying Number" column on the EL (see 6.1.2).

4.2.4.2 Minor characteristics and tests. Acceptance inspection equipment for minor characteristics is not specified on ELs. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for minor classification inspection shall be approved by the Government representative authorized by the procuring agency.

4.3 Test methods. The tolerances specified herein are absolute with no allowance for test equipment inaccuracy. The tolerances used by the manufacturer shall be equal to the absolute tolerances less the accuracy tolerances of the test equipment used.

4.3.1 Static load. A static load of 960 pounds shall be applied to one end of the case section assembly with the other end resting on a flat surface. The load shall be applied for a period of one minute and then removed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.1.1 Level A. The case section shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169(MU).

5.1.2 Level C. The case section shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169(MU).

5.2 Packing.

5.2.1 Levels A and C. The case section shall be packed in accordance with the applicable instructions contained in MIL-STD-1169(MU).

5.3 Marking. Marking shall be in accordance with MIL-STD-1169(MU).

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

6.1.1 Procurement requirements.

a. Title, number, and date of this specification.
b. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.1.2 Contract data requirements (see 4.2.4.1). Data specified in 4.2.4.1 will be delivered as identified on a numbered DD Form 1664 when required on a DD Form 1423 incorporated in the contract.

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment (see 4.2.4.1). The contractor shall obtain approval from the Commander, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SARPA-QA-N-I.

6.4 Supersession data. This specification supersedes the requirements of Purchase Description PA-PD-1812 dated 25 August 1960 with Amendment 2 dated 15 September 1964.

Custodian:
Army - PA

Preparing activity:
Army - PA

Project No. 1115-A050

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.