MIL-G-82405(CG)
3 October 1966
Superseding
MIL-G-82405(CG)
6 May 1966

MILITARY SPECIFICATION

GLOVE, CLOTH, JERSEY, WORK, POLYVINYL IMPREGNATED

1. SCOPE

1.1 Scope. This specification covers two types of men's jersey fabric, water-repellent, oil resistant, non-slip, vinyl impregnated elastic wrist gloves.

1.2 Classification. The gloves shall be of the following types and sizes as specified (see 6.2):

Type I— Grey back
  Class 1 — Medium
  Class 2 — Large
Type II —Orange back
  Class 1 — Medium
  Class 2 — Large

2. APPLICABLE DOCUMENTS

2.1 The following specifications and standards, of the issues in effect on date of invitations for bids, form a part of this specification:

SPECIFICATIONS

Federal

V-T-276 - Thread, Cotton
UU-P-268 - Paper, Kraft, Untreated, Wrapping
CCC-T-191 - Textile Test Methods
DDD-L-20 - Label; For Clothing, Equipage and Tentage (General Use)

Military

MIL-B-17757 - Boxes, Fiber, Corrugated (Modular sizes)

STANDARDS

Federal

FED-STD-102 - Preservation, Packaging and Packing Levels
FED-STD-751 - Stitches, Seams and Stitching

Military

MIL-STD-105 - Sampling Procedures and Tables for Inspections by Attributes
MIL-STD-129 - Marking for Shipment and Storage

FSC 8415

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:06Z
Check the source to verify that this is the current version before use.

Uniform Freight Classification Rules

(Copies of Military Specification and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Guide Sample. Samples when furnished are solely for guidance and information to contractors. Variation from this specification may appear in the sample in which case this specification shall govern.

3.2 MATERIAL

3.2.1 Glove Fabric (Types I and II). A single napped jersey shall be used. It shall be 12.00 oz./sq. yd. in weight, ± .30 oz. The fabric shall be knife coated with a polyvinyl chloride compound.

3.2.2 Polyvinyl Chloride Conting (Types I and II). The gloves shall be coated with a properly compounded polyvinyl chloride.

3.2.3 Coated Fabric Weight.(Types I and II). The total weight of fabric, after coating, shall be within specified ranges of 24.75 ozs./sq. yd. ± .90 ozs. for the front of the glove and 19.20 ozs./sq. yd. ± .75 for the back of the glove.

3.2.4 Elastic (Types I and II). A white heat resistant elastic 1/4 inch wide and 3-3/4 inch long shall be applied to each glove using a zig-zag stitch.

3.3 DESIGN AND CONSTRUCTION

3.3.1 Pattern (Types I and II). A Gunn-cut pattern with a wing thumb, shall be used. The pattern is composed of four parts, which includes the palm, thumb, fingers and back.

3.3.2 Seaming (Types I and II). All seam widths shall be 1/8 inch ± 1/32 inch. All seams shall be in.

3.3.3 Stitching (Types I and II). The No. 401, double lock stitch, as specified in Federal Standard No. 751, shall be used for stitching all parts together.

3.3.4 Binding. A black bias binding, 1-1/8 inch flat, shall be applied to each Class I glove. A grey binding, 1-1/8 inch flat, shall be applied to each Class II glove.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:06Z
Check the source to verify that this is the current version before use.

3.3.5 Dimensions Type I and II -

3.3.5.1 Length (Classes 1 and 2). The total finished length, measured from tip of second finger to bottom of glove, shall be 9-1/2 inches ± 1/4 inch.

3.3.5.2 Width (Class 1). The width of the glove shall be 5 inches ± 1/4 inch measured in flat state of thumb crotch.

3.3.5.3 Width (Class 2). The width of the glove shall be 5-1/4 inch ± 1/4 inch measured in flat state of thumb crotch.

3.3.6 Sizes. The sizes shall be designated by the measurement across the palm at the base of the knuckles, and shall be in accordance with paragraph 3.3.5. (see 6.2)

3.3.7 Printing on Gloves. The right hand palm of each pair of first grade gloves shall have the size printed in black ink.

3.3.8 Welting. A piece of sheeting, double coated with red vinyl, and slit, shall be used as reinforcement welt in the thumb crotch area. The length of welting shall be 1-1/2 inch ± 1/4 inch.

3.3.9 Forming. Each glove shall be loaded on a heated form to shape the glove properly.

4. QUALITY ASSURANCE PROVISIONS

4.1 Unless otherwise specified herein the supplier is responsible for the performance of all inspection requirements prior to submission for Government inspection and acceptance. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. Inspection records of the examinations and tests shall be kept complete and available to the Government as specified in the contract or order.

4.2 Sampling for acceptance inspection-

4.2.1 Inspection lot. All pairs of gloves of the same type and size offered for delivery at one time shall be considered a lot for purposes of acceptance inspection.

4.2.2 Sampling for visual and dimensional examination. A random sample of pairs of gloves shall be selected from each lot offered for inspection in accordance with Standard MIL-STD-105 at inspection level II. The acceptable quality level (AQL) shall be equal to 2.5 percent defective.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:06Z
Check the source to verify that this is the current version before use.

4.2.3 Sampling for acceptance inspection. A random sample of pairs of gloves shall be selected from each inspection lot offered for inspection in accordance with appendix to Standard MIL-STD-105 at inspection level S-2, and shall be subjected to the tests specified in 4.4. If any pair of gloves fail any test, the lot represented by the sample shall be rejected.

4.3 Visual and dimensional examination. Each of the sample pairs of gloves selected in accordance with 4.2.2 shall be visually and dimensionally examined to verify compliance with this specification. Any pair of gloves in the sample containing one or more visual or dimensional defects shall be rejected.

4.4 Test procedures.

4.4.1 Abrasion Resistance. Using a Taber Abrader machine with H-18 wheels, two 1,000 gram weights and vacuum system; the charcoal impregnated fabric shall withstand a minimum of 1,300 revolutions; both the grey and orange impregnated fabric shall withstand a minimum of 500 revolutions. None of the fabrics shall show breakage under the specified test.

4.4.2 Flexibility. Using the Fabric Development tester, the drape shall be a maximum of 1.60 and the flex shall be a maximum of 38.0.

4.4.3 Testing Reports. The contractor shall submit a certificate of compliance with the requirements specified in paragraph 3, and that the product has passed the tests specified in paragraphs 4.4.1 and 4.4.2.

5. PREPARATION FOR DELIVERY

5.1 Packaging. All packaging shall be in accordance with good commercial practices.

6. NOTES

6.1 Intended Use. The gloves covered by this specfication are primarily work gloves for use by Coast Guard personnel.

6.2 Ordering Data. Procurement documents should specify the following:

a. Title, number and date of this specification

b. Type (see 1.2), and size (see 3.3.6)

c. Availability of sample (see 3.1)

Preparing Activity:
U. S. Coast Guard

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:06Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

SPECIFICATION

ORGANIZATION *(Of submitter)* | CITY AND STATE

CONTRACT NO. | QUANTITY OF ITEMS PROCURED | DOLLAR AMOUNT $

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)* | DATE

DD FORM 1 APR 63 1426 REPLACES NAVSHIPS FORM 4863, WHICH IS OBSOLETE PLATE NO. 15419

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:06Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

COMMANDANT
U.S. COAST GUARD HEADQUARTERS
STATION C-19
WASHINGTON, D.C. 20226

FOLD

PLATE NO. 15419 (BACK)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:06Z
Check the source to verify that this is the current version before use.