MIL-R-52065B
23 January 1978
SUPERSEDING
MIL-R-52065A
8 April 1969

# MILITARY SPECIFICATION

## RAIL ANCHOR, RAILWAY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

## 1. SCOPE

1.1 This specification covers rail anchors to resist the longitudinal movement of rails under traffic and to hold the rail in a fixed position with respect to the tie.

## 2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

| | |
|---|---|
| QQ-S-781 | - Strapping, Steel, and Seals. |
| PPP-B-601 | - Boxes, Wood, Cleated-Plywood. |

MILITARY

| | |
|---|---|
| MIL-R-3518 | - Rails, Tee, Railway. |

FSC 2250

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Mobility Equipment Research and Development Command, ATTN: DRDME-DS, Fort Belvoir, VA 22060 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:06Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

| | |
|---|---|
| MIL-STD-105 | - Sampling Procedures and Tables for Inspection by Attributes. |
| MIL-STD-129 | - Marking for Shipment and Storage. |
| MIL-STD-130 | - Identification Marking of US Military Property. |

(Copies of specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

A576 - Special Quality Hot Rolled Carbon Steel Bars.
E8 - Tension Testing of Metallic Materials.
E18 - Rockwell Hardness and Rockwell Superficial Hardness of Metallic Materials, Test For.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, ATTN: Tariff Publishing Officer, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., ATTN: Traffic Department, 1616 P Street NW, Washington, DC 20036.)



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:06Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Description. Rail anchors shall be one-piece type, and be designed and fabricated so that they may be applied, removed, and reapplied to the rail base without breakage, significant loss in holding power or other damage that could impair serviceability. Rail anchors shall be designed so they may be applied with a flat-faced sledge hammer, automatic anchor driving machine, or similar tool normally used in trackwork.

3.2 Material. Material shall be as specified herein (see 6.3).

3.2.1 Steel. Steel shall conform to ASTM A576.

3.2.1.1 Elongation. Steel used in the fabrication of rail anchors shall have a percentage elongation of not less than 8 percent in a 2-inch (50-mm) gage length when tested in accordance with ASTM E8.

3.2.1.2 Hardness. Finished rail anchors shall have a hardness in the range of 38 to 44 Rockwell C-scale, when tested in accordance with ASTM E18.

3.3 Sizes. Rail anchors shall be of the appropriate size for use with rails conforming to MIL-R-3518, size as specified.

3.4 Identification marking. Rail anchors shall be identified in accordance with MIL-STD-130.

3.5 Workmanship. All parts of the rail anchor shall be clean and free from sand, dirt, fins, pits, loose scale, and other harmful, extraneous material. External surfaces shall be sufficiently free of burrs, sharp edges, and corners so as to preclude injury in handling. Gloves should be worn when handling.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsiblity for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:06Z
Check the source to verify that this is the current version before use.

4.1.1 Component and material inspection. The contractor is responsible for insuring that components and materials used are manufactured, examined, and tested in accordance with referenced specifications and standards.

4.2 Quality conformance inspection.

4.2.1 Sampling. Sampling for examination and tests shall be in accordance with MIL-STD-105.

4.2.2 Examination. Samples selected in accordance with 4.2.1 shall be examined as specified in 4.3.1. AQL shall be 2.5 percent defective for major defects and 4.0 percent defective for minor defects.

4.2.3 Tests. Samples selected in accordance with 4.2.1 shall be tested as specified in 4.3.2.2 and 4.3.2.3. AQL shall be 4.0 percent defective.

4.3 Inspection procedure.

4.3.1 Examination. The rail anchors shall be examined for the following defects:

Major

101. Material not as specified.
102. Rail anchor size not as specified.
103. Defects impairing strength or function such as fins, cracks, nicks, flaws, and seams.

Minor

201. Identification marking missing or illegible.
202. Workmanship not as specified.

4.3.2 Tests.

4.3.2.1 Test conditions. Unless otherwise specified, tests shall be performed at the climatic conditions existing at the place of test.

4.3.2.2 Tension. The rail anchor shall be tested in accordance with ASTM E8. Nonconformance to 3.2.1.1 shall constitute failure of this test.

4.3.2.3 Hardness. The rail anchor shall be tested in accordance with ASTM E18. Nonconformance to 3.2.1.2 shall constitute failure of this test.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:06Z
Check the source to verify that this is the current version before use.

4.4 Inspection of packaging.

4.4.1 Quality conformance inspection of pack.

4.4.1.1 Unit of product. For the purpose of inspection, a completed ack prepared for shipment shall be considered a unit of product.

4.4.2 Sampling. Sampling for examination shall be in accordance with IL-STD-105.

4.4.3 Examination. Samples selected in accordance with 4.4.2 shall be xamined for the following defects. AQL shall be 2.5 percent defective for ajor defects and 4.0 percent defective for minor defects.

Major

104. Containers not as specified.
105. Strapping not as specified.

Minor

203. Rail anchors of unlike description packed together.
204. Marking illegible, incomplete, incorrect, or missing.

5. PACKAGING

5.1 Packing. Packing shall be Level A, Level B, or Commercial as specified (see 6.2).

5.1.1 Level A. Rail anchors of like description shall be packed in close-fitting boxes conforming to PPP-B-601, Overseas Type, style optional. Strapping shall conform to QQ-S-781, Class 1, Type I or IV, size as applicable. Unless otherwise specified (see 6.2), strapping shall be Finish B. When specified (see 6.2), strapping shall be Finish A.

5.1.2 Level B. Rail anchors shall be packed as specified in 5.1.1 for Level A except that boxes shall be Domestic Type and strapping shall be Finish A.

5.1.3 Commercial. Rail anchors shall be packed to assure carrier acceptance and delivery to destination, without damage, at the lowest ratings of the carrier in compliance with Uniform Freight Classification rules or National Motor Freight Classification rules.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:06Z
Check the source to verify that this is the current version before use.

5.2 Marking.

5.2.1 Military packaging. Marking shall be in accordance with MIL-STD-129.

5.2.2 Commercial packaging. Marking shall reflect as a minimum, the item name, National Stock Number, quantity, contract number, and appropriate address markings. The marking shall be applied with a waterproof material, be legible, and shall provide a definite contrast.

6. NOTES

6.1 Intended use. The rail anchors are intended for use as checks for longitudinal movement of rails under traffic with respect to the ties.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Size of rail anchor required (see 3.3).
(c) Degree of packing required (see 5.1).
(d) When Finish A strapping is required (see 5.1.1).

6.3 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the specification (see 3.2).

Custodians:
Army - ME
Navy - YD

Preparing activity:
Army - ME

Project 2250-0048



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:06Z
Check the source to verify that this is the current version before use.

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-R-52065B Rail Anchor, Railway

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:06Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID

U.S.MAIL

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
US Army Mobility Equipment Research
and Development Command
ATTN: DRDME-DS
Ft. Belvoir, VA 22060

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:06Z
Check the source to verify that this is the current version before use.