MIL-T-82298A
12 December 1980
SUPERSEDING
MIL-T-82298
27 October 1970

MILITARY SPECIFICATION

TAPE, MEASURING, CLOTH, COTTON

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope This specification covers the requirements for a coated cotton measuring tape.

2. APPLICABLE DOCUMENTS

*2.1 Issue in effect The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

STANDARDS

FEDERAL

FED-STD-191	- Textile Test Methods

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	- Marking for shipment and Storage

LAWS AND REGULATIONS

US POSTAL SERVICE MANUAL

(Copies of the manual may be obtained from the Superintendent of Documents. US Government Printing Office, Washington, DC 20402).

(Copies of specifications, standards, drawings and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Beneficial comments (recommendations, additions, and deletions) and any pertinent data which may be of use in improving this document should be addressed to: Officer in Charge, Navy Clothing and Textile Research Facility, 21 Strathmore Road, Natick, MA 01760 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:01Z
Check the source to verify that this is the current version before use.

*2.2 Other publications The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issues in effect on date of invitation for bids or request for proposal shall apply:

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC.

National Motor Freight Classification
(Application for copies should be addressed to American Trucking Associations, ATTN: Traffic Department Section, 1616 P Street, NW, Washington, DC 20036.)

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Application for copies shall be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, ILL 60606.)

3. REQUIREMENTS

3.1 Guide sample Samples, when furnished, are solely for guidance to the contractor (see 6.3). Variation from this specification may appear in the sample in which case this specification shall govern.

*3.2 First article When specified (see 6.2), the contractor shall furnish sample unit(s) for first article inspection and approval (see 4.3 and 6.2).

3.3 Materials

3.3.1 Base cloth The base cloth shall be woven cotton cloth.

3.3.2 Coating compound The coating compound shall be suitably formulated to provide a flexible and non-tacky finish and shall be applied equally to both sides of the base cloth.

3.3.3 Coated cloth The coated cloth shall have a minimum weight of 6.5 ounces per square yard and a minimum of 58 ends and 46 picks per inch when tested as specified in 4.4.4.

3.3.4 End clip The end clip shall be fabricated from a non-ferrous metal having a minimum thickness of 0.01 inch and shall measure 5/8 (+ 0, -1/16) inch in width by 5/16 (± 1/16) inch in length.

3.4 Color The color of the finished measuring tape shall be yellow.

3.5 Construction The measuring tape shall be of one piece construction, graduated and numbered on each side, with a metal clip securely clinched to each end.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:01Z
Check the source to verify that this is the current version before use.

3.5.1 Graduations The tape shall be graduated on both sides in inches (1 to 60) with subdivisions in eighths of an inch. The graduation marks shall be perpendicular to the vertical axis (length direction) and parallel to each other. The heights of the various graduation marks shall be as follows:

Graduation values	Height of graduation mark
1 inch	Equal to width of tape
1/2 inch	3/8 (± 1/16) inch
1/4 inch	1/4 (± 1/16) inch
1/8 inch	3/16 (± 1/16) inch

3.5.2 Numerals Arabic numerals, not less than 1/4 inch in height, shall be used to indicate the inch values only. The numerals shall be placed at or upon the respective graduation marks to which they refer. The position of the numerals on one side shall range in reverse direction to those on the opposite side. One side of the measuring tape shall have all graduation marks and numerals imprinted with black indelible ink. The opposite side of the tape shall be imprinted with black or red ink.

3.6 Dimensions

3.6.1 Length The length of the finished measuring tape shall be 60 (± 1/8) inches.

3.6.2 Width The width of the finished measuring tape shall be 3/8 (± 1/16) inch.

3.7 Workmanship The tape shall conform to the quality established by this specification. The occurrence of defects shall not exceed the applicable acceptable quality levels.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may utilize his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Certificate of compliance Where certificates of compliance are submitted, the Government reserves the right to check test such items to determine the validity of the certification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:01Z
Check the source to verify that this is the current version before use.

*4.2 Classification of inspection The inspection requirements specified herein are classified as follows:

1. First article inspection (see 4.3).
2. Quality conformance inspection (see 4.4).

4.3 First article inspection The first article submitted in accordance with 3.2 shall be inspected as specified in 4.4.2 for compliance with design, construction, workmanship and dimensional requirements.

4.4 Quality conformance inspection Inspection shall be in accordance with the provisions set forth in MIL-STD-105, except where otherwise indicated herein.

4.4.1 Component and material inspection In accordance with 4.1 above, components and materials shall be inspected and tested in accordance with all requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in the specification or applicable purchase document. In addition, the supplier shall furnish a certificate of compliance for the cotton fiber identification and the composition of the end clip.

4.4.2 Examination of the end item

4.4.2.1 Visual examination Examination of the end item shall be in accordance with the classification of defects in Table I. The sample unit shall be one tape. The sample size shall be in accordance with inspection level I. The lot size shall be expressed in units of one tape each. The acceptable quality expressed in terms of defects per hundred units.

Table I - Classification of visual examination of defects

Defects	Classification	
	Major	Minor
Tape:		
a. Any frayed edge	X	
b. Not color specified		X
c. Any cut, hole or tear	X	
d. Not one piece construction	X	
Coating:		
a. Any tackiness	X	
b. Any uncoated area	X	
c. Uneven coating (area where coating is noticeably thinner)	X	
d. Not flexible (coating cracks, flakes or peels when flexed)	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:01Z
Check the source to verify that this is the current version before use.

Table I - Classification of visual examination of defects (cont'd)

Defects	Classification Major	Minor
Metal Clip:		
a. Not width or length specified		X
b. Not positioned properly (askew or not squared with edge of tape)	X	
c. Missing or not securely clinched to end	X	
Marking:		
a. Incomplete or missing	X	
b. Illegible	X	
c. Not size specified (graduations or numerals)		X
d. Graduations not perpendicular to length direction or not parallel to each other	X	
e. Not color specified		X
f. Not arabic numerals	X	
g. Numerals misplaced	X	
h. Numerals of one side not ranging in opposite direction to that of reverse side		X
i. Graduations spaced more or less than 1/8 inch apart	X	

4.4.2.2 Dimensional examination An examination shall be performed for defects of dimensions. Any deviations from dimensions and tolerances specified shall be classified as a defect. The lot size shall be expressed in units of one tape each. The sample unit shall be one tape. The sample size shall be in accordance with inspection level S-4. The acceptable quality level (AQL) shall be 4.0 expressed in terms of defects per hundred units.

4.4.3 Examination of packaging requirements An examination shall be made to determine that packaging, packing and marking comply with Section 5 requirements of this specification. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully prepared for delivery, with the exception that it need not be sealed. Defects of closure listed below shall be examined in shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and the AQL shall be 2.5 defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:01Z
Check the source to verify that this is the current version before use.

Examine	Defect
Marking (exterior and interior)	Omitted, incorrect, illegible, of improper size, location, sequences or method of application.
Materials	Any component missing, damaged, or not as specified.
Workmanship	Inadequate application of components, such as: incomplete closure of container flaps, inadequate stapling, improper taping or distorted container.
Content	Number of items per container less than indicated.

4.4.4 Testing of the end item The methods of testing specified in FED-STD-191, wherever applicable, and as listed in Table II shall be followed. The physical values specified in Section 3, except where otherwise specified, apply to the average of the determinations made on the sample unit for test purposes as specified in the applicable test methods. All test reports shall contain the individual values utilized in expressing the final results. The sample size shall be in accordance with inspection level S-1. The lot size shall be expressed in units of one tape. The sample unit for test purposes shall be 5 finished tapes. The lot shall be unacceptable if the average of the test results fail to meet any requirements specified.

Table II - Test methods

Characteristics	Requirement reference	Test method
Weight (oz/sq yd)	3.3.3	5041 1/
Yarns per inch		
Warp	3.3.3	5050
Filling	3.3.3	5050

1/ The test specimen shall be one full length of tape with the end clips removed.

5. PACKAGING

*5.1 Preservation-packaging Packaging shall be level C (Commercial).

*5.1.2 Level C (Commercial packaging) Tapes shall be packaged to afford adequate protection against physical damage during shipment from the supply source to the first receiving activity. The contractor may use his standard practice when it meets this requirement. The package and the quantity per package shall be the same as that normally used by the contractor for retail distribution.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:01Z
Check the source to verify that this is the current version before use.

*5.2 Packing Packing shall be level C (Commercial).

*5.2.1 Level C (Commercial packing) Tapes, packages as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. The quantity per shipping container shall be the same as that normally used by the contractor for retail distribution. Containers shall conform with the US Postal Service Manual, Uniform Freight Classification Rules or National Motor Freight Classification Rules, as applicable.

5.3 Marking In addition to any special marking required by the contract or order (see 6.2), unit packages, intermediate packages, and shipping containers shall be marked in accordance with the requirements of MIL-STD-129.

6. NOTES

6.1 Intended use The measuring tape covered by this specification is intended for use by tailors and dressmakers for all general measuring work involved in tailoring various articles of clothing and as a component in medical equipment sets.

*6.2 Ordering data Procurement documents should specify the following:

a. Title, number and date of this specification.
b. Stock number.
c. When first article sample is required (see 3.2).
d. Whether special marking is required (see 5.3).

6.3 Samples For access to samples, address the procuring office issuing the invitation for bids.

*6.4 Changes from previous issue The margin of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidder and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Navy - NU
Air Force- 11
Army - GL

Review Activity:
DLA - CT

User Activities:
Navy - MC
Air Force- 82

Preparing activity:
Navy - NU

Project No. 8315-0290

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:01Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL

FIRST CLASS PERMIT NO. 12503 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Officer In Charge
Navy Clothing and Textile Research Facility
21 Strathmore Road
Natick, MA 01760

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:01Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-T-82298A TAPE, MEASURING, CLOTH, COTTON

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 Replaces edition of 1 Jan 72 which may be used. S/N 0102-LF-001-4260

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:01Z
Check the source to verify that this is the current version before use.