INCH-POUND

MIL-DTL-15665/100B
14 September 2016
SUPERSEDING
MIL-DTL-15665/100A
15 October 2007

DETAIL SPECIFICATION SHEET


INSIGNIA, CAP, SUPERVISORY POLICE, DEPARTMENT OF THE ARMY

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-15665.



BASE



RANKS



DEVICE

MATERIAL: Red Brass 85/15 (UNS Alloy No. C-230)

FINISH: Epoxy resin, 24K Gold Plated, Mirror-like Polished, and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 6.

DIMENSION:
BASE:
HEIGHT: 2-1/2 inches (REF)
WIDTH: 2-1/2 inches (REF)
THICKNESS (At thickest point): 0.120 ± 0.010 inch
DEVICE:
DIAMETER: 3/4 inch (REF)
THICKNESS (At thickest point): 0.075 ± 0.005 inch
ASSEMBLED THICKNESS: 0.135 ± 0.010 inch

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:03Z
Check the source to verify that this is the current version before use.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. A full forcer shall be used to bring up the details of the base design.

3. The cap insignia shall be dapped to a radius of 3-1/2 inch ± 1/4 inch along the horizontal plane.

4. Lettering on the base shall be base metal and as detailed below:
   TOP SCROLL (Rank Scroll): Lettering in the top scroll shall be added during manufacturing. Letters shall be approximately 3/16 inch in height, block style, and shall read "CHIEF," "CAPTAIN," "LIEUTENANT," or "SERGEANT" as required. The letters shall be surrounded with enamel or epoxy as specified in Note 5.
   BOTTOM SCROLL: "POLICE" already in government furnished die.

5. Epoxy resin (stoning epoxy) may be at the option of the manufacturer. When hard enamel is used, the material requirement shall be gilding metal. When epoxy is used, the material requirement shall be either red brass or gilding material. Colors shall conform to TIOH Hard Enamel Color Chip Numbers listed below:

BASE:	
Background of both scrolls	Ultramarine Blue #18
DEVICE (also see TIOH Drawing B-5-158):	
Flag stripes	Alternating Scarlet #1 & White #28
Background of stars in flag	Ultramarine Blue #18
Stars above Liberty Bell	Ultramarine Blue #18
Background around flag & Liberty Bell	White #28
Motto band	Ultramarine Blue #18

6. The attaching device shall be a prong attached at the center of the eagle's head and a screw post with thumb nut centered on the vertical center line of the cap insignia.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Preparing activity:
Army – IH

Review activity:
DLA - CT

(Project No. 8455-2016-770)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:03Z
Check the source to verify that this is the current version before use.