NOT MEASUREMENT SENSITIVE

MIL-DTL-15665/95
23 September 1997

DETAIL SPECIFICATION SHEET

INSIGNIA, GARRISON CAP, OFFICERS,
NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION

This specification is approved for use by all Departments
and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-15665 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

DEVICE

BASE

MATERIAL: Red Brass

FINISH:
BASE: Nickel Plated, Mirror-like Polished and shall match TIOH Metal Finish Chip Number 16.
DEVICE:
EAGLE AND GLOBE: Gold Plated, Matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip Number 8.

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:01Z
Check the source to verify that this is the current version before use.

DIMENSIONS:
  BASE:
    HEIGHT (Overall): 3/4 inch (1.91 cm) (REF)
    WIDTH (Overall): 1-1/8 inches (2.86 cm) (REF)
    THICKNESS (Minimum): 0.102 inch (2.59)
  DEVICE:
    HEIGHT (Overall): 15/16 inch (2.38 cm) (REF)
    WIDTH (Overall): 1-1/8 inches (2.86 cm) (REF)
    THICKNESS (Minimum): 0.124 inch (3.15)

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. A forcer may be used to bring up the design of both the base and the device.

3. Piercing shall be as indicated.

4. The base shall be spherically dapped to fit the contour of the globe on the device.

5. The base shall contain a 1/16 inch ± 1/64 inch (0.16 cm ± 0.04 cm) diameter hole centered at the intersection of the crossed anchors.

6. The device shall have one post 1/16 inch ± 1/64 inch (0.16 cm ± 0.04 cm) in diameter and 1/16 inch ± 1/64 inch (0.16 cm ± 0.04 cm) long soldered on the vertical center line of the globe, 1/8 inch ± 1/64 inch (0.32 cm ± 0.04 cm) from the bottom of the globe on centers.

7. The device shall be mounted to the base by inserting the lower post through the hole at the horizontal center of the globe swedged in place.

Custodians:
Army - IH

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-0910)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T07:01Z
Check the source to verify that this is the current version before use.