INCH-POUND

MIL-PRF-32032
07 August 1998

PERFORMANCE SPECIFICATION

CLEANER, STEAM, PRESSURE JET, DIESEL POWERED,

TRAILER-MOUNTED

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE.

1.1 Scope. This specification covers one kind of a mobile high pressure hot water aircraft washer. An additional requirement is the washing of aerospace ground equipment and supporting and decontamination of aircraft exposed to chemical/biological environments.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements documents cite in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

DEPARTMENT OF DEFENSE

MIL-H-8794	Hose, Rubber, Hydraulic, Fuel and Oil Resistant
MIL-H-8795	Hose Assemblies, Rubber, Hydraulic, Fuel and Oil Resistant

STANDARDS

FEDERAL

FED-STD-595	Colors, Used in Government Procurement

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in the improving of this document should be addressed to: Resources & Logistics Services Division, SA-ALC/TILDD, 485 Quentin Roosevelt Rd., Bldg 171, Kelly AFB, TX 78241-6524 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 4940

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:22Z
Check the source to verify that this is the current version before use.

DEPARTMENT OF DEFENSE

MS51336	Lunette-Coupler, Drawbar, Ring

HANDBOOKS

DEPARTMENT OF DEFENSE

MIL-HDBK-808	Finish, Protective and Codes for Finishing Schemes for Ground and Ground Support Equipment
MIL-HDBK-1784	Mobility, Towed and Manually Propelled Support Equipment
MIL-HDBK-1791	Designing for Internal Aerial Delivery in Fixed Wing Aircraft

(Unless otherwise indicated, copies of the above specifications, standards, and handbooks are available from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

2.2.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

AIR FORCE

7545352	Requirements for Finishes, Materials and Processes for Corrosion Prevention and Control on San Antonio ALC Ground Support Equipment

(Copies of the Air Force Drawing is available from SA-ALC/TILDB, 485 Quentin Roosevelt Rd., Bldg 171, Kelly AFB, TX 78241-6524)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspections (see 4.4 and 4.6).

3.2 Design. The cleaning unit shall consist of a diesel engine, foam generating system; cleaning compound tank, fuel tank, anti-freeze tank, alternator; fluid heater including a combustion chamber and pressure-atomizing burner; fluid pumps, instrumentation; control panel; fluid delivery hoses; foam delivery hoses; application wands/nozzles; and insulated spray guns. The unit shall be designed and constructed to provide a convenient and safe method of applying a mixture of water and cleaning compound or clear rinse water to the external surfaces of aircraft and aerospace ground equipment.

3.3 Materials. Materials not specifically designed shall be of standard commercial quality.

3.3.1 Materials protective treatment. Materials that are subject to deterioration upon exposure to climatic and environmental conditions during use shall be given a protective treatment which shall not hinder the performance of the cleaner as required by this specification. The use of any protective coating that will crack, chip, or scale with age or extremes of environmental conditions shall be avoided.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:22Z
Check the source to verify that this is the current version before use.

3.3.2 Dissimilar metals. Unless suitably protected against electrolytic corrosion, dissimilar metals shall not be used in intimate contact with each other.

3.4 Performance. The unit shall be equipped with a ratio control mechanism capable of delivering water and a mixture of water and cleaning compound in various proportions. The unit shall be capable of operating in a steam mode, hot water rinse mode and cold water rinse mode (see 4.4.6).

3.4.1 Steam capacity. With 25 feet of steam hose and the cleaning wand attached, burning No. 2 fuel, the unit shall discharge the rated output of saturated steam at no less than:

200 gallons per hour (gph) (see 4.4.6)
325 degrees Fahrenheit (°F) (see 4.4.6)
200 pounds per square inch gage (psig) (see 4.4.6)

From a cold start with 40°F or colder water, the unit shall produce the rated output of saturated steam in no more than 8 minutes (see 4.4.6).

3.4.2 Hot water rinse mode. In the hot water rinse mode, using 25 feet of steam hose with the gun and the high pressure rinse nozzle attached, the unit shall be capable of discharging no less than 240 gph of 185 to 210°F water at no less than 400 psig pressure as measured at the discharge manifold (see 4.4.3).

3.4.3 Cold water rinse mode. While in the cold water rinse mode, using 25 feet of steam hose with the gun and the high pressure rinse nozzle attached, the unit shall be capable of discharging no less than 240 gph of inlet water (at no greater than 50°F) at no less than 400 psig pressure as measured at the discharge manifold (see 4.4.2).

3.4.4 Other requirements. The unit shall perform as specified on a 208 volt ± 10 percent, 50 and 60 hertz, single phase alternating current power supply. The power supply may be transformed at the control panel to operate control circuits at lower voltages. The steady state current draw (excluding start up of surge) shall be no greater than 15 amperes (see 4.4.6).

3.5 Details of components.

3.5.1 Component parts. This unit shall consist of the following component parts as specified.

3.5.2 Transporter. The unit, including components and accessories, shall be mounted on a four-wheeled chassis constructed of welded steel. A minimum of four tie-down rings shall be provided for both tie-down and lifting operations (see 4.4.1).

3.5.3 Parking brakes. The rear wheels shall be equipped with parking brakes (see 4.4.1).

3.5.4 Towing Provisions. The towbar shall be equipped with a lunette ring conforming to MS51336. A latch shall be provided for stowing the towbar in a vertical position when not in use. The latch shall be so designed that the towbar cannot be removed from the vertical position without manually actuating the latch (see 4.4.1).

3.5.5 Storage compartment. A storage compartment shall be provided on the trailer (see 4.4.1).

3.5.6 Spray gun. The spray gun shall have the capability to independently switch from wash to rinse by simply turning a valve or electrical switch. In addition, the nozzle will be made to change from the wash cycle (40 degree spray angle, high 4-8 gpm) to rinse cycle (20 degree spray angle, low pressure, 10-15 gpm). The wands shall be of double wand construction (see 4.4.1).

3.5.7 Foam-generating system. The unit shall have a foam generating system consisting of an air compressor, 50-gallon foam compound tan, foam delivery hoses, applicator wands, air inlet pressure gauge, control valve, and all necessary plumbing (see 4.4.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:22Z
Check the source to verify that this is the current version before use.

3.5.8 Air compressor. The foam generating system shall have an air compressor to provide pressurized air for the foam-generator. The output of the compressor shall be a minimum of 60 psi and maximum of 150 psi. The minimum volumetric output shall be 15 scfm (see 4.4.6).

3.5.9 Foam compound tank. The foam compound tank shall have a capacity of 50 gallons of compound with room for expansion due to increase in temperature and adequate air space remaining on top for proper operation. The tank shall be rigidly constructed of corrosion resistant material (see 4.4.1).

3.5.10 Water supply tank. A water supply tank shall be furnished to provide a constant supply of water to the cleaner and to meet all the performance requirements specified herein (see 4.4.1).

3.5.11 Burner. The burner shall be of the pressure-atomizing or air-atomizing type equipped with continuous electric ignition, fan and controls (see 4.4.6).

3.5.12 Foam delivery hoses. The foam delivery hoses shall be 200 feet in length and meet the requirements of MIL-H-8794. The hose assembly shall meet the requirements of MIL-H-8795.

3.5.13 Air inlet pressure gauge. An air inlet pressure gauge shall be provided to allow accurate variation of the foam consistency when adjusting the control valve (see 4.4.6).

3.5.14 Diesel engine. The engine shall be an air-cooled diesel engine. This engine shall also be capable of burning military jet fuels JP4 and JP8 (primary), commercial jet fuel JET-A and military diesel fuels DF-1 and DF-2. In addition, the engine shall be capable of starting at -25°F without the use of external starting aids. The diesel engine shall meet the requirements of Appendix A as well as all requirements of this specification.

3.5.15 Hose reel assemblies. The hose reel assemblies shall have hose guides and flex-joints to prevent kinks, binding, and weakened joints when extending or retracting the various fluid delivery hoses. As a minimum, easily accessible handcranks shall be provided to retract or extend the hose (see 4.4.6).

3.5.17 Bolted connections. Bolt holes shall be accurately punched or drilled and shall have burrs removed. Washers or lockwashers shall be provided in accordance with good commercial practice, and all bolts, nuts, and screws shall be tight (see 4.4.1).

3.6 Finishes. MIL-HDBK-808 as supplemented by Type I exposure and Air Force drawing 7545352 outlines guidance as to finishes for application to equipment and parts thereof. The use of cadmium coating cited in MIL-HDBK-808, paragraph 5.5.1.2a and c shall be prohibited unless options cited in paragraphs b, d, e, f, and g cannot meet performance requirements.

3.6.1 Finishing colors. The painting shall be in accordance with the general requirements and procedures defined in MIL-HDBK-808 as supplemented by Air Force drawing 7545352. The exterior and interior film coats shall be forest green (FED-STD-595, color no. 24052).

3.7 Static electricity. The machine shall be equipped with suitable grounding devices for static electricity (see 4.4.1).

3.8 Safety devices. The unit shall be equipped with safety devices to adequately protect the operator from all hazards incident to its operation (see 4.4.1).

3.9 Air transportability. The unit shall be designed for air transportability. The unit must be air transportable with one-half to three-fourths of a full tank (see 4.4.1).

3.10 Size and weight. The unit shall be designed with the objective towards minimum weight and size (4.4.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:22Z
Check the source to verify that this is the current version before use.

3.11 Workmanship. All equipment being furnished shall be made and finished with uniformity and good workmanship.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2)

b. Conformance inspection (see 4.3)

4.2 First article inspection. One unit shall be tested for first article inspection and shall consist of all tests described under 4.4.

4.3 Conformance inspection. Each production item shall be subjected to a conformance inspection consisting of the tests as described in paragraphs 4.4.1 and 4.4.5.

4.4 Test methods.

4.4.1 Examination of the unit. The unit shall be examined in detail to confirm adherence with specified requirements not otherwise tested for. This examination shall be accomplished using a contractor developed check list that shall identify the specific unit attributes for which examination is made and results attained. The checklist shall conform with the requirements specified in section 3 of this specification. This element of inspection shall encompass all visual examination and conformance with the requirements of this specification. Noncompliance with any specified requirements or presence of one or more defects preventing or lessening maximum efficiency shall constitute cause for rejection.

4.4.2 Cold water discharge test. The unit shall be operated in the cold water mode for at least 15 minutes under 60 Hz power and for at least 15 minutes under 50 Hz power. The temperature of the inlet water shall be less than 50°F for at least 5 minutes of both the 60 and 50 Hz portions of the test. Failure of the unit to continuously discharge at least 240 gph of water through the rinse gun at a pressure of at least 400 psig for the full period of operation under either source of power shall be cause for rejection.

4.4.3 Hot water discharge test. The unit shall be operated in the hot water mode under 60 Hz power for 15 minutes after the water temperature at the coil outlet has stabilized and for the same period under 50 Hz power. The temperature of the inlet water shall be 40°F or less for the duration of both the 60 Hz and 50 Hz portions of the test. Failure of the unit to continuously discharge at least 240 gph of water heated to a temperature of at least 185°F at a pressure of at least 400 psig for 15 minutes while operating under either source of power shall be cause for rejection.

4.4.5 Cold start test. The unit shall be configured for operation at 50 Hz power using No. 2 diesel fuel. It shall operate in the cold water mode for 5 minutes to insure that the coil is cool. The unit shall then be set for operation in the vapor mode, supplied with water at a temperature of not more than 40°F, and operated for eight minutes. Failure of the unit to discharge vapor heated to a temperature of at least 325°F at a pressure of at least 200 psig and a rate of at least 200 gph by the end of the eight minute period shall be cause for rejection.

4.4.6 Operational test. The unit shall be operated in the vapor mode under 50 Hz power and under 60 Hz. The unit shall be operated for 1 minute under each source of power after the temperature at the coil outlet has stabilized. During each 15 minute operating period, the pressure at the pump outlet and at the gun nozzle shall be measured and recorded. Failure of the unit to continuously discharge water vapor heated to a temperature of at least 325°F at a pressure of at least 200 psig and at a rate of at least 200 gph for the full 15 minute period while operating under each source shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:22Z
Check the source to verify that this is the current version before use.

4.4.7 Blowdown test. After the unit has been in operation in a sufficient amount of time to build up scale deposits, as demonstrated by a decrease in the coil outlet pressure, a blowdown operation shall be performed in accordance with the manufacturer's instructions. Failure of the blowdown operation to return the coil outlet pressure to normal, or evidence of damage to any component of the unit as a result of the blowdown operation shall be cause for rejection.

4.4.8 Noise. The exterior noise level of the unit in operation shall be measured. Noise levels at a distance of 25 feet from the perimeter of the unit shall be measured at eight stations, 45 degrees apart, and 5'4" from the ground. At no time shall the noise level exceed 85 dB(A).

4.4.9 Transportability. The analytical equipment restraint-proof test, as described in paragraph 4.2.3 of MIL-HDBK-1791, shall be accomplished to demonstrate compliance with the requirements of air transportability.

4.4.10 Mobility tests. Mobility tests shall be performed in accordance with MIL-HDBK-1784, Type II, Group C, vehicles excluding the following (a) the maximum towing speed is 15 miles per hour, and (b) the maximum cramping angle for turns shall be conducted at 4 miles per hour, and the minimum ground clearance shall be 10 inches.

5. PACKAGING.

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or purchase order (see 6.2). When actual packaging of materiel is to be performed by DoD personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activity within the Military Department or Defense Agency, or within the Military Department's System Command. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The cleaner covered by this specification is intended for use on aerospace ground equipment and aircraft.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of specification.

b. Issue of DoDISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.2.1 and 2.2.2)

c. When first article is required (see 3.1).

6.3 Subject term (key word) listing.

Foam generating system
Spray gun
Water supply tank

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:22Z
Check the source to verify that this is the current version before use.

DIESEL ENGINE PERFORMANCE REQUIREMENTS

A.1 SCOPE

A.1.1 Scope. This document provides selection guidance and performance requirements for commercial diesel engines used in Air Force (AF) end item Support Equipment (SE).

A.2 APPLICABLE DOCUMENTS

(This section is not applicable to this MIL-PRF-XXXXX appendix)

A.3 REQUIREMENTS

A.3.1 Engine certifications. In addition to any other contract required engine certification or warranty, an engine manufacturer's certification must be obtained for any engine selected and included in the bid sample literature submittal. The engine manufacturer must certify the following:

A.3.1.1 End item contractor. The engine selected by the end item contractor is acceptable for the intended use with the fuels and lubricants specified. The general engine application (cooling/starting, etc.) shall also be approved.

A.3.1.2 Current production model. The engine is a current production model and production is not scheduled to be terminated in the foreseeable future.

A.3.1.3 Production terminated. At such time production is terminated, the engine manufacturer shall, to the best of its ability, maintain spare parts for a minimum of 10 years.

A.3.1.4 Distribution and service system. If the engine is not manufactured in the U.S., the manufacturer must have a complete distribution and service system in the U.S. for both commercial and Air Force requirements and the manufacturer must also certify compliance with the criteria outlined in paragraph A.3.1.3 above.

A.3.1.5 Performance requirements. The engine shall satisfy all performance requirements set forth in the end item equipment specifications, this document, and all exhaust emission requirements as outlined in A.4.2.

A.4 End item diesel engine requirements

A.4.1 Identification marking. Unless otherwise specified, the engine shall be identified in accordance with engineer manufacturer's standard commercial practice.

A.4.2 Engine exhaust and crankcase emissions. The Department of Defense (DoD) has been directed to exercise "Environmental Leadership" and meet all federal, state and local environmental regulations. AF SE is designed to be mobile, portable and standardized so forces from different locations can meet

at a deployed site, and use common SE. Meeting local requirements with unique equipment is not practical so all SE must meet the strictest environmental requirements promulgated by the state of California or the EPA as outlined in the following paragraphs.

A.4.2.1 California Air Resources Board (CARB), Utility, Lawn and Garden Engine (ULGE) Rule. The CARB rule goes into effect 1 January 1995 for engines rated 2 hp and below. There appears to be regulatory omission between 25 and 50 hp in California and from 0 to 50 hp in EPA standards for diesel engines. It is believed these omissions will be filled by extending the CARB ULGE Rule to 50 hp. It is further believed that engines using indirect injection or other exhaust emission reduction technology can be adapted to meet this rule.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:22Z
Check the source to verify that this is the current version before use.

A.4.2.1.1 Engines rated 25 hp or less. Engines rated 25 hp or less must have CARB ULGE certification before production deliveries begin. This testing can be part of the bid sample testing required for Commercial Item Description (CID) for performance specification end items.

A.4.2.1.2 Engines rated between 25 and 50 hp. Engines rated between 25 and 50 hp must have manufacturers or independent test laboratory test data showing the engine meets the emission requirements of the CARB ULGE rule before production deliveries begin. This also can be part of the bid sample testing.

A.4.2.2 CARB ULGE Rule. The CARB ULGE Rule is a complex legal/technical requirements document with many cross references in California law. Engine manufacturers/importers normally have personnel with detailed knowledge of these requirements. Suggest end item contractors discuss these requirements with the engine suppliers. If additional information is required, including a list of engines that are certified (25 hp and below), contact Air Resources Board at 9528 Telstar Ave., El Monte, CA 91731.

A.4.2.3 United States EPA, Nonroad Engine Rule (NER). On 17 June 1994, the EPA promulgated the NER for diesel engines 50 hp and greater rated power. Actual emission standards will be phased in over time by horse power classes for new engines.

A.4.2.3.1 Engines 175 to 750 hp. Engines 175 to 750 hp must meet the NER standard, 1 Jan 96. Engines in this class should be available before this date. While the non-road standards are different, the engine technology (turbo charged, after cool, and electronic fuel injection control) is well established and should allow engines to meet the non-road requirements. Engines in this class must meet the NER by the time bid sample testing begins or be accomplished as part of the testing so that production engines will meet the NER.

A.4.2.3.2 Engines rated 100 to 175 hp. Engines rated 100 to 175 hp must meet the NER standard by 1 Jan 97. The Ford, Dodge, and Chevy/GMC pickup truck diesels (and possibly others) have the on-road certification technology to meet the non-road requirements. Engines in this category must meet the non-road standard by the time bid sample testing begins, or be accomplished as part of the testing so that production engines meet the NER.

A.4.2.3.3 Engines rated from 50 to 100 hp. Engines rated from 50 to 100 hp must meet the NER standards by 1 Jan 98. Engines in this class do not have the on-road technology from which to draw. Engine manufacturers and importers shall be researched for ones that have an engine to meet this non-road standard or will agree to participate in the certification process as part of the acquisition process. If no engine supplier will agree to meet the standards, then an engine shall be selected that the supplier will certify his intentions to meet the standards with the same basic model type so future end item changes can be kept to a minimum to install a certified engine.

A.4.2.3.3.1 Waivers. If engines will not be certified by the time production begins, a waiver of this requirement can be requested from the procuring activity. The request shall describe all efforts taken to comply with the non-road standard and propose a remedial plan for bringing the engine into compliance post-production.

A.4.2.3.4 Engines over 750 hp. Any requirement for engines over 750 hp will be handled on a case by case basis.

A.4.2.4 Complex rule. As above, the rule is complex, lengthy and with many cross references. Suggest end item contractors discuss this requirement with engine suppliers. If additional information is required, contact the U.S. EPA; Washington, D.C. 20460; Telephone Number (202) 233-9256. The EPA does not maintain a list of engines meeting this requirement, individual suppliers maintain their own lists.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:22Z
Check the source to verify that this is the current version before use.

Custodians:
Air Force - 99
Army - AL

Reviews:
Navy - YD1
DLA - CC

Preparing Activity:
Air Force - 82

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:22Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.

2. The submitter of this form must complete blocks 4, 5, 6, and 7.

3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	**1. DOCUMENT NUMBER** MIL-PRF-32032	**2. DOCUMENT DATE (YYMMDD)** 98/08/07

3. DOCUMENT TITLE **CLEANER, STEAM, PRESSURE JET, DIESEL POWERED, TRAILER-MOUNTED**

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME *(Last, First, Middle Initial)*	b. ORGANIZATION	
c. ADDRESS *(Include Zip Code)*	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON *(if applicable)*	**7.DATE SUBMITTED** (YYMMDD)

8. PREPARING ACTIVITY

a. NAME San Antonio Air Logistics Center/TILDD	b. TELEPHONE *Include Area Code)* (1) Commercial (210) 925-6314 (2) AUTOVON 945-6314
c. ADDRESS *(Include Zip Code)Commander* 485 Quentin Roosevelt Road, Bldg. 171 Kelly AFB, TX 78241-6524	**IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:** DEFENSE QUALITY AND STANDARDIZATION OFFICE 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22401-3466 Telephone (703) 756-2340 AUTOVON 289-2340

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:22Z
Check the source to verify that this is the current version before use.