MIL-C-47244(MI)
AMENDMENT 1
1 November 1976

MILITARY SPECIFICATION

COATING, ABLATIVE RESISTANT

This amendment forms a part of Military Specification MIL-C-47244(MI) dated 26 July 1974.

Page 1

Paragraph 2.1, under specifications, Federal, delete: "TT-M-268" and substitute: "TT-M-261 Methyl Ethyl Ketone, Technical."

Page 2

Paragraph 2.1, under specifications, Military, delete: "MIL-P-116, Preservation-Packaging Methods of."

Under Standards, Federal, delete: "FED-STD-406, Plastics, Methods of Testing."

Paragraph 2.2 Other publications add:

"American Society for Testing and Materials

ASTM D-568 -74	Flammability of Flexible Plastics, Method of Test For
ASTM D-792	Specific Gravity and Density of Plastics by Displacement, Methods of Test For.
ASTM D-2240-75	Indentation Hardness of Rubber and Plastics by Means of a Durometer, Methods of Test For

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103)."

Page 9

Paragraph 4.4.2.2, line 1, delete: "MIL-P" and substitute "MIL-P-47215".

Paragrapn 4.4.3.2, delete: "FED-STD-406" and substitute: "ASTM D-792."

FSC 8030

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T08:04Z
Check the source to verify that this is the current version before use.

Page 9 (Continued)

Paragraph 4.4.3.3, line 10, delete: "The gun shall be attached to a constant supply of air or inert gas at not less than 85 pounds per square inch gage (psig) (for line variation or gage error)."

and substitute: "The gun shall be attached to a constant supply of air or inert gas at not less than 85 psig nor more than 95 psig (for line variation or gage error)."

Page 11

Paragraph 4.4.3.5, line 2, delete: "FED-STD-406, Method 1083" and substitute: "ASTM D-2240."

Page 12

Paragraph 4.4.3.8, line 8, delete: "MIL-S-6855" and substitute: MIL-R-6855."

Paragraph 4.4.3.9, line 5, delete: "shall be tested for impact resistance in accordance with FED-STD-406, Method 1074."

and substitute: "shall be tested for impact resistance. A steel ball weighing 0.5 pound shall be dropped from successively increasing heights in one foot intervals, starting at one foot until a height of 20 feet is attained."

Page 13

Paragraph 4.4.3.10, delete entire paragraph and substitute:

"4.4.3.10 Flammability. The cured system shall be tested for flammability in accordance with ASTM D-568. The cured resin system shall be self-extinguishing by this test."

Page 16

Paragraph 6.3, delete entire paragraph and substitute:

"6.3 Supersession data. This specification includes the requirements of MIS-16062 dated 27 August 1969. Products covered by this specification are substitutable for products as shown in the following cross reference.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T08:04Z
Check the source to verify that this is the current version before use.

Part Number	Contractors Part Number
M47244	APF-100, FSCM-09205

Custodian:
Army - MI

Preparing Activity:
Army - MI

Project No. 8030-A080

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T08:04Z
Check the source to verify that this is the current version before use.