FED SUP CLASS
5310



THD T	A +.002 −.007	B MIN	øC	øD	E	F	G	H	PART NO
190-32	.375	420	.200	.375	.078 +.010 −.005	060 ± 020	094	188	AN150432
250-28	437	491	.260	438	.078 +.010 −.005	060 ± .020	094	188	AN150433
313-24	500	562	322	500	.078 +.010 −.005	060 ± 020	094	188	AN150434
375-24	562	633	.385	562	125	120 ± 020	109	219	AN150435
438-20	625	705	448	625	125	120 ± 020	109	219	AN150436
500-20	750	847	510	750	125	120 ± .020	141	.250	AN150437
563-18	875	990	572	875	156	120 ± 030	188	312	AN150438
625-18	938	1 061	635	938	156	120 ± 030	188	.312	AN150439
750-16	1 062	1 203	760	1 062	156	120 ± 030	250	.375	AN150440

(a) MULTIPLE MARKING OF BAR STOCK IS PERMISSIBLE PROVIDED POSITIVE IDENTIFICATION IS SHOWN PARTS SHALL BE MARKED BEFORE THREADING DASH NUMBERS MAY APPEAR ON ADJACENT FALTS.

REQUIREMENTS

1 MATERIAL. STEEL AMS 6320, AMS 6322, OR AMS 6325
2 HARDNESS. ROCKWELL C19-26 PARTS SHALL BE HARDENED (OIL QUENCHED) AND TEMPERED BEFORE THREADING
3 FINISH. CADMIUM PLATE PER AMS 2400
4 SURFACE TEXTURE. ANSI/ASME B46 1 UNLESS OTHERWISE SPECIFIED SURFACES TO BE 125 MICROINCHES
5 PARTS SUBJECT TO MAGNETIC PARTICLE INSPECTION PER AMS2640
6 THREAD INSPECTION SHALL BE IN ACCORDANCE WITH FED-STD-H28/20 SYSTEM 21

NOTES.
1 BREAK SHARP EDGES .003 - .015 UNLESS OTHERWISE SPECIFIED
2 DIMENSIONS IN INCHES UNLESS OTHERWISE SPECIFIED TOLERANCES, LINEAR DIMENSIONS ± 010 ANGULAR DIMENSIONS ± 2°

(1) ENTIRE STANDARD REVISED

INCH-POUND

THIS STANDARD WAS DEVELOPED COOPERATIVELY WITH THE GENERAL STDS FOR AEROSPACE PROPULSION SYSTEMS COMMITTEES OF THE SAE.

APPROVED 9 JAN 50 REVISED (1) 1 FEB 1994

P.A. DLA - IS Other Cust AS, AV, 82, 99	AIR FORCE - NAVY AERONAUTICAL STANDARD	AN150426 THRU AN150450
	NUT-HEX, CHECK	
PROCUREMENT SPECIFICATION NONE	SUPERSEDES	SHEET 1 OF 1

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

PROJECT NO 5310-1969

REVIEWER SYMBOLS

NOTICE When Government drawings, specifications or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto

DISTRIBUTION STATEMENT A APPROVED FOR PUBLIC RELEASE; DISTRIBUTION IS UNLIMITED.
NOTE This drawing was approved by joint action of the Air Force and Navy Departments as the Air Force-Navy standard for this product. This standard becomes effective for the procurement of equivalent products and data upon approval of subsequent standard drawings for the same product and data, or on the date specified in the notice of approval thereof, whichever is earlier. It does not become effective for the procurement of equivalent products, or for use in new design, not later than 6 months after the latest date of approval shown.

AMSC N/A

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:27Z
Check the source to verify that this is the current version before use.