MIL-S-87212
AMENDMENT 1
21 September 1984

MILITARY SPECIFICATION

SOCKS, FLYER'S, ANTIEXPOSURE CWU-67/P

This amendment forms a part of Military Specification MIL-S-87212, dated 23 April 1984, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

3.7, add new paragraph:

"3.7 Performance

"3.7.1 Leakage. The socks shall show no evidence of leakage when tested as specified in 4.4.7.1."

3.7: Change "3.7" to "3.8".

PAGE 6

4.4.6, add new paragraph:

"4.4.6 Palletization examination. An examination shall be made to determine that the palletization complies with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one palletized unit load fully packaged. The lot size shall be the number of palletized unit loads in the inspection lot. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirements.
Palletization	Pallet pattern not as specified. Interlocking of loads not as specified. Load not bonded with required straps as specified.
Weight	Exceeds maximum load limits.
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application."

4.4.7, add new paragraph:

"4.4.7 End item testing

FSC 8475

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:20Z
Check the source to verify that this is the current version before use.

"4.4.7.1 Leakage. The end item shall be tested for conformance to the leakage requirements in 3.7.1. The sample unit shall be one sock and the selection shall be by pairs. The lot shall be expressed in units of socks. The sample socks shall be tested individually and shall not show evidence of leaks when immersed in water to within 1 ±1/8 inch from the top edge. Failure of any sample unit to conform to the applicable requirement shall be cause for rejection of the lot."

PAGE 10

5.4, delete and substitute:

"5.4 Palletization. Socks, packed as specified (see 5.2), shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with K and L or film bonding means O or P. Pallet patterns shall be in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the patterns specified in MIL-STD-147, the pallet patterns used shall be approved by the contracting officer."

6.3, line 2: Delete "DAR 7-104.55" and substitute "FAR 52.209-4".

Custodian:
Army - GL
Air Force - 11

Review activity:
Air Force - 82, 99

Preparing activity:
Air Force - 11

Project No. 8475-0196

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:20Z
Check the source to verify that this is the current version before use.