
FED. SUP CLASS
5305



D NOMINAL SIZE		#2 (.086)	#4 (.112)	#6 (.138)	#8 (.164)	#10 (.190)	1/4	5/16
B THREADS PER INCH		64NF-3A	48NF-3A	40NF-3A	36NF-3A	32NF-3A	28UNF-3A	24UNF-3A
J WIDTH OF SOCKET ACROSS FLAT	Max.	.0355	.051	.0635	.0791	.0947	.127	.1582
	Min.	.035	.050	.0625	.0781	.0937	.125	.1562
R POINT RADIUS		.0625	.084	.1093	.125	.1406	.1875	.2343
T KEY ENGAGEMENT	Min.	.028	.040	.050	.062	.075	.100	.125
L LENGTH	Tolerance	Dash No.	Dash No.	Dash No.	Dash No.	Dash No.	Dash No.	Dash No.
1/8	± 1-1/2% of L with a minimum of ± .010 in.	1*	8*	16*				
3/16		2*	9*	17*	24*	32		
1/4			10*	18*	25*	33	41	
5/16					26*	34*	42*	51
3/8						35*	43	52
1/2							44*	53*
5/8							45*	54*
3/4								

D NOMINAL SIZE		3/8	1/2
B THREADS PER INCH		24UNF-3A	20UNF-3A
J WIDTH OF SOCKET ACROSS FLAT	Max.	.1895	.2520
	Min.	.1875	.2500
R POINT RADIUS		.2812	.3750
T KEY ENGAGEMENT	Min.	.150	.200
L LENGTH	Tolerance	Dash No.	Dash No.
3/8	± 1-1/2% of L with a minimum of ± .010 in.	60	
1/2		61	69
5/8		62*	70*
3/4		63*	71*

Ⓐ CANCELLED AFTER 11 MAR 1964. Use MS51982. INTERCHANGEABILITY RELATIONSHIP - MS51982 can replace the cancelled screws of the same size. The cancelled MS51050 cannot always replace MS51982 and should be used until existing stock is depleted. Then use only the superseding MS screws of the same size for design and replacement.

* Indicates manufacturer's non-stock production items.
KEY ENGAGEMENT: These dimensions apply to screws one diameter in length or longer. For screws shorter than one diameter in length, socket shall be as deep as practicable.
MATERIAL: Steel, High-Grade Alloy, in accordance with Procurement Specification.
HARDNESS: Setscrews shall be hardened by Heat Treatment to a hardness of Rockwell C45 to 53.
PROTECTIVE COATING: Cadmium Plated, in accordance with Specification QQ-P-416, Type II, Class 3. Zinc Plated, in accordance with Specification QQ-Z-325, Type II, Class 3.
THREADS: The threads shall be in accordance with Screw-Thread Standards for Federal Services Handbook H-28.
DIMENSIONS: All dimensions are in inches unless otherwise specified.
PART NUMBER: The MS part number consists of the MS number, plus the dash number. Example: MS51050-1.
NOTES: (1) Referenced documents shall be of the issue in effect on date of invitations for bid.
(2) This standard takes precedence over documents referenced herein.

Ⓐ CANCELLED
SEE NOTE

This document has been promulgated by the Department of Defense as the Military Standard to limit the selection of the item, product, or design covered herein in engineering, design, and procurement. This standard shall become effective not later than 90 days after the latest date of approval shown.

APPROVED 7 MAY 58 REVISED Ⓐ 11 MAR 1964

P.A.	WC	TITLE	MILITARY STANDARD
Other Cust	SHIPS ASD	SETSCREW, HEXAGON SOCKET, OVAL POINT, ALLOY STEEL, CADMIUM OR ZINC, NF-3A AND UNF-3A	MS51050
PROCUREMENT SPECIFICATION FF-S-103		SUPERSEDES:	SHEET 1 OF 1

DD FORM 1 SEP 57 672-1 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

NOTICE—When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

This military standard is approved by the Department of Defense and is mandatory on all activities. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

Source: https://assist.dla.mil -- Downloaded: 20240-23117:562
Check the source to verify that this is the current version before use.