THIS SPECIFICATION IS APPROVED FOR USE BY ALL DEPARTMENTS AND AGENCIES OF THE DEPARTMENT OF DEFENSE

THE REQUIREMENTS FOR ACQUIRING THE PRODUCT(S) DESCRIBED HEREIN SHALL CONSIST OF THIS SPECIFICATION SHEET AND THE ISSUE OF THE FOLLOWING SPECIFICATION LISTED IN THAT ISSUE OF THE DODISS SPECIFIED IN THE SOLICITATION NONE

Form Approved
OMB No 0704-0188

PART NO	NOM TUBE O D	THREAD T	A	B	ØC ± .005	D ± .005	F MIN	ØH ± .005	J BASIC	ØM	ØN	P	APPROX WEIGHT LB/100
MS9099-02	.125	.3125-24UNJF-3B	.553- .564	.250	.483	.037	.831	.047	.240	.562	.322	.125	44
MS9099-03	.188	.375-24UNJF-3B	.616- .627	.250	.546	.037	.703	.047	.270	.625	.385	.125	51
MS9099-04	.250	.4375-20UNJF-3B	.679- .690	.281	.608	.042	.775	.047	.305	.688	.448	.140	68
MS9099-05	.312	.500-20UNJF-3B	.741- .752	.281	.670	.042	.846	.055	.340	.750	.510	.140	76
MS9099-06	.375	.5625-18UNJF-3B	.803- .814	.297	.733	.042	.916	.055	.370	.812	.572	.148	90
MS9099-07	.438	.625-18UNJF-3B	.865- .877	.297	.795	.042	.987	.055	.405	.875	.635	.148	1 01
MS9099-08	.500	.750-16UNJF-3B	.990-1 002	.344	.920	.042	1 130	.062	.470	1 000	.760	.172	1 41
MS9099-09	.562	.8125-16UNJ-3B	1 052-1 064	.344	.983	.042	1 200	.062	.500	1 062	.822	.172	1 51
MS9099-10	.625	.875-14UNJF-3B	1 114-1 127	.391	1 045	.054	1 271	.062	.540	1 125	.885	.195	1 90
MS9099-11	.688	1 000-12UNJF-3B	1 301-1 314	.438	1 210	.054	1 484	.070	.625	1 312	1 010	.219	3 05
MS9099-12	.750	1 0625-12UNJ-3B	1 364-1 377	.438	1 295	.054	1 558	.070	.660	1 375	1 072	.219	3 25
MS9099-14	.875	1 1875-12UNJ-3B	1 489-1 502	.438	1 417	.054	1 699	.070	.725	1 500	1 198	.219	3 68
MS9099-16	1 000	1 3125-12UNJ-3B	1 614-1 627	.438	1 541	.054	1 842	.070	.790	1 625	1 322	.219	4 06
MS9099-18	1 125	1 500-12UNJF-3B	1 800-1 814	.438	1 729	.054	2 054	.070	.890	1 812	1 510	.219	4 69
MS9099-20	1 250	1 625-12UNJ-3B	1 926-1 940	.438	1 854	.054	2 198	.070	.960	1 938	1 635	.219	5 15
MS9099-24	1 500	1 875-12UNJ-3B	2 176-2 190	.438	2 104	.054	2 483	.070	1 095	2 188	1 885	.219	6 07
MS9099-28	1 750	2 250-12UNJ-3B	2 549-2 564	.438	2 478	.054	2 908	.070	1 295	2 562	2 260	.219	7 52
MS9099-32	2 000	2 500-12UNJ-3B	2 799-2 814	.438	2 728	.054	3 194	.070	1 425	2 812	2 510	.219	8 55

REQUIREMENTS

1. MULTIPLE MARKING OF BAR STOCK IS PERMISSIBLE PROVIDED POSITIVE IDENTIFICATION IS SHOWN PARTS SHALL BE MARKED BEFORE THREADING DASH NUMBERS MAY APPEAR ON ADJACENT FLATS
2. (C) MATERIAL ALUMINUM, QQ-A-225/8 (2024) TEMPER T8
3. FINISH ANODIC TREATMENT AMS2470
4. (C) SURFACE TEXTURE ANSI/ASME B46 1 UNLESS OTHERWISE SPECIFIED SURFACES TO BE 125 MICRONCHES EXCEPT HEX FACES

NOTES

1. BREAK SHARP EDGES .003-.015 UNLESS OTHERWISE SPECIFIED
2. DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES LINEAR DIMENSIONS ± .010, ANGULAR DIMENSIONS ± 5°
3. DO NOT USE UNASSIGNED PART NUMBERS
4. IN THE EVENT OF A CONFLICT BETWEEN THIS SPECIFICATION SHEET AND THE REFERENCES CITED HEREIN THE TEXT OF THIS SPECIFICATION SHEET SHALL TAKE PRECEDENCE
5. REFERENCED GOVERNMENT (OR NON-GOVERNMENT) DOCUMENTS OF THE ISSUE LISTED IN THAT ISSUE OF THE DEPARTMENT INDEX OF SPECIFICATIONS AND STANDARDS (DoDISS) SPECIFIED IN THE SOLICITATION FORM A PART OF THIS STANDARD TO THE EXTENT SPECIFIED HEREIN

AS & AMS ARE SOCIETY OF AUTOMOTIVE ENGINEERS, INC PUBLICATIONS
THIS STANDARD WAS DEVELOPED COOPERATIVELY WITH THE MILITARY SERVICES BY THE SAE AEROSPACE PROPULSION DIVISION

(C) DENOTES CHANGE(S)

INCH-POUND

PREPARING ACTIVITY DLA-IS
CUSTODIANS ARMY- AV NAVY- AS
AIR FORCE- 82 DLA-
REVIEW 11
USER AT, ER
PROJECT NUMBER 5310-1935

MILITARY SPECIFICATION SHEET

TITLE
NUT - HEX, BOSS CONNECTION ALUMINUM

SPECIFICATION SHEET NUMBER
MS9099 20 SEP 93 REV C

SUPERSEDING
MS9099 B (23 OCT 74)

AMSC- N/A FSC 5310

DISTRIBUTION STATEMENT
A. Approved for public release distribution is unlimited

Page 1 of 1

DD Form 672, MAY 88 PREVIOUS EDITIONS ARE OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:10Z
Check the source to verify that this is the current version before use.