

FED SUP CLASS
5306





SECTION THRU THREAD PROFILE



OPTIONAL SHAPE OF HEAD

TABLE I DASH NUMBER AND DIMENSIONS

DASH NO.	L	K +.000 -.060	APPROX WEIGHT LBS/100
-06	.750	1/	3.74
-07	.812	1/	3.90
-08	.875	1/	4.07
-09	.938	1/	4.24
-10	1.000	1/	4.41
-11	1.062	1/	4.58
-12	1.125	.125	4.75
-13	1.188	.188	4.91
-14	1.250	.250	5.08
-15	1.312	.312	5.25
-16	1.375	.375	5.43
-17	1.438	.438	5.60
-18	1.500	.500	5.76
-19	1.562	.562	5.93
-20	1.625	.625	6.10
-21	1.688	.688	6.27
-22	1.750	.750	6.44
-23	1.875	.875	6.77
-24	2.000	1.000	7.11
-25	2.125	1.125	7.44
-26	2.250	1.250	7.78
-27	2.375	1.375	8.11
-28	2.500	1.500	8.44
-29	2.625	1.625	8.78
-30	2.750	1.750	9.12
-31	2.875	1.875	9.46
-32	3.000	2.000	9.80
-33	3.125	2.125	10.13
-34	3.250	2.250	10.47
-35	3.375	2.375	10.80
-36	3.500	2.500	11.14
-37	3.625	2.625	11.47
-38	3.750	2.750	11.80
-39	3.875	2.875	12.14
-40	4.000	3.000	12.47
-41	4.125	3.125	12.80
-42	4.250	3.250	13.13
-43	4.375	3.375	13.46
-44	4.500	3.500	13.89
-45	4.625	3.625	14.23
-46	4.750	3.750	14.56
-47	4.875	3.875	14.89
-48	5.000	4.000	15.23
-49	5.125	4.125	15.57
-50	5.250	4.250	15.90
-51	5.375	4.375	16.23
-52	5.500	4.500	16.56
-53	5.625	4.625	16.89
-54	5.750	4.750	17.23
-55	5.875	4.875	17.57
-56	6.000	5.000	17.91

1/ THREAD TO HEAD. MAXIMUM TWO IMPERFECT THREADS.

REQUIREMENTS:

1. MATERIAL: STEEL AMS 6322.
2. THREADS: THREADS IN ACCORDANCE WITH MIL-S-7742. INCOMPLETE THREADS NOT TO ENTER FILLET.
3. HARDNESS: 26-32 HRC
4. FINISH: BLACK OXIDE TREATMENT IN ACCORDANCE WITH AMS 2485.
5. DIMENSIONING AND TOLERANCING: DIMENSIONING AND TOLERANCING SHALL BE IN ACCORDANCE WITH ANSI Y14.5M.
6. WRENCHING CONFIGURATION: WRENCHING CONFIGURATION IN ACCORDANCE WITH AS 870.
7. SURFACE TEXTURE: SURFACE TEXTURE, UNLESS OTHERWISE SPECIFIED, SHALL BE 125 MICROINCHES EXCEPT UPSET HEAD IN ACCORDANCE WITH ANSI B46.1.
8. MAGNETIC PARTICLE INSPECTION: MAGNETIC PARTICLE INSPECTION IN ACCORDANCE WITH AMS 2640.

Ⓐ ENTIRE STANDARD REVISED

APPROVED 5 AUG 57 REVISED Ⓐ 6 MAY 87

P.A. NAVY-AS	INTERNATIONAL INTEREST	TITLE	MILITARY STANDARD
Other Cust AIR FORCE-11		BOLT-MACHINE,STEEL, DRILLED 12 POINT HEAD, .375-24,BLACK OXIDE	MS9172
PROCUREMENT SPECIFICATION AMS 7452	SUPERSEDES		PAGE 1 OF 2

DD FORM 672-1 (COORDINATED) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE 5306-1166

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.
This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

USER ACTIVITIES:
REVIEWER ACTIVITIES: DLA-IS

AMSC N/A

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:11Z
Check the source to verify that this is the current version before use.

FED. SUP CLASS 5306

9. TOLERANCES : UNLESS OTHERWISE SPECIFIED, TOLERANCES SHALL BE FOR LINEAR DIMENSIONS ±.010, ANGULAR DIMENSIONS ±5°.

10. EDGES : BREAK SHARP EDGES .003-.015 UNLESS OTHERWISE SPECIFIED.

11. PART NUMBER : THE PART NUMBER SHALL CONSIST OF THE BASIC MS NUMBER FOLLOWED BY A DASH NUMBER FROM TABLE I.

EXAMPLE: MS9172-06

DASH NUMBER

BASIC MS NUMBER

MS9172-06 INDICATES: BOLT-MACHINE, STEEL, DRILLED 12 POINT HEAD, .375-24, BLACK OXIDE, .750 LONG.

NOTES:

1. ALL DIMENSIONS ARE IN INCHES.
2. DO NOT USE UNASSIGNED PART NUMBERS.
3. IN THE EVENT OF A CONFLICT BETWEEN THE TEXT OF THIS STANDARD AND THE REFERENCES CITED HEREIN, THE TEXT OF THIS STANDARD SHALL TAKE PRECEDENCE.
4. REFERENCED GOVERNMENT (OR NON-GOVERNMENT) DOCUMENTS OF THE ISSUE LISTED IN THAT ISSUE OF THE DEPARTMENT OF DEFENSE INDEX OF SPECIFICATIONS AND STANDARDS (DODISS) SPECIFIED IN THE SOLICITATION FORM A PART OF THIS STANDARD TO THE EXTENT SPECIFIED HEREIN.
5. THIS STANDARD WAS DEVELOPED COOPERATIVELY WITH THE SAE AEROSPACE PROPULSION DIVISION.
6. AS AND AMS ARE SAE PUBLICATIONS.

APPROVED 5 AUG 87 REVISED (A) FOR CHANGES SEE PAGES 1 AND 2

P.A.	INTERNATIONAL INTEREST	TITLE	MILITARY STANDARD
NAVY-AS Other Cust AIR FORCE-11		BOLT-MACHINE, STEEL, DRILLED 12 POINT HEAD, .375-24, BLACK OXIDE	MS9172
PROCUREMENT SPECIFICATION AMS 7452	SUPERSEDES		PAGE 2 OF 2

DD FORM 672-1 (COORDINATED) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE 5306-1166

USER ACTIVITIES:

REVIEWER ACTIVITIES:
DLA-IS

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:11Z
Check the source to verify that this is the current version before use.