INCH-POUND

MIL-M-55565C
9 November 1988
SUPERSEDING
MIL-M-55565B
24 January 1984

MILITARY SPECIFICATION

MICROCIRCUITS, PACKAGING OF

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

* 1.1 Scope. This specification covers the requirements for the preservation, packing, and container marking of all types of microcircuits. For the purpose of this specification, the term "microcircuits" shall include active delay lines in FSC 5999 and all integrated circuits and other microelectronic devices which are primarily in FSC 5962. Excluded from this specification are printed wiring boards, circuit card assemblies, and modules composed of discrete electronic parts (see 6.1).

2. APPLICABLE DOCUMENTS

* 2.1 Government documents.

* 2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

	QQ-S-781	- Strapping, Steel, and Seals.
	PPP-B-566	- Boxes, Folding, Paperboard.
	PPP-B-601	- Boxes, Wood, Cleated-Plywood.
	PPP-B-621	- Boxes, Wood, Nailed and Lock-Corner.
	PPP-B-636	- Boxes, Shipping, Fiberboard.
	PPP-B-676	- Boxes, Setup.
	PPP-C-795	- Cushioning Material, Flexible, Cellular, Plastic Film for Packaging Applications.
*	PPP-C-1752	- Cushioning Material, Packaging, Unicellular Polyethylene Foam, Flexible.
*	PPP-C-1797	- Cushioning Material, Resilient, Low Density, Unicellular, Polypropylene Foam.
	PPP-C-1842	- Cushioning Material, Plastic, Open Cell (for Packaging Applications).

* Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Communications - Electronics Command, ATTN: AMSEL-ED-TO, Fort Monmouth, NJ 07703 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

*AMSC N/A

AREA PACK

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:34Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-P-116	-	Preservation, Methods of.
MIL-B-117	-	Bags, Sleeves and Tubing - Interior Packing.
MIL-M-38510	-	Microcircuits, General Specification for.
MIL-B-81705	-	Barrier Materials, Flexible, Electrostatic-Free, Heat Sealable.
* MIL-D-83532	-	Delay Lines, Active, General Specification for.

STANDARDS

FEDERAL

FED-STD-123	-	Marking for Shipment (Civil Agencies).

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	-	Marking for Shipment and Storage.
MIL-STD-202	-	Test Methods for Electronic and Electrical Component Parts.
MIL-STD-794	-	Parts and Equipment, Procedures for Packaging of.
MIL-STD-883	-	Test Methods and Procedures for Microelectronics.
* MIL-STD-2073-1	-	DoD Materiel, Procedures for Development and Application of Packaging Requirements.
MIL-STD-45662	-	Calibration Systems Requirements.

* (Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099.)

* 2.2 Order of precedence. In the event of a conflict between the text of this document and the references cited herein (except for related associated detail specifications, specification sheets, or MS standards), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

* 3.1 General. The packaging terms used herein shall be in accordance with the definitions listed in MIL-STD-129, MIL-STD-794, and MIL-STD-2073-1. The following general requirements apply, as applicable, to levels A, B, and C as well as to shipments to non-Government activities.

* 3.1.1 Physical protection. Microcircuits shall be packaged in a manner that will ensure compliance with the applicable requirements of MIL-P-116 as well as those specified herein. For shipments to non-Government activities, large quantity unit packs designed for automatic insertion equipment may be used. To avoid damage, any unused microcircuits remaining in an opened multiple carrier shall be immediately repackaged to prevent damaging movement (see 3.1.1.1).

* 3.1.1.1 Carrier. Each microcircuit shall be positioned within a suitable noncorrosive carrier of sufficient strength to withstand vibration and shock without introducing damaging resonances. The carrier shall hold the contained device(s) firmly in place to prevent sliding or shifting within the carrier during handling and shipment. When a rail (a type of multiple carrier) is used, a spring or a noncorrosive, antistatic or conductive resilient retainer (e.g., a foam plug) shall be inserted at one or both ends to prevent sliding or shifting. Anchoring of device(s) or leads by means of tape or adhesives is not permitted. The carrier shall maintain physical separation of device leads during packaging, handling, and storage operations. The carrier shall be designed without sharp edges to protect the barrier material and to permit safe and easy removal, inspection, and

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:34Z
Check the source to verify that this is the current version before use.

replacement of the device(s) without damaging either the device(s) or the carrier. A rigid container meeting these requirements may be used as a carrier. Exclusive of individual carriers designed for electrical testing without device removal, carriers shall be conductive or impregnated or coated with antistatic material. Carriers coated but not impregnated with antistats shall only be used if the antistatic properties are proven to be intact on the surface.

* 3.1.1.2 Wrapping and cushioning. Wrapping or cushioning is required for shock and vibration protection. These materials shall be antistatic or static dissipative and noncorrosive and shall not crumble, flake, powder, or shed. Materials conforming to type II of MIL-B-81705 or small bags conforming to MIL-B-117, type I, class A, style 2 shall be used as wraps or small pouches, respectively. Alternatively, cushioning materials conforming to PPP-C-795, class 2; PPP-C-1752, type VII, class 1, grade B; PPP-C-1797, type II; or PPP-C-1842, type III may be used.

* 3.1.2 Environmental field force protection (shielding). For packaging purposes all military microcircuits are considered sensitive electronic devices. This specification does not require any tests to determine the degree or class of sensitivity. Microcircuits shall be protected by the procedures specified herein to prevent damage to these devices from electrostatic and electromagnetic forces during handling, shipment, and storage from time of manufacture until point of use (see 3.1.2.1). When specified in the contract (see 6.2), shielding from magnetic or radioactive fields shall also be required (see 3.1.2.2 and 3.1.2.3).

3.1.2.1 Electrostatic and electromagnetic protection. Electrostatic and electromagnetic protection (as well as protection from corrosion, biological contamination, foreign particle intrusion, thermal stress, and thermal shock) shall be provided by placing the carrier enclosed microcircuits in heat sealed bags or envelopes conforming to MIL-B-81705, type I. To avoid capacitor effects, each bag or envelope shall be fabricated from one continuous piece of barrier material. Additional electrostatic protection may be added within the barriers by the use of the materials specified in 3.1.1.2. For immediate use applications and for those instances where only limited exposure to weak, nondamaging electrostatic or electromagnetic fields is anticipated, barrier material conforming to type II of MIL-B-81705 may be used for shipments to non-Government activities to meet level C protection requirements.

3.1.2.2 Magnetic protection. Protection from simple magnetic fields (as opposed to RF or electromagnetic radiation) shall be accomplished by completely enclosing the microcircuits in metals or ferritic compositions of sufficient thickness to provide the degree of protection required.

3.1.2.3 Radioactive protection. Protection against radioactivity shall be accomplished by completely enclosing the microcircuits in lead or lead filled compositions of sufficient thickness to provide the degree of protection desired.

3.1.3 Exterior containers. Exterior containers shall be of minimum tare and cube consistent with the protection required and shall contain equal quantities of identical stock numbered or otherwise designated items to the greatest extent practicable (see 3.3).

3.2 Preservation. Preservation shall be in accordance with level A, B, or C, as specified (see 6.2).

* 3.2.1 Level A.

3.2.1.1 Cleaning. Microcircuits shall be cleaned in accordance with MIL-P-116, process C-1.

3.2.1.2 Drying. Microcircuits shall be dried in accordance with MIL-P-116.

3.2.1.3 Preservatives. Contact preservatives shall not be used.

Source: https://assist.dla.mil -- Downloaded: 202610-22T23:34Z
Check the source to verify that this is the current version before use.

* 3.2.1.4 Unit packs.

* 3.2.1.4.1 Individual item unit packs. Each carrier enclosed microcircuit, protected as required under 3.1, shall be individually unit packed in accordance with submethod IA-8 of MIL-P-116 in bags or envelopes conforming to MIL-B-117, type I, class F, style 1.

* 3.2.1.4.2 Multiple item unit packs. When specified in the contract (see 6.2), microcircuits, protected as required under 3.1 and enclosed in conductive or antistatic multiple device carriers (e.g., rails), shall be unit packed in accordance with submethod IA-8 of MIL-P-116 in bags or envelopes conforming to MIL-B-117, type I, class F, style 1. Unless otherwise specified in the contract (see 6.2), the quantity per unit pack shall be at the option of the supplier. Cushioning shall be required as specified in 3.1.1.2. Each unit pack shall be enclosed within a supplementary container conforming to variety 2 of either PPP-B-566 or PPP-B-676; or PPP-B-636, class weather resistant. Alternatively, nonweather or nonwater resistant versions of these containers may be used provided they are overwrapped with waterproof barrier materials. No intermediate packs are required.

* 3.2.1.5 Intermediate packs. Except for multiple item unit packs (see 3.2.1.4.2), when the unit pack is a bag of any type or the unit pack is less than 64 cubic inches (1,049 cubic centimeters), uniform quantities of unit packed microcircuits of the same NSN shall be placed in intermediate containers conforming to variety 2 of either PPP-B-566 or PPP-B-676. Alternatively, nonweather or nonwater resistant versions of these containers may be used provided they are overwarapped with waterproof barrier materials. Intermediate containers shall contain multiples of five unit packs not to exceed 100 unit packs. No intermediate packs are required when the total quantity shipped to a single destination will result in only one intermediate pack per shipping container.

* 3.2.2 Level B. The level B preservation for microcircuits shall be identical to that specified for level A except that any variety or class of the supplementary and intermediate containers specified may be used.

3.2.3 Level C. In addition to the applicable provisions of 3.1, the level C preservation for the carrier enclosed microcircuits shall conform to the MIL-STD-794 requirements for this level. Unless otherwise specified in the contract (see 6.2), the quantity per unit pack shall be at the option of the supplier.

3.3 Packing. Packing shall be level A, B, or C, as specified (see 3.1 and 6.2).

3.3.1 Level A. Microcircuits, preserved as specified in 3.2, shall be packed in wood containers conforming to PPP-B-601, overseas type or PPP-B-621, class 2. Closure and strapping shall be in accordance with the applicable container specification except that metal strapping shall conform to QQ-S-781, type I, finish A. The requirements for level B packing shall be used when the total quantity of a stock numbered microcircuit for a single destination does not exceed a packed volume of one cubic foot.

3.3.2 Level B. Microcircuits, preserved as specified in 3.2, shall be packed in fiberboard containers conforming to PPP-B-636, class weather resistant, style optional, special requirements. The requirements for box closure, waterproofing and reinforcing shall be in accordance with method V of the PPP-B-636 appendix.

3.3.3 Level C. Microcircuits, preserved as specified in 3.2, shall be packed in fiberboard containers conforming to PPP-B-636, class domestic, style optional, special requirements. Closures shall be in accordance with the PPP-B-636 appendix.

* 3.4 Marking. The following marking is mandatory for shipments both to U.S. Government and non-Government activities.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:34Z
Check the source to verify that this is the current version before use.

* 3.4.1 Standard marking. In addition to any special or other identification marking required by the contract (see 6.2), each unit, intermediate, and exterior container shall be marked in accordance with MIL-STD-129. The complete military or contractor's type or part number, as applicable, including the Commercial and Government Entity (CAGE) code, shall be marked on all unit and intermediate packs in accordance with the identification marking provisions of MIL-STD-129. When specified in the contract (see 6.2), the marking of domestic shipments for civil agencies shall be in accordance with FED-STD-123.

* 3.4.2 Special marking. In addition to the marking requirements of 3.4.1 and regardless of the level or type of packaging specified, all of the unit (including carriers), intermediate, and exterior containers shall be marked with the sensitive electronic device unit pack label or the sensitive electronic device caution label (as applicable) as specified in MIL-STD-129. Unless space is available for additional unit pack marking, the marking for single device carriers shall be limited to the sensitive electronic device symbol.

* 3.4.3 Additional unit pack marking of microcircuits conforming to FSC 5962 commodity specifications or drawings. Unit packs of microcircuits conforming to FSC 5962 commodity specifications or drawings shall additionally be marked with the following:

a. Inspection lot identification code.

b. Manufacturer's identification (name or trademark).

c. Country of origin (at manufacturer's option for JAN microcircuits only).

d. JAN certification mark.

e. Serialization, when applicable.

f. Special marking.

The details of this additional marking are specified in the microcircuit marking requirements of MIL-M-38510 or other applicable FSC 5962 commodity specification or drawing. If all the marking listed above is clearly visible on the microcircuits and legible through the multiple carrier, then the MIL-STD-129 sensitive electronic device marking only shall be required on the multiple carrier (see 3.4.2). These requirements apply to the original or repackaged microcircuits by the manufacturer or distributor. In addition, for old stock a reinspection lot identification code, structured as specified for the original lot identification code, shall be added to the unit pack marking. This code shall be for accepted microcircuits in lots reinspected prior to shipment to the user (when held in inventories by manufacturers or their authorized distributors longer than the time specified in the applicable FSC 5962 commodity specification or drawing).

3.5 First article and quality conformance inspections. First article and quality conformance inspections and tests shall be required as specified in 4.4 and 4.5, respectively. Samples for these tests shall be furnished in accordance with the procedures outlined in 4.4 and 4.5. The performance of the visual and dimensional inspections, rough handling tests, and leakage tests shall conform to the inspections and tests outlined in 4.6.1, 4.6.2.1, and 4.6.2.2, respectively.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:34Z
Check the source to verify that this is the current version before use.

3.5.1 Functional requirements.

* 3.5.1.1 Rough handling test (when specified, see 6.2). When packs have been tested in accordance with 4.6.2.1, all materials and components comprising each pack shall be free from damage or evidence of misplacement which might affect the utility of the preservation method or pack. The microcircuits within the tested packs shall show no visible signs of damage. When specified in the contract (see 6.2), functional tests in accordance with method 5005 of MIL-STD-883 and the group A inspection requirements of MIL-M-38510 or other applicable FSC 5962 commodity specification or drawing shall be conducted on those microcircuits in FSC 5962 subjected to the rough handling test to determine freedom from operational malfunction. These microcircuits shall also be externally inspected in accordance with method 2009 of MIL-STD-883. Delay lines shall be similarly inspected in accordance with MIL-D-83532. When specified in the contract (see 6.2), group A inspection requirements of MIL-D-83532 shall be conducted on those active delay lines subjected to the rough handling test to determine freedom from operational malfunction.

3.5.1.2 Leakage test (when applicable). When a barrier enclosed unit pack has been tested in accordance with 4.6.2.2, there shall be no evidence of moisture within the unit pack.

3.6 Workmanship. The quality of workmanship shall assure acceptance of the completed preservation, packing, and marking requirements in accordance with the inspections specified in section 4.

4. QUALITY ASSURANCE PROVISIONS

* 4.1 Responsibility for inspection. Unless otherwise specified in the contract (see 6.2), the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.1.1 Responsibility for compliance. All items must meet all requirements of section 3. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Test equipment and inspection facilities. Test and measuring equipment and inspection facilities of sufficient accuracy, quality, and quantity to permit performance of the required inspection shall be established and maintained by the contractor. The establishment and maintenance of a calibration system to control the accuracy of the measuring and test equipment shall be in accordance with MIL-STD-45662.

4.1.3 Inspection conditions. All inspections shall be performed in accordance with the test conditions specified in the general requirements of MIL-STD-202.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:34Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections. The inspections specified herein are classified as follows:

a. Materials inspection (see 4.3).

b. First article inspection (see 4.4).

c. Quality conformance inspection (see 4.5).

4.3 Materials inspection. Materials inspection shall consist of certification supported by verifying data that the materials used are in accordance with the applicable requirements specified herein.

4.4 First article inspection. When specified (see 6.2), first article inspection shall be performed by the contractor, after award of contract and prior to production, at a time and location acceptable to the Government. First article inspection shall not be required:

a. When there have been no changes in materials, processes, or packaging design that will not adversely affect item protection since the last recorded inspection.

b. When detailed packaging instructions are furnished by the acquisition activity.

c. When level C protection is specified.

d. When a prior successful inspection was conducted on a like item and pack (subject to the approval of the administrative contracting officer).

4.4.1 Sample size. One sample unit consisting of a level A or level B, as applicable, fully packed shipping container, shall be submitted for first article inspection. The sample for the rough handling test shall consist of the pack selected for first article inspection. The sample for the leakage test shall be five unit packs selected at random from the first article exterior pack (shipping container).

4.4.2 Inspection routine. The sample shall be subjected to the inspections specified in tables I and II. The leakage test, when applicable, shall follow the rough handling test.

4.4.3 Failures. One or more failures shall be cause for refusal to grant first article approval.

4.4.4 Resubmission of first article sample. If the sample fails to pass first article inspection, the contractor shall change the preservation and packing processes to correct the cause of the deficiency. First article inspection shall be performed on a corrected sample to prove that the corrective action is acceptable.

4.5 Quality conformance inspection. This inspection shall consist of the inspections and tests specified in tables I and II, respectively.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:34Z
Check the source to verify that this is the current version before use.

* TABLE I. Visual and dimensional inspections.

Major defects	Requirement paragraph	Method paragraph
Packaging materials not conforming to referenced specification requirements	Section 3	4.6.1
Inadequate or missing carrier	3.1.1.1	
Insufficient field force protection (shielding)	3.1.2	
Punctured or improperly fabricated barrier bag	3.1.2.1, 3.2.1.4.1, and 3.2.1.4.2	
Uncleaned or improperly cleaned items	3.2.1.1 and 3.2.1.2	
Incorrect preservation method	3.2.1.4.1 and 3.2.1.4.2	
Wrong quantity per unit pack	3.2.1.4.1, 3.2.1.4.2, and 3.2.3	
Nonuse or incorrect applications of intermediate containers	3.2.1.5	
Improper box closures	3.3.1 and 3.3.2	
Omitted, incorrect, or illegible marking	3.4	

TABLE II. Functional inspections.

Test	Requirement paragraph	Method paragraph
Rough handling (when specified)	3.5.1.1	4.6.2.1
Leakage (when applicable)	3.5.1.2	4.6.2.2

4.5.1 Inspection lot. An inspection lot, as far as practicable, shall consist of unit or exterior (shipping) packs produced under essentially the same conditions and offered for inspection at one time. For the purpose of selecting samples to be inspected and tested for compliance with the requirements of this specification, either items in process or completed packs except as stated herein, may be combined into lots without regard to individual items, contracts, or the quantities therein. Unit packs of the same size and made from the same packaging materials may be grouped together except when item complexity, item value, or the complexity of the preservation method warrants that the inspection of such items be performed on a separate basis. A separate application of the sampling or inspection procedure shall be made on these items. The combination of items to be subjected to inspection shall be determined by either the Government or the contractor, subject to the approval of the Government.

4.5.2 Visual and dimensional inspection. Visual and dimensional inspection shall consist of those inspections specified in table I.

4.5.2.1 Sampling plan. Statistical sampling and inspection shall be in accordance with MIL-STD-105 for special inspection level S-4. The acceptable quality level (AQL) shall be 4.0 percent defective for all inspections of table I combined.

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T23:34Z
Check the source to verify that this is the currentversion before use.

4.5.2.2 Rejected lots. If an inspection lot is rejected, the contractor may rework it to correct the defects, or screen out the defective units, and resubmit for reinspection. Resubmitted lots shall be inspected using tightened inspection. Such lots shall be separate from new lots, and shall be clearly identified as reinspected lots.

4.5.2.3 Disposition of sample units. Sample units which have passed all the inspections specified in table I may be delivered on the contract, provided the lot is accepted.

4.5.3 Functional inspection. Functional inspection shall consist of the tests specified in table II.

4.5.3.1 Sampling plan. Sampling plans shall be as follows:

a. One sample unit for the rough handling test shall be selected whenever the design of the item or packaging is changed.

b. For unit packs requiring waterproof or water-vaporproof barriers, five sample units for the leakage test shall be selected daily at random from the first lot processed each day. Five additional samples shall be selected at random from the day's total production.

c. The leakage test shall also be performed following the rough handling test on unit packs requiring waterproof or water-vaporproof barriers. Five sample units or the number of units contained within the shipping container (if less than five) shall be selected.

4.5.3.2 Failures. One or more failures shall be cause for rejection of the lot.

4.5.3.3 Disposition of sample units. Sample units which have passed the inspections specified in table II may be delivered on the contract if the lot is accepted and opened packs have been reprocessed.

4.5.3.4 Noncompliance. If a sample fails to pass the inspections specified in table II, the contractor shall take corrective action on the materials or processes or both, as warranted, on all unit, intermediate, and exterior (shipping) packs which can be corrected and which were processed under essentially the same conditions, with essentially the same materials, and which are considered subject to the same failure. Acceptance of the unit, intermediate, and exterior packs shall be discontinued until corrective action has been taken and the applicable inspections specified in table II have been repeated on additional sample units. (All inspections or the inspection which the original sample failed shall be at the option of the Government.) Inspections specified in table II may be reinstituted; however, final acceptance shall be withheld until the reinspection in accordance with table II has shown that the corrective action was successful. In the event of failure after reinspection, information concerning the failure and corrective action taken shall be furnished to the administrative contracting officer.

4.6 Methods of inspections and tests.

4.6.1 Visual and dimensional inspections. Unit, intermediate, and exterior packs shall be examined to verify that the materials, designs, methods, physical limitations, marking, and workmanship are in accordance with the applicable requirements (see 3.1 through 3.6).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:34Z
Check the source to verify that this is the current version before use.

4.6.2 Functional tests.

4.6.2.1 Rough handling. Packs shall be subjected to the applicable rough handling tests and the interpretation of results or cause for rejection as specified in 3.5.1.1 and MIL-P-116.

4.6.2.2 Leakage. When a waterproof or water-vaporproof barrier is required, the unit pack shall be subjected to the applicable leakage test and interpretation of results specified in 3.5.1.2 and MIL-P-116.

5. PACKAGING.

This section is not applicable to this specification.

6. NOTES

* (This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

* 6.1 Intended use. The preservation, packing, and marking specified herein are intended for direct shipments to the Government. The general requirements (3.1) and marking requirements (3.4) are applicable for the preparation of all microcircuits covered by military specifications or drawings for shipment from the parts manufacturer to non-Government activities.

* 6.2 Acquisition requirements. Acquisition documents must specify the following:

* a. Title, number, and date of the specification.

* b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1).

c. If shielding from magnetic or radioactive fields is required (see 3.1.2).

d. Levels of preservation and packing (see 3.2 and 3.3).

* e. When multiple item unit packs are required (see 3.2.1.4.2).

* f. Quantity per unit pack, if other than specified (see 3.2.1.4.2 and 3.2.3).

* g. Whether any other standard or special marking is required (see 3.4.1).

h. If FED-STD-123 is required for civil agency marking (see 3.4.1).

i. Whether a rough handling test is required (see 3.5.1.1).

j. Whether microcircuit functional tests are required (see 3.5.1.1).

k. Whether the contractor is not responsible for the performance of all inspection requirements (see 4.1).

l. Whether first article inspection is required (see 4.4).

Source: https://assist.dla.mil -- Downloaded: 202610-22T23:34Z
Check the source to verify that this is the currenversion before use.

* 6.3 First article. The sample pack submitted for first article inspection (when satisfactorily performed as specified in 4.4) will serve as the production standard for subsequent packaging operations. The contractor should inform the acquisition activity or the activity administering the contract of the time and location of this specification so that the Government representative will have an opportunity to witness the tests.

* 6.4 Conditions for use of level B preservation. When level B preservation is specified (see 3.2), this level of protection should be reserved for the acquisition of microcircuits for resupply worldwide under known favorable conditions or for assembly line type operations or other large scale use (see 3.2.2).

* 6.5 Subject term (key word) listing.

Carrier
Electromagnetic protection
Electrostatic protection
Environmental field force protection
Field force protection
Integrated circuits
Microcircuits
Packaging
Packing
Physical protection
Preservation
Sensitive electronic devices
Shielding
Special marking

* 6.6 Changes from previous issue. The margins of this specification are marked with asterisks to indicate those paragraphs where changes (additions, modifications, and corrections) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 99
DLA - ES

Review activities:
Army - AR, MI
Navy - AS, MC
Air Force - 11, 17, 80, 85

User activities:
Navy - OS, SH

Civil agency coordinating activity:
NASA - NA

Preparing activity:
Army - CR

Agent:
DLA - ES

(Project PACK-0885)

Source: https://assist.dla.mil -- Downloaded: 202610-22T23:34Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-M-55565C	MICROCIRCUITS, PACKAGING OF

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
	☐ USER
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ MANUFACTURER
	☐ OTHER *(Specify)*:

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 62 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 202610-22T23:34Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provi suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, as mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY
AMSEL-ED-TO
Fort Monmouth, NJ 07703-5000

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY CARD
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Communications-Electronics Command
ATTN: AMSEL-ED-TO
Fort Monmouth, NJ 07703-5000

Source: https://assist.dla.mil -- Downloaded: 202610-22T23:34Z
Check the source to verify that this is the current version before use.