INCH-POUND

MIL-PRF-52955D
w/AMENDMENT 1
13 April 2015
SUPERSEDING
MIL-PRF-52955D
7 April 2009

PERFORMANCE SPECIFICATION

IMPROVED POSITION AND AZIMUTH DETERMINING SYSTEM (IPADS)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1 SCOPE

1.1 Scope. This specification covers an improved position and azimuth determining system, which is an inertial surveying system that may be Global Positioning System (GPS) aided.

1.2 Requirements. Threshold (T) requirements are the minimum acceptable requirements. Objective (O) requirements indicate desired performance and must be met when specified in the solicitation (6.2). Unless specifically identified as (O), all requirements are (T).

2 APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements documents cited in section 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

Comments, suggestions, or questions on this document should be addressed to the Commander, U.S. Army ARDEC, ATTN: RDAR-EIQ-SA, Picatinny, NJ 07806-5000 or emailed to ardecstdzn@conus.army.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

A-A-52567	Survey Instrument Automated, Integrated (AISI)
A-A-52573	Theodolites, Surveying, Direction: Third Order
A-A-52574	Theodolites, Surveying, Direction: Second Order

DEPARTMENT OF DEFENSE

MIL-DTL-55116/2	Connector, Plug, Six Pin Audio, Crimp Sleeve Terminals, Wire Strain Relief, U-229 Type

STANDARDS

FEDERAL

FED-STD-595/34083	Colors Used In Government Procurement

DEPARTMENT OF DEFENSE

MIL-STD-130	Identification Marking of U.S. Military Property
MIL-STD-461	Requirements for the Control of Electromagnetic Interference Characteristics of Subsystems And Equipment
MIL-STD-464	Electromagnetic Environmental Effects
MIL-STD-810	Environmental Engineering Considerations and Laboratory Tests
MIL-STD-1275	Characteristics of 28 Volt DC Electrical Systems in Military Vehicles
MIL-STD-1472	Human Engineering
MIL-STD-1474	Noise Limits

HANDBOOKS

DEPARTMENT OF DEFENSE

MIL-HDBK-781	Reliability Test Methods, Plans and Environments for Engineering, Development, Qualification and Production
MIL-HDBK-783	Chemical and Biological (CB) Contamination Avoidance and Decontamination
MIL-HDBK-784	Design to Minimize Contamination and to Facilitate Decontamination of Military Vehicles and Other Equipment: Interiors and Exteriors

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

(Unless otherwise indicated, copies of the above specifications, standards and handbooks are available from the Standardization Document Order Desk, 700 Robbins Avenue, Bldg. 4D, Philadelphia, PA 19111-5094. They also may be downloaded from http://quicksearch.dla.mil/.)

2.2.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications, form a part of this document, to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

SAAL-RP 4 Jan 2000	MEMORANDUM, SUBJECT: Development, Acquisition and Fielding of Weapon and Information Systems with Batteries

(This document may be accessed at: http://lrc7.monmouth.army.mil/QuickPlace/ipm/PageLibrary85256AE1004DB1FD.nsf/h_Toc/8A26328FBC6148FE85256BAB006763E7/?OpenDocument)

	Army Guide On Selection/Approval of Portable/Mobile Power Sources

(This document may be obtained from Program Manager, Joint lightweight 155mm Howitzer, Building 151, Picatinny Arsenal, NJ 07806-5000.)

FGDC-STD-007.2	Geospatial Positioning Accuracy Standards Part 2: Standards for Geodetic Networks

(This document may be downloaded from http://www.fgdc.gov/standards/projects/FGDC-standards-projects/accuracy/part2/index_html/?searchterm=Geospatial Positioning Accuracy Standards.)

FSS-SS-0011-ICD	Improved Position And Azimuth Determining System Interface Control Document for the Forward Observer System

(This document may be obtained from Program Manager, Joint lightweight 155mm Howitzer, Building 151, Picatinny Arsenal, NJ 07806-5000.)

	NGA/NASA EGM96, N=M=360 Earth Gravitational Model

(EGM96 documentation and data files may be downloaded from http://earth-info.nga.mil/GandG/wgs84/gravitymod/egm96/egm96.html.)

NIMA TR8350.2 Third Edition Amendment 1	Department of Defense World Geodetic System 1984, Its Definition and Relationships with Local Geodetic Systems

(NIMA TR8350.2 may be downloaded from http://earth-info.nga.mil/GandG/publications/tr8350.2/wgs84fin.pdf)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

SEL Form 1183 Feb 2001	System Safety Design Verification Checklist

(SEL Form 1183 can be downloaded from http://www.peostri.army.mil/SAFETY/1183-94b.jsp.)

42 U.S.C. 4321-4370d	National Environmental Policy Act

(This document can be downloaded from http://epw.senate.gov/nepa69.pdf.)

29 C.F.R 1910.145	Specifications for Accident Prevention Signs and Tags

(29 C.F.R 1910.145 can be viewed at http://www.osha.gov/pls/oshaweb/owadisp.show_document?p_table=STANDARDS&p_id=9794.)

40 C.F.R. 1500-1508	National Environmental Policy Act Regulations

(These regulations can be accessed at http://www.access.gpo.gov/nara/cfr/waisidx_01/40cfrv28_01.html.)

Executive Order 12114	Environmental Effects Abroad of Major Federal Actions

(This document can be downloaded from http://www.archives.gov/federal-register/codification/executive-order/12114.html.)

FM 3-11.5	Multiservice Tactics, Techniques, and Procedures for Chemical, Biological, Radiological, and Nuclear Decontamination

(FM 3-11.5 may be downloaded from http://www.globalsecurity.org/wmd/library/policy/army/fm/3-11-5/fm-3-11-5.pdfor obtained from Program Manager, Joint lightweight 155mm Howitzer, Building 151, Picatinny Arsenal, NJ 07806-5000.)

IS-GPS-153	GPS User Equipment Interface Specification for the GPS Standard Serial Interface Protocol (GSSIP) of DoD Standard GPS UE Radio Receivers
IS-GPS-164	GPS User Equipment Interface Specification for Defense Advanced GPS Receiver (DAGR) Unique Interface Characteristics

(Application for copies of these documents may be made to the GPS Wing Program Library, 483 North Aviation Blvd., El Segundo, CA 90245-2808)

2.3 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI)

ANSI C63.16-1993	American National Standard Guide for Electrostatic Discharge Test Methodologies and Criteria for Electronic

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

Equipment

(Application for copies should be addressed to American National Standards Institute, 1819 L Street NW, Suite 600, Washington, DC 20036. http://webstore.ansi.org)

GENERAL MOTORS CORPORATION

GM9540P	Accelerated Corrosion Test

(Application for copies should be addressed to Global Engineering Documents, 15 Inverness Way East, Englewood, CO 80112. http://global.ihs.com/)

SOCIETY OF AUTOMOTIVE ENGINEERS, INC.

SAE ARP 1199	Selection, Application, and Inspection of Electric Overcurrent Protective Devices (DoD Adopted).

(Application for copies should be addressed to the Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale, PA 15096. http://www.sae.org/servlets/productDetail?PROD_TYP=STD&PROD_CD=ARP1199B)

VT MILTOPE

Maintenance Support Device (MSD) Data Sheet

(This document may be downloaded fromhttp://mymiltope.com/pdf/datasheets/MyMiltope_MSD-V3_Datasheet_w.pdf)

TELECOMMUNICATION INDUSTRY ASSOCIATION (TIA)

TIA-232-F	Interface Between Data Terminal Equipment and Data Circuit-Terminating Equipment Employing Serial Binary Data Interchange

(TIA documents may be ordered from http://www.tiaonline.org, or from Telecommunications Industry Association, Standards and Technology Department, 2500 Wilson Blvd., Arlington VA 22201.)

2.4 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3 REQUIREMENTS

3.1 Design verification. When specified in the contract, (6.2), a sample of the IPADS shall be subjected to design verification in accordance with 4.2.

3.2 First article. When specified in the contract (6.2), a sample of the IPADS shall be subjected to first article inspection in accordance with 4.3.

3.3 Performance characteristics.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

3.3.1 External signals. IPADS shall not solely use external, electromagnetic signals in the determination of position and azimuth.

3.3.1.1 GPS signals. IPADS may use data derived from Y-code GPS signals to aid in meeting objective requirements. When selected by the operator, IPADS may use data derived from Y-code or P-code GPS signals to aid in meeting objective requirements. IPADS shall not use data derived from C/A code GPS signals for survey operations. IPADS may use data derived from C/A code GPS signals while in transport mode. When using GPS data, IPADS shall meet the requirements for the selected operating mode (3.3.6.1 and 3.3.6.2)

3.3.1.1.1 Loss of GPS signals. Loss, intentional and unintentional jamming, and spoofing of GPS signals shall not degrade IPADS performance outside of threshold requirements.

3.3.2 Geographic area of operation. IPADS shall operate as specified herein throughout the latitude range of 75º South to 75º North (T), 80º South to 84º North (O.)

3.3.3 Local operational area. IPADS shall perform as specified herein when operated within a circle of 75 Km (T), 100 Km (O) radius, minimum, centered on the initialization point or subsequent update point.

3.3.4 Vehicle dynamics and attitudes. IPADS shall perform as specified herein when operated within the following envelopes for vehicle dynamics and attitudes:

a. Horizontal velocity, ground speed: 0 to 150 knots, in any direction.

b. Vertical velocity: 0 to 2400 feet per minute.

c. Acceleration: 0 to 3g in any direction.

d. Angular velocity: 0 to 140º per second around any axis.

e. Pitch (longitudinal vehicle axis): -85º to +85º from the horizontal.

f. Roll (transverse vehicle axis): -180º to +180º from the horizontal.

3.3.4.1 Base motion while stationary. IPADS shall perform as specified herein when the host vehicle, while nominally stationary, is subject to wind buffeting, normal crew movement, engine vibration, vibration from engine/generator sets, and other sources of motion usually found on the battlefield.

3.3.5 Initialization. Initialization time begins at IPADS power turn-on and ends when the system is fully initialized and ready to start a survey.

3.3.5.1 Normal initialization.

3.3.5.1.1 Normal Initialization Time. While nominally stationary (3.3.4.1), IPADS initialization time shall not exceed the values shown in Table I.

3.3.5.1.2 Initial coordinate accuracy. IPADS shall be capable of meeting the normal initialization time requirements of 3.3.5.1.1 when provided initial coordinates accurate to 100 meters, horizontal, and 10 meters, vertical. IPADS shall meet the accuracy requirements of 3.3.7 after position has been updated at a Survey Control Point (SCP) and initialization is complete. The SCP may be remote from the initialization site.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

3.3.5.1.3 Initialization site. IPADS shall initialize and operate as specified herein when moved to any location within the geographic area of operation regardless of where it was last turned off. IPADS may be powered on before or after reaching the initialization site.

3.3.5.2 "Hot start" initialization. If not moved since the last shutdown, IPADS shall be capable of being initialized, without requiring position data entry, within the "hot start" initialization time specified in Table I. "Hot start" initialization time begins at IPADS power turn-on and ends when the system is fully initialized and ready to start a survey.

3.3.5.2.1 Excessive motion. IPADS shall automatically revert to normal initialization if it was moved and cannot meet the survey accuracies specified in Table I with "hot start" initialization.

3.3.5.3 Moving base initialization. When acceptable GPS data are available and IPADS is moving, IPADS shall meet the accuracy requirements of 3.3.7 when initialization is complete.

3.3.5.3.1 Interrupted normal initialization. When normal initialization is interrupted by motion, IPADS shall continue to initialize if acceptable GPS data are available.

3.3.5.3.2 Interrupted moving base initialization. When the host vehicle is stopped during moving base initialization, initialization shall revert to normal initialization.

3.3.5.3.3 Interrupted GPS reception. Initialization shall continue when GPS reception is restored after interruption during moving base initialization.

3.3.6 Operating modes.

3.3.6.1 High order survey. IPADS shall have a high order survey mode.

3.3.6.2 Lower order survey. IPADS shall have a lower order survey mode.

3.3.6.3 Unadjusted survey. IPADS shall operate as specified herein when furnished no information other than the horizontal position and elevation coordinates of the starting point entered during initialization.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

TABLE I. IPADS performance requirements.

Latitude of Operation		**0° - 65° N/S**		**65° -75° N/S (T) 80° - 65° S, 65° - 84° N (O)**	
Survey Order		**High**	**Lower**	**High**	**Lower**
Initialization Time (minutes)		10.0	10.0	20.0	20.0
"Hot Start" Initialization Time (minutes)		5.0	5.0	10.0	10.0
Zero-velocity update interval (minutes)		5.0 (T) 10.0 (O)	10.0 (T) 20.0 (O)	5.0 (T) 10.0 (O)	10.0 (T) 20.0 (O)
Horizontal position (meters)	CEP	4.0	7.0	4.0	7.0
	99% radial errors	10.4	18.2	10.4	18.2
Elevation (meters)	PE	2.0	3.0	2.0	3.0
	99% errors	±7.8	±11.7	±7.8	±11.7
Azimuth error (mils)	PE	0.4	0.4	0.6	0.6
	99% errors	±1.6	±1.6	±2.3	±2.3

3.3.6.4 Adjusted survey. IPADS shall adjust the data for a survey traverse leg, to minimize error, when provided with the known coordinates of the SCP ending the leg, when no GPS aiding was used throughout the leg. IPADS shall not adjust the data for a survey traverse leg when GPS aiding was used during any portion of the leg.

3.3.6.5 Transport mode. IPADS shall have a transport mode which can be activated after IPADS has been initialized. While in transport mode, IPADS shall:

a. Not request ZUPT stops.

b. Maintain the selected GPS aiding mode.

c. Inhibit survey marking if accuracy for the selected survey order can not be maintained.

d. Inhibit survey marking if GPS aiding using data derived from C/A code signals is used.

e. Allow the operator to exit transport mode.

f. Require a position update before enabling survey marking if required to restore accuracy of the selected survey order.

g. Require a position update before enabling survey marking if GPS aiding using data derived from C/A code signals was used.

h. Enable survey marking when accuracy of the selected survey order is available.

3.3.7 Accuracy. The allowable errors specified below include errors associated with transfer of horizontal position, elevation, and azimuth to and from IPADS and apply to both unadjusted and adjusted traverse operations. For no GPS aiding or GPS relative aiding, accuracy is relative

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

to the SCP used to initialize or update IPADS at the start of the survey traverse leg. For GPS-centric aiding, accuracy is relative to the World Geodetic System 1984 (WGS 84).

3.3.7.1 Horizontal position. Horizontal position circular error probable (CEP) shall not exceed the values specified in Table I . 99 percent or more of individual horizontal position radial errors shall be within the ranges specified in Table I .

3.3.7.2 Elevation. Elevation probable error (PE) shall not exceed the values specified in Table I. 99 percent or more of individual elevation errors shall be within the ranges specified in Table I.

3.3.7.2.1 Height-Above-Ellipsoid (HAE)/Mean-Sea-Level (MSL) conversion. The error introduced by converting between HAE and MSL shall not exceed the error inherent in geoid undulations calculated by bi-linear interpolation of the NGA/NASA EGM96 (Earth Gravity Model 1996) 30’ x 30’ geoid undulation table.

3.3.7.3 Azimuth. Azimuth PE shall not exceed the values specified in Table I . 99 percent or more of individual azimuth errors shall be within the ranges specified in Table I . Azimuth accuracy requirements apply to orienting lines (OLs) 100 meters in length and longer established using a survey instrument (3.4.5,d). Azimuth accuracy requirements apply to OLs within in the range 100 through 400 meters in length established using the two-position method (3.4.5.b).

3.3.8 Operating time. IPADS shall perform as specified herein for 24 continuous hours including initialization time. This requirement does not preclude the operator from extending operating time indefinitely.

3.3.9 Zero-velocity stops. The average required stationary time for a zero-velocity stop shall not exceed 30 seconds. The maximum required stationary time for a zero-velocity stop shall not exceed 60 seconds.

3.3.9.1 Travel intervals. Travel intervals between required zero-velocity stops shall be no less than the values specified in Table I .

3.3.10 Time to update or establish position and azimuth.

3.3.10.1 Position only. The mean time to update or establish horizontal position and elevation shall not exceed 5 minutes using the driver’s interface (3.4.5.a.) The mean time to update or establish horizontal position and elevation shall not exceed 15 minutes using the offset interface (3.4.5.c.) The duration includes the time to perform all crew actions required to establish, physically mark, and record the position.

3.3.10.2 Position and azimuth. The mean time to establish horizontal position, elevation and azimuth shall not exceed 20 minutes using the two-position method or offset interface (3.4.5.b, c, and d.) The duration includes the time to perform all crew actions required to establish, physically mark, and record the azimuth and the positions of both ends of the OL.

3.3.10.2.1 Two-position azimuth movement time. IPADS shall allow a minimum of 60 seconds to move from the OS to the EOL of a 100 meter OL being established using the two-position method. The time allowed to traverse the OL shall be increased proportionally for OLs

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

exceeding 100 meters. The time allowed to move shall not start until the vehicle starts to move from the OS.

3.3.11 Back-up power. IPADS shall include a rechargeable battery that will automatically sustain IPADS operation for not less than 15 minutes after loss of external power at ambient temperatures -22° F (-30° C) and above.

3.3.11.1 Battery charge. IPADS shall automatically charge the back-up battery when the host vehicle power system is outputting sufficient voltage to charge the vehicle battery. After IPADS is operated only on the back-up battery for a minimum of 15 minutes, and host vehicle power is available, the back-up battery shall be sufficiently recharged within 4 hours to support another 15 minutes of IPADS operation with only the back-up battery, at ambient temperatures -22° F (-30° C) and above.

3.3.11.2 Overcharge. IPADS shall not overcharge the back-up battery.

3.3.11.3 Battery replacement. When provided with host vehicle power, IPADS operation shall be maintained while batteries are being replaced.

3.3.12 Power loss. While stationary or moving, IPADS shall not be damaged by:

a. Loss of vehicle power and/or

b. Disconnection or exhaustion of back-up power.

3.3.13 Data retention and maintenance. After normal shutdown or inadvertent loss of primary and back-up power, IPADS shall:

a. Retain all data needed for operation.

b. Retain all survey data. The power-on ellipsoid and datum shall be those last used prior to shutdown.

c. Retain user defined ellipsoid and datum parameters.

d. While stationary, retain data required to perform a “hot start”.

e. Retain critical GPS data (6.3.5.)

f. Maintain current GPS time.

3.3.14 Survey data storage. IPADS shall retain survey data for a minimum of 360 SCPs for later recall (3.4.4.3.z), survey adjustment (3.3.6.4), The minimum data set for each SCP shall contain: SCP identifier, horizontal position, elevation, mark identifier(s), azimuth(s), and any other data required for survey adjustment.

3.3.15 Information security. IPADS shall not:

a. Permit external devices to access or alter IPADS software or firmware, except for intentional reprogramming (3.6.8.7.)

b. Permit external devices to interfere with IPADS operation.

c. DELETED.

d. Contain malicious code, viruses, or trap doors.

e. Retain GPS cryptovariables except in a GPS Wing approved SAASM.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

f. Permit external access to classified GPS information.

3.3.16 Vehicle-to-vehicle transfer. An operating IPADS shall be transferable from one host vehicle to another, by a two-person crew, and be ready to continue the mission in the second vehicle within 10 minutes, without losing information or requiring reinitialization. Installation hardware and cables may be pre-installed in ground vehicles to meet this requirement.

3.3.17 Visibility. IPADS controls and displays shall be visible under conditions ranging from full darkness to direct, bright sunlight.

3.3.17.1 Night vision. IPADS shall be operable by personnel wearing night vision goggles. Night vision of personnel in the vicinity of IPADS shall not be degraded, whether they are wearing night vision goggles or not.

3.3.17.2 Blackout. IPADS shall be operable under blackout conditions. When operated under blackout conditions, no part of IPADS shall be visible at distances 10 meters and greater from the center of the system.

3.4 Interface and Interoperability requirements.

3.4.1 Mechanical interface requirements. When installed in a host vehicle, the IPADS shall operate without interference with or from normal operation of the host vehicle or vehicle accessories.

3.4.1.1 Installation. IPADS shall mount in all host vehicles, see 3.4.1.1.1, utilizing additional interface hardware (installation kit), if required. Interface hardware (installation kit(s)) shall be provided for host vehicle(s) specified in acquisition documents (6.2). Installation kits shall contain all hardware items and electrical cables necessary to install and operate IPADS in the specified host vehicle(s).

3.4.1.1.1 Ground vehicles. IPADS shall interface with the host ground vehicles listed below. Host vehicle modifications must be approved by the Government (T.) No permanent modification to the host vehicle is permitted (O.)

a. Utility Truck: Cargo/Troop carrier, 1-1/4 ton, 4 x 4, M998
b. Truck, Utility: Heavy Variant, 10,300 GVW, 4 x 4, M1123
c. Truck, Utility: Expanded Capacity, Armament Carrier, IAP/Armor Ready, M1151A1, with and without B-kit perimeter armor installed.
d. Truck, Utility: Expanded Capacity, Enhanced, IAP/Armor Ready, M1152A1, with and without B-kit perimeter armor installed.
e. Carrier, cargo, 1-1/2 Ton, M973 Small Unit Support Vehicle (SUSV).

3.4.1.1.2 Transport aircraft. IPADS installed in a ground host vehicle shall be transportable when sling hoisted by the aircraft listed below. When transported, IPADS may be non-operating or operating from its backup batteries and the ground vehicle batteries.

a. Aircraft, Rotary Wing, Cargo-Transport: CH-46, CH-47 and CH-53.

3.4.1.1.3 GPS antenna. The GPS antenna shall be mounted so that it has clear sky visibility. The antenna and mount shall be retained in place throughout the full range of vehicle

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

dynamics. The antenna, cable and mount shall not be damaged and shall be retained in place during and after contact with foliage, brush, etc.

3.4.2 Power interface.

3.4.2.1 Ground vehicle power. IPADS shall function as specified herein when provided with power from a vehicle power system meeting the requirements of MIL-STD-1275 under fault free and single fault conditions.

3.4.2.1.1 Multiple fault conditions. IPADS shall not be damaged by multiple fault malfunction of the host vehicle power system as specified in MIL-STD-1275.

3.4.2.1.2 Power connection. IPADS shall obtain power from the host vehicle battery or other available terminals. IPADS also shall be capable of obtaining power from the host vehicle NATO receptacle, where available.

3.4.2.2 Reverse polarity. IPADS shall not be damaged from reverse polarity connection of DC power.

3.4.2.3 Power consumption. IPADS shall consume no more than 150 watts from the host vehicle, including any power required to (re)charge IPADS batteries.

3.4.2.4 Power disconnect. IPADS shall provide a capability to draw no power from the host vehicle without disconnecting cables or removing fuses.

3.4.3 Digital interfaces.

3.4.3.1 Digital data interface. DELETED.

3.4.3.1.1 Hot connect/disconnect. DELETED.

3.4.3.1.2 Time synchronization. DELETED.

3.4.3.2 Reprogramming interface(s). IPADS shall interface to a Maintenance Support Device (MSD) or equivalent to reprogram all Line Replaceable Units (LRUs) and Shop Replaceable Units (SRUs), which utilize software or firmware. Reprogramming cables shall be provided for those reprogramming devices specified in acquisition documents (6.2).

3.4.3.3 Cryptographic key loading interface. The IPADS shall accept and utilize valid GPS cryptographic keys provided by an AN/CYZ-10 Data Transfer Device (DTD) and an AN/PYQ-10(C) Simple Key Loader (SKL) through a standard cryptofill cable.

3.4.3.3.1 Key fill connector. IPADS shall have a key fill connector that mates with a cable having a MIL-DTL-55116/2 connector. The key fill connector shall be accessible for connection to DTD and SKL key loading devices with IPADS installed in the host vehicle. Connector pin designations are specified below.

Pin	Function
A	Ground
B	TIA-232 Flow control out (output from GPS receiver to key loading device)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

C	TIA-232 Receive (input to GPS receiver from key loading device)
D	TIA-232 Transmit (output from GPS receiver to key loading device
E	TIA-232 Flow control input (input to GPS receiver from key loading device)

3.4.3.4 GPS initialization interface. IPADS shall accept transfer of position, ephemeris, and precision timing data from a Defense Advanced GPS Receiver (DAGR) to initialize the internal GPS receiver for direct Y-code acquisition.

3.4.3.4.1 Serial data interface. The GPS initialization interface shall have a TIA-232 compatible serial data port.

3.4.3.4.2 Message protocol. The initialization interface message and data protocols shall conform to IS-GPS-153D.

3.4.3.4.3 Timing pulse input. The initialization interface shall accept one pulse per second (1 PPS) timing pulses meeting the electrical requirements of the IS-GPS-164 COM1 PPS output.

3.4.3.4.4 External GPS receiver interconnection. IPADS shall have an initialization interface connector compatible with a DAGR-to-DAGR/PLGR Cable, as specified in IS-GPS-164, or shall include an adapter cable compatible with the COM1 serial data and PPS output interfaces on DAGR J2, as specified in IS-GPS-164.

3.4.3.4.5 Hot connect/disconnect. IPADS shall not be damaged or cause damage to the interfacing GPS receiver and IPADS operation shall not be interrupted when the GPS initialization interface is connected and disconnected while IPADS is operating. IPADS shall automatically accept transfer of GPS initialization data when transfer is initiated by the GPS receiver.

3.4.4 Control and display interface. IPADS shall provide a control and display interface for the operator. From a single location, the operator shall be able to control the IPADS mode of operation; accomplish data entry, readout, and update; observe system status; display survey and other operational parameters

3.4.4.1 Control and display location. The control and display interface shall be visible and accessible for hands-free operation (except for data entry and selection procedures) by both the vehicle driver and IPADS operator (not necessarily at the same time).

3.4.4.2 Display parameters. IPADS shall display:

a. Survey control point identifier.
b. Universal Transverse Mercator (UTM) easting, northing and grid zone.
c. Latitude and longitude.
d. Military Grid Reference System (MGRS) (see Appendix B) (O).
e. Elevation.
f. Mark identifier.
g. Azimuth.
h. Distance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

i. Angle.

j. Ellipsoid display name.

k. Semi-major axis, flattening or semi-minor axis indicator, and semi-minor axis or inverse flattening of user defined ellipsoids.

l. Datum display name.

m. X, Y, Z-shifts for user defined datums.

n. Current date and time of day.

o. Date and time of day a SCP or Mark was established.

p. Unadjusted or adjusted survey indicator for stored SCP data.

q. IPADS and GPS receiver software version(s).

r. GPS warning messages.

s. Estimated Horizontal Error (EHE) and Estimated Vertical Error (EVE).

t. Number of healthy, visible, GPS satellites.

u. Number of healthy GPS satellites being tracked, displayed by code type.

v. Number of GPS satellites used in the solution, displayed by code type.

w. GPS cryptographic key type and number of days keys are valid.

x. GPS almanac age.

y. Overall indication of received signal carrier-to-noise ratio (C/N_0), low or Ok.

z. All other parameters required to operate IPADS.

3.4.4.2.1 Display field characteristics. Characteristics of display fields shall be as specified in Appendix A.

3.4.4.2.2 Survey data page. Survey control point identifier, horizontal position, elevation, mark identifier, azimuth, distance from last initialization or update point (if displaying survey in progress), length of OL (if displaying saved survey data), ellipsoid name, and datum name shall be displayed on a single page.

3.4.4.2.3 Display field selection. At any time, IPADS shall allow the operator to select display of:

a. Geodetic (T), UTM (T), or MGRS (O) horizontal coordinates.

b. UTM coordinates with respect to the normal or adjacent zone, when horizontal position is within 40 Km of a UTM zone boundary.

c. Grid or geodetic (true) azimuth.

d. Azimuth in mils; degrees, minutes and seconds; or decimal degrees.

e. User ellipsoid inverse flattening or semi-minor axis.

f. Geodetic coordinates in decimal degrees or degrees, minutes, and seconds.

3.4.4.2.4 Horizontal position display. Horizontal position shall be displayed with respect to the selected horizontal datum.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

3.4.4.2.5 UTM zone.

a. UTM coordinates shall be displayed with respect to standard, 6° wide longitude zones throughout the UTM coverage area.

b. Within 40 Km of a UTM zone boundary, IPADS shall accept initialization or update UTM coordinates with respect to the normal UTM zone, for that location, or the adjacent (extended) UTM zone. IPADS shall display UTM coordinates with respect to the input zone until the operator changes the zone (3.4.4.2.3.b.) or a normal or extended zone boundary is crossed.

c. The first time a normal UTM zone boundary is crossed from west to east during a mission, IPADS shall prompt the operator to select whether display of UTM coordinates shall remain with respect to the previous zone or shall be with respect to the new zone. For subsequent crossings of the same zone boundary, IPADS shall display UTM coordinates with respect to the previously selected zone for the current side of the boundary.

d. The first time IPADS crosses into an extended zone from east to west during a mission, IPADS shall prompt the operator to select whether display of UTM coordinates shall remain with respect to the current (normal) zone or shall be with respect to the adjacent (extended) zone. For subsequent crossings of the same extended zone boundary, IPADS shall display UTM coordinates with respect to the previously selected zone for the current side of the boundary.

e. When further than 40 Km from a UTM zone boundary, IPADS shall display UTM coordinates with respect to the normal UTM zone for that location.

3.4.4.2.6 Vertical datum. Elevation shall be displayed with respect to the local vertical (msl) datum when no GPS aiding or relative GPS aiding is used. Elevation shall be displayed with respect to the WGS 84 geoid when GPS-centric aiding is used. Elevation shall not be transformed between datums.

3.4.4.3 Operator control functions and data entry. IPADS shall allow the operator to:

a. Turn IPADS on and off.

b. Read out survey data from the previous mission, if not previously cleared by the operator.

c. Perform “hot start” initialization (3.3.5.2.)

d. Initialize and update IPADS position using GPS data, if available.

e. Select high or lower order operating mode.

f. Enter and exit transport mode.

g. DELETED.

h. Select the vehicle reference or offset reference for position and azimuth transfer.

i. Establish the relative location of the vehicle reference for different host vehicles.

j. Enter distance for offset position and azimuth transfer.

k. Enter angle for offset azimuth transfer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

l. Enter date and time.

m. Initialize date and time to GPS UTC time, within two seconds, when GPS time is available

n. Enter survey control point identifiers. If the operator does not enter a survey control point identifier, IPADS shall populate the field with an unambiguous identifier.

o. At any time, select ellipsoid and horizontal datum from preprogrammed table of all datums listed in NIMA TR8350.2 without requiring reinitialization or a position update.

p. At any time, select ellipsoid from preprogrammed table of all ellipsoids listed in NIMA TR8350.2 and enter shift parameters for two user-defined horizontal datums without requiring reinitialization or a position update.

q. At any time, enter ellipsoid and shift parameters for two user-defined horizontal datums without requiring reinitialization or a position update.

r. At any time, initialize and update horizontal position coordinates and elevation.

s. Enter mark identifiers. If the operator does not enter a mark identifier, IPADS shall populate the field with an unambiguous identifier.

t. Establish the position of a survey control point, except when accuracy for the selected survey order can not be maintained.

u. Associate up to four azimuth marks with a survey control point

v. Establish the azimuth of an orienting line, except when accuracy for the selected survey order can not be maintained.

w. Save survey control point data.

x. Display current IPADS position and heading.

y. Display current GPS position, if available, with EHE, and EVE. GPS position shall be with respect to the driver's position transfer interface (3.4.5.a.)

z. Display data for any saved survey control point.

aa. Delete data for any saved survey control point.

bb. Delete data for all saved survey control points.

cc. When GPS aiding wasn't used, adjust all survey control points on a survey traverse leg for closure.

dd. DELETED.

ee. DELETED.

ff. Adjust control and display lighting intensity.

gg. Turn the audible alarm on and off.

hh. Select GPS aiding mode from: No GPS Aiding, GPS Centric Aiding, and GPS Relative Aiding. GPS Centric Aiding shall be the power on default.

ii. Select use of All Y-code or Mixed Y and P-code GPS signals. All Y-code shall be the power-on default.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

jj. Zeroize GPS cryptovariables.

kk. Zeroize GPS cryptovariables and all classified GPS data (typically called “Emergency Zeroization).

3.4.4.4 Status indications. IPADS shall indicate to the operator:

a. Operational status (BIT) of all LRUs.

b. Status of vehicle power and backup power.

c. DELETED.

d. Requirements to stop the vehicle or remain stationary, both audibly and visually.

e. Travel time until a stop is required.

f. Time remaining to complete alignment.

g. When a UTM zone boundary or extended zone boundary has been crossed, both audibly and visually.

h. When data entry or other operator action is needed.

i. When a data entry is outside the allowable limits.

j. When an operator entered position update is inconsistent with valid GPS data.

k. After initialization is complete, when an operator entered position update is inconsistent with current IPADS position data.

l. When a dynamic or attitude limit (3.3.4) has been exceeded and IPADS accuracy has been degraded.

m. When initialization has failed or requires additional operator action to complete.

n. High order, lower order or transport operating mode, or when performance is degraded.

o. GPS availability and aiding status.

p. GPS cryptographic key status.

3.4.5 Position and azimuth transfer interfaces. IPADS shall provide interfaces to:

a. Transfer the position of a SCP on the ground to IPADS, from the host ground vehicle driver position.

b. Transfer IPADS determined position and azimuth (two-position method) from the vehicle to points on the ground.

c. Transfer position coordinates in and out of IPADS, from and to a location offset from the host vehicle, using a survey instrument to autoreflect and determine distance to the IPADS. (The survey instrument is not an IPADS component.) The minimum range of transfer distances shall be from 1 to 16 meters. Transfer requirements shall be met when the survey instrument is a mil-reading theodolite, conforming to A-A-52573 or A-A-52574, or a mil-reading Automated Integrated Survey Instrument (AISI), conforming to the basic requirements of A-A-52567. Transfer requirements shall be met when the host ground vehicle is on slopes and side slopes within the range of ±15°. Transfer shall be possible under any visibility conditions greater than 150 meters.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

d. Transfer azimuth from IPADS to an orienting line offset from the host vehicle, using a survey instrument to autoreflect, turn the angle between IPADS and the EOL, and determine distance to the IPADS. The minimum range of transfer distances shall be from 1 to 16 meters. Transfer requirements shall be met when the survey instrument is a mil-reading theodolite, conforming to A-A-52573 or A-A-52574, or a mil-reading, AISI, conforming to the basic requirements of A-A-52567. Transfer requirements shall be met when the host ground vehicle is on slopes and side slopes within the range of ±15°. Transfer shall be possible under any visibility conditions greater than 150 meters.

3.5 Environmental requirements.

3.5.1 Operating conditions. The IPADS operating ambient temperature range shall be -50° F (-46° C), with negligible solar energy, to +125° F (+52° C), with solar radiation to 360 BTU per square foot, per hour. When the IPADS temperature is below -22° F (-30° C), initialization may be delayed until heat from the vehicle has warmed IPADS to -22° F (-30° C). Use of vehicle heating does not apply to the GPS antenna. IPADS shall not allow survey operations until it has warmed sufficiently to initiate initialization, with full performance, and shall notify the operator when initialization has been delayed by extreme cold temperature. If easily replaceable by personnel wearing arctic clothing, the Control and Display Unit, only, may have an operating ambient temperature range from -22° F (-30° C), with negligible solar energy, to +125° F (+52° C), with solar radiation to 360 BTU per square foot, per hour.

3.5.2 Storage conditions. The IPADS storage ambient temperature range shall be -50°F (-46° C) to +160° F (71° C) in and out of transit cases. If easily replaceable by personnel wearing arctic clothing, the Control and Display Unit, only, may have a storage ambient temperature range from -40° F (-40° C) to +160° F (71° C) in and out of transit cases.

3.5.3 Atmospheric pressure (elevation).

3.5.3.1 Operational. IPADS shall operate at elevations from 500 feet below to 10,000 feet above sea level.

3.5.3.2 Storage/transport. IPADS, in its transit cases, shall not be damaged when transported or stored at elevations from 500 feet below to 15,000 feet above sea level.

3.5.3.3 Rapid decompression. IPADS, in its transit cases, shall survive rapid decompression from an initial aircraft cabin elevation of 8,000 feet to a final cabin elevation of 40,000 feet.

3.5.4 Dust. IPADS shall not be damaged and shall perform as specified herein during and after a 12 hour exposure with dust concentrations of 0.3 ± 0.2 grams per cubic foot and air velocity from 300 ft/min (1.5 m/s) to 1750 ft/min (8.9 m/s).

3.5.5 Sand. IPADS shall not be damaged and shall perform as specified herein during and after a 90-minute exposure to each exposed surface with sand concentrations of 1.32×10^{-4} lb/ft^3 (2.19×10^{-3} kg/m^3) and air velocity from 3540 ft/min (18 m/s) to 5700 ft/min (29 m/s).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

3.5.6 Rain. IPADS shall operate and not be damaged during and after exposure to rain at a rate not less than 4 in/hr (10 cm/hr) with a wind velocity greater than 40 mph (18 m/s). Compartments containing electronics and other sensitive components shall not contain any water after exposure to rain.

3.5.7 Humidity. IPADS shall not be damaged by operation, transportation, or storage when exposed to ambient relative humidity within the range of 1 to 100 percent (condensing).

3.5.8 Fungus. IPADS shall not be damaged and shall operate after exposure for 28 days to a viable spore suspension containing at least the following fungi: Aspergillus Niger, Aspergillus Flavus, Aspergillus Versicolor, Penicillium Funiculosum, and Chaetomium Globosum.

3.5.9 Salt fog. IPADS shall not be damaged and shall operate during and after 2 weeks of continual exposure to salt fog.

3.5.10 Vibration.

3.5.10.1 Ground vehicle vibration. An operating IPADS shall perform as specified herein and shall not be damaged when exposed to the random vibration profiles in Table II for 40 minutes in each axis.

3.5.10.2 Loose cargo. IPADS LRUs, in their transit cases, shall not be damaged when transported as loose cargo. Transit cases shall show no evidence of damaged seals, impaired structural integrity, malfunctioning latches, damaged carrying devices, and damaged pressure relief valves. Any dents or warpage sustained shall not impair normal opening and closing of the case.

3.5.11 Shock.

3.5.11.1 Operational shock. An operating IPADS shall perform as specified herein and not be damaged when subjected to shocks with peak acceleration of 40 g’s, effective transient duration (T_E) of 15 - 23 ms., and cross over frequency of 45 Hz.

3.5.11.2 Non-operating shock. A non-operating IPADS shall not be damaged when subjected to shocks with peak acceleration of 40 g’s, effective transient duration (T_E) of 15 - 23 ms., and cross over frequency of 45 Hz.

3.5.11.3 Ground vehicle crash hazard shock. All IPADS components shall remain secured and shall not become hazards to personnel and other equipment in the host vehicle when subjected to shocks with peak acceleration of 75 g’s, effective transient duration (T_E) of 8 - 13 ms., and cross over frequency of 80 Hz.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

TABLE II. Composite wheeled vehicle random vibration profiles.

Vertical Axis		Transverse Axis		Longitudinal Axis	
Frequency (Hz)	**PSD (g^2/Hz)**	**Frequency (Hz)**	**PSD (g^2/Hz)**	**Frequency (Hz)**	**PSD (g^2/Hz)**
5	0.2308	5	0.1373	5	0.0605
8	0.7041	9	0.09	6	0.0577
12	0.0527	12	0.0902	8	0.0455
16	0.03	14	0.0427	12	0.0351
20	0.0235	16	0.0496	15	0.0241
22	0.0109	18	0.0229	16	0.035
24	0.0109	119	0.0008	19	0.0092
26	0.0154	146	0.0013	25	0.0159
69	0.0018	166	0.0009	37	0.0041
79	0.0048	201	0.0009	41	0.006
87	0.0028	273	0.0053	49	0.0017
123	0.0063	289	0.0021	105	0.0006
161	0.0043	371	0.0104	125	0.0004
209	0.0057	382	0.0019	143	0.0013
224	0.015	402	0.0077	187	0.0013
247	0.0031	422	0.0027	219	0.0028
278	0.0139	500	0.0016	221	0.0068
293	0.0037	**1.6 g RMS**		247	0.0325
357	0.0028			249	0.0098
375	0.0052			270	0.0026
500	0.0011			293	0.0094
2.18 g RMS				336	0.012
				353	0.0247
				379	0.0085
				431	0.0224
				433	0.0092
				500	0.0014
				1.96 g RMS	

3.5.11.4 Transit drop. IPADS, in its transit case, and IPADS LRUs, in their transit cases, shall not be damaged and shall perform as specified herein after being dropped from the height(s) specified in Table III. Transit cases shall show no evidence of damaged seals, impaired structural integrity, malfunctioning latches, damaged carrying devices, and damaged pressure relief valves. Any dents or warpage sustained shall not impair normal opening and closing of the case.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

TABLE III. Drop height.

Weight lbs (kg)	Largest Dimension, in (cm)	Height of Drop, in (cm)
Under 100 (45.4)	Under 36 (91)	48 (122)
	36 (91) & over	30 (76)
100 – 200 (45.4 - 90.8)	Under 36 (91)	30 (76)
	36 (91) & over	24 (61)
200 – 1000 (90.8 - 454)	No limit	24 (61)

3.5.12 Airdrop. When installed in a host ground vehicle (M998 HMWWV), which has been rigged for airdrop, IPADS shall not be damaged after multiple airdrops from cargo aircraft (see 6.6.)

3.5.13 Leakage. The transit cases shall not leak more than 4 cubic centimeters per 28,000 cubic centimeters when submerged in water to a depth of 6 inches above the highest point.

3.5.14 Electromagnetic interference.

3.5.14.1 Intra-system electromagnetic compatibility (EMC). When installed in host vehicles, IPADS shall meet requirements 5.2 and 5.2.3 of MIL-STD-464. Intra-system electromagnetic compatibility includes compatibility with communications equipment and other electronic equipment in the host vehicles.

3.5.14.2 Electromagnetic pulse (EMP). Operating and non-operating, IPADS shall not be damaged by the radiated transient electromagnetic field specified in MIL-STD-461 requirement RS105. IPADS is not required to remain operating through an EMP event.

3.5.14.3 Subsystems and equipment electromagnetic interference (EMI). IPADS subsystems and equipment shall meet the following requirements.

3.5.14.3.1 Conducted emissions, power leads, 10 kHz to 10 MHz. IPADS power lead conducted emissions shall not exceed the limits of MIL-STD-461 requirement CE102 from 10 kHz to 10 MHz.

3.5.14.3.2 Conducted susceptibility, power leads, 30 Hz to 150 kHz. IPADS power lead conducted susceptibility shall not exceed the limits of MIL-STD-461 requirement CS101 from 30 Hz to 150 kHz.

3.5.14.3.3 Conducted susceptibility, bulk cable injection, 10 kHz to 200 MHz. IPADS bulk cable injection conducted susceptibility shall not exceed the limits of MIL-STD-461 requirement CS114 from 10 kHz to 200 MHz.

3.5.14.3.4 Conducted susceptibility, bulk cable injection, impulse excitation. IPADS bulk cable injection conducted susceptibility to impulse excitation shall not exceed the limits of MIL-STD-461 requirement CS115.

3.5.14.3.5 Conducted susceptibility, damped sinusoidal transients, cables and power leads, 10 kHz to 100 MHz. IPADS cable and power lead conducted susceptibility to damped

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

sinusoidal transients shall not exceed the limits of MIL-STD-461 requirement CS116 from 10 kHz to 100 MHz.

3.5.14.3.6 Radiated emissions, magnetic field, 30 Hz to 100 kHz**.** IPADS magnetic field radiated emissions shall not exceed the limits of MIL-STD-461 requirement RE101 from 30 Hz to 100 kHz.

3.5.14.3.7 Radiated emissions, electric field, 10 kHz to 18 GHz**.** IPADS electric field radiated emissions shall not exceed the limits of MIL-STD-461 requirement RE102 from 10 kHz to 18 GHz, with no reduction in the upper limit.

3.5.14.3.8 Radiated susceptibility, magnetic field, 30 Hz to 100 kHz**.** IPADS magnetic field radiated susceptibility shall not exceed the limits of MIL-STD-461 requirement RS101 from 30 Hz to 100 kHz.

3.5.14.3.9 Radiated susceptibility, electric field, 2 MHz to 18 GHz**.** IPADS electric field radiated susceptibility shall not exceed the limits of MIL-STD-461 requirement RS103 from 2 MHz to 18 GHz.

3.5.14.3.10 Electrostatic charge control. IPADS shall control and dissipate the build-up of electrostatic charges in accordance with requirement 5.7 of MIL-STD-464. When installed in a ground vehicle sling hoisted from a helicopter, IPADS shall meet requirement 5.7.1 of MIL-STD-464.

3.5.14.4 Electrical bonding. IPADS shall meet requirements 5.10, 5.10.1, 5.10.2, 5.10.3 and 5.10.4 of MIL-STD-464.

3.5.15 Nuclear, Biological & Chemical (NBC) Survivability. IPADS and transit cases shall survive NBC contamination and decontamination. NBC contaminants remaining on, desorbed from, or re-aerosolized from exposed surfaces after decontamination using standard field decontaminates, equipment and procedures, shall result in no more than a negligible risk to unprotected personnel working one meter from the IPADS. MIL-HDBK-784 provides guidance. An overview of potential threat agents, available decontamination and contamination avoidance countermeasures, and design and material selection guidelines which will enable design of systems which can operate effectively in a CB-agent-contaminated environment is given in MIL-HDBK-783. FM 3-11.5 describes decontamination operations.

3.6 Support and ownership requirements.

3.6.1 Design, materials and manufacturing processes. Unless otherwise specified, the design, materials, and manufacturing processes selected are the prerogative of the contractor provided they fully meet the operating, interface, ownership and support, and environmental requirements specified herein.

3.6.1.1 Battery selection. All battery(ies) shall be available from Army inventory and shall have been approved for IPADS use in accordance with the policy stated in MEMORANDUM SAAL-RP, SUBJECT: Development, Acquisition and Fielding of Weapon and Information Systems with Batteries, 4 Jan 2000, and Army Guide On Selection/Approval of Portable/Mobile Power Sources.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

3.6.1.1.1 Memory battery. If a battery is used to retain critical GPS data or maintain current GPS time (3.3.13.e and 3.3.13.f):

a. The memory battery shall have a useful lifetime of one year or longer.
b. The memory battery shall be replaceable by the operator, within 120 seconds, if its lifetime is less than ten years.
c. IPADS shall notify the operator when the memory battery must be replaced. Notification shall be initiated before the battery is depleted to the extent that GPS data could be lost if primary and back-up power were removed.
d. IPADS shall retain critical GPS data and maintain GPS time if the memory battery is removed and primary or back-up power is supplied.

3.6.1.2 Color. The color of IPADS and transit case external surfaces shall be in accordance with FED-STD-595/34083.

3.6.1.3 Connector caps. Connector caps shall be provided for all connectors that are not mated during all normal IPADS operations. Connector caps shall be tethered to IPADS near the applicable connector.

3.6.2 GPS receiver. The IPADS GPS receiver shall incorporate a Selective Availability/Anti-Spoofing Module (SAASM) and be approved for use by the GPS Wing.

3.6.2.1 M-Code. IPADS shall provide a migration path for an M-Code receiver.

3.6.3 Interchangeability. All parts having the same part number shall be functionally and dimensionally interchangeable.

3.6.4 Nameplates and Product Marking. An identification plate shall be permanently attached to each IPADS LRU. Identification plates shall be marked in accordance with MIL-STD-130 with the following information:

a. Nomenclature.
b. Design activity CAGE or NCAGE and PIN.
c. Manufacturer's identification, if different from the design activity CAGE or NCAGE.
d. Acquisition instrument identification number.
e. Serial number.
f. U.S.
g. NSN.

3.6.4.1 Item unique identification (IUID). IUID designated items, identified in the contract or delivery order, shall be marked with Machine Readable Information (MRI) in accordance with MIL-STD-130. (6.2.)

3.6.5 Transit cases.

3.6.5.1 IPADS transit case. A transit case shall be provided with each IPADS end item.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

3.6.5.1.1 Size. Transit case dimensions shall not exceed 38.7 inches (98.3 Cm) in height, 39.5 inches (100.3 Cm) in width, and 37.3 inches (94.7 Cm) in depth.

3.6.5.1.2 Weight. The transit case weight shall not exceed 205 lb. (93.2 kg.) If the loaded transit case weight exceeds the criteria for lifting and carrying by six soldiers, the transit case shall have provisions for handling by forklift.

3.6.5.2 LRU transit cases. Transit cases shall be provided for each type of LRU as specified in the contract or delivery order (6.2.)

3.6.5.3 Pressure relief valve. Transit cases shall have an automatic pressure relief valve.

3.6.5.4 Handles. Transit cases shall be fitted with a handle for each soldier (maximum of six) needed to lift and carry the loaded transit case (3.6.11). Each transit case shall have at least one handle. Handles shall be located such that the load is balanced and equally distributed between the carrying soldiers.

3.6.6 Accessory storage. Storage shall be provided on the IPADS for all tools, accessories, cables, supplies, and contractor supplied manuals.

3.6.6.1 Tool kit. All tools necessary to perform routine maintenance and to install the IPADS in the host vehicles shall be supplied. The tools shall be readily accessible and constrained to prevent damage to manuals, accessories, cables, supplies, equipment, and other tools. Tools shall be common hand tools available from Army inventory.

3.6.7 Reliability. The IPADS Mean-Time-Between-Failure (MTBF) shall be 2,400 hours or greater (6.7). Failures attributable to hardware and software shall be included in the computation of MTBF.

3.6.8 Maintenance.

3.6.8.1 Maintenance level. IPADS shall not require scheduled maintenance above the Unit (first echelon) maintenance level.

3.6.8.2 Fault isolation. The IPADS shall possess Built-in Test or Built-in Test Equipment (BIT/BITE) to fault isolate 95 percent of all system abort failures to the single Line Replaceable Unit (LRU) at the organizational level.

3.6.8.2.1 False removal rate. False removal rate shall not exceed 5 percent.

3.6.8.2.2 False alarm rate. False alarm rate for system abort failure BIT/BITE notification shall not exceed 5 percent.

3.6.8.2.3 Fault display. IPADS shall be capable of determining and displaying faults or errors and indicating corrective actions.

3.6.8.3 Replacement time. Any LRU requiring replacement at the unit level shall have a mean time for removing and replacing of 30 minutes or less and require no more than 10 minutes for calibration or adjustment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

3.6.8.4 Maintenance items. Components requiring maintenance or having a limited life (e.g. batteries) shall be maintainable and replaceable without exposing electronics and other sensitive components to the external environment.

3.6.8.5 Special support equipment. IPADS shall not require any special equipment at the user, unit, DS, and GS levels.

3.6.8.6 Calibration and adjustment. Any calibration or adjustment required periodically or after a repair action shall be performed automatically, at the unit level.

3.6.8.7 Reprogramming. All IPADS LRUs and SRUs, which utilize software or firmware, shall be reprogramable using a Maintenance Support Device (MSD) or equivalent IBM-compatible Personal Computer.

3.6.9 Environment, Safety, and Occupational Health (ESOH). IPADS shall not present health hazards to personnel and shall comply with applicable sections of 42 U.S.C. 4321-4370d, 40 C.F.R. 1500-1508, and E.O. 12114.

3.6.10 Safety. IPADS and its transit cases, installation in host vehicles, and operation shall have no hazards with a risk level greater than "Medium" as specified in Table IV.

TABLE IV. Risk level matrix.

Hazard Severity (see Table XI)	**Hazard Probability** (See Table X)				
	Frequent	**Likely**	**Occasional**	**Seldom**	**Unlikely**
Catastrophic	High	High	Serious	Serious	Medium
Critical	High	Serious	Serious	Medium	Medium
Marginal	Serious	Serious	Medium	Medium	Low
Negligible	Serious	Medium	Medium	Low	Low

3.6.10.1 Weight and balance. The host vehicle weight and balance limits shall not be exceeded when IPADS is installed and the vehicle is carrying a crew, the crew's personal equipment and rations, and full range of fuel.

3.6.10.2 Electrical connections. A mistake-proof means to prevent the inadvertent reversing or mismating of electrical connections shall be provided.

3.6.10.3 Electrical overload protection. IPADS and the host vehicle shall be protected from damage resulting from electrical overloads induced by normal or abnormal (fault) IPADS operation and conditions. SAE ARP 1199 provides design guidance.

3.6.10.4 Ground fault protection. When IPADS is connected to 115 VAC power, personnel shall be protected from shock hazards resulting from ground faults. Leakage currents in excess of six milliamperes are considered shock hazards.

3.6.10.5 Battery safety. Battery(ies) shall be firmly secured. Adequate room shall be provided for battery installation, maintenance, testing and removal without disassembly of the equipment. The housing shall prevent pressure build-up from heat, gases, rupture, or chemicals released during battery operation and charging, within the enclosure and shall also prevent such

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

materials from entering the electronic compartment. The design shall preclude build-up of explosive gas concentrations under normal operating and fault conditions.

3.6.10.5.1 Battery installation markings. Connections, polarity, normal voltage, minimum acceptable voltage for equipment operation, and the type of batteries required shall be marked in a prominent place on or near the battery unit.

3.6.10.5.2 Caution labels. The IPADS shall be labeled externally as follows:

CAUTION
REMOVE BATTERIES BEFORE
SHIPMENT
OR
INACTIVE STORAGE OF 30 DAYS OR MORE

If the weight of a component or loaded transit case exceeds 42 pounds, a caution placard or label shall be attached to the component or transit case permanently. Wording shall be as follows:

CAUTION
XX POUNDS
X PERSONS LIFT OR CARRY

Color coding of caution placards or labels shall be in compliance with 29 C.F.R. 1910.145. The caution wordings may be stenciled on the applicable component(s).

3.6.11 Human factors engineering. IPADS shall be operable, maintainable, and supportable in daylight and darkness by 5th percentile female through 95th percentile male soldiers dressed appropriately for the anticipated environments of operation (battle dress uniform, cold/wet weather gear, arctic clothing, and MOPP IV protective equipment).

3.6.11.1 Soldier Performance. IPADS shall be capable of being operated in performance of a mission with less than 5 percent error (to include errors of omission and commission) in performance of mission critical tasks and with not more than 1 percent error for data entry and display reading tasks. The IPADS shall be capable of being installed on and removed from the host vehicle by no more than two people. The weight of any single IPADS component shall not exceed 84 pounds. Installation of the IPADS on a host vehicle shall not impede access for routine maintenance on the host vehicle or ingress and egress for personnel.

3.6.11.2 Human Factors Design. The IPADS shall comply with the human engineering design criteria, principles, and practices of MIL-STD-1472. Special design emphasis shall be given to MIL-STD-1472, paragraphs 4 (General Requirements), 5.1 (Control/Display Integration), 5.2 (Visual Displays), 5.3 (Audio Displays), 5.4 (Controls), 5.5 (Labeling), 5.9 (Design for Maintainer), 5.10 (Design of Equipment for Remote Handling), 5.11 (Small Systems and Equipment), 5.13 (Hazards and Safety), and 5.14 (User-computer interface) as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

3.6.12 Noise limits. When installed in a stationary ground vehicle, with engine off, an operating IPADS shall not exceed the steady state noise limits of MIL-STD-1474, Requirement 1, Category F, for all normal operator and driver locations.

3.6.13 Government furnished property. Government furnished property shall be as specified in acquisition documents (6.2).

3.6.14 Workmanship. Workmanship in the fabrication and assembly of the IPADS shall comply with best commercial practices. The parts shall be clean and free of burrs, sharp edges, unblended radii, surface defects, cracks, chips, dirt, grease, oil (except where specifically required), rust, foreign matter or any evidence of poor workmanship that could render the system unsuitable for its intended purpose or that would affect life, serviceability or appearance.

4 VERIFICATION

TABLE V. Requirement/verification cross-reference matrix.

METHOD OF VERIFICATION N/A - NOT APPLICABLE 1 - ANALYSIS 2 - DEMONSTRATION 3 - EXAMINATION 4 - TEST						CLASSES OF VERIFICATION A - DESIGN VERIFICATION B - FIRST ARTICLE C – ACCEPTANCE			
SECTION 3 REQUIREMENT	VERIFICATION METHOD					VERIFICATION CLASS			SECTION 4 VERIFICATION
	N/A	1	2	3	4	A	B	C	
3.1		X	X	X	X	X			4.2
3.2		X	X	X	X		X		4.3
3.3	X								
3.3.1		X				X			4.6.1.1
3.3.1.1			X			X			4.6.1.1.1
3.3.1.1.1			X			X			4.6.1.1.2
3.3.2		X				X			4.6.1.2
3.3.3			X			X	X	X	4.6.1.5
3.3.4		X				X			4.6.1.3
3.3.4.1			X			X	X	X	4.6.1.5
3.3.5	X								
3.3.5.1	X								
3.3.5.1.1			X			X	X		4.6.1.5
					X			X	4.6.1.4
3.3.5.1.2			X			X	X		4.6.1.5
3.3.5.1.3			X			X	X		4.6.1.5
3.3.5.2			X			X	X		4.6.1.5
3.3.5.2.1			X			X			4.6.1.9
3.3.5.3			X			X			4.6.1.5
3.3.5.3.1			X			X			4.6.1.5
3.3.5.3.2			X			X			4.6.1.5
3.3.5.3.3			X			X			4.6.1.5
3.3.6	X								
3.3.6.1			X			X	X	X	4.6.1.5
3.3.6.2			X			X	X		4.6.1.5
3.3.6.3			X			X	X	X	4.6.1.5

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

TABLE V. Requirement/verification cross-reference matrix.

METHOD OF VERIFICATION N/A - NOT APPLICABLE 1 - ANALYSIS 2 - DEMONSTRATION 3 - EXAMINATION 4 - TEST						CLASSES OF VERIFICATION A - DESIGN VERIFICATION B - FIRST ARTICLE C – ACCEPTANCE			
SECTION 3	VERIFICATION METHOD					VERIFICATION CLASS			SECTION 4
REQUIREMENT	N/A	1	2	3	4	A	B	C	VERIFICATION
3.3.6.4			X			X	X	X	4.6.1.5
3.3.6.5			X			X			4.6.1.5
3.3.7	X								
3.3.7.1			X			X	X		4.6.1.5
					X			X	4.6.1.4
3.3.7.2			X			X	X		4.6.1.5
					X			X	4.6.1.4
3.3.7.2.1		X				X			4.6.1.6
3.3.7.3			X			X	X		4.6.1.5
					X			X	4.6.1.4
3.3.8			X			X			4.6.1.10
3.3.9			X			X	X	X	4.6.1.5
3.3.9.1			X			X	X	X	4.6.1.5
3.3.10	X								
3.3.10.1			X			X	X	X	4.6.1.5
3.3.10.2			X			X	X	X	4.6.1.5
3.3.10.2.1			X			X	X		4.6.1.8
3.3.11					X	X	X		4.6.3.4, 4.6.3.6
3.3.11.1					X	X	X		4.6.3.4, 4.6.3.6
3.3.11.2		X				X			4.6.1.11
3.3.11.3			X			X			4.6.1.12
3.3.12			X			X			4.6.1.13, 4.6.1.14
3.3.13			X			X			4.6.1.13, 4.6.1.14
3.3.14			X			X			4.6.1.16
3.3.15				X		X			4.6.1.17
3.3.16			X			X			4.6.1.18
3.3.17				X		X			4.6.1.19
3.3.17.1			X			X			4.6.1.20
3.3.17.2			X			X			4.6.1.21
3.4	X								
3.4.1				X		X			4.6.2.1
3.4.1.1				X		X			4.6.2.1
3.4.1.1.1				X		X			4.6.2.1
3.4.1.1.2				X		X			4.6.2.1
3.4.1.1.3				X		X			4.6.2.1.1
3.4.2	X								
3.4.2.1					X	X			4.6.2.2
3.4.2.1.1			X			X			4.6.2.3
3.4.2.1.2			X			X			4.6.2.4
3.4.2.2			X			X			4.6.2.5
3.4.2.3					X	X			4.6.2.6

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

TABLE V. Requirement/verification cross-reference matrix.

METHOD OF VERIFICATION N/A - NOT APPLICABLE 1 - ANALYSIS 2 - DEMONSTRATION 3 - EXAMINATION 4 - TEST						CLASSES OF VERIFICATION A - DESIGN VERIFICATION B - FIRST ARTICLE C – ACCEPTANCE			
SECTION 3	VERIFICATION METHOD					VERIFICATION CLASS			SECTION 4
REQUIREMENT	N/A	1	2	3	4	A	B	C	VERIFICATION
3.4.2.4					X	X			4.6.2.7
3.4.3	X								
3.4.3.1			X			X	X	X	4.6.2.8
3.4.3.1.1			X			X			4.6.2.9
3.4.3.1.2			X			X			4.6.2.10
3.4.3.2			X			X			4.6.2.11
3.4.3.3			X			X	X		4.6.2.12
3.4.3.3.1				X		X	X		4.6.2.12
3.4.3.4			X			X	X		4.6.2.13
3.4.3.4.1			X			X	X		4.6.2.13
3.4.3.4.2			X			X	X		4.6.2.13
3.4.3.4.3			X			X	X		4.6.2.13
3.4.3.4.4			X			X	X		4.6.2.13
3.4.3.4.5			X			X	X		4.6.2.13
3.4.4			X			X			4.6.2.14
3.4.4.1				X		X			4.6.2.15
3.4.4.2			X			X			4.6.2.16
3.4.4.2.1			X			X			4.6.2.17
3.4.4.2.2			X			X			4.6.2.18
3.4.4.2.3			X			X			4.6.2.19
3.4.4.2.4			X			X			4.6.2.20
3.4.4.2.5			X			X			4.6.2.21, 4.6.2.22
3.4.4.2.6			X			X			4.6.2.23
3.4.4.3			X			X			4.6.2.24
3.4.4.4			X			X			4.6.2.25
3.4.5			X			X	X		4.6.1.7
						X	X	X	4.6.1.5
3.5	X								
3.5.1					X	X	X		4.6.3.4, 4.6.3.6
3.5.2					X	X	X		4.6.3.3, 4.6.3.5
3.5.3	X								
3.5.3.1					X	X			4.6.3.7
3.5.3.2					X	X			4.6.3.8
3.5.3.3					X	X			4.6.3.9
3.5.4					X	X			4.6.3.10
3.5.5					X	X			4.6.3.11
3.5.6					X	X	X		4.6.3.12
3.5.7					X	X	X		4.6.3.13
3.5.8					X	X			4.6.3.14
3.5.9					X	X			4.6.3.15
3.5.10	X								

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

TABLE V. Requirement/verification cross-reference matrix.

METHOD OF VERIFICATION N/A - NOT APPLICABLE 1 - ANALYSIS 2 - DEMONSTRATION 3 - EXAMINATION 4 - TEST						CLASSES OF VERIFICATION A - DESIGN VERIFICATION B - FIRST ARTICLE C – ACCEPTANCE			
SECTION 3	VERIFICATION METHOD					VERIFICATION CLASS			SECTION 4
REQUIREMENT	N/A	1	2	3	4	A	B	C	VERIFICATION
3.5.10.1					X	X	X		4.6.3.16
3.5.10.2					X	X			4.6.3.17
3.5.11	X								
3.5.11.1					X	X	X		4.6.3.18
3.5.11.2					X	X			4.6.3.19
3.5.11.3					X	X			4.6.3.20
3.5.11.4					X	X			4.6.3.21
3.5.12			X			X			4.6.3.22
3.5.13					X	X	X		4.6.3.23
3.5.14	X								
3.5.14.1		X	X			X			4.6.3.24
3.5.14.2					X	X			4.6.3.25
3.5.14.3	X								
3.5.14.3.1					X	X			4.6.3.26
3.5.14.3.2					X	X			4.6.3.27
3.5.14.3.3					X	X			4.6.3.28
3.5.14.3.4					X	X			4.6.3.29
3.5.14.3.5					X	X			4.6.3.30
3.5.14.3.6					X	X			4.6.3.31
3.5.14.3.7					X	X			4.6.3.32
3.5.14.3.8					X	X			4.6.3.33
3.5.14.3.9					X	X			4.6.3.34
3.5.14.3.10					X	X			4.6.3.35
3.5.14.4		X			X	X			4.6.3.36
3.5.15		X		X	X	X			4.6.3.37
3.6	X								
3.6.1	X								
3.6.1.1				X		X			4.6.4.1
3.6.1.1.1			X			X			4.6.1.15
3.6.1.2				X		X			4.6.4.2
3.6.1.3				X		X	X	X	4.6.4.3
3.6.2		X				X			4.6.4.4
3.6.2.1		X				X			4.6.4.5
3.6.3			X			X			4.6.4.6
3.6.4				X		X	X	X	4.6.4.7
3.6.4.1				X		X	X	X	4.6.4.7
3.6.5	X								
3.6.5.1				X		X	X		4.6.4.8
3.6.5.1.1				X		X	X		4.6.4.9
3.6.5.1.2				X		X	X		4.6.4.10
3.6.5.2				X		X	X		4.6.4.8

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

TABLE V. Requirement/verification cross-reference matrix.

METHOD OF VERIFICATION N/A - NOT APPLICABLE 1 - ANALYSIS 2 - DEMONSTRATION 3 - EXAMINATION 4 - TEST						CLASSES OF VERIFICATION A - DESIGN VERIFICATION B - FIRST ARTICLE C – ACCEPTANCE			
SECTION 3	VERIFICATION METHOD					VERIFICATION CLASS			SECTION 4
REQUIREMENT	N/A	1	2	3	4	A	B	C	VERIFICATION
3.6.5.3				X		X	X		4.6.4.11
3.6.5.4				X		X	X		4.6.4.12
3.6.6				X		X	X		4.6.4.13
3.6.6.1				X		X	X		4.6.4.14
3.6.7		X				X			4.6.4.15
			X				X		4.6.4.16
3.6.8	X								
3.6.8.1			X			X			4.6.4.17
3.6.8.2		X				X			4.6.4.18
3.6.8.2.1		X				X			4.6.4.19
3.6.8.2.2		X				X			4.6.4.20
3.6.8.2.3			X			X			4.6.4.21
3.6.8.3			X			X			4.6.4.22
3.6.8.4				X		X			4.6.4.23
3.6.8.5				X		X			4.6.4.24
3.6.8.6			X			X			4.6.4.25
3.6.8.7			X			X			4.6.2.11
3.6.9		X				X			4.6.4.26
3.6.10				X		X			4.6.4.27
3.6.10.1		X				X			4.6.4.28
3.6.10.2			X			X			4.6.4.29
3.6.10.3		X		X		X			4.6.4.30
3.6.10.4		X		X		X			4.6.4.31
3.6.10.5		X	X			X			4.6.4.32
3.6.10.5.1				X		X	X	X	4.6.4.33
3.6.10.5.2				X		X	X	X	4.6.4.34
3.6.11				X		X			4.6.4.35
3.6.11.1			X			X			4.6.4.36
3.6.11.2			X			X			4.6.4.37
3.6.12			X			X			4.6.4.38
3.6.13	X								
3.6.14				X		X	X	X	4.6.4.39

4.1 Classifications of verifications. The inspection requirements specified herein are classified as follows:

a. Design verification (4.2)

b. First article inspection (4.3)

c. Acceptance verification (4.4)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

4.1.1 Verification conditions. Unless otherwise specified, all inspections shall be performed in accordance with the conditions specified in 4.5.1 and 4.6.1.5.2.

4.2 Design verification. When specified in the contract, a sample of the IPADS shall be subjected to design verification in accordance with Table V.

4.2.1 Design verification quantity. Design verification shall be performed on three IPADS. If LRU transit cases are being verified at the same time, design verification shall be performed on four IPADS.

4.2.2 Verification to be performed. The design verification shall be performed in accordance with Table V.

4.2.3 Design verification rejection. If any item of the sample fails to comply with the design verification requirements, the sample shall be rejected.

4.3 First article inspection. When specified in the contract, a sample of the IPADS shall be subjected to first article verification in accordance with Table V.

4.3.1 First article quantity. First article verification shall be performed on a minimum of three IPADS. If LRU transit cases are being verified at the same time, first article verification shall be performed on a minimum of four IPADS.

4.3.2 Inspections to be performed. As determined by the Government, the first article assemblies, components and test specimens may be subjected to any or all of the examinations and tests specified in this specification and be inspected for compliance with any or all requirements of the specification and the applicable drawings.

4.3.3 First article rejection. If any assembly, component or test specimen fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate inspection upon any failure of an assembly, component or test specimen to comply with any of the requirements.

4.4 Acceptance verification. Acceptance verification shall be performed on all IPADS production equipment in accordance with Table V.

4.4.1 Acceptance rejection. Nonconformance to any specified requirement, the failure of any test or the presence of one or more defects shall be cause for rejection.

4.5 Verification methods. Methods utilized to accomplish verification include:

a. Analysis. An element of verification that utilizes established technical or mathematical models or simulations, algorithms, charts, graphs, circuit diagrams, or other scientific principles and procedures to provide evidence that stated requirements were met.

b. Demonstration. An element of verification, which generally denotes the actual operation, adjustment, or re-configuration of items to provide evidence that the designed functions were accomplished under specific scenarios. The items may be instrumented and quantitative limits of performance monitored.

c. Examination. An element of verification and inspection consisting of investigation, without the use of special laboratory appliances or procedures, of items to determine

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

conformance to those specified requirements which can be determined by such investigations. Examination is generally nondestructive and typically includes the use of sight, hearing, smell, touch, and taste; simple physical manipulation; mechanical and electrical gauging and measurement; and other forms of investigation.

d. Test. An element of verification and inspection that generally denotes the determination, by technical means, of the properties or elements of items, including functional operation, and involves the application of established scientific principles and procedures.

4.5.1 Test conditions. Unless otherwise specified, all tests shall be performed under shelter at the climatic conditions existing at the place of test. IPADS shall be operated as specified herein without maintenance, other than the scheduled maintenance as established by the maintenance schedule prepared and submitted by the contractor prior to testing. Failure attributable to Government-loaned equipment will not constitute failure of any test specified herein.

4.6 Verification methods.

4.6.1 Performance characteristics verification.

4.6.1.1 External signals analysis. The IPADS design shall be analyzed for use of external, electromagnetic signals in the determination of position and azimuth. Sole use of external, electromagnetic signals or use of external electromagnetic signals other than GPS, in the determination of position and azimuth, constitutes failure.

4.6.1.1.1 GPS signals demonstration. When code type is set to All-Y, use of signals derived from only Y-code satellites for survey operations shall be demonstrated. Use of signals derived from C/A or P-code for survey operations constitutes failure. When code type is set to Mixed Y and P, use of signals derived from Y or P-code satellites for survey operations shall be demonstrated. Use of signals derived from C/A-code for survey operations constitutes failure. Use of signals derived from Y, P, and C/A-code for transport mode shall be demonstrated. Failure to use GPS signals of acceptable accuracy, when signals from four or more healthy satellites are incident on the antenna, constitutes failure.

4.6.1.1.2 Loss of GPS signals. IPADS performance shall be demonstrated while GPS signals are subjected to attenuation, jamming, and spoofing. Degradation of performance outside threshold requirements constitutes failure.

4.6.1.2 Geographic area of operation analysis. A system analysis shall be performed of IPADS horizontal position accuracy, elevation accuracy, azimuth accuracy, and initialization time as a function of latitude. The analysis shall consider all error sources having significant contribution to the overall system error, including devices and external survey equipment used to transfer position and azimuth. The analysis shall be validated using the results of performance testing at the latitude(s) of the test site(s). The performance test results shall be extrapolated to the performance expected at 65° and 75° latitude, north and south. The performance test results shall be extrapolated to the performance expected at 80° South and 84° North latitude (O). Failure to meet the accuracies specified in Table I, and relevant initialization times, constitutes failure.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

4.6.1.3 Vehicle dynamics and attitudes analysis. IPADS performance shall be analyzed as functions of the vehicle dynamics and attitudes specified in 3.3.4. Failure to meet the accuracies specified in Table I, and relevant initialization times, at the worst-case combinations of vehicle dynamics and attitudes constitutes failure.

4.6.1.4 Acceptance performance verification. The capability of each IPADS to meet the accuracies specified in Table I, and relevant initialization times, over the geographic area of operation and full range of environmental conditions shall be verified. This verification may include analysis of appropriate production (test) data. Failure to meet the requirements of the approved Acceptance Procedure constitutes failure.

4.6.1.5 Performance demonstrations. IPADS performance, in a ground vehicle, shall be demonstrated in accordance with Table VI using the course(s) (4.6.1.5.1), conditions (4.6.1.5.2), demonstration data (4.6.1.5.3), and data analysis (4.6.1.5.4) specified below.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

TABLE VI. IPADS performance demonstration requirements.

Verification Classification	GPS Aided	Initialization Type	Survey Mode/Order	Number of Missions
Design Verification	No	Normal	Survey/High	4
			Survey/Lower	4
		"Hot Start"	Survey/High	2
			Survey/Lower	2
			Transport /High	2
	GPS centric	Normal	Survey/High	2
		"Hot Start"	Survey/High	2
		Moving Base	Survey/High	2
		Interrupted Normal	Survey/High	2
		Interrupted Moving Base	Survey/High	2
	GPS centric (receiver not keyed)	"Hot Start"	Transport /High	1
	Interrupted	"Hot Start"	Survey/High	2
	Relative	Normal	Survey/High	2
		"Hot Start"	Survey/High	2
		Interrupted Moving Base	Survey/High	2
First Article Inspection	No	Normal	Survey/High	3
			Survey/Lower	3
		"Hot Start"	Survey/High	1
			Survey/Lower	1
	GPS centric	Normal	Survey/High	1
		"Hot Start"	Survey/High	1

4.6.1.5.1 Performance demonstration course(s). IPADS performance shall be demonstrated by operating IPADS in its host vehicle(s) over a Government approved course(s) with the following characteristics:

a. The test course shall have at least 12 known SCPs and OLs, including starting point, approximately equally spaced. Test data shall be taken at each survey point.

b. Reference coordinates for all SCPs shall meet the 1-Decimeter accuracy classification of FGDC-STD-007.2 relative to a High Accuracy Reference Network (HARN) or network of equivalent accuracy.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

c. Errors in reference azimuths for all SCPs shall be 0.1 mil or less at 95-percent confidence.

d. Approximately 40 percent of the SCPs and OLs shall be offset from the location of the occupying host vehicle. The remaining SCPs and OLs shall permit direct occupation by the host vehicle (two-position transfer method).

e. The radial distance between the initialization point and farthest SCP shall be approximately 75 km (T) and 100 km or greater (O).

f. The distance traveled per survey test shall be approximately 200 km.

4.6.1.5.2 Performance demonstration conditions. Unless otherwise specified, the following conditions apply to performance demonstrations:

a. Unless environmental conditions are outside the limits of this specification or preclude safe operation of the host vehicle, performance demonstrations shall be conducted under the environmental conditions existing at the demonstration site at the time of demonstration.

b. IPADS shall be subjected to base motions (3.3.4.1) created by the environmental conditions and host vehicle at the time of demonstration.

c. Unless necessitated by safety or traffic conditions, the vehicle shall not stop during travel between SCPs unless requested by IPADS.

d. For non-requested stops, travel shall be resumed as soon as it is safe to do so.

e. For requested stops, travel shall be resumed as soon as IPADS indicates travel is permitted.

f. For ground vehicles, the host vehicle engine shall be turned off for 1 minute at 75-minute intervals during each performance demonstration mission.

g. IPADS shall be shut down at least 1 hour between performance demonstration missions.

h. Except for “hot start” missions, the host vehicle shall be moved between missions while IPADS is off.

i. For non-GPS-aided missions, survey adjustment shall be performed at the end of each performance demonstration mission.

j. For normal initialization missions, the coordinates supplied to IPADS at the start of initialization shall be in error by 95 ± 5 meters, horizontal, and 9 ± 1 meters, vertical, relative to the SCP where the first position update will be performed.

k. For half the normal initialization missions, IPADS shall be turned on and initialized at a location at least 200 meters from the location where it was last turned off. For the other half of normal initialization missions, IPADS shall be turned on and then moved to an initialization location at least 200 meters from the location where it was last turned off.

l. For interrupted GPS aided missions, GPS reception shall be discontinued approximately half way through the mission.

m. GPS reception shall be interrupted for approximately two minutes in the middle of moving base initialization missions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

n. For interrupted normal initialization missions, vehicle movement shall start approximately half way through alignment.

o. For interrupted moving base initialization missions, vehicle movement shall cease approximately half way through alignment.

p. For transport mode missions, IPADS shall be initialized at a location approximately 100 km distant from the test course initial SCP. When initialization is complete, the system shall be placed in transport mode and driven to the test course initial SCP. Stops shall be made only when required by safety regulations or are needed to safely operate the vehicle. The system shall be updated at the test course initial SCP and a normal survey mission conducted.

4.6.1.5.3 Performance demonstration data. The following parameters shall be recorded for each performance demonstration mission:

a. Initialization time.

b. Travel time between stops.

c. Duration of each stop.

d. Unadjusted IPADS determined horizontal position of each SCP.

e. Unadjusted IPADS determined elevation of each SCP.

f. Unadjusted IPADS determined azimuth of each OL.

g. Adjusted IPADS determined horizontal position of each SCP, when mission is non-GPS-aided.

h. Adjusted IPADS determined elevation of each SCP, when mission is non-GPS-aided.

i. Adjusted IPADS determined azimuth of each OL, when mission is non-GPS-aided.

j. Time to update IPADS position.

k. Time to establish each position.

l. Time to establish each azimuth.

m. Failures.

n. Mission duration.

o. Number and types (data entry, display readout, or other) of operator tasks performed.

p. Number and types of operator errors.

q. GPS availability to IPADS, GPS EHE, GPS EVE, and IPADS use of GPS.

r. Availability of survey marking.

4.6.1.5.4 Performance demonstration data analysis. The following parameters shall be analyzed for conformance to requirements. Unless otherwise specified, no data shall be excluded from the analysis.

a. Initialization time for each mission. Any initialization time in excess of that specified in Table I constitutes failure.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

b. Average travel time between requested stops for each mission. Average travel time less than that specified in Table I, while in survey mode, or any requests for stops, while in transport mode, constitutes failure.

c. Average duration of requested stops for each mission. Average stop time greater than that specified in 3.3.9 constitutes failure.

d. Duration of requested stops. Any stop time greater than the maximum specified in 3.3.9 constitutes failure.

e. Unadjusted survey horizontal position CEP for each mission. The initialization point shall be excluded from the CEP determination. Any mission CEP in excess of that specified in Table I constitutes failure.

f. Adjusted survey horizontal position CEP for each non-GPS-aided mission. The initialization and closure points shall be excluded from the CEP determination. Any mission CEP in excess of that specified in Table I constitutes failure.

g. Radial errors. More than one percent of the radial errors for the performance demonstration exceeding the 99 percent criterion of Table I constitutes failure.

h. Unadjusted survey elevation PE for each mission. The initialization point shall be excluded from the elevation PE determination. Any mission elevation PE in excess of that specified in Table I constitutes failure.

i. Adjusted survey elevation PE for each non-GPS-aided mission. The initialization and closure points shall be excluded from the elevation PE determination. Any mission elevation PE in excess of that specified in Table I constitutes failure.

j. Elevation errors. More than one percent of the elevation errors for the performance demonstration exceeding the 99 percent criterion of Table I constitutes failure.

k. Survey azimuth PE for each mission. The initialization point shall be excluded from the azimuth PE determination. Any mission azimuth PE in excess of that specified in Table I constitutes failure.

l. Azimuth errors. More than one percent of the azimuth errors for the performance demonstration exceeding the 99 percent criterion of Table I constitutes failure.

m. Time to update position. Any time to update IPADS position in excess of that specified in 3.3.10.1 constitutes failure.

n. Time to establish position, only. Any time to establish the position of a SCP in excess of that specified in 3.3.10.1 constitutes failure.

o. Time to establish position and azimuth. Any time to establish position of an OS and azimuth of an OL in excess of that specified in 3.3.10.2 constitutes failure.

p. Percentage of operator errors. Errors in excess of those specified in 3.6.11.1 constitutes failure.

q. Availability of survey marking capability.

    1) Availability of survey marking capability when accuracy criteria can’t be met constitutes failure.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

2) Availability of survey marking capability when GPS aided in transport mode and the receiver is not keyed constitutes failure.

r. Use of GPS signals. Use of GPS aiding data, in survey mode, derived from GPS signals not conforming to the selected code type (All-Y or mixed Y and P) constitutes failure.

4.6.1.6 HAE/MSL conversion accuracy analysis. HAE/MSL conversion accuracy shall be analyzed for conformance with 3.3.7.2.1. Failure to meet the requirements of 3.3.7.2.1 constitutes failure.

4.6.1.7 Position and azimuth transfer demonstration. The ability to transfer position and azimuth to remote locations with the host vehicle parked on slopes and side slopes within the range of ±15° shall be demonstrated. Failure to achieve the accuracies specified in Table I or the transfer ranges in 3.4.5 constitutes failure.

4.6.1.8 Two-position azimuth movement time demonstration. The requirements of 3.3.10.2.1 shall be demonstrated at nominal distances of 100, 200, and 300 meters. Failure to meet the requirements of 3.3.10.2.1 constitutes failure.

4.6.1.9 "Hot start" excessive motion demonstration. At the end of a mission, IPADS shall be normally shutdown with the host vehicle parked on nominally level pavement. With IPADS off, the host vehicle shall be driven approximately 10 meters in a nominally straight direction. IPADS shall be turned on and initialized in such a manner that would result in "hot start" initialization if IPADS hadn't been moved. The operator shall complete initialization, following any instructions provided by IPADS. After initialization is complete, the operator shall conduct a survey. Failure to meet the requirements of 3.3.5.2.1 or failure to achieve the accuracies specified in Table I constitutes failure.

4.6.1.10 Operating time demonstration. IPADS shall be operated in the high order survey mode over the performance demonstration course for 24 continuous hours without position update except for the initial position at the start of the mission and at mission completion. Failure to maintain operation for 24 hours or failure to achieve the accuracies specified in Table I constitutes failure.

4.6.1.11 Overcharge analysis. The IPADS back-up battery charging circuitry shall be analyzed for its ability to overcharge the back-up battery throughout the ambient and induced temperature range. An ability to overcharge the back-up battery constitutes failure.

4.6.1.12 Battery replacement demonstration. While IPADS is operating from host vehicle power, the back-up battery(ies) shall be replaced. Inability to replace the battery(ies) or failure to sustain IPADS operation constitutes failure.

4.6.1.13 Stationary power loss demonstration. While stationary, at the end of a normal mission, host vehicle power and back-up power shall be disconnected. Upon restoration of power, survey data and ellipsoid and datum parameters from the previous mission shall be recalled and a "hot start" attempted. Damage to IPADS; missing or erroneous recalled data, GPS critical data, or current GPS time; or failure to achieve "hot start" initialization constitutes failure.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

4.6.1.14 Moving power loss demonstration. While moving, at the end of a normal mission, host vehicle power and back-up power shall be disconnected. Upon stopping and restoration of power, survey data and ellipsoid and datum parameters from the previous mission shall be recalled and a normal initialization attempted. Damage to IPADS; missing or erroneous recalled data, GPS critical data, or current GPS time; acceptance of "hot start" initialization; or failure to achieve normal initialization constitutes failure.

4.6.1.15 GPS memory battery lifetime analysis. If used, the lifetime of a battery used to retain GPS data shall be determined by analysis for the full range of environmental conditions to which IPADS will be exposed. Failure to meet the requirements of 3.6.1.1.1 constitutes failure.

4.6.1.16 Survey data storage demonstration. Complete survey data sets for 360 SCPs shall be stored. Each data set shall be recalled and compared to the data originally stored. Inability to recall all stored data sets, or incomplete or erroneous data constitutes failure.

4.6.1.17 Information security examination. The IPADS design and software/firmware shall be examined for vulnerabilities to information security. Software/firmware containing malicious code, viruses, or trap doors; the capability for an external device to access or alter IPADS software or firmware, except for intentional reprogramming, interfere with IPADS operation, or access classified GPS data; or store/retain GPS cryptovariables except in an approved SAASM constitutes failure.

4.6.1.18 Vehicle-to-vehicle transfer demonstration. A two-person, or fewer, crew shall transfer an operating IPADS from one prepared vehicle to another. Failure to be ready to continue the mission in the second vehicle within 10 minutes, or loss of information, or a need to reinitialize constitutes failure.

4.6.1.19 Visibility examination. IPADS controls and displays shall be examined under lighting conditions ranging from full darkness to direct, bright sunlight. Inability to accurately operate IPADS, enter data, and read out data constitutes failure.

4.6.1.20 Night vision demonstration. IPADS, in full darkness, shall be operated by personnel wearing night vision goggles and observed by personnel with both unaided vision and wearing night vision goggles. Inability to accurately operate IPADS, enter data, and read out data, or degradation of observers' night vision constitutes failure.

4.6.1.21 Blackout demonstration. IPADS shall be observed when operated under blackout conditions in full darkness. Visibility of IPADS at distances beyond 10 meters from the center of the system constitutes failure.

4.6.2 Interface and Interoperability requirements verification.

4.6.2.1 Mechanical interface examination. IPADS shall be installed, using the applicable installation kit(s), and operated in the host vehicle(s) specified in the contract (6.2). Incomplete installation kits, or interference with or from normal operation of the host vehicle or vehicle accessories constitutes failure.

4.6.2.1.1 GPS antenna examination. The GPS antenna installation shall be examined or tested for antenna sky visibility, retention during dynamic vehicle operation, and vulnerability to contact damage. Obstructed view of the sky, failure to be retained during dynamic vehicle

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

operation, or damage by contact with objects normally encountered during normal operations of the host tactical vehicle.

4.6.2.2 Ground vehicle power test. IPADS shall be operated from power meeting the extreme limits of MIL-STD-1275 under fault free and single fault conditions. Damage, failure to operate or maintain operation, and failure to perform as specified herein constitutes failure.

4.6.2.3 Multiple fault demonstration. An operating IPADS shall be subjected to the extreme multiple fault malfunction condition as specified in MIL-STD-1275. Damage to IPADS constitutes failure.

4.6.2.4 Power connection examination. Installation kit power cables for host ground vehicles shall be examined for the requirements of 3.4.2.1.2. Failure to meet the requirements of 3.4.2.1.2 constitutes failure.

4.6.2.5 Reverse polarity demonstration. IPADS shall be connected to DC power with reverse polarity and turn-on shall be attempted. Damage to IPADS constitutes failure.

4.6.2.6 Power consumption test. The power consumption of an operating IPADS shall be measured with the DC power voltage at the nominal value and high and low limits, and the back-up battery fully discharged and fully charged. Failure to meet the specified power consumption for any combination of power voltage and state of back-up battery charge constitutes failure.

4.6.2.7 Power disconnect test. With IPADS operating from host power, the power disconnect capability shall be activated and the power drain from the host measured. With IPADS connected to host power and not operating, the power disconnect capability shall be activated and the power drain from the host measured. Power drain in excess of one milliwatt or disconnection of cables or fuses to meet the requirement constitutes failure.

4.6.2.8 Digital data interface demonstration. DELETED.

4.6.2.9 Hot connect/disconnect demonstration. DELETED.

4.6.2.10 Time synchronization demonstration. DELETED.

4.6.2.11 Reprogramming demonstration. Software download from a MSD or equivalent IBM-compatible Personal Computer to all LRUs and SRUs, which utilize software or firmware, shall be demonstrated. Failure to correctly download software/firmware to any LRU or SRU constitutes failure.

4.6.2.12 Cryptographic key loading demonstration. Acceptance of GPS cryptographic keys from an AN/CYZ-10 Data Transfer Device (DTD) and an AN/PYQ-10(C) Simple Key Loader (SKL) through a standard cryptofill cable shall be demonstrated. Failure to comply with the requirements of 3.4.3.3 and 3.4.3.3.1 constitutes failure.

4.6.2.13 GPS initialization demonstration. The ability to initialize the IPADS GPS receiver from a keyed DAGR shall be demonstrated. Failure to comply with the requirements of 3.4.3.4 through 3.4.3.4.5 constitutes failure.

4.6.2.14 Control and display interface demonstration. The IPADS operator control and display interface shall be demonstrated. Inability of an operator to control the IPADS mode of

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

operation; accomplish data entry, readout, and update; observe system status; display survey and other operational parameters; constitutes failure.

4.6.2.15 Control and display location examination. The location(s) of control and display functions shall be examined. Failure to meet the criteria of 3.4.4.1 constitutes failure.

4.6.2.16 Display parameter demonstration. Display of the parameters specified in 3.4.4.2 shall be demonstrated. Failure to correctly display the specified parameters constitutes failure.

4.6.2.17 Display field characteristic demonstration. Display field characteristics shall be demonstrated. Failure to meet the requirements of Appendix A constitutes failure.

4.6.2.18 Survey data page demonstration. The survey data page shall be demonstrated. Failure to display all the parameters specified in 3.4.4.2.2 constitutes failure.

4.6.2.19 Display field selection demonstration. Selection of the display fields and formats specified in 3.4.4.2.3 shall be demonstrated during initialization, travel during a survey, and when establishing a SCP. Failure to be able to select or display a specified field constitutes failure.

4.6.2.20 Horizontal position display demonstration. UTM, MGRS, and geodetic coordinates for a SCP shall be observed while the ellipsoid and datum are changed. The displayed coordinates shall be compared to those obtained from reference datum shifting software, such as GEOTRANS. Comparisons shall be made for at least 10 different ellipsoids and datums, including WGS 72. Differences between the IPADS displayed and reference coordinates outside the range ±0.1 meter constitutes failure.

4.6.2.21 UTM zone width demonstration. The geodetic coordinates in Table VII shall be input into IPADS, horizontal position display type switched to UTM, and the UTM coordinates compared to those in Table VII. Lack of agreement by more than 0.1 meter constitutes failure.

TABLE VII. UTM zone demonstration coordinates.

Datum	Latitude	Longitude	Zone	Easting	Northing
WGS 84	73° N	8° E	32	467367.7	8100752.1
WGS 84	73° N	10° E	32	532632.3	8100752.1
WGS 84	73° N	20° E	34	467367.7	8100752.1
WGS 84	73° N	22° E	34	532632.3	8100752.1
WGS 84	73° N	32° E	36	467367.7	8100752.1
WGS 84	73° N	34° E	36	532632.3	8100752.1

4.6.2.22 UTM zone boundary crossing demonstration. IPADS shall be operated using the following scenarios:

a. IPADS shall be initialized at a SCP that is greater than 40 Km west of an actual or simulated UTM zone boundary. IPADS shall be moved eastward, until the UTM zone

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

boundary is crossed, and stopped at a known SCP. IPADS shall be observed for alerts and prompts and the coordinates recorded. Continued operation in the previous zone shall be selected and the coordinates recorded. IPADS shall be moved eastward more than 40 Km and stopped at a known SCP. IPADS shall be observed for alerts and prompts and the coordinates recorded. IPADS shall be moved westward, to inside the extended zone boundary, and stopped at a known SCP. IPADS shall be observed for alerts and prompts and the coordinates recorded. IPADS shall be moved westward to cross the UTM zone boundary and stopped at a known SCP. IPADS shall be observed for alerts and prompts and the coordinates recorded.

b. IPADS shall be initialized at a SCP that is greater than 40 Km west of an actual or simulated UTM zone boundary. IPADS shall be moved eastward, until the UTM zone boundary is crossed, and stopped at a known SCP. IPADS shall be observed for alerts and prompts and the coordinates recorded. Operation in the new zone shall be selected and the coordinates recorded. IPADS shall be moved eastward more than 40 Km and stopped at a known SCP. IPADS shall be observed for alerts and prompts and the coordinates recorded. IPADS shall be moved westward, to inside the extended zone boundary, and stopped at a known SCP. IPADS shall be observed for alerts and prompts and the coordinates recorded. IPADS shall be moved westward to cross the UTM zone boundary and stopped at a known SCP. IPADS shall be observed for alerts and prompts and the coordinates recorded.

c. IPADS shall be initialized at a SCP that is greater than 40 Km east of an actual or simulated UTM zone boundary. IPADS shall be moved westward, until the extended UTM zone boundary is crossed, and stopped at a known SCP. IPADS shall be observed for alerts and prompts and the coordinates recorded. Continued operation in the normal zone shall be selected and the coordinates recorded. IPADS shall be moved westward until the zone boundary is crossed and stopped at a known SCP. IPADS shall be observed for alerts and prompts and the coordinates recorded. IPADS shall be moved westward, more than 40 Km, and stopped at a known SCP. IPADS shall be observed for alerts and prompts and the coordinates recorded. IPADS shall be moved eastward to cross the UTM zone boundary and stopped at a known SCP. IPADS shall be observed for alerts and prompts and the coordinates recorded.

d. IPADS shall be initialized at a SCP that is greater than 40 Km east of an actual or simulated UTM zone boundary. IPADS shall be moved westward, until the extended UTM zone boundary is crossed, and stopped at a known SCP. IPADS shall be observed for alerts and prompts and the coordinates recorded. Operation in the extended western zone shall be selected and the coordinates recorded. IPADS shall be moved westward until the zone boundary is crossed and stopped at a known SCP. IPADS shall be observed for alerts and prompts and the coordinates recorded. IPADS shall be moved westward, more than 40 Km, and stopped at a known SCP. IPADS shall be observed for alerts and prompts and the coordinates recorded. IPADS shall be moved eastward to cross the UTM zone boundary and stopped at a known SCP. IPADS shall be observed for alerts and prompts and the coordinates recorded.

Failure to meet the requirements of 3.4.4.2.5, 3.4.4.4, and the accuracy requirements of Table I constitutes failure.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

4.6.2.23 Vertical datum demonstration. Elevation for a SCP shall be observed while the ellipsoid and datum are changed for at least 10 different ellipsoids and datums, including WGS 72. Any difference between the IPADS displayed and initial elevation constitutes failure.

4.6.2.24 Operator control functions and data entry demonstration. The operator control and data entry functions specified in 3.4.4.3 shall be demonstrated. Failure to perform the specified function or incorrect entry of data constitutes failure.

4.6.2.25 Status indication demonstration. Each of the status indications specified in 3.4.4.4 shall be demonstrated. Failure to provide the correct indication constitutes failure.

4.6.3 Environmental tests.

4.6.3.1 General Conditions.

4.6.3.1.1 Pre and post exposure testing. Before and after each environmental test, normal operation of the IPADS shall be simulated, including operation of all switches, controls, input and output devices, displays, indicators, and azimuth transfer devices. IPADS performance shall be monitored using system displays as much as possible. IPADS shall be operated in a manner that simulates travel in the high accuracy survey mode after initialization is complete. IPADS shall be operated with the input supply voltage at the normal level, lowest limit, and highest limit. Survey parameter accuracy (horizontal position, elevation, and azimuth), and initialization, simulated travel, and times shall be recorded. Any indicated failure or failure to achieve the performance specified in Table I constitutes failure.

Should the test setup remain the same from one environmental test to the next, the post-functional test may serve as the pre-functional test for the following test.

4.6.3.1.2 Operation during environmental exposure. Normal operation of the IPADS shall be simulated during operational portions of environmental test. IPADS shall be operated in a manner that simulates travel in the high accuracy survey mode after initialization is complete. IPADS shall be operated with the input supply voltage at the normal level, lowest limit, and highest limit. Survey parameter accuracy (horizontal position, elevation, and azimuth), and initialization, simulated travel, and times shall be recorded. Any indicated failure or failure to achieve the performance specified in Table I constitutes failure.

4.6.3.1.3 Post-test inspection. The equipment shall be inspected for damage after each environmental test. Unless otherwise specified, any damage constitutes failure. Damage includes, but is not limited to:

a. Any condition which will present a hazard to personnel or equipment if operated further.
b. Loose or missing hardware or components.
c. Inability of a part or component to perform its normal function.
d. Broken components.
e. Embrittlement, discoloration, cracking or breaking of material.
f. Binding of parts.
g. Loss of lubrication.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

h. Deterioration of closures and seals.

i. Oxidation and/or corrosion of metals.

4.6.3.2 Order of inspection. Laboratory environmental tests shall be performed in the order specified in Table VIII.

TABLE VIII. Order of laboratory environmental tests.

Test	Order of Test			
	Unit 1	**Unit 2**	**Unit 3**	**Unit 4 ***
High Temperature Storage	4			6
High Temperature And Solar Radiation Operation	5			
Low Temperature Storage	6			5
Low Temperature Operation	7			
Operational Low Pressure	8			1
Storage/Transport Low Pressure		1		
Rapid Decompression			4	
Blowing Dust		3		
Blowing Sand		4		
Rain	9			
Humidity	10			
Fungus Resistance		2		
Salt Fog			3	
Ground Vehicle Vibration	1			
Loose Cargo Vibration				2
Operational Shock	2			
Non-Operating Shock	3			
Crash Hazard Shock			5	
Transit Drop			1	3
Leakage			2	4

* For verification of LRU transit cases.

4.6.3.3 High temperature storage. IPADS, in its transit case, and LRUs, in their transit cases, shall be tested in accordance with MIL-STD-810, Method 501, Procedure I, at a constant +160° F (71° C) ambient temperature, for at least four hours after achieving temperature stabilization.

4.6.3.4 High temperature and solar radiation operation. IPADS shall be tested in accordance with MIL-STD-810, Method 505, Procedure I, for a minimum of three A1 cycles

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

using full spectrum lamps. IPADS shall be turned on and operated for six hours during the peak temperature portion of each cycle. One hour after starting operation in the second cycle, external power shall be turned off and IPADS operated on its back-up power for 15 minutes. External power shall be restored at the conclusion of the 15-minute period. Four hours after restoring external power, external power shall be turned off and IPADS operated on its back-up power for 15 minutes. External power shall be restored at the conclusion of the 15-minute period. In addition to the criteria in 4.6.3.1.2, failure to maintain operation while on back-up power constitutes failure.

4.6.3.5 Low temperature storage. IPADS, in its transit case, and LRUs, in their transit cases, shall be tested in accordance with MIL-STD-810, Method 502, Procedure I, at a constant -50° F (-46° C) ambient temperature, for at least 24 hours after achieving temperature stabilization. Exception: If easily replaceable by personnel wearing arctic clothing, the Control and Display Unit, only may be tested at a constant -40° F (-40° C) ambient temperature.

4.6.3.6 Low temperature operation. IPADS shall be tested in accordance with MIL-STD-810, Method 502, Procedure II, at a constant -50° F (-46° C) ambient temperature. After achieving temperature stabilization, IPADS shall be turned on and operated for six hours. Exceptions:

a. If easily replaceable by personnel wearing arctic clothing, the Control and Display Unit, only may be tested at a constant -22° F (-30° C) ambient temperature.

b. IPADS, except GPS antenna, may be exposed to simulated heating from the vehicle's heating system until it has reached -22° F (-30° C) internal temperature.

One hour after starting operation, external power shall be turned off and IPADS operated on its back-up power for 15 minutes. External power shall be restored at the conclusion of the 15-minute period. Four hours after restoring external power, external power shall be turned off and IPADS operated on its back-up power for 15 minutes. External power shall be restored at the conclusion of the 15-minute period. In addition to the criteria in 4.6.3.1.2, failure to maintain operation while on back-up power or failure to inhibit survey operation or notify the operator as specified in 3.5.1 constitutes failure.

4.6.3.7 Operational low pressure test. IPADS shall be tested in accordance with MIL-STD-810, Method 500, Procedure II, at a simulated elevation of 10,000 feet above sea level. After achieving elevation stabilization, IPADS shall be turned on and operated for six hours. The elevation change rate during test shall not exceed 2,000 ft/min (10 m/s).

4.6.3.8 Storage/transport low pressure test. IPADS, in its transit case, and LRUs, in their transit cases, shall be tested in accordance with MIL-STD-810, Method 500, Procedure I, at a simulated elevation of 15,000 feet above sea level. The elevation change rate during test shall not exceed 2,000 ft/min (10 m/s).

4.6.3.9 Rapid decompression test. IPADS, in its transit case, and LRUs, in their transit cases, shall be tested in accordance with MIL-STD-810, Method 500, Procedure III.

4.6.3.10 Blowing dust test. IPADS shall be tested in accordance with MIL-STD-810, Method 510, Procedure I, with dust concentrations of 0.3 ± 0.2 grams per cubic foot and air

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

velocity from 300 ft/min (1.5 m/s) to 1750 ft/min (8.9 m/s). Each face of IPADS, normally exposed to the elements, shall be exposed to blowing dust for equal time during each exposure. The first six-hour exposure shall be at a temperature of +74° F, with IPADS non-operating. The second six-hour exposure shall be at a temperature of +125° F, with IPADS operating. In addition to the criteria in 4.6.3.1, entry of dust into electronic compartments or optical devices constitutes failure.

4.6.3.11 Blowing sand test. IPADS shall be tested in accordance with MIL-STD-810, Method 510, Procedure II, with sand concentrations of 1.32×10^{-4} lb/ft^3 (2.19×10^{-3} kg/m^3) and air velocity from 3540 ft/min (18 m/s) to 5700 ft/min (29 m/s). Each face of IPADS, normally exposed to the elements, shall be exposed to blowing sand for 90 minutes. IPADS shall be operated during the last hour of exposure. In addition to the criteria in 4.6.3.1, entry of sand into electronic compartments or optical devices, or damage to optical components, which doesn't allow them to meet the intended purpose, constitutes failure.

4.6.3.12 Rain test. IPADS shall be tested in accordance with MIL-STD-810, Method 506, Procedure I, with 4 in/hr (10 cm/hr) rain and a wind velocity of 40 mph (18 m/s). All surfaces onto which the rain could fall or be driven shall be exposed to the test conditions for a minimum of 30 minutes per surface. Test item temperature shall be 18°F (10°C) higher than the rain temperature at the beginning of each exposure. IPADS shall be operated throughout the test and switches and keys shall be manipulated during the last 10 minutes of the exposure on each surface. In addition to the criteria in 4.6.3.1, entry of water into electronic compartments or optical devices constitutes failure.

4.6.3.13 Humidity test. IPADS shall be tested in accordance with MIL-STD-810, Method 507, Procedure II, for ten, 24-hour, cycles.

4.6.3.14 Fungus resistance test. IPADS, its transit case, and LRU transit cases shall be tested in accordance with MIL-STD-810, Method 508, for 28 days using the U.S. standard set of fungi. In addition to the criteria in 4.6.3.1, growth of fungus on electronic or optical components constitutes failure.

4.6.3.15 Salt fog test. IPADS, in its operational configuration, shall be tested in accordance with GM9540P for eight 24 hour cycles. IPADS installation in the test chamber shall simulate the pooling of liquids and splash that would be experienced when installed in an open HMMWV. IPADS shall be operated during the humidity chamber exposure portion of the fourth and eighth cycles.

4.6.3.16 Ground vehicle vibration test. An operating IPADS shall be exposed to the vibration profiles in Table II for 120 minutes in each of three mutually perpendicular axes in accordance with MIL-STD-810, Method 514, Procedure I.

4.6.3.17 Loose cargo vibration test. IPADS LRUs, in their transit cases, shall be tested in accordance with MIL-STD-810, Method 514, Procedure II. Test duration shall be 40 minutes.

4.6.3.18 Operational shock test. An operating IPADS shall be tested in accordance with MIL-STD-810, Method 516, Procedure I. IPADS shall be subjected to three shock pulses, with peak acceleration of 40 g's, effective transient duration (T_E) of 15 - 23 ms., and cross over frequency of 45 Hz, along each direction of each of three mutually orthogonal axes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

4.6.3.19 Non-operating shock test. A non-operating IPADS shall be tested in accordance with MIL-STD-810, Method 516, Procedure I. IPADS shall be subjected to three shock pulses, with peak acceleration of 40 g's, effective transient duration (T_E) of 15 - 23 ms., and cross over frequency of 45 Hz, along each direction of each of three mutually orthogonal axes.

4.6.3.20 Ground vehicle crash hazard shock test. An IPADS, in its ground vehicle configuration, shall be tested in accordance with MIL-STD-810, Method 516, Procedure V. IPADS shall be subjected to two shock pulses, with peak acceleration of 75 g's, effective transient duration (T_E) of 8 - 13 ms., and cross over frequency of 80 Hz, along each direction of each of three mutually orthogonal axes. Failure of any component to remain secured during and after exposure constitutes failure. Mass mock-ups, with the same mounting provisions, mount strength, mass and center of gravity, may be substituted for IPADS LRUs during this test.

4.6.3.21 Transit drop test. IPADS, in its transit case, and LRUs, in their transit cases, shall be tested in accordance with MIL-STD-810, Method 516, procedure IV. Drop height(s) shall be as specified in Table III. IPADS damage or failure to perform in accordance with 4.6.3.1.1 and 4.6.3.1.3 constitutes failure. Transit case damaged seals, impaired structural integrity, malfunctioning latches, damaged carrying devices, damaged pressure relief valves, or impaired opening and closing of the case constitutes failure.

4.6.3.22 Airdrop demonstration in vehicle. A M998 HMWWV, with IPADS installed, shall be rigged for airdrop in accordance with established procedures, and shall be airdropped a minimum of three times from a cargo aircraft. Damage to IPADS or failure to meet the requirements of Table I after airdrop constitutes failure.

4.6.3.23 Leakage. The IPADS and LRU transit cases shall be tested in accordance with MIL-STD-810, Method 512, procedure I, to a depth of 6 inches above the highest point on the case. Prior to immersion, the case shall be preconditioned to a temperature 49° F (27° C) above the water temperature. In addition to the criteria in 4.6.3.1.3, water penetration more than 4 cubic centimeters per 28,000 cubic centimeters constitutes failure.

4.6.3.24 Intra-system electromagnetic compatibility (EMC) verification. IPADS intra-system shall be verified in accordance with requirements 5.2 and 5.2.3 of MIL-STD-464. Failure to meet the requirements of 3.5.14.1 constitutes failure.

4.6.3.25 Electromagnetic pulse (EMP) test. IPADS EMP resistance shall be tested in accordance with MIL-STD-461 requirement RS105 for both the operating and non-operating conditions. IPADS is not required to remain operating through an EMP event. Any damage to IPADS or inability of IPADS to meet the performance requirements of Table I after exposure constitutes failure.

4.6.3.26 Conducted emissions, power leads, 10 kHz to 10 MHz, test. IPADS power lead conducted emissions shall be tested in accordance with MIL-STD-461 requirement CE102 from 10 kHz to 10 MHz. Any emission exceeding the limits of MIL-STD-461 requirement CE102 constitutes failure.

4.6.3.27 Conducted susceptibility, power leads, 30 Hz to 150 kHz, test. IPADS power lead conducted susceptibility shall be tested in accordance with MIL-STD-461 requirement CS101

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

from 30 Hz to 150 kHz. Any damage to IPADS or degradation of performance constitutes failure.

4.6.3.28 Conducted susceptibility, bulk cable injection, 10 kHz to 200 MHz, test. IPADS bulk cable injection conducted susceptibility shall be tested in accordance with MIL-STD-461 requirement CS114 from 10 kHz to 200 MHz. Any damage to IPADS or degradation of performance constitutes failure.

4.6.3.29 Conducted susceptibility, bulk cable injection, impulse excitation, test. IPADS bulk cable injection conducted susceptibility to impulse excitation shall be tested in accordance with MIL-STD-461 requirement CS115. Any damage to IPADS or degradation of performance constitutes failure.

4.6.3.30 Conducted susceptibility, damped sinusoidal transients, cables and power leads, 10 kHz to 100 MHz, test**.** IPADS cable and power lead conducted susceptibility to damped sinusoidal transients shall be tested in accordance with MIL-STD-461 requirement CS116 from 10 kHz to 100 MHz. Any damage to IPADS or degradation of performance constitutes failure.

4.6.3.31 Radiated emissions, magnetic field, 30 Hz to 100 kHz, test**.** IPADS magnetic field radiated emissions shall be tested in accordance with MIL-STD-461 requirement RE101 from 30 Hz to 100 kHz. Any emission exceeding the limits of MIL-STD-461 requirement RE101 constitutes failure.

4.6.3.32 Radiated emissions, electric field, 10 kHz to 18 GHz, test**.** IPADS electric field radiated emissions shall be tested in accordance with MIL-STD-461 requirement RE102 from 10 kHz to 18 GHz, with no reduction in the upper limit. Any emission exceeding the limits of MIL-STD-461 requirement RE102 constitutes failure.

4.6.3.33 Radiated susceptibility, magnetic field, 30 Hz to 100 kHz, test**.** IPADS magnetic field radiated susceptibility shall be tested in accordance with MIL-STD-461 requirement RS101 from 30 Hz to 100 kHz. Any damage to IPADS or degradation of performance constitutes failure.

4.6.3.34 Radiated susceptibility, electric field, 2 MHz to 18 GHz, test**.** IPADS electric field radiated susceptibility shall be tested in accordance with MIL-STD-461 requirement RS103 from 2 MHz to 18 GHz. Any damage to IPADS or degradation of performance constitutes failure.

4.6.3.35 Electrostatic charge control verification. IPADS susceptibility to electrostatic charges shall be verified in accordance with ANSI C63.16-1993 for an uncontrolled environment, using the hand/metal, air discharge method. The voltage range shall be from 1 kV to 15 kV, in 2 kV steps. Any non-recoverable or destructive response constitutes failure. IPADS susceptibility to electrostatic charges when sling hoisted by helicopter shall be verified in accordance with requirement 5.7.1 of MIL-STD-464. Failure to meet the requirements of 3.5.14.3.10 constitutes failure.

4.6.3.36 Electrical bonding verification. IPADS electrical bonding shall be verified in accordance with requirements 5.10, 5.10.1, 5.10.2, 5.10.3 and 5.10.4 of MIL-STD-464. Failure to meet the requirements of 3.5.14.4 constitutes failure.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

4.6.3.37 Nuclear, Biological & Chemical (NBC) Survivability verification. The IPADS and transit case designs shall be analyzed for survival when exposed to NBC contaminates and when decontaminated using the procedures of FM 3-11.5, and for entrapment of contaminates after decontamination. Tests shall be performed on materials that will be exposed to NBC contamination and decontamination when authoritative information on their survivability is not available. Deterioration of materials such that IPADS operation would be impaired or leaves IPADS vulnerable to leakage, or entrapment of contaminates constitutes failure.

4.6.4 Support and ownership requirements verifications.

4.6.4.1 Battery selection verification. All IPADS batteries shall be examined for approval. Lack of approval in accordance with 3.6.1.1 constitutes failure.

4.6.4.2 Color verification. The color of IPADS and transit case external surfaces shall be examined. Failure to conform to 3.6.1.2 constitutes failure.

4.6.4.3 Connector cap verification. IPADS shall be examined for connector caps. Failure to conform to 3.6.1.3 constitutes failure.

4.6.4.4 GPS receiver verification. GPS receiver documentation shall be examined for SAASM compliance and approval by the GPS Wing. Use of a non-SAASM based receiver or lack of documented approval by the GPS Wing constitutes failure.

4.6.4.5 M-code analysis. The IPADS design shall be analyzed for upgradability to M-code. Lack of a migration path to M-code constitutes failure.

4.6.4.6 Interchangeability demonstration. Components supplied as spare or repair parts shall be substituted for those, with the same part number, they are intended to replace in the IPADS. They shall be examined for form and fit, with respect to their interface with mating and adjoining components. Failure to install, or the modification of any component to accommodate, constitutes failure. After replacement, normal IPADS operation shall be simulated, including operation of all switches, controls, input and output devices, displays, indicators, and azimuth transfer devices. Surveying parameter errors (horizontal position, elevation, and azimuth) and initialization times shall be recorded. Any erroneous reading, malfunction, or failure to meet specified values for any parameter specified in Table I constitutes failure.

4.6.4.7 Nameplates and product marking examination. Identification plates and product markings shall be examined. Non-conformance with the requirements of 3.6.4 or 3.6.4.1 constitutes failure.

4.6.4.8 Transit case examination. Product drawings shall be examined to verify a transit case is supplied with each IPADS and that transit cases have been designed for each LRU. Lack of a transit case constitutes failure.

4.6.4.9 Transit case size examination. The IPADS transit case maximum exterior dimensions shall be measured. Non-conformance with the requirements of 3.6.5.1.1 constitutes failure.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

4.6.4.10 Transit case weight examination. The empty and loaded IPADS transit case weights shall be measured and the transit case shall be examined for handling provisions. Non-conformance with the requirements of 3.6.5.1.2 constitutes failure.

4.6.4.11 Pressure relief valve examination. The transit case shall be examined for the presence of an automatic pressure relief valve. Lack of a pressure relief valve constitutes failure.

4.6.4.12 Handle examination. Transit cases shall be examined for handles conforming to the requirements of 3.6.5.4. Non-conformance with the requirements of 3.6.5.4 constitutes failure.

4.6.4.13 Accessory storage examination. IPADS storage provisions shall be examined. Non-conformance with the requirements of 3.6.6 constitutes failure.

4.6.4.14 Tool kit examination. The IPADS tool kit shall be examined. Non-conformance with the requirements of 3.6.6.1 constitutes failure.

4.6.4.15 Reliability analysis. The IPADS Mean-Time-Between-Failure (MTBF) shall be calculated using the Reliability Information Analysis Center (RAC) 217Plus software tool or equivalent. The MTBF shall be calculated for a Ground, Mobile, Light Wheeled, Chassis Mounted environment, at an ambient temperature of +35 degrees C, dormant temperature of +14 degrees C, relative humidity of 40% and vibration levels of 4.0 G RMS. The reliability time is measured while IPADS is operational. A peacetime scenario will be used for the MTBF calculation. A calculated MTBF less than that specified in 3.6.7 constitutes failure.

4.6.4.16 Reliability demonstration. The IPADS Mean-Time-Between-Failure (MTBF) shall be demonstrated to a consumer's risk of a nominal 20 percent or lower. MIL-HDBK-781 provides guidance. Operating time may be accumulated from operation in host vehicles and simulated operation when subjected to shock, vibration and temperature conditions typical of the operational environment. A demonstrated MTBF less than that specified in 3.6.7 constitutes failure.

4.6.4.17 Maintenance level demonstration. IPADS manuals shall be examined for scheduled maintenance tasks above the Unit (first echelon) maintenance level. All scheduled maintenance tasks shall be demonstrated using skill levels and tools available at Unit level. Any scheduled maintenance task identified for performance above the Unit level or that is outside the capability of Unit level maintenance constitutes failure.

4.6.4.18 Fault isolation verification. IPADS BIT/BITE fault isolation capability shall be analyzed. Failure to meet the fault isolation requirements of 3.6.8.2 constitutes failure.

4.6.4.19 False removal rate verification. IPADS false removal rate shall be analyzed. Failure to meet the false removal rate requirements of 3.6.8.2.1 constitutes failure.

4.6.4.20 False alarm rate. IPADS false alarm rate shall be analyzed. Failure to meet the false alarm rate requirements of 3.6.8.2.2 constitutes failure.

4.6.4.21 Fault display demonstration. IPADS capability to determine and display faults or errors and indicate corrective actions shall be demonstrated by introducing simulated fault conditions. Failure to display faults, errors, or corrective actions constitutes failure.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

4.6.4.22 Replacement time demonstration. Removal and replacement of all LRUs replaced at the Unit level shall be demonstrated using the procedures in the technical manuals. Remove/replace and adjustment/calibration times shall be measured. Proper IPADS operation after replacement shall be verified. A remove/replace or adjustment/calibration time outside the limits of 3.6.8.3, or a malfunction or a failure to meet the performance requirements of Table I constitutes failure.

4.6.4.23 Maintenance items examination. IPADS and its manuals shall be examined to identify any maintenance items. Maintenance items shall be examined. Non-conformance with the requirements of 3.6.8.4 constitutes failure.

4.6.4.24 Special support equipment examination. IPADS manuals shall be examined for the identification of any special equipment requirements at the user, Unit, DS, or GS levels. Any special equipment requirement at the user, Unit, DS, or GS levels constitutes failure.

4.6.4.25 Calibration and adjustment demonstration. IPADS manuals shall be examined to identify any calibrations or adjustments required periodically or after a repair action. All calibrations and adjustments shall be demonstrated. Non-conformance with the requirements of 3.6.8.6 constitutes failure.

4.6.4.26 Environment, Safety, and Occupational Health (ESOH) verification. IPADS ESOH shall be analyzed. Non-conformance with the requirements of 3.6.9 constitutes failure.

4.6.4.27 Safety examination. IPADS and its transit cases, installations in host vehicles, and operation shall be examined by a qualified safety engineer for safety hazards, using SEL Form 1183 as a guide, information provided in the System Safety Assessment Report (if required), System Health Hazard Assessment Report (if required), and information obtained during testing. Non-conformance with the requirements of 3.6.10 constitutes failure.

4.6.4.28 Weight and balance verification. Weight and balance computations shall be made for IPADS installed in all host vehicles specified in the contract (6.2). Non-conformance with the requirements of 3.6.10.1 constitutes failure.

4.6.4.29 Electrical connections demonstration. Mating of all IPADS connectors and cables shall be attempted. The ability to mate connections not intended to be mated, or mismate and make electrical connections, constitutes failure.

4.6.4.30 Electrical overload protection verification. The IPADS design shall be analyzed for protection of IPADS and the vehicle from damage resulting from electrical overloads induced by normal or abnormal (fault) IPADS operation and conditions. Protective devices shall be examined for listing or certification by a nationally recognized testing laboratory. Inadequate conductor current capacity, lack of protection or use of non-listed or non-certified protective devices constitutes failure.

4.6.4.31 Ground fault protection verification. The IPADS design shall be analyzed to verify that personnel are protected from ground fault leakage currents when connected to 115 VAC power. Protective devices shall be examined for listing or certification by a nationally recognized testing laboratory. Failure to meet the requirements of 3.6.10.4 constitutes failure.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

4.6.4.32 Battery safety verification. The battery installation shall be examined for safety. The design shall be analyzed for explosive gas concentrations build-up under normal operating and fault conditions. Non-conformance with the requirements of 3.6.10.5 constitutes failure.

4.6.4.33 Battery installation markings examination. IPADS battery installation markings shall be examined. Non-conformance with the requirements of 3.6.10.5.1 constitutes failure.

4.6.4.34 Caution label examination. IPADS caution labels shall be examined. Non-conformance with the requirements of 3.6.10.5.2 constitutes failure.

4.6.4.35 Human factors engineering demonstration. The capabilities of the specified personnel to operate, maintain, and support the IPADS wearing the specified clothing shall be demonstrated. Failure to comply with the requirements of 3.6.11 constitutes failure of this demonstration.

4.6.4.36 Soldier performance demonstration. The capability for personnel to perform the required tasks with the required accuracy shall be demonstrated. Failure to comply with the provisions of 3.6.11.1 constitutes failure of this demonstration.

4.6.4.37 Human factors design examination. The IPADS shall be examined by a qualified human factors engineer for conformance with the requirements of 3.6.11.2. Failure to comply with the provisions of 3.6.11.2 constitutes failure of this examination.

4.6.4.38 Noise limits test. IPADS shall be tested for conformance with 3.6.12 in accordance with MIL-STD-1474. Nonconformance to the requirements of 3.6.12 constitutes failure.

4.6.4.39 Workmanship examination. Workmanship shall be examined for conformance with the requirements of 3.6.14. The presence of any defect constitutes failure.

5 PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (6.2). When actual packaging of materiel is to be performed by DOD personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activity within the Military Department or Defense Agency, or within the Military Department's System Command. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6 NOTES

(This Section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The Improved Position and Azimuth Determining System is intended for use in the conduct of field artillery surveys to determine the horizontal coordinates and elevations of locations critical in the fire control function, such as battery centers, launcher positions, orientating stations, declination stations, target acquisition devices, and survey control points. The system will determine the azimuth of the orienting lines for weapons and target

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

acquisition systems. The system will operate in any geographic area except above 84° north latitude and below 80° south latitude. IPADS may utilize valid GPS data. IPADS will operate when GPS, and other systems relying on radio frequency transmissions, are not available.

The IPADS covered by this specification is military unique because it must operate after exposure to low velocity airdrop, high elevation electromagnetic pulses, and the nuclear, biological and chemical (NBC) warfare environments and subsequent decontamination. Commercial equipment is not designed to withstand such extreme environments and would experience catastrophic failure. IPADS must meet the security requirements for tactical use of GPS, which requires use of military security technology not commercially available.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number and date of this specification.
b. Objective requirements to be met (1.2.)
c. The specific issue of individual documents referenced (2.2.1, 6.2.1.)
d. Requirements for submission of first article sample.
e. Requirements for submission of design verification sample.
f. Packaging requirements.
g. Serialization requirements.
h. Reprogramming cables required and type of reprogramming device (3.4.3.2).
i. Installation kit(s) required and type of host vehicle (3.4.1.1).
j. IUID requirements (3.6.4.1).
k. LRU transit cases required (3.6.5.2).

6.2.1 Government specifications and standards referenced in this document. The specific versions of government specifications and standards listed below were used in the preparation of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

A-A-52567B	Survey Instrument Automated, Integrated (AISI)
A-A-52573A	Theodolites, Surveying, Direction: Third Order
A-A-52574A	Theodolites, Surveying, Direction: Second Order
MIL-DTL-55116/2B	Connector, Plug, Six Pin Audio, Crimp Sleeve Terminals, Wire Strain Relief, U-229 Type
FED-STD-595C(1)	Colors Used In Government Procurement
MIL-STD-130N	Identification Marking of U.S. Military Property
MIL-STD-461E	Requirements for the Control of Electromagnetic Interference Characteristics of Subsystems And Equipment
MIL-STD-464	Electromagnetic Environmental Effects
MIL-STD-810G	Environmental Engineering Considerations and Laboratory Tests
MIL-STD-1275B	Characteristics of 28 Volt DC Electrical Systems in Military Vehicles
MIL-STD-1472F	Human Engineering
MIL-STD-1474D(1)	Noise Limits

6.2.2 217Plus Software Tool. The 217Plus Software Tool is a product of the DOD sponsored Reliability Information Analysis Center. Information on 217Plus can be obtained from http://theriac.org/.

6.3 Definitions. For the purposes of this specification, the following definitions apply.

6.3.1 Elevation. Elevation is the height above (positive) or below (negative) the reference surface for the vertical datum. The reference surface typically is mean-sea-level (msl) or the WGS 84 geoid. For the purposes of this specification, the reference surface is never the ellipsoid.

6.3.2 Autoreflection. Autoreflection is a method of creating a perpendicular line by projecting an image of a theodolite or AISI sight to a reflecting porro prism, then back to the telescope.

6.3.3 Azimuth. Azimuth is the horizontal angle measured clockwise from geodetic (true) north (geodetic or true azimuth), or from grid north (grid azimuth), to a line through an observed or designated point.

6.3.4 Circular Error Probable (CEP). CEP is the radius of a circle, centered about true, such that any measured position, selected from the total sample population, has a 50 percent probability of lying inside the circle. When the RMS errors in easting and northing are similar and the errors are normally distributed about the true position, CEP may be calculated as:

$$CEP = 1.1774 \times \frac{RMS_N + RMS_E}{2}$$

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

Where: RMS_N and RMS_E are the RMS errors in Northing and Easting, respectively.

6.3.5 Critical GPS data. Critical GPS data elements are identified in Table IX.

TABLE IX. Critical GPS data.

Initialization/TTFF/Satellite Related	Cryptographic Related
Almanac Data	Keys
Ephemeris	Mission Duration
Special Message	RMDZ Command and Event Time
UTC/Ionospheric Data Subframe 4 [SV(Page)ID 56]	NRMDZ Command and Event Time
HAC Data Subframe 4 [SV(Page)ID 63]	
Subframe 4 [SV(Page)ID 57-62]	
SV Health Subframe 5 [SV(Page)ID 51]	
WAGE Data Subframe 4 [SV(Page)ID 52]	
Supplemental Navigation Data Subframe 4 [SV(Page)ID 53]	
Supplemental Navigation Data Subframe 4 [SV(Page)ID 54]	
Operator entered/Last computed PVT data	

6.3.6 Datum. A set of constants specifying the coordinate system used for geodetic control, i.e. for calculating coordinates of points on Earth. The datum for a defined area contains the start point from which all survey in that area ultimately originates.

6.3.7 5th Order Survey. Field Artillery survey performed to an accuracy of 1 unit of error in 1,000 similar units of survey, for position accuracy. It is usually written as 1:1,000. 5th order survey azimuth accuracy is an azimuth of a line used in the extension of 5th order survey which, from its point of origin, has depreciated by a PE of 0.090 mils per main scheme angle turned.

6.3.8 4th Order Survey. Field Artillery survey performed to an accuracy of 1 unit of error in 3,000 similar units of survey, for position accuracy. It is usually written as 1:3,000. 4th order survey azimuth accuracy is an of a line used in the extension of 4th order survey that, from its point of origin at a 4th order astronomic azimuth line or higher-order direction, has depreciated by a PE of 0.030 mils per main scheme angle turned.

6.3.9 End Orienting Line (EOL). The EOL is a survey station used as an azimuth mark for the OS. The EOL must be located so that it is visible and at least 100 meters from the OS.

6.3.10 Ground fault. An unintentional electrical path between a part operating normally at some potential to ground, and ground.

6.3.11 GPS Centric Aiding. When GPS Centric Aiding is enabled and valid GPS data are available, IPADS determined positions will be referenced to GPS WGS 84 position regardless of any manually input position used to initialize IPADS.

6.3.12 GPS Relative Aiding. When GPS Relative Aiding is enabled and valid GPS data are available, IPADS determined positions will be referenced to the last SCP used to initialize or

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

update IPADS, regardless of any error between the SCP position and GPS position for that location.

6.3.13 Hazard probability. Hazard probabilities are defined in Table X.

TABLE X. Hazard probability definitions.

Description	Level	Individual Item	Fleet or Inventory
Frequent	**A**	Likely to occur frequently	Continuously experienced
Probable	**B**	Will occur several times in life of item	Will occur frequently
Occasional	**C**	Likely to occur sometime in life of item	Will occur several times
Remote	**D**	Unlikely, but possible to occur in life of item	Unlikely, but can reasonably be expected to occur
Improbable	**E**	So unlikely it can be assumed occurrence may not be experienced	Unlikely to occur but possible

6.3.14 Hazard severity. Hazard severity levels are defined in Table XI.

TABLE XI. Hazard severity definitions.

Description	Category	Accident definition
Catastrophic	**I**	Death, system loss, or severe environmental damage
Critical	**II**	Severe injury, severe occupational illness, major system damage, or environmental damage
Marginal	**III**	Minor injury, minor occupational illness, minor system damage, or environmental damage
Negligible	**IV**	Less than minor injury, occupational illness, system damage, or environmental damage

6.3.15 High Accuracy Reference Network (HARN). A HARN is a statewide or regional upgrade in accuracy of NAD 83 coordinates using Global Positioning System (GPS) observations. HARNs were observed to support the use of GPS by Federal, state, and local surveyors, geodesists, and many other applications. The cooperative network upgrading program began in Tennessee in 1986. The last field observations were completed in Indiana in September 1997 after horizontally upgrading some 16,000 survey stations to A-order or B-order status. Horizontal A-order stations have a relative accuracy of 5 mm +/- 1:10,000,000 relative to other A-order stations. Horizontal B-order stations have a relative accuracy of 8 mm +/- 1:1,000,000 relative to other A-order and B-order stations Of these 16,000 stations, The National Geodetic Survey (NGS) has committed to maintaining about 1,400 survey stations, named the Federal Base Network, and the various states will maintain the remainder.

6.3.16 High Order Survey. IPADS equivalent to 4th order survey. Requires a position accuracy of 4 meters (CEP), elevation of 2 meters (PE), an azimuth of 0.4 mils (PE).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

6.3.17 Hub. A hub is a temporary traverse-station marker, usually of wood. The stake is driven flush with the ground with a tack or small nail on top to mark the exact point of reference for angular and linear measurements.

6.3.18 Interchangeable. Interchangeable parts are defined as two or more parts possessing such functional and physical characteristics as to be equivalent in performance and durability, and capable of being exchanged one for the other without alteration of the parts, of mating or adjoining parts, except for adjustment, and without selection for fit or performance.

6.3.19 Leakage current. All currents, including capacitively coupled currents, which may be conveyed between energized parts of a circuit and ground or other parts.

6.3.20 Lower Order Survey. IPADS equivalent to 5th order survey. Requires a position accuracy of 7 meters (CEP), elevation of 3 meters (PE), an azimuth of 0.4 mils (PE).

6.3.21 Malicious Code Insertion. An attack on a computer designed to install a malicious code. This attack can come from an external source (infected email or infected shareware) or may come in software that has been infected at the manufacturer's plant.

6.3.22 Mean-Time-Between-Failure (MTBF). The operating time divided by the number of equipment failures, including hardware and software. For example, a system operating 500 hours before suffering a hardware and a software failure would have a MTBF of 250 hours.

6.3.23 Mean-Time-Between-System-Abort (MTBSA). The operating time divided by the number of system aborts. For example, a system operating 500 hours before suffering 2 system aborts would have a MTBSA of 250 hours.

6.3.24 Mils. Unit for angular measurements used by the Field Artillery. A circle (360°) contains 6400 mils.

6.3.25 Orienting Line (OL). A line of direction from an orienting station (OS) to an end of orienting line (EOL)

6.3.26 Orienting Station (OS). A station used by the personnel of a firing battery or platoon to orient the weapons. The coordinates and height of the OS and a line of known direction are required for use.

6.3.27 Probable Error (PE). PE is the equally likely deviation (50 percent probability) of a set of linear measurements about the true (reference) value. Where the measurements are normally distributed about the reference value(s), PE may be calculated as:

$$PE = 0.6745 \times RMS_x$$

6.3.28 Radial error (RE). Radial error is the horizontal distance between the reference horizontal coordinates and IPADS determined horizontal coordinates of a SCP.

$$RE = \sqrt{(E_R - E_I)^2 + (N_R - N_I)^2}$$

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

Where:

E_R and E_I are the reference and IPADS eastings, respectively.

N_R and N_I are the reference and IPADS northings, respectively.

6.3.29 Root-Mean-Square (RMS) error. RMS error is the square root of the mean of the sum of the squared errors, relative to the reference value(s), for all measurements in the sample population.

$$RMS_x = \sqrt{\frac{\sum_{i=1}^{N} (x_i)^2}{N}}$$

Where:

N is the total number of measurements in the sample.

$X_i = m_i - M_i$ for linear or angular errors.

m_i is the i'th measurement in the sample. (m_0 is the initial measurement)

M_i is the reference value associated with the i'th measurement.

6.3.30 Survey Control Point (SCP). A point on the earth, with known coordinates and elevation, which is used to start or close a survey.

6.3.31 3rd Order Survey. Survey performed to an accuracy of 1 unit of error in 5,000 similar units of survey, for position accuracy. It is usually written as 1:5,000.

6.3.32 Trap Door. Malicious software designed to allow a non-authorized user to access a computer, through its own systems, bypassing security requirements.

6.3.33 Two-position method. The two-position method of azimuth transfer utilizes inverse computations between two positions established by the system. Typically, distances between the two positions range from 100 to 1000 meters.

6.3.34 Universal Transverse Mercator (UTM). The grid projection system upon which all U.S. Army maps are based.

6.3.35 Virus/Viruses. Malicious software designed to cause a computer to act in a manner other than that intended by its users.

6.3.36 Witness stake. A witness stake is a stake driven into the ground at an angle, usually with a piece of highly visible cloth attached. Used as an aid in recovery of a survey station or hub.

6.4 Acronyms and abbreviations. The following acronyms and abbreviations may be used in the main text or appendices of this specification.

AISI	Automated Integrated Survey Instrument
ANSI	American National Standards Institute
BIT	Built-In-Test

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

BITE	Built-In-Test-Equipment
BTU	British Thermal Unit
C	Centigrade
CEP	Circular Error Probable
cm	Centimeter
C/N_0	Carrier to noise ratio in 1 Hz bandwidth
D/M/S	Degrees, Minutes, Seconds
DC	Direct Current
DEG	Degrees
E	East
EGM	Earth Gravity Model
EGM96	Earth Gravity Model 1996
EMC	Electromagnetic Compatibility
EMI	Electromagnetic Interference
EMP	Electromagnetic Pulse
E.O.	Executive Order
EOL	End of Orienting Line
ESOH	Environment, Safety, and Occupational Health
F	Fahrenheit
ft	Feet
g, G	Gravity
GHz	Giga-Hertz
GPS	Global Positioning System
GVW	Gross Vehicle Weight
HAC	Health, Anti-Spoofing, Configuration Code
HAE	Height-Above-Ellipsoid
HARN	High Accuracy Reference Network
hr	Hour
Hz	Hertz
IAP	Integrated Armor Package
ICD	Interface Control Document
ID	Identifier
in	Inch

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

IPADS	Improved Position and Azimuth Determining System
IS	Interface Specification
IUID	Item Unique Identification
K	One thousand
kg	Kilogram
kHz	Kilohertz
km	Kilometer
kV	Kilovolt
Lat	Latitude
lbs	Pounds
Lon	Longitude
LRU	Line Replaceable Unit
m	Meter
M	Mil
m/s	Meters per Second
MGRS	Military Grid Reference System
MHz	Megahertz
min	Minutes
MRI	Machine Readable Information
MSD	Maintenance Support Device
msl	Mean-Sea-Level
MTBF	Mean-Time-Between-Failure
MTBSA	Mean-Time-Between-System-Abort
N	North
N/A	Not Applicable
NAD 83	North American Datum 1983
NBC	Nuclear-Biological-Chemical
NGS	National Geodetic Survey
NRMDZ	Non-Recoverable Mission Duration Zeroization
NSN	National/NATO stock number
O	Objective
OL	Orienting Line
ORD	Operational Requirements Document
OS	Orienting Station

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

PE	Probable Error
PPS	Pulse per Second
PSD	Power Spectral Density
PVT	Position, Velocity and Time
RE	Radial error
RMDZ	Recoverable Mission Duration Zeroization
RMS	Root Mean Square
S	South
SAE	Society of Automotive Engineers
SAASM	Selective Availability/Anti-Spoofing Module
sec	Second
S/N	Serial Number
SUSV	Small Unit Support Vehicle
SV	Space Vehicle (satellite)
T	Threshold
TTFF	Time-to-First-Fix
UTC	Universal Time, Coordinated
UPS	Universal Polar Stereographic
UTM	Universal Transverse Mercator
V	Volts
VAC	Volts alternating current
W	West
WAGE	Wide Area GPS Enhancement
WGS	World Geodetic System
WGS 84	World Geodetic System 1984

6.5 Personnel duties.

6.5.1 IPADS operator. IPADS will be operated by MOS 13S20 or 13S30 Field Artillery Surveyors. Operator duties include:

a. IPADS preoperational checks and services.

b. IPADS turn-on and initialization (cold and hot start).

c. IPADS operation.

d. Providing directions to the driver on positioning/orienting the vehicle.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

e. Set up and tear down theodolites and total station instruments used for remote transfer of position and azimuth.

f. Performing operations necessary to transfer position to and from SCPs remote from the vehicle. (e.g. auto-reflection operations.)

g. Performing operations necessary to transfer azimuth to OLs remote from the vehicle.

h. Establishing and storing SCP and Mark data.

i. Updating IPADS position.

j. Performing traverse closure (survey adjustment) operations.

k. Performing data communication operations.

l. Notifying driver when zero-velocity stops are required.

m. IPADS shutdown and post operational checks and services.

n. IPADS installation and transfer between vehicles.

o. Failure diagnosis, LRU replacement, battery replacement, other unit level repair actions, and repair verification.

p. Performing driver duties, as required to conduct the mission.

6.5.2 Vehicle driver. IPADS ground vehicles will be operated by MOS 13S10 Field Artillery Surveyors. Driver duties include:

a. Vehicle preoperational checks and services.

b. Vehicle operation.

c. Positioning/orienting the vehicle per IPADS operator instructions.

d. Occupying, as necessary, positions remote from the vehicle to transfer position and azimuth.

e. Setting hubs (temporary survey markers).

f. Setting witness stakes.

g. Recording data on witness stakes.

h. Stopping the vehicle when zero-velocity stops are required.

i. Vehicle shutdown and post operational checks and services.

j. IPADS installation and transfer between vehicles.

k. Performing IPADS operator duties, as required to conduct the mission.

6.6 Airdrop environment. Airdropped materiel is extracted from a C-130 aircraft at 140 knots, from C-141 and C-5 aircraft at 150 knots by extraction parachutes at an elevation of 700 feet or more. Recovery parachutes are attached to the load to slow the descent and to allow an impact velocity of approximately 28.5 ft/sec. The vertical impact is approximately equivalent to that from a freefall from 12.7 ft. The load is placed on energy absorbing material and rigged for airdrop as described in MIL-HDBK-669, Loading Environment and Related Requirements for Platform Rigged Airdrop Materiel. The Government performs the rigging design. Equipment secured to a M998 HMMWV, at a GVW of 8400 pounds, will experience approximately 21 G's deceleration for about 60 milliseconds duration upon impact. These values should not be used as

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

design limits, as they are theoretical and not based on test data. Actual values may be higher or lower. Rigging for HMMWVs is described in FM 4-20.117, Rigging High Mobility Multipurpose Wheeled Vehicles (available at http://155.217.58.58/atdls.htm).

6.7 Reliability relationships. The IPADS Operational Requirements Document (ORD) specifies a 2,000 hour Mean-Time-Between-System-Abort (MTBSA). Experience indicates approximately 80% to 90% of Operational "failures or aborts" are hardware/software related. The remainder are operator/maintainer related. The equipment MTBF is specified at 2,400 hours to meet the ORD requirement.

6.8 Subject term (key words) listing.

Elevation
Easting
GPS
Latitude
Longitude
Northing

6.9 Amendment notations The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

APPENDIX A

CHARACTERISTICS OF REQUIRED DISPLAY FIELDS

A.1 SCOPE

A.1.1 Scope. This appendix provides standardized display field characteristics. This appendix is a mandatory part of this specification. The information herein is intended for compliance.

A.2 APPLICABLE DOCUMENTS

A.2.1 General. The documents listed in this section are specified in section 3 of this appendix. This section does not include documents in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements documents cited in section 3 of this appendix, whether or not they are listed.

A.2.2 Government documents.

A.2.2.1 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues are those in effect on the date of the solicitation.

PUBLICATIONS

NIMA TR 8350.2 Third Edition Amendment 1	Department of Defense World Geodetic System 1984, Its Definition and Relationships with Local Geodetic Systems

(Copies of NIMA TR8350.2 may be downloaded from http://164.214.2.59/GandG/tr8350_2.html)

A.2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

A.3 REQUIREMENTS

A.3.1 Display field characteristics. The characteristics of display fields for displayed parameters listed in Table A - I shall be as specified in Table A - I.

A.3.1.1 Ellipsoid and datum names. Ellipsoid and datum names shall be displayed as specified in Table A - II. Display ellipsoid and datum names may be cross-referenced to ellipsoid and datum shift parameters in NIMA TR8350.2 using the identifier codes listed in Table A - II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

A.3.1.2 Other display fields. The characteristics of display fields for parameters not listed in Table A - I or Table A - II shall be selected to minimize operator errors in exercising control functions, inputting data, and reading out data.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

APPENDIX A

TABLE A - I. Characteristics of required display fields.

Parameter	Field Layout *	Range	Comment
Survey control point identifier	**PNT NAME:** *aaaaaaaaaaaaaaa*		
UTM Easting	**EAST:** *######.##* **M**	100000.00 – 900000.00	
UTM Northing	**NORTH:** *########.##* **M**	0.00 – 10000000.00	
Elevation	**ELEVATION:** *####.#* M	-400.0 to 9999.9	
UTM grid zone	**GRID ZONE:** *###*	-60 to 60, except 0	Negative in southern hemisphere; positive in northern hemisphere
Mark identifier	**MARK** *n*: *aaaaaaaa*		
Azimuth (mils)	**AZIMUTH** *n*: *####.###* **MILS**	0.000 to 6399.999	
Azimuth (decimal degrees)	**AZIMUTH** *n*: *###.####* **DEG**	0.0000 to 359.9999	
Azimuth (degrees, minutes, seconds)	**AZIMUTH** *n*: *###/##/##* **D/M/S**	0/0/0 to 359/59/59	
Azimuth type	tttt	TRUE or GRID	
Latitude (degrees, minutes, seconds)	**LAT:** *##/##/##.###/*t	84/59/59.999/S to 84/59/59.999/N	*t* = **N** in northern hemisphere; *t* = **S** in southern hemisphere
Longitude (degrees, minutes, seconds)	**LONG:** *###/##/##.###/*t	180/00/00.000/W to 180/00/00.000/E	*t* = **E** in eastern hemisphere; *t* = **W** in western hemisphere
Latitude (decimal degrees)	**LAT:** *##.#######/*t	84.9999999/S to 84.9999999/N	*t* = **N** in northern hemisphere; *t* = **S** in southern hemisphere

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

APPENDIX A

TABLE A - I. Characteristics of required display fields.

Parameter	Field Layout *	Range	Comment
Longitude (decimal degrees)	**LONG:** ###.#######/t	180.0000000/W to 180.0000000/E	t = **E** in eastern hemisphere; t = **W** in western hemisphere
Ellipsoid name	**ELLIP:** tttttttttttttt	See Table A-2.	
Semi-major axis of user defined ellipsoid (meters)	**MAJOR:** #######.### **M**	6360000.000 to 6380000.000	
Flattening or semi-minor axis indicator	**FLAT/MINOR:** tttttttttt	FLATTENING or SEMI-MINOR	
Semi-minor axis of user defined ellipsoid (meters)	**MINOR:** #######.### **M**	6330000.000 to 6360000.000	
Inverse flattening of user defined ellipsoid	**FLAT:** ###.#########	290.000000000 to 310.000000000	
Datum name	**DATUM:** tttttttttttttt	See Table A-2.	
X-shift for user defined datum (meters)	**X-SHIFT:** #####	-9999 to 9999	
Y-shift for user defined datum (meters)	**X-SHIFT:** #####	-9999 to 9999	
Y-shift for user defined datum (meters)	**X-SHIFT:** #####	-9999 to 9999	
Date set	**DATE SET:** ##/##/##	Day 01 to 31 Month 01 to 12 Year 00 to 99	
Time set	**TIME SET:** ##:##:##	Hour 00 to 23 Minute 00 to 59	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

APPENDIX A

TABLE A - I. Characteristics of required display fields.

Parameter	Field Layout *	Range	Comment
		Second 00 to 60	
Time zone designator	**TIME ZONE:** *t*	A-Z (excluding 'J')	Z = GMT A = GMT + 1 hr … M = GMT + 12 hrs N = GMT – 1 hr … Y = GMT – 12 hrs
Daylight savings time indicator	**DAYLIGHT SAVINGS:** *ttt*	YES or NO	
Time display	*##:##:##*	Hour 00 to 23 Minute 00 to 59 Second 00 to 60	
Estimated Horizontal Error	**EHE:** *t*±*##.#* **M**	0.0 to 99.9	Display >±99.9 for EHE > 99.9
Estimated Vertical Error	**EVE:** *t*±*##.#* **M**	0.0 to 99.9	Display >±99.9 for EVE > 99.9
Number of healthy satellites	**Healthy SVs:** *##*	0 to 99	
Number of tracked satellites	**Tracked SVs:** *##*-**Y** *##*-**P** *##*-**C/A**	0 to 99	
Number of used satellites	**Used SVs:** *##*-**Y** *##*-**P** *##*-**C/A**	0 to 99	
GPS key type loaded	**CV Loaded:** *tttt*	None, GUV, or CV	
Days keys remaining	*##* **days remaining**	0 to 99	Displayed on CV Loaded line only when CVw or BCVm loaded

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

APPENDIX A

TABLE A - I. Characteristics of required display fields.

Parameter	Field Layout *	Range	Comment
GPS almanac age	**`Almanac Age:`** *`t`*`##` **`days`**	0 to 99	Display >99 if almanac age > 99 days
Carrier-to-noise ratio (C/N_0)	**C/N_0:** *ttt*	Low, Ok	Display Ok if C/N_0 > 35 dB-Hz for any SV being used in PVT solution, else display Low
* Displayed field labels are in bold text. *a* = alpha-numeric characters in the range of A-Z; 0-9; and space. *t* = specified text. # = numeric digit 0-9; +; -. *n* = index number from 1 to the maximum value.			

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

TABLE A - II. Ellipsoid and datum display names.

Ellipsoid		Associated Datum	
ID*	**Display Name**	**ID***	**Display Name**
AA	AIRY 1830	OGB-M	OSGB 36 (MEAN)
		OGB-A	OSGB 36 (ENG)
		OGB-B	OSGB 36(ENG&WL)
		OGB-C	OSGB 36 (SCOT)
		OGB-D	OSOB 36 (WALES)
			USER DEFINED *n*
AN	AUSTRALIAN NATL	ANO	ANNA 1 ASTRO 65
		AUA	AUSTRLN GEOD 66
		AUG	AUSTRLN GEOD 84
			USER DEFINED *n*
BR	BESSEL 1841	BUR	BUKIT RIMPAH
		BAT	DJAKARTA BATAV
		EST	ESTONIA
		GSE	GUNUNG SEGARA
		HER	HERMANNSKOGEL
		MAS	MASSAWA
		CCD	S-JTSK
		TOY-M	TOKYO (MEAN)
		TOY-A	TOKYO (JAPAN)
		TOY-B1	TOKYO (KOREA)
		TOY-C	TOKYO (OKINAWA)
			USER DEFINED *n*
BN	BESSEL (NAMIBIA)	SCK	SCHWARZECK
			USER DEFINED *n*
CC	CLARKE 1866	AMA	AM SAMOA 1962
		BER	BERMUDA 1957
		CAC	CAPE CANAVERAL
		GUA	GUAM 1963
		LCF	L C 5 ASTRO 61
		LUZ-A	LUZON (PHILPNS)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

TABLE A - II. Ellipsoid and datum display names.

Ellipsoid		Associated Datum	
ID*	**Display Name**	**ID***	**Display Name**
		LUZ-B	LUZON (MIND IL)
		NAS-C	NA 27 (CONUS)
CC	CLARKE 1866	NAS-B	NA 27 (WEST US)
		NAS-A	NA 27 (EAST US)
		NAS-D	NA 27 (ALASKA)
		NAS-V	NA 27 (ALN IS E)
		NAS-W	NA 27 (ALN IS W)
		NAS-Q	NA 27 (BAHAMAS)
		NAS-R	NA 27 (SAN SLV)
		NAS-E	NA 27 (CANADA)
		NAS-F	NA 27 (ALB&BC)
		NAS-G	NA 27 (E CANDA)
		NAS-H	NA 27 (MAN&ONT)
		NAS-I	NA 27 (NW TERR)
		NAS-J	NA 27 (YUKON)
		NAS-O	NA 27 (CANL ZN)
		NAS-P	NA 27 (CARIBAN)
		NAS-N	NA 27 (C AMER)
		NAS-T	NA 27 (CUBA)
		NAS-U	NA 27 (GREENLD)
		NAS-L	NA 27 (MEXICO)
		OHA-M	OLD HWN (MEAN)
		OHA-A	OLD HWN (HAWAI)
		OHA-B	OLD HWN (KAUAI)
		OHA-C	OLD HWN (MAUI)
		OHA-D	OLD HWN (OAHU)
		PUR	PUERTO RICO
			USER DEFINED *n*
CD	CLARKE 1880	ADI-M	ADINDAN (MEAN)
		ADI-E	ADINDAN (BURK)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

TABLE A - II. Ellipsoid and datum display names.

Ellipsoid		Associated Datum	
ID*	**Display Name**	**ID***	**Display Name**
		ADI-F	ADINDAN (CAMRN)
		ADI-A	ADINDAN (ETHOP)
		ADI-C	ADINDAN (MALI)
		ADI-D	ADINDAN (SENEG)
CD	CLARKE 1880	ADI-B	ADINDAN (SUDAN)
		AIA	ANTIGUA IL AST
		ARF-M	ARC 1950 (MEAN)
		ARF-A	ARC 1950 (BOTS)
		ARF-H	ARC 1950 (BURU)
		ARF-B	ARC 1950 (LESO)
		ARF-C	ARC 1950 (MALA)
		ARF-D	ARC 1950 (SWZL)
		ARF-E	ARC 1950 (ZAIR)
		ARF-F	ARC 1950 (ZAMB)
		ARF-G	ARC 1950 (ZIMB)
		ARS-M	ARC 1960 (MEAN)
		ARS-A	ARC 1960 (KENA)
		ARS-B	ARC 1960 (TANZ)
		PHA	AYABELLE LIGHT
		CAP	CAPE
		CGE	CARTHAGE
		DAL	DABOLA
		DID	DECEPTION IS
		FOT	FT THOMAS 1955
		LEH	LEIGON
		LIB	LIBERIA 1964
		MIK	MAHE 1971
		MER	MERCHICH
		MIN-A	MINNA (CAMRN)
		MIN-B	MINNA (NIGERIA)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

APPENDIX A

TABLE A - II. Ellipsoid and datum display names.

Ellipsoid		Associated Datum	
ID*	**Display Name**	**ID***	**Display Name**
		ASM	MONTSERRAT IL
		MPO	M'PORALOKO
		NAH-A	NAHRWAN (OMAN)
		NAH-B	NAHRWAN (UAE)
		NAH-C	NAHRWAN (SAUDI)
		NSD	NOR SAHARA 1959
CD	CLARKE 1880	FAH	OMAN
		PTB	POINT 58
		PTN	POINTE NOIRE 48
		SRL	SIERRA LEONE 1960
		VOI	VOIROL 1874
		VOR	VOIROL 1960
		MVS	VITI LEVU 1916
			USER DEFINED *n*
EB	EVEREST (BRUNEI)	TIL	TIMBALAI 1948
			USER DEFINED *n*
EA	EVEREST (1830)	IND-B	INDIAN (BANGLD)
		INF-A	INDIAN 1954
		ING-A	IND 1960 (VIET)
		ING-B	IND 1960 (CS IS)
		INH-A1	INDIAN 1975
		KAN	KANDAWALA
			USER DEFINED *n*
EC	EVEREST (1956)	IND-I	INDIA & NEPAL
			USER DEFINED *n*
EF	EVEREST (PAKIS)	IND-P	INDIAN (PAKIS)
			USER DEFINED *n*
EE	EVEREST (1948)	KEA	KERTAU 1948
			USER DEFINED *n*
RF	GRS 80	NAR-A	NA 83 (ALASKA)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

APPENDIX A

TABLE A - II. Ellipsoid and datum display names.

Ellipsoid		Associated Datum	
ID*	**Display Name**	**ID***	**Display Name**
		NAR-E	NA 83 (ALUT IS)
		NAR-B	NA 83 (CANADA)
		NAR-C	NA 83 (CONUS)
		NAR-H	NA 83 (HAWAII)
		NAR-D	NA 83 (MX&C AM)
		SIR	SIRGAS
			USER DEFINED *n*
HE	HELMERT	OEG	OLD EGYPT 1907
			USER DEFINED *n*
HO	HOUGH 1960	ENW	WAKE-ENIWETOK
			USER DEFINED *n*
ID	INDONESIAN 1974	IND	INDONESIAN 1974
			USER DEFINED *n*
IN	INTERNATIONAL	AIN-A	AIN ABD 70 (BAR)
		AIN-B	AIN ABD 70 (SAU)
		ASC	ASCENSION IL 58
		ATF	ASTRO BEACON E
		SHB	ASTRO DOS 71/4
		TRN	ASTRO TERN IL
		ASQ	ASTRO STA 1952
		IBE	BELLEVUE IGN
		BID	BISSAU
		BOO	BOGOTA OBSERVTY
		CAZ	CAMP AREA ASTRO
		CAI	CAMPO INCHAUSPE
		CAO	CANTON ASTRO 66
		CHI	CHATHAM IL 71
		CHU	CHUA ASTRO
		COA	CORREGO ALEGRE
		GIZ	DOS 1968

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

TABLE A - II. Ellipsoid and datum display names.

Ellipsoid		Associated Datum	
ID*	**Display Name**	**ID***	**Display Name**
		EAS	EASTER IL 67
		EUR-M	EUR 50 (MEAN)
		EUR-E	EUR 50 (CYPRUS)
		EUR-F	EUR 50 (EGYPT)
		EUR-G	EUR 50 (BRT IL)
		EUR-B	EUR 50 (GREECE)
		EUR-H	EUR 50 (IRAN)
		EUR-S	EUR 50 (IRAQ)
		EUR-I	EUR 50 (SARDIN)
IN	INTERNATIONAL	EUR-J	EUR 50 (SICILY)
		EUR-L	EUR 50 (MALTA)
		EUR-C	EUR 50 (NOR&FN)
		EUR-D	EUR 50 (PGL&SP)
		EUR-A	EUR 50 (W EUR)
		EUR-T	EUR 50 (TUNISA)
		EUS	EUR 79
		GAA	GAN 1970
		GEO	GEOD DATUM 49
		GRA	GRACIOS BASE SW
		DOB	GUX 1 ASTRO
		HEN	HERAT NORTH
		HJO	HJORSEY 1955
		HKD	HONG KONG 1963
		HTN	HU-TZU-SHAN
		ISG	ISTS 061 AST 68
		IST	ISTS 073 AST 69
		JOH	JOHNSTON IL 61
		KEG	KERGUELEN IL 49
		KUS	KUSAIE ASTRO 51
		MID	MIDWAY ASTRO 61

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

APPENDIX A

TABLE A - II. Ellipsoid and datum display names.

Ellipsoid		Associated Datum	
ID*	**Display Name**	**ID***	**Display Name**
		NAP	NAPARIMA BWI
		FLO	OBSERVIO MET 39
		OHI-M	OLD HWN (MEAN)
		OHI-A	OLD HWN (HAWAI)
		OHI-B	OLD HWN (KAUAI)
		OHI-C	OLD HWN (MAUI)
		OHI-D	OLD HWN (OAHU)
		PLN	PICO DE LAS NVS
		PIT	PITCAIRN AST 67
		POS	PORTO SANTO 36
		PRP-M	PR SA 56 (MEAN)
IN	INTERNATIONAL	PRP-A	PR SA 56 (BOLV)
		PRP-B	PR SA 56 (N CH)
		PRP-C	PR SA 56 (S CH)
		PRP-D	PR SA 56 (COLM)
		PRP-E	PR SA 56 (ECUD)
		PRP-F	PR SA 56 (GUYN)
		PRP-G	PR SA 56 (PERU)
		PRP-H	PR SA 56 (VENZ)
		HIT	PR S CHILE 1963
		QAT	QATAR NATIONAL
		QUO	QORNOQ
		REU	REUNION
		MOD	ROME 1940
		SAE	SANTO DOS 1965
		SAO	SAO BRAZ
		SAP	SAPPER HILL 43
		SGM	SELVAGEM GRANDE
		TAN	TANANARIVE OBS
		TDC	TRISTAN AST 68

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

APPENDIX A

TABLE A - II. Ellipsoid and datum display names.

Ellipsoid		Associated Datum	
ID*	**Display Name**	**ID***	**Display Name**
		WAK	WAKE ISLAND AST
		YAC	YACARE
		ZAN	ZANDERIJ
			USER DEFINED *n*
KA	KRASSOVSKY 1940	AFG	AFGOOYE
		PUK	PULKOVO 1942
		SPK-A	S-42 (HUNGARY)
		SPK-B	S-42 (POLAND)
		SPK-C	S-42 (CZECH)
		SPK-D	S-42 (LATVIA)
		SPK-E	S-42 (KAZAKSTN)
		SPK-F	S-42 (ALBANIA)
		SPK-G	S-42 (ROMANIA)
KA	KRASSOVSKY 1940		USER DEFINED *n*
AM	MOD AIRY	IRL	IRELAND 1965
			USER DEFINED *n*
FA	MOD FISCHER 60	SOA	SOUTH ASIA
			USER DEFINED *n*
SA	SO AMERICAN 69	SAN-M	SA 69 (MEAN)
		SAN-A	SA 69 (ARGENTA)
		SAN-B	SA 69 (BOLIVIA)
		SAN-C	SA 69 (BRAZIL)
		SAN-D	SA 69 (CHILE)
		SAN-E	SA 69 (COLMBIA)
		SAN-F	SA 69 (ECUADOR)
		SAN-J	SA 69 (GALP IL)
		SAN-G	SA 69 (GUYANA)
		SAN-H	SA 69 (PARAGUA)
		SAN-I	SA 69 (PERU)
		SAN-K	SA 69 (TRN&TBG)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

TABLE A - II. Ellipsoid and datum display names.

Ellipsoid		Associated Datum	
ID*	**Display Name**	**ID***	**Display Name**
		SAN-L	SA 69 (VENEZLA)
			USER DEFINED *n*
WD	WGS 72		WGS 72
			USER DEFINED *n*
WE	WGS 84	KGS	KOREAN GS 1995
			WGS 84
			USER DEFINED *n*
	USER DEFINED *n*		USER DEFINED *n*

* ID per NIMA TR 8350.2, third edition, January 2000 update.

n = index number from 1 to the maximum value.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

APPENDIX B

MILITARY GRID REFERENCE SYSTEM (MGRS)

B.1 SCOPE

B.1.1 Scope. This appendix provides requirements for implementing MGRS in IPADS. This appendix is a mandatory part of this specification. The information herein is intended for compliance.

B.2 APPLICABLE DOCUMENTS

B.2.1 General. The documents listed in this section are specified in section 3 of this appendix. This section does not include documents in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements documents cited in section 3 of this appendix, whether or not they are listed.

B.2.2 Government documents.

B.2.2.1 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues are those in effect on the date of the solicitation.

PUBLICATIONS

ERDC/TEC SR-00-1	Handbook for Transformation of Datums, Projections, Grids, and Common Coordinate Systems

(Copies of ERDC/TEC SR-00-1 may be obtained from the contracting officer.)

B.2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

B.3 REQUIREMENTS

B.3.1 MGRS implementation. MGRS shall be implemented in IPADS in accordance with ERDC/TEC SR-00-1 except selection of the 100,000 meter grid square identification letter scheme shall be in accordance with Table B-I.

B.3.2 MGRS resolution. The resolution of MGRS coordinates shall be one meter.

B3.2 MGRS coverage area. MGRS shall be implemented for the UTM coverage area. Implementation for the UPS coverage area is not required.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

APPENDIX B

TABLE B-I MGRS 100,000 meter grid square identification.

Ellipsoid		100,000 Meter Grid Square Identification	
Ellipsoid Name	**ID Code**	**AA ***	**AL ***
Airy 1830	AA	X	
Australian National	AN	X	
Bessel 1841 (Ethiopia, Indonesia)	BR		X
Bessel 1841 (Namibia)	BN		X
Clarke 1866	CC		X
Clarke 1880	CD		X
Everest (Sabah Sarawak)	EB	X	
Everest (India 1830)	EA	X	
Everest (India 1956)	EC	X	
Everest (Pakistan)	EF	X	
Everest (Malaysia and Singapore 1948)	EE	X	
Everest (Malaysia1969)	ED	X	
Geodetic Reference System 1980 (GRS 80)	RF	X	
Helmert 1906	HE	X	
Hough 1960	HO	X	
Indonesian 1974	ID	X	
International 1924	IN	X	
Krassovsky 1940	KA	X	
Modified Airy	AM	X	
Modified Fischer 1960	FA	X	
South American 1969	SA	X	
World Geodetic System 1972 (WGS 72)	WD	X	
World Geodetic System 1984 (WGS 84)	WE	X	
User Defined		X	

* Letter scheme “AA” corresponds to ERDC/TEC SR-00-1 Figure 7.8, “AL” to ERDC/TEC SR-00-1 Figure 7.7.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.

Custodian:

Army- AR

Navy-AS

Air Force – 99

Preparing activity:

Army-AR

(Project 6675–2015-002)

Review activity:

Army-CE3, CR, MI,

Navy – MC, YD

Air Force –03, 33, 71

DLA – IS, GS1

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:42Z
Check the source to verify that this is the current version before use.