MILITARY SPECIFICATION

RAILWAY CAR, FLAT, 56-1/2-INCH GAGE, HEAVY DUTY, 140-TON CAPACITY, DOMESTIC SERVICE

This specification is approved for use by the Mobility Equipment Research and Development Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers heavy duty flat cars for transporting tracked vehicles, and American National Standards Institute/International Organization for Standardization (ANSI/ISO) containers.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified (see 6.2), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-P-3320	- Painting and Marking: Freight and Maintenance Cars.
MIL-P-3558	- Plate, Identification, Locomotive, Railway Cars, and Work Equipment.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Mobility Equipment Research and Development Command, ATTN: DRDME-DS, Fort Belvoir, VA 22060 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:43Z
Check the source to verify that this is the current version before use.

MIL-D-23003 - Deck Covering Compound, Non-Slip, Lightweight.

MIL-P-52192 - Primer Coating, Epoxy.

STANDARD

FEDERAL

FED-STD-H28 - Screw-Thread Standards for Federal Services.

MILITARY

MIL-STD-129 - Marking for Shipment and Storage.

(Copies of specifications and standards required by manufacturers in connection with specific acquisition functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

DEPARTMENT OF TRANSPORTATION (DOT)

Federal Railroad Administration, Office of Safety.

Railroad Safety Appliance Standards, Part 231 (Title 49 of Code of Federal Regulations).

(Application for copies should be addressed to Superintendent of Documents, Government Printing Office, Washington, DC 20402.)

2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. The issues of the documents which are indicated as DoD adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME)

Welding Qualifications of the ASME

(Application for copies should be addressed to the American Society of Mechanical Engineers, 345 East 47th Street, New York, NY 10017.)

AMERICAN SOCIETY OF TESTING AND MATERIALS (ASTM)

A53 - Pipe, Steel, Black and Hot-Dipped, Zinc-Coated, Welded and Seamless.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:43Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

AMERICAN WELDING SOCIETY (AWS)

D1.1 Structural Welding Code, Section 5, Qualification.

(Application for copies should be addressed to the American Welding Society, 2501, NW 7th Street, Miami, FL 33125.)

ASSOCIATION OF AMERICAN RAILROADS (AAR)

Manual of Standards and Recommended Practices, Mechanical Division

Section B - Couplers and Freight Car Draft Components.
M-921 Special Cushioning Devices for Freight Cars.
Section C, Part II, Volume I - Specifications for Design, Fabrication and Construction of Freight Cars, M-1001.
Section D - Trucks and Truck Details.
M-114 Helical Springs, Heat Treated Steel.
Section E - Brakes and Brake Equipment.
S-400 Specification No. 2518, Freight Car Brake Equipment, Installation Specification.
S-401 Basic Freight Car Design Data.
S-473 Application Form for AAR Approval of New and Untried Freight Cars.
M-601 Hose, Air-Brake and Train Air-Signal.
Section E, Part II - Maintenance Requirements for Freight Car Air Brake Control.
Valves and Equipment - Shop Certification.
S-486 Single Car Testing Device - Code of Test for Freight Car Equipment. Instruction Pamphlet No. 5039-4, Sup. 1.
Section G - Wheels and Axles.
M-101 Axles, Carbon Steel, Non-Heat-Treated and Heat-Treated.
Section G, Part II - Wheel and Axle (Shop) Manual.
Section H - Journal Bearings and Lubrication.
M-934 Freight Car Journal Roller Bearings.
S-701 Locking Plate, Journal Roller Bearings.
Section I - Specially Equipped Freight Car and Intermodal Equipment.
M-952 Intermodel Support And Securement System for Freight Cars.
Section L - Lettering and Marking of Cars.

Supplement to Manual of Standards and Recommended Practices.
Equipment Diagram, AAR Plates B and B-1 for Unrestricted Interchange Service.

Interchange Rules

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:43Z
Check the source to verify that this is the current version before use.

Loading of Commodities on Open Top Cars,
Section No. 1 - General Rules.

(Application for copies should be addressed to the Association of American Railroads, 59 East Van Buren Street, Chicago, IL 60605.)

(Industry association specifications and standards are generally available for reference from libaries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Description. The flat car shall be "FMS" designated, 140 ton capacity, 12 wheels, 56-1/2-inch gage in accordance with the applicable Association of American Railroads (AAR) requirements and as specified herein. The flat car shall be designed to carry two M1 tanks, multiple ANSI/ISO Standard containers to be loaded with Class A explosives and other commodities. It shall be equipped with integral securement systems to restrain each of these items. The car shall be designed to permit movement of tracked vehicles from car to car without the use of bridge plates. The underframe shall be welded construction. Cars shall be designed and constructed in accordance with AAR specifications.

3.1.1 Overall Dimensions. The flat car shall be designed to meet these overall dimensions:

Minimum width between bolsters (see 3.10)	10'-5"
Minimum width at endsills	Max. allow. to meet plates B & B-1 requirements
Light car deck height (plus or minus 1")	49"
Nominal distance between truck centers	46'-3"
Nominal wheel base between axles	5'-6"
Nominal length of car over striker plates	68'-2"
Maximum span between like cars (in draft position)	60"

3.2 First article (first-produced cars). The contractor shall furnish a car for examination and test within the time frame specified (see 6.2), to prove prior to starting production that his production methods and choice of design detail will produce cars that comply with the requirements of this specification. Examination and tests shall be as specified in Section 4 and shall be subject to surveillance and approval by the Government (see 6.3).

3.3 Materials. Materials shall conform to applicable AAR and commercial specifications currently used by the railroad industry for this type of equipment unless otherwise specified herein (see 6.9).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:43Z
Check the source to verify that this is the current version before use.

3.3.1 Threaded parts. Threaded parts shall conform to FED-STD-H28. The American National fine thread series shall be used for threaded parts less than 1/4-inch diameter. The Unified or American National coarse thread series shall be used for threaded parts 1/4-inch diameter and larger; however, the American National fine thread series may be employed for these sizes when applicable. Airbrake pipe threads shall conform to the American National pipe thread series.

3.3.2 Substitution of materials. Materials not conforming to the specifications referenced herein shall not be substituted, unless such substitutions are specifically approved by the contracting officer and; (1) it is clearly demonstrated that an improvement in operating characteristics, a saving in weight, conservation of critical or strategic materials, or a reduction in cost without sacrifice of reliability can be accomplished thereby; (2) that such substitutions will not preclude the subsequent use of specified materials in effecting repairs or replacements. Requests for approval of such substitutions shall be accompanied by completely detailed supporting data which clearly illustrate the use of the proposed substitute material.

3.4 Interchangeability. Jigs, templates, gages, and fixtures shall be used to insure interchangeability of like components and parts with respect to assembly, performance and quality. All parts having the same part number shall be functionally and dimensionally interchangeable.

3.5 Tolerances and fits. Tolerances and fits shall conform to appropriate AAR Manuals applicable to railway cars and as specified herein.

3.5.1 Adjustments. All parts and components subject to adjustment or replacement by operating or maintenance personnel shall be accessible. Adjusting facilities where provided shall operate without interference and shall maintain such adjustments under all conditions of service.

3.6 Clearance. Clearance dimensions shall not exceed those shown on AAR Plates B and B-1 for unrestricted interchange service. Maximum allowable width is required for supporting tracks of the M1 tank.

3.7. Curvature. The car shall be capable of negotiating a 38-degree horizontal curve (150-foot radius) when uncoupled. The car shall be capable of negotiating a 150-foot radius horizontal curve when coupled by an auxiliary type coupler similar to National 31629 (see 4.5.2.6). Car shall be designed to negotiate specified horizontal and AAR required vertical curves without interference between trucks and carbody, attached parts or brake riggings. The design shall include allowance for truck springs deflected to 75 percent of their total travel plus body deflection.

3.8 Design and construction. Design and construction shall be in accordance with the AAR Manual of Standards and Recommended Practices, Section C, Part II Volume I - Specifications for Design, Fabrication and Construction of Freight Cars, M-1001, and AAR Supplement to the Manual of Standards and Recommended Practices, except as specified herein. The car shall be designed to carry the

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:43Z
Check the source to verify that this is the current version before use.

maximum allowable payload consistent with AAR Interchange Rule 89. Structural members shall be free of notch sensitive areas and discontinuities that could result in highly localized stress concentrations. Sufficient documentation shall be submitted to the AAR, for approval of car design. A full set of drawings and design calculations with complete structural analysis shall be submitted to the contracting officer. The contractor shall provide to the government a letter of approval from the AAR.

3.8.1 Jacking pads and lifting lugs. Car shall be equipped with jacking pads and lifting lugs in accordance with AAR specifications.

3.9 Underframe. The underframe shall be welded construction in accordance with AAR Manual of Standards and Recommended Practices and Supplement thereto. The underframe shall be designed to sustain 600,000 pounds of coupler force applied at the end of the car. The center sill, rear draft stops and their connections shall be designed to withstand a static compressive end load of 1,000,000 pounds.

3.10 Decking. Deck floor plates shall be welded to the underframe and shall extend the full width of the car (3.1.1). For anti-skid protection, a special compound shall be properly applied (see 3.17.1).

3.11 Cargo securement system. The securement system shall be capable of containing the maximum allowable payload while undergoing AAR rail impact tests in accordance with Part 3, Section No. 1 of the AAR loading rules without failure, damage or permanent deformation. The securement system shall also be capable of withstanding without failure, transportation vibration equivalent to that produced by over-the-road movement in a 150-car train. The securement system shall be self-contained on the car deck, shall provide sufficient space for storage below deck level when not in use, and shall not require periodic maintenance, lubrication or adjustment to maintain its serviceability.

3.11.1 Tank securement system. The securement system shall be of chain tie-down configuration. An AAR approved 48 chain per car tie-down system shall be provided for transporting two M1 tanks. Any tie-down system which deviates from that described above must be presented to the contracting officer for approval prior to implementation and such approval does not relieve the contractor of responsibility for securing AAR approval. If testing is required to obtain approval, the Government will loan two M1 tanks (see 6.10). Each tie-down device shall consist of all the components required to secure a tank to the railcar without requiring any special tools. Steel anchoring channels shall be flush-mounted parallel along the entire length of the car. The bolster area may be excluded. Each channel shall have provisions for the movable heavy duty anchors. The anchoring devices shall move freely in the channel, with the ability to be locked at positions in maximum of six (6) inch increments along the full length of the channels. The anchoring device shall remain in the channels when not in use. The securement devices shall be designed to have an ultimate strength of not less than 50,000 pounds for each tie-down device. The construction shall be such that one man can position anchors and chain assembly

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:43Z
Check the source to verify that this is the current version before use.

without special tools. Sufficient anchoring devices shall be furnished to secure two M1 tanks. Each chain tie-down and anchoring device shall be permanently fixed to the flatcar. A complete set of masterlinks and shackles sufficient to secure two M1 tanks to the flatcar shall be provided with the car. A covered stowage space which is accessible to personnel on the deck shall be provided for this complete set of master links and shackles.

3.11.2 Intermodel containers. The securement shall be either of the built-in twist lock type or pedestal type for securing a single ANSI/ISO standard size 40-foot-long container; three 20-foot containers or combinations of both. The twist lock type shall adjust vertically for different container locking heights, and shall retract flush with the floor level by use of single operating handles when not in use. The built-in pedestal type shall automatically lock the container into position when the container is lowered onto the pedestals. Upward lift of the container shall automatically release the lock for unloading. Construction shall be such that the operator can position the pedestal without special tools. The pedestals shall be permanently secured to the flat car by means of an anti-theft device. The securement system shall meet requirements of the AAR Manual of Standards and Recommended Practices, Section I, Specially Equipped Freight Cars and Intermodel Equipment, M-952, Intermodal Support and Securement System for Freight Cars.

3.12 Couplers. Couplers shall be AAR approved bottom shelf E type, rotary bottom operated with coupler operating levers at diagonal corners. Design and installation shall be in conformance with the AAR Manual of Standards and Recommended Practices, Section B - Couplers and Freight Car Draft Components, as applicable.

3.12.1 Cushioning device. The car shall be equipped with end-of-car hydraulic cushioning devices as approved in AAR Specification M-921, Special Cushioning Devices for Freight Cars. The cushioning device shall have a 15-inch travel.

3.13 Brake system. Design and installation shall be in accordance with AAR Manual of Standards and Recommended Practices, Section E - Brakes and Brake Equipment; S-400 Specification No. 2518, Freight Car Brake Equipment, Installation Specifications; S-401, Basic Freight Car Design Data; and other AAR requirements as applicable.

3.13.1 Airbrakes. Airbrakes, single capacity, providing constant braking force, shall be furnished and shall consist of an AB-10-12 brake system with ABDW control valve and approved vent valve or an appropriately-sized truck mounted brake system. High friction composition brake shoes shall be in accordance with latest AAR requirements at time of solicitation. The car brake piping system shall consist of 1-1/4 inch extra heavy pipe conforming to ASTM A-53 or latest revision and shall meet the requirements of AAR. Brake valves and breathers shall be protected from damaging effect of road splash and passing couplers. Cars shall pass testing as specified in AAR Standard S-486 Single Car Testing Device - Code of Tests for Freight Car Equipment, Instruction Pamphlet No. 5039-4, Sup. 1.

Source: https://assist.dla.mil -- Downloaded: 20261O-22T21:43Z
Check the source to verify that this is the currentversion before use.

3.13.2 Braking force. Net airbrake and handbrake force, as determined by a static brake test shall conform to AAR Standards S-401 as above, and S-473 Application Form for AAR Approval of New and Untried Freight Cars.

3.13.3 Airbrake hose. Airbrake hose shall conform to AAR Specification M-601 Hose, Air-Brake and Train Air-Signal.

3.13.4 Handbrakes. The handbrake shall be side-mounted below deck level. It shall be operable from deck and ground level.

3.13.5 Badge plate. A metal badge plate, cast, etched, or stamped, showing brake rigging and dimensions as specified in AAR Manual of Standards and Recommended Practices, Section D - Trucks and Truck Details, shall be attached in an accessible location near each applicable system.

3.14 Trucks. Trucks shall be six-wheel, 56-1/2 inch gage designed for a 140-ton minimum capacity car and shall be an AAR approved design in accordance with Section D - Trucks and Truck Details. Snubbing device shall be an AAR approved design.

3.14.1 Wheels. Wheels shall be 36-inch one-wear type cast or wrought steel, as specified in the AAR's Section G - Wheels and Axles and shall be in accordance with the aforementioned section and other applicable AAR requirements. Wheels shall be inspected and mounted in accordance with AAR's Section G, Part II - Wheel and Axle (Shop) Manual.

3.14.2 Axles. Axles shall be forged carbon steel in accordance with AAR requirements. Ends of axles shall be drilled and tapped for roller bearing retaining caps.

3.14.3 Journal roller bearings. Journal roller bearings shall be no field lubrication (NFL) type with 6-1/2-inch x 12-inch journal conforming to AAR Specification M-934 Freight Car Journal Roller Bearings in Section H - Journal Bearings and Lubrication, and other AAR requirements as applicable.

3.14.3.1 Locking plate. Each roller bearing assembly shall include a locking plate in accordance with AAR Standard S-701 Locking Plate, Journal Roller Bearings.

3.14.4 Springs. Springs shall conform to AAR Specification M-114 Helical Springs, Heat Treated Steel. The spring travel shall be compatible with snubbing device used. The solid spring group capacity shall conform to AAR Requirements.

3.15 Side bearings. Each car shall be equipped with AAR approved friction or double roller-type side bearings adjusted to AAR specifications.

3.16 Identification plates. An identification plate conforming to MIL-P-3558, Type II, shall be attached to the car underframe in a visible location.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:43Z
Check the source to verify that this is the current version before use.

3.17 Painting and marking. Painting and marking shall conform to MIL-P-3320, color 14064. Substitute systems affording equal protection are acceptable if approved by the Government. Reporting marks shall be DODX in lieu of USAX as specified in MIL-P-3320 and the words US Army shall not be applied. Stencilling on ends of car will include but not be limited to identification of couplers, wheels, end-of-car cushioning, springs and snubbers. Additional markings shall be in accordance with AAR's Section L - Lettering and Marking of Cars, as applicable. Car numbers conforming to MIL-P-3320 shall be applied and shall be provided by the contracting officer. Decals shall be applied to the side sills when furnished (see 6.7)

3.17.1 Anti-skid deck covering compound. To the commercially sand-blasted steel deck plate, an epoxy primer conforming to MIL-P-52192 shall be applied in one coat of 1 to 1.5 ml thickness. Following this procedure, within a minimum of 4 hours and a maximum of 24 hours, an anti-skid deck covering compound conforming to specification MIL-D-23003, Type 3, shall be applied with 3 to 5 ml thickness. All instructional markings to be applied to the deck surface thereafter shall be located only on areas that the tank treads will not traverse.

3.18 Lubrication. NFL roller bearings shall be grease lubricated in conformance to AAR requirements and applied in quantities approved by the bearing manufacturer. Truck centerplates shall be lubricated in accordance with AAR recommended practices.

3.19 Safety appliances. Safety appliances shall comply with the current issue of DOT Railway Safety Appliance Standards (Code of Federal Regulations, Title 49, Part 231). Four-inch wide sill steps conforming to AAR standards shall be provided to aid in safe operation of hand brake from side of car. Recessed design handholds shall be provided to ensure maximum deck width at ends of car.

3.20 Routing cardboard. An AAR approved routing cardboard shall be applied to each side of the car number.

3.21 Defect cardholder. An AAR type defect cardholder shall be applied to each car.

3.22 Workmanship. Workmanship for fabrication and construction shall be in accordance with AAR Section C, Part II, Volume 1 - Specifications for Design, Fabrication, and Construction of Freight Cars, M-1001.

3.22.1 Welding. Welding shall be in accordance with the American Welding Society Code and AAR Section C, Part II or other applicable requirements. The surface of parts to be welded shall be free from rust, scale, paint, grease, mill scale that can be removed by chipping and wire brushing or other foreign matter. Spot, tack, or intermittent welds for strength will not be permitted. Weld penetration shall be such as to provide transference of maximum design stress through the base metal juncture. Fillet welds shall be provided, when necessary, to reduce stress concentration.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:43Z
Check the source to verify that this is the current version before use.

3.22.2 Welders. Before assigning any welder to manual welding work covered by this specification, the contractor shall provide the Government with certification that the welder has passed qualification tests as prescribed by either of the following listed codes for the type of welding operations to be performed and that such qualification is effective as defined by the particular code:

Welding Qualifications of the ASME.
AWS, Structural Welding Code, Section 5, Qualification, D1.1.

Contractors who only make horizontal welds need not qualify welders for "all position welding". Subject to approval by the Government, contractor's standard welder qualification may be substituted in lieu of the above codes provided that the contractor's procedure is equivalent to the above codes. The contractor shall be responsible for determining that automatic welder equipment operators are capable of producing quality welds.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Acceptability criteria. Cars which conform to all requirements in Sections 3 and 5 of this specification and pass all applicable examinations and tests in Section 4 of this specification and meet requirements of the AAR Rules of Interchange will be considered acceptable by the Government. The contractor shall furnish a certification of design approved from AAR to the contracting officer.

4.1.2 Component and material inspection. The contractor is responsible for insuring that components and materials used are manufactured, examined, and tested in accordance with referenced specifications and standards or for providing evidence that components have been previously approved by AAR.

4.2 Classification of inspections. The inspection requirements are classified as follows:

(a) First-produced car inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).
(c) Inspection of packaging (see 4.6).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:43Z
Check the source to verify that this is the current version before use.

4.3 First-produced car inspection. The first-produced car which shall have been produced from production tooling shall be examined and tested to determine conformance to the requirements of this specification.

4.3.1 Examination. The first-produced car shall be examined as specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.3.2 Tests. The first-produced car shall be tested as specified in 4.5.2 through 4.5.2.7. Failure of any test or lack of AAR required approval shall be cause for rejection.

4.4 Quality conformance inspection.

4.4.1 Examination. Each car shall be examined as specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.4.2 Tests. Each car shall be tested as specified in 4.5.2.2 through 4.5.2.5. The number of braking force tests (see 4.5.2.5) performed shall be in accordance with AAR requirements. Failure of any tests shall be cause for rejection.

4.5 Inspection procedure.

4.5.1 Examination. Each car shall be examined for the following characteristics:

101. Material not as specified.
102. Parts and components not interchangeable.
103. Threaded parts not as specified.
104. Car dimensions exceed dimensions shown on AAR Plate B and B-1.
105. Dimensions not as specified.
106. Safety appliances not as specified.
107. Lubrication not as specified.
108. Identification plate not as specified.
109. Painting and marking not as specified.
110. Certification of construction and design approval not in accordance with AAR Specifications.
111. Workmanship not as specified.
112. Tolerances and fits are not as specified.
113. Brake equipment not as specified.
114. Defect cardholder not furnished or applied as specified.

4.5.2 Tests.

4.5.2.1 Test conditions. Any tests required by AAR shall be in accordance with AAR specifications, and as specified herein. No specific order of testing is required.

4.5.2.2 Airbrake. The entire airbrake system shall be tested to insure correct functioning of all components. The car shall be tested with a single

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:43Z
Check the source to verify that this is the current version before use.

car testing device in accordance with AAR leaflet 5039-4, supplement 1, or latest revision for type of brake equipment. All pipe joints shall be tested for leaks at an air pressure of 90 psi. The brake cylinder piston travel shall be as specified in Air Brake Specification No. 2518 and shall be tested for interference and correct travel. Nonconformance to 3.13 or AAR requirements shall constitute failure of this test.

4.5.2.3 Handbrake. The specified braking force shall be determined at each wheel. Nonconformance to 3.13.4 shall constitute failure of this test.

4.5.2.4 Side bearing clearance. With the car on level tangent track and the car body level, side bearing clearances shall be measured at each bearing. Nonconformance to AAR standard limits shall constitute failure of this test.

4.5.2.5 Braking force. Test in accordance with AAR requirements. Determine brake shoe pressure at shoe. Nonconformance to 3.13.2 shall constitute failure of this test.

4.5.2.6 Curvature. The car, uncoupled, shall be moved through a simulated 150 foot radius horizontal curve. At maximum swing, the brake rigging and the car body rigging shall be inspected to determine that when springs are at 75 percent deflection clearances have been provided and the brake systems function as specified. Calculations are to be furnished to prove that the car coupled to a locomotive by means of an auxiliary coupler similar to National 31629 will move through a 150-foot-radius curve. Nonconformance to this test or 3.7 shall constitute failure.

4.5.2.7 Cargo securement system. The cargo securement system's ability to restrain two M1 tanks and ANSI/ISO containers shall be demonstrated. When the securement systems are not of previously AAR approved design, dimensional compatibility and load capability may be shown by analytical methods if acceptable to the AAR Open Top Loading Rules Committee. If required by AAR, the AAR rail impact tests shall be conducted with both the two tank configuration and one tank configuration. Nonconformance to 3.11, 3.11.1, 3.11.2 and AAR requirements shall constitute failure of this test.

4.6 Inspection of packaging. The packaging and marking shall be inspected to determine conformance to Section 5 of this specification.

5. PACKAGING

5.1 Car. Each car shall be prepared for delivery in accordance with AAR Requirements for Interchange Service (see 6.8).

5.2 Marking. Marking for shipment shall be in accordance with MIL-STD-129. Additional marking shall be as required by applicable AAR Rules and Regulations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:43Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The domestic service heavy duty flatcar is intended for transporting two tracked vehicles and a single 40-foot or three 20 foot ANSI/ISO containers or combinations of both.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Date of issue of DoDISS applicable and exceptions thereto (see 2.1.1).
(c) Time frame required for submission of first-produced car (see 3.2).

6.3 First-produced cars. Any changes or deviations of production cars from the approved first-produced car during production will be subject to the approval of the contracting officer. Approval of the first-produced car will not relieve the contractor of his obligation to furnish cars conforming to this specification.

6.4 Data requirements. The contracting officer should include requirements for such data as Bill of Material; renewal parts catalogues; details of specialty items including appropriate part numbers, specifications, serial numbers, drawings and drawing numbers; Instructional materials; and Universal Machine Language Equipment Register (UMLER) Card and Document Input will be furnished as necessary.

6.5 Drawings. Drawings shall be made available to the contracting officer prior to submission of first-produced car. A complete set of blue line prints and black line reproducible drawings on 3 mil mylar shall be furnished to the contracting officer.

6.6 Car numbers. The contracting officer should arrange to furnish car numbers to the contractor to be applied to each car (see 3.16).

6.7 Decals. The contracting officer should arrange to furnish decals to the contractor when provided by the Military Traffic Management Command (see 3.17).

6.8 Packaging. Levels of packaging have not been included as the cars are for domestic service and will be delivered over the rails. Storage periods exceeding normal domestic limitations are not anticipated.

6.9 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the specification (see 3.3).

6.10 Government-loaned property. The contracting officer should arrange for the loan of property specified in 3.11.1 when required.

Custodian:
Army - ME

Preparing activity:
Army - ME

Review activity:
Army - MT

Project 2220-A191

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:43Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE MIL-R-52968C(ME) Railway Car, Flat, 56-1/2-Inch Gage, Heavy Duty, 140-Ton Capacity, Domestic Service

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:43Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAG
NECESSAR
IF MAILEI
IN THE
UNITED STA

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
USA Mobility Equipment R & D Command
Attn: DRDME-DS
Ft. Belvoir, VA 22060

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:43Z
Check the source to verify that this is the current version before use.