MILITARY SPECIFICATION
SHIPPING AND STORAGE CONTAINER
FUZE: PA2

1. SCOPE

1.1 This specification covers an ammunition container of medium gage metal, fitted with hinged, gasketed covers, capable of repeated openings and closings, yet being hermetically tight when closed.

1.2 CLASSIFICATION

1.2.1 Type.-The ammunition container shall be of one type.

1.2.2 Size.-The container size shall be as shown on applicable drawings and shall be identified by model number.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids, or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-2550 - Ammunition and Special Weapons, General Specification of
MIL-I-45607 - Inspection Equipment, Supply and Maintenance of

FEDERAL

TT-C-490 - Cleaning Methods and Pretreatment of Ferrous Surface for Organic Coatings

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)
MIL-STD-109 - Quality Assurance Terms and Definitions
MIL-STD-406 - Visual Inspection Standards for Terne Plate Cans and Steel Boxes Used in Small Arms Ammunition Packaging

FSC: 8140

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:34Z
Check the source to verify that this is the current version before use.

MIL-STD-414 - Sampling Procedures and Tables for Inspection by Variables for Percent Defective
MIL-STD-1168 - Lot Numbering of Ammunition.
MIL-STD-1169 - Packaging, Packing and Marking for Interplant Shipment of Inert Ammunition Components, General Specification for
MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

DRAWINGS

ARMY

8864492 - Box, Ammo, Metal for Artillery Type and Rocket Fuzes
9217658 - Shipping and Storage Container, Fuze: PA2

PUBLICATIONS

ARMY

ET-9217658 - Equipment Tabulation

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

2.2 Other publications.-The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply.

AMERICAN SOCIETY FOR TESTING AND MATERIALS PUBLICATIONS

B-117 - Salt Spray (fog) Testing

(Applications for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pennsylvania, 19103).

3. REQUIREMENTS

3.1 General.-Materials, components, sub-assemblies shall comply with the applicable drawings, referenced specifications and the following.

3.2 Material.-The contractor shall be responsible for selecting from the classification list contained in the raw material specification the surface and physical condition of the raw material intended for use in manufacture.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:34Z
Check the source to verify that this is the current version before use.

3.2.1 Physical and chemical properties.-The physical and chemical properties specified on the applicable drawing shall be uniform throughout each part within specified tolerances.

3.3 First article inspection.-The specification makes provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.4 Protective finish.-When protective finish is required by component or assembly details, finish requirements shall be as required on the drawing and referenced specification and shall apply to all surfaces of the assembled container regardless of contour configuration.

3.4.1 Adherence.-The protective finish shall not peel, flake or fail to adhere after 24 hours of drying.

3.4.2 Salt spray.-The finished container shall withstand 120 hours exposure to a salt spray of a five percent sodium chloride solution.

3.5 Functioning

3.5.1 Cover assembly.-The cover of the container shall open, close and be removable without binding or requiring exertion of undue force. The cover shall not fall off when opened fully and allowed to hang freely when the container is in an up-right position. The formed lip in the side of each cover skirt shall catch beneath the edge of the body fold and restrain the cover from opening fully when the partially opened container is inverted. The gasket shall not stick to top edges of the container be cut or split, nor shift when the cover is opened. Hinge pins shall be secure in body half of hinge.

3.5.2 Hasp and latch.-Mating parts of the body hasp and the latch shall meet without requiring deformation of any container part, and the latch shall close and open freely. When closed, the latch of the assembled container shall remain closed until manually opened.

3.5.3 Elevated temperature storage.-Following storage of the container in its closed position at an air temperature of 165 plus or minus 2 degrees Fahrenheit (F) for a period of 24 hours and subsequent return to ambient temperature, the cover shall function as required in 3.5.1.

3.6 Welds and hardware components

Source: https://assist.dla.mil -- Downloaded: 202640-23T00:34Z
Check the source to verify that this is the current version before use.

3.6.1 Cover handle assembly.-The cover handle of the container shall withstand a pull of 300 pounds for a period of one minute without separation from the cover or failure of either link, clip or any weld.

3.6.2 Latch, cover and hinge assembly.-The latch, cover and hinge assembly shall withstand a pull of 500 pounds for a period of one minute without breakage or distortion of any of the components or welds

3.6.3 Hasp assembly.-The assembly of the hasp to the container shall withstand a pull of 1000 pounds for one minute without failure of the hasp or weld.

3.7 Interchangeability (cover and body assembly).-Fabrication of body assemblies and cover assemblies shall be such that these assemblies can be interchanged at random to produce containers which comply with the requirements of 3.5.1 and 3.5.2 also the applicable requirement of drawing 8864492 for air leakage.

3.8 Workmanship.-All parts and assemblies shall be fabricated in a thorough workmanlike manner. They shall be free of burrs, chips, sharp edges, surface defects, dirt, grease, rust, corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except at otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspection are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to Standard MIL-STD-109 in order to define terms used herein. The provisions of Specification MIL-A-2550 shall apply.

4.1.1 Submission of product.-At the time each completed lot of items deliverable under the contract is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all of the quality assurance provisions specified in this specification.

b. Drawing and specification number and date, together with identification and date of changes thereto.

c. A statement that all material purchased by the contractor meets requirements, when such material is controlled by Government or commercial specifications referenced in any of the contractual documents, and that certificates of conformance are on file and available for review.

Source: https://assist.dla.mil -- Downloaded: 202640-23T00:34Z
Check the source to verify that this is the current version before use.

d. Number of items in the lot.
e. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.2 First Article Inspection

4.2.1 Submission.-Prior to initiation of regular production the contractor shall submit a first article sample as designated by the contracting officer, (see 6.1) for evaluation in accordance with the provisions of 4.2.2. The first article sample shall consist of 96 containers and 5 complete sets of parts (i.e. 5 each of every component) which have been produced by the contractor or furnished by a supplier and which have been manufactured using the same production processes, procedures and equipment which will be used in fulfilling the contract. All parts and materials shall be obtained from the same source of supply as will be used in regular production. Prior to submission, the contractor shall inspect the sample to the degree necessary to assure that it conforms to the requirements of the contract and submit a record of this inspection with the sample, including statements of findings for materials, processes and tests. A sample containing known defects will not be submitted unless specifically authorized by the Contracting Officer. A first article sample, or portion thereof, as directed by the contracting officer, shall also be submitted whenever there is a lapse in production for a period in excess of 90 days or whenever a change occurs in manufacturing process, material used, drawing or specification such as to significantly affect product uniformity as determined by the Government.

4.2.2 Inspections to be performed.-Assemblies and components will be subjected by the Government to any or all the examinations or tests specified in 4.3 and 4.4 of this specification and any or all requirements of the applicable drawings.

4.2.3 Rejection.-If any assembly or component fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate its inspection upon failure of an assembly or component to comply with any of the stated requirements.

4.3 Inspection provisions

4.3.1 Lot formation.-The term "inspection lot" as used in this specification is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer in one unchanged process, in accordance with the same

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:34Z
Check the source to verify that this is the current version before use.

drawing, same drawing revision, same specification and same specification revision and complies with the provisions for submission of product as specified in MIL-STD-105. Changes to the process, specification, or drawing not affecting safety, performance, interchangeability, or storage, as determined by the Government, shall not be deemed to alter the homogeneity of an inspection lot. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein regardless of the type of sampling procedure which is being applied to determine conformance with requirements. Lot numbering, as required, shall be in accordance with MIL-STD-1168.

4.3.2 Examination.-The examinations listed in the following subparagraphs shall be performed on inspection lots (see 4.2.1) of the components or assemblies designated in the applicable paragraph headings. Inspection for critical defects (and major defects, when so specified) shall be 100 percent. Sampling plans for major and minor defects shall be in accordance with MIL-STD-105 except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the Government. Instead of applying the AQL's designated herein to the groups of major and minor defects listed, the contractor may elect to apply AQL's to individual defects using an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. When this method is elected, it shall be applied to all of the major and minor defects listed in the applicable subparagraph of this section, except where 100 percent inspection is specified, and be documented as part of the contractor's inspection system. Equipment necessary for the performance of the inspections listed shall be accordance with 4.3.4.

4.3.2.1 Hinge, Body (see dwg. 9218387 covering a detail of dwg. 9217658).

Categories	Defects	Method of Inspection	Code No. (see 6.2)
Critical:	None defined.		
Major:	AQL 0.40 percent		
101.	Diameter of pin hole	Gage	01001
102.	Any operation missing or incomplete	Visual	01002
Minor:	AQL 1.5 percent		
201.	Hardness	Test	01003
202.	Thickness	Gage	01004
203.	Radii missing	Visual	01005
204.	Evidence of poor workmanship (see 3.8)	Visual	01006

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:34Z
Check the source to verify that this is the current version before use.

4.3.2.2 Pin, Hinge (dwg. 9218386 covering a detail of dwg. 9217658).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.40 percent		
101.	Length of knurl minimum, from rearward face	Gage	02001
102.	Diameter over knurl	Gage	02002
Minor:	AQL 1.5 percent		
201.	Hardness	Test	02003
202.	Total length	Gage	02004
203.	Evidence of poor workmanship (see 3.8)	Visual	02005

4.3.2.3 Hinge, Cover (see dwg. 9218051 covering a detail of dwg. 9217658).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.40 percent		
101.	Diameter of pin hole	Gage	03001
Minor:	AQL 1.5 percent		
201.	Hardness	Test	03002
202.	Thickness	Gage	03003
203.	Evidence of poor workmanship (see 3.8)	Visual	03004

4.3.2.4 Hasp (see dwg. 9217652 covering a detail of dwg. 9217658).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	None defined.		
Minor:	AQL 2.5 percent		
201.	Hardness	Test	04001
202.	Thickness	Gage	04002
203.	Height	Gage	04003
204.	Radii missing or incorrect	Visual	04004
205.	Evidence of poor workmanship (see 3.8)	Visual	04005

Source: https://assist.dla.mil -- Downloaded: 202640-23T00:34Z
Check the source to verify that this is the current version before use.

4.3.2.5 Latch (see dwg. 9218967 covering a detail of dwg. 9217658).

Categories	Defects	Method of Inspection	Code No.
Critical: None defined			
Major:	AQL 0.40 percent		
101.	Latch link groove mislocated	Gage	05001
102.	Height of flange (large)	Gage	05002
Minor:	AQL 2.5 percent		
201.	Hardness	Test	05003
202.	Thickness	Gage	05004
203.	Length	Gage	05005
204.	Radii missing	Visual	05006
205.	Evidence of poor workmanship (see 3.8)	Visual	05007

4.3.2.6 Gasket, Cover (see dwg. 9217655 covering a detail of dwg. 9217658).

Categories	Defects	Method of Inspection	Code No.
Critical: None defined.			
Major: None defined.			
Minor:	AQL 2.5 percent		
201.	Total length	Gage	06001
202.	Total width	Gage	06002
203.	Thickness	Gage	06003
204.	Location of seating groove	Gage	06004
205.	Evidence of poor workmanship (see 3.8)	Visual	06005

4.3.2.7 Bottom (see dwg. 9218969 covering a detail of dwg. 9217658).

Categories	Defects	Method of Inspection	Code No.
Critical: None defined			
Major: None defined.			

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:34Z
Check the source to verify that this is the current version before use.

Minor:	AQL 4.0 percent		
201.	Total width	Gage	07001
202.	Total length	Gage	07002
203.	Thickness	Gage	07003
204.	Location of emboss	Gage	07004
205.	Length of emboss	Gage	07005
206.	Width of emboss	Gage	07006
207.	Depth of emboss	Gage	07007
208.	Evidence of poor workmanship (see 3.8)	Visual	07008

4.3.2.8 Link, Cover Handle (see dwg. 7580052 covering a detail of dwg. 9217658.

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.40 percent		
101.	Split or crack in wire	Visual	08001
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.8)	Visual	08002

4.3.2.9 Clip, Cover Handle (see dwg. 7553305 covering a detail of dwg. 9217658).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	None defined		
Minor:	AQL 1.5 percent		
201.	Thickness	Gage	09001
202.	Height	Gage	09002
203.	Evidence of poor workmanship (see 3.8)	Visual	09003

4.3.2.10 Link, Latch (see dwg. 7553311 covering a detail of dwg. 9217658).

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:34Z
Check the source to verify that this is the current version before use.

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.40 percent		
101.	Split or crack in wire	Visual	10001
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.8)	Visual	10002

4.3.2.11 Body (dwg. 9218968 covering a detail of dwg. 9217658).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 1.0 percent		
101.	Internal length	Gage	11001
102.	Internal width	Gage	11002
103.	Depth	Gage	11003
104.	Hem, bottom or sides concaved or convexed (see MIL-STD-406)	Visual	11004
105.	Burred or sintered bottom (see MIL-STD-406)	Visual	11005
106.	Split hem at seam weld (see MIL-STD-406)	Visual	11006
107.	Offset seam weld (see MIL-STD-406)	Visual	11007
108.	Rough seam edge (see MIL-STD-406)	Visual	11008
109.	Double seam bottom (see MIL-STD-406)	Visual	11009
110.	Bulge (see MIL-STD-406)	Visual	11010
Minor:	AQL 2.5 percent		
201.	Thickness	Gage	11011
202.	Width of overlap (bottom)	Gage	11012
203.	Width of overlap (top)	Gage	11013
204.	End weld above flush	Visual	11014
205.	Surface imperfection	Visual	11015
206.	Manufacturer's identification missing	Visual	11016
207.	Evidence of poor workmanship (see 3.8)	Visual	11017

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:34Z
Check the source to verify that this is the current version before use.

4.3.2.12 Cover (see dwg. 9217654 covering a detail of dwg. 9217658).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.40 percent		
101.	Total length	Gage	12001
102.	Outside width	Gage	12002
Minor:	AQL 2.5 percent		
201.	Inside length of cover emboss	Gage	12003
202.	Thickness	Gage	12004
203.	Width of cover emboss	Gage	12005
204.	Any emboss stop missing	Visual	12006
205.	Evidence of poor workmanship (see 3.8)	Visual	12007

4.3.2.13 Handle Cover (see dwg. 7553304 covering a detail of dwg. 9217658).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	None defined		
Minor:	AQL 2.5 percent		
201.	Thickness	Gage	13001
202.	Total length	Gage	13002
203.	Width	Gage	13003
204.	Any operation missing	Visual	13004
205.	Evidence of poor workmanship (see 3.8)	Visual	13005

4.3.2.14 Cover Assembly (see dwg. 9217658 covering a detai of dwg. 9217658).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 1.0 percent		
101.	Cover convexed or concaved on hem	Visual	14001

Source: https://assist.dla.mil -- Downloaded: 202640-23T00:34Z
Check the source to verify that this is the currenversion before use.

102.	Handle fails to operate freely	Manual	14002
103.	Gasket missing, damaged or incorrectly assembled (see (MIL-STD-406)	Visual	14003
104.	Any operation missing or incomplete	Visual	14004
105.	Cover handle clip bent or malformed (see MIL-STD-406)	Visual	14005
106.	Cover handle clip misaligned (see MIL-STD-406)	Visual	14006
Minor:	AQL 1.0 percent		
201.	Location of clip	Gage	14007
202.	Evidence of poor workmanship (see 3.8 and MIL-STD-406)	Visual	14008

4.3.2.15 Body Assembly (see dwg. 9217653 covering a detail of dwg. 9217658).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.65 percent		
101.	Any weld missing or incomplete	Visual	15001
102.	Hasp misaligned (see MIL-STD-406)	Visual	15002
103.	Hasp not welded (see MIL-STD-406)	Visual	15003
104.	Body hinge off center more than 1/32 inch (see MIL-STD-406)	Visual	15004
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.8)	Visual	15005

4.3.2.16 Shipping and Storage Container, Fuze: PA2 (see dwg. 9217658).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:34Z
Check the source to verify that this is the current version before use.

Major:	AQL 1.5 percent		
101.	Total length	Gage	16001
102.	Outside width, max	Gage	16002
103.	Height over handle, max	Gage	16003
104.	Failure of any component to operate freely	Manual	16004
105.	Hinge pin missing	Visual	16005
106.	Incomplete latch (see MIL-STD-406)	Visual	16006
107.	Emboss stops not engaging underside of hem (see MIL-STD-406)	Visual	16007
108.	Front of body distorted at hem (see MIL-STD-406)	Visual	16008
109.	Sharp projection on interior or exterior (see MIL-STD-406)	Visual	16009
110.	Protective finish with total incomplete coverage in excess of 1/4 square inch (see MIL-STD-406)	Visual	16010
111.	Rust in interior (see MIL-STD-406)	Visual	16011
112.	Rust on exterior exceeding 1/4 square inch	Visual	16012
Minor:	AQL 1.5 percent		
201.	Protective finish incomplete (except as specified in Major 110)	Visual	16013
202.	Rust on exterior up to 1/4 square inch (see MIL-STD-406)	Visual	16014
203.	Paint blister on interior or exterior (see MIL-STD-406)	Visual	16015
204.	Paint runs (see MIL-STD-406)	Visual	16016

4.3.3 Testing

4.3.3.1 Protective finish

4.3.3.1.1 Adherence (see 3.4.1) - Major Defect - Code No. 20001.-Samples to be tested shall be obtained in accordance with Federal Specification TT-C-490. Failure of any sample to meet the applicable requirement, when tested as specified in 4.4.1 shall be cause for rejection of the lot.

Source: https://assist.dla.mil -- Downloaded: 20260-23T00:34Z
Check the source to verify that this is the current version before use.

4.3.3.1.2 Salt spray.-(see dwg. 9217658) - Major defect - Code No. 20002.-A sample of 3 containers shall be subjected to the salt spray test without resulting in rust spots, wrinkles or blisters on any of the body or cover surfaces or evidence of rust creepage extending more than 1/8 inch on either side of the scratch marks or rusting of part of the hardware subject to pressure or abrasion in normal use or exceeding the standards permissible in Standard MIL-STD-406. When a container fails this test, the lot shall be rejected, and the manufacturer shall be required to immediately correct his painting processes to comply with applicable specifications. After air drying for 24 hours, the enamel shall be no softer than unexposed enamel.

4.3.3.1.3 Film thickness - (see dwg. 9217658) - Major defect - Code No 20003.-A sample of 3 containers shall be checked for film thickness. Failure of any container so tested to conform to the drawing requirements shall be cause for rejection of the lot. The manufacturer shall be required to correct his painting practice immediately to comply with the applicable drawing.

4.3.3.2 Functioning

4.3.3.2.1 Cover assembly - Major defect - Code No. 20004.-Each container of the examination sample (4.3.2) shall be tested for compliance with the requirement of 3.5.1. Failure of the sample to meet acceptance criteria of Standard MIL-STD-105 for an AQL of 1.0% shall be cause for rejection of the lot.

4.3.3.2.2 Hasp and latch - Major defect - Code No. 20005.-Each container of the examination sample (4.3.2) shall be tested for compliance with the requirement of 3.5.2. Failure of the sample to meet the acceptance criteria of Standard MIL-STD-105 for an AQL of 1.0% shall be cause for rejection of the lot.

4.3.3.2.3 Elevated temperature - Major defect - Code No. 20006. - A sample of 32 acceptable containers shall be selected from the examination sample (4.3.2) and tested for compliance with 3.5.3. Failure of any container to comply with the requirement shall be cause for rejection of the lot.

4.3.3.3 Air leakage test - Major defect, Code No. 20007.-The sampling plan for this test shall be in accordance with Standard MIL-STD-105, Code Letter G, and an AQL of 0.40 percent. The test shall be performed as specified in 4.4.6 using equipment in accordance with 4.3.4.

4.3.3.4 Welds and hardware components - Major defect - Code No. 20008.-The same containers used for the air leakage test (4.3.3.3) shall be tested for compliance with the requirements of 3.6. Failure of any component to meet the applicable requirement shall be cause for rejection of the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:34Z
Check the source to verify that this is the current version before use.

4.3 3.4.1 Disposition of tested containers.-Those containers which have successfully passed the tests prescribed in 4.3.3.4 may be returned to the lot provided they are subsequently tested for air leakage and ambient functioning and are found acceptable.

4.3.3.5 Gasket compression test - Major defect - Code No. 20009.-A sample of 10 acceptable containers shall be selected from the examination sample (4.3.2) and tested for Gasket Compression. The variables sampling plan of Standard MIL-STD-414 example C3 for an AQL of 1.00 percent shall be used. Failure of any container to comply with the drawing requirements or failure of the sample to meet the criteria of the variables sampling plan, shall be cause for rejection of the lot.

4.3.3.6 Interchangeability (cover and body assembly - Major defect - Code No. 20010.-A sample of 5 acceptable containers shall be selected from the examination sample (4.3.2) and tested for compliance with the requirements of 3.7. Failure of more than one assembled container to comply with the requirements of 3.5.1 and 3.5.2 or failure of more than one assembled container to comply with the applicable drawing (air leakage) requirement shall be cause for rejection of the lot.

4.3.4 Inspection Equipment.-Equipment Tabulation Number ET-9217658 identifies the inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment in accordance with the instructions in 6.3.

4.3.4.1 Government rights to documentation.-Inspection equipment drawings and lists provided and revised in accordance with the requirements of the ET may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement parts, inspection of items at overhaul, general maintenance of equipment, construction, survey and whenever inspection equipment drawings are needed.

4.3.4.2 Supply and maintenance.-Supply and maintenance of the equipment listed in the ET shall be in accordance with Specification MIL-I-45607.

4.3.4.3 Government use of contractor's inspection equipment.-The contractor shall make available to the Government all inspection equipment necessary for determining conformance with contract requirements. Personnel for operating the equipment

Source: https://assist.dla.mil -- Downloaded: 202640-23T00:34Z
Check the source to verify that this is the current version before use.

and verification of its accuracy, shall be supplied by the contractor for the performance of examination or test by the Government.

4.4 Test methods and procedures

4.4.1 Adherence.-Pain adherence shall be determined in accordance with the provisions of Federal Specification TT-C-490.

4.4.2 Salt spray.-The sample shall be tested as specified in American Society for Testing and Material Publications (ASTM B-117) for a period of 120 hours with a five percent solution of sodium chloride. The sample shall be so positioned that the hinged edge of the assembled container is elevated approximately 15 degrees from the horizontal and rests upon a wooden support while the cover face is parallel to the principal direction of horizontal flow of the fog through the chamber. Prior to exposure, cross marks (X) approximately three inches long and penetrating to the base metal of the sample shall be made with a machinists scriber (or equivalent) across the flat portion of each side, the bottom, the hinge end and the cover.

4.4.3 Film thickness.-Measurements shall be made at a random location on the exterior of each body surface, a cover surface and an accessible hardware surface.

4.4.4 Functioning.-The container shall be manually and visually examined to assure compliance with the requirements of 3.5.

4.4.5 Elevated temperature storage.-The containers shall be conditioned as prescribed in 3.5.3 and tested in accordance with 4.4.4.

4.4.6 Air Leakage Test.-Each container in the sample shall be tested in accordance with the provisions of paragraph 4.3.4. Under no circumstances shall water be employed as a test media.

4.4.7 Cover handle assembly.-The cover handles shall be tested by clamping the assembled, latched containers in a suitable fixture and slowly applying a force of 300 pounds for a period of one minute through a support having a 3 inch long continuous bearing

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:34Z
Check the source to verify that this is the current version before use.

with the underside of the handles.

4.4.8 Cover and hinge assembly.-The assembly shall be tested in a suitable fixture with the container resting on its bottom and with the cover raised at a right angle. The container comprising the cover, cover hinge, body and body hinge (may contain latch and latch link) shall be clamped securely with the body supported to prevent distortion or collapse by means of a snug fitting wood filler block. A vertical force of 500 pounds shall be slowly applied for a period of one minute with the bearing to the cover by means of a clamp or other means. (Do not apply force to latch or latch link).

4.4.9 Hasp assembly.-The container shall be clamped in a suitable fixture, resting on its bottom and with cover fully open. A force of 1000 pounds shall be slowly applied in a vertical direction, with bearing against the underside of the offset of the hasp over the entire surface available, for a period of one minute. The container body shall be supported, to prevent distortion or collapse, by means of a snug fitting wood filler block.

4.4.10 Gasket compression.-The gaskets shall be measured using gages specified on the applicable equipment tabulation and in accordance with the instructions provided thereon. For each sample container, the average of the four compression measurements shall be computed. The average values thus obtained shall be used in the application of the procedures of Standard MIL-STD-414.

4.4.11 Interchangeability.-The cover shall be removed from each of the completely assembled containers and be reassembled in turn on each of the different container bodies from which the cover was removed. Each reassembled container shall be tested for functioning (4.4.4) and air leakage (4.4.6)

4.4.12 Latch, latch line and cover.-The latch, latch link and the assembly of latch link to cover shall be tested in a suitable fixture with the container resting on the hinge end and the cover raised at a right angle and the cover clamped securely in place. A 500 pound pull shall be applied to the latch when the latch and latch link are positioned at a right angle to face of cover.

5. PREPARATION FOR DELIVERY

5.1 Packing and marking.-The containers with covers attached and the hasps closed shall be packed and marked in accordance with Standard MIL-STD-1169.

Source: https://assist.dla.mil -- Downloaded: 202640-23T00:34Z
Check the source to verify that this is the current version before use.

5.2 Delivery.-A lot which has been officially accepted by the Government inspector shall be considered as prepared for delivery when the containers are packed, the packing containers sealed and marked as required by the applicable drawings and the packed containers have been accepted.

6. NOTES

6.1 Ordering data.-Procurement documents shall specify the following:

a. Title, number and date of this specification
b. Type of packing
c. Provision for the submission of acceptance inspection reports, in duplicate, to the contracting officer, containing final inspection results for each lot of containers forwarded to the Government.
d. Provisions for submission of First Article Samples.

6.2 Inspection code numbers.-The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government.

6.3 Inspection equipment.-The contractor shall design inspection equipment as required by the referenced inspection Equipment Lists (EL) in accordance with the instruction of paragraphs 6.3.1 through 6.3.5.

6.3.1 Inspection equipment lists.-Inspection equipment lists indicate the availability of inspection equipment designs by showing in the "number" column of the list of inspection equipment (Form SMUPA-1010) the numbers of drawings or Federal Stock numbers of existing equipment designs, or codes as indicated in paragraph 6.3.2. Design action required of the contractor is described in paragraphs 6.3.3 and 6.3.4. The contractor will be required to prepare detailed drawings in accordance with 6.3.4 for all the equipment coded as "Contractor Design" in the number column. These contractor designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6 3.2 Inspection equipment list codes.-The inspection equipment as defined in 6.3.3 and 6.3.4 will be designated in the EL by the following codes:

CD - Contractor design on controlled contractor format and/or commercial equipment.
MU - Army design, mandatory for use.

6.3.3 Army designs.-Army designs are reflected on detailed drawings which completely depict all the information necessary for

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:34Z
Check the source to verify that this is the current version before use.

the fabrication of the item of inspection equipment. The contractor need provide no design when an Army design is listed for an item of inspection equipment. Army designs fall into two basic classifications, mandatory (designated "MU") and non-mandatory (indicated by drawing or Federal Stock Number). When an inspection equipment list references mandatory Army designs the contractor shall comply with, and use these designs accordingly. The contractor may, however, in connection with non-mandatory designs, design alternate inspection equipment or use comparable commercial equipment to facilitate his operations. Such contractor prepared designs or commercial equipment selections must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.4 Contractor designs.-Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finish, notes, operating and calibration, instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Unless otherwise specified contractor designs may be developed on the format the contractor normally employs in his equipment design procedure provided such format reflects the detail and information specified above, subject to the following controls: All submitted contractor designs shall conform to MIL-D-1000, Category E, Form 2. Legibility and reproducibility shall permit conventional making of clearly and understandable, high contrast reproductions. Contractors shall submit one copy of final designs as a rolled set. Designs shall be submitted for approval as specified in 6.3.5.

6.3.5 Submission of contractor designs.-All submitted designs shall contain a reference to the applicable five digit Code Number contained in Section 4 of this specification. Unless otherwise specified on the EL, all designs of equipment for inspection of defects classified as critical and major shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-QA-A-P. All other designs of inspection equipment shall be approved by the inspection element of the agency administering the contract; submission shall be as directed by the contracting officer. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion date for design review will be based on the date of the final submission normally within one month after receipt.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:34Z
Check the source to verify that this is the current version before use.

6.4 Intended use.-The PA2 container is intended for diversified use in the packaging of ammunition (primarily artillery type and rocket fuzes).

Custodian:
Army-MU

Preparing Activity:
Army-MU

Project Nunber: 8140

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:34Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS

Department of the Army
Picatinny Arsenal
ATTN: SMUPA-QA-A
Dover, N.J. 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:34Z
Check the source to verify that this is the current version before use.

To detach this form, cut along this line

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS. This sheet is to be filled out by personnel either Government or contractor involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

[ ] DIRECT GOVERNMENT CONTRACT [ ] SUBCONTRACT

1 HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A GIVE PARAGRAPH NUMBER AND WORDING

B RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2 COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3 IS THE SPECIFICATION RESTRICTIVE?

[ ] YES [ ] NO *(If "yes" in what way?)*

4 REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional pages attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:34Z
Check the source to verify that this is the current version before use.