MILITARY SPECIFICATION

TEST SET, COUNTERMEASURES SET

TS-3614( )/ALQ-136(V)1

This specification is approved for use by the U.S. Army Electronics Research and Development Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification defines the requirements for Test Set, Countermeasures Set TS-3614( )/ALQ-136(V)1, hereinafter referred to as the flight line test set (FLTS).

1.2 Description. The Test Set, Countermeasures Set TS-3614( )/ALQ-136 (V)1 is a type of Special Test Equipment used to test the operation of Countermeasures Set AN/ALQ-136(V)1, hereinafter referred to as the Countermeasures Set (CMS), at the organizational level of maintenance, Aviation Unit Maintenance (AVUM).

Beneficial comments, (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, USAERADCOM, ATTN: DELET-DP, Fort Monmouth, N. J. 07703, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document, or by letter.

FSC 5865

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:03Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents form a part of this specification to the extent specified herein. The effective issues or revisions of specifications and standards shall be those listed in the Department of Defense Index of Specifications and Standards (DODISS) and supplements thereto, unless (a) specific issues are set forth herein, or (b) different issues than those specified in this specification are set forth in the solicitation. The date of the applicable DODISS and supplements thereto, and the effective issue or revision of drawings cited herein, shall be as specified in the solicitation or contract.

SPECIFICATIONS

FEDERAL

L-P-378	Plastic Sheet and Strip, Thin Guage, Polyolefin
NN-P-71	Pallet, Material Handling, Wood, Stringer Construction, 2 Way and 4 Way (Partial)
QQ-S-781	Strapping, Steel, Flat and Seals
PPP-B-585	Box, Wood, Wirebound
PPP-B-601	Box, Wood, Cleated, Plywood
PPP-B-621	Box, Wood, Nailed and Lock Corner
PPP-B-636	Box, Shipping, Fiberboard
PPP-B-640	Box, Fiberboard, Corrugated, Triple Wall
PPP-F-320	Fiberboard, Corrugated and Solid, Sheetstock (Container Grade) and Cut Shapes
PPP-S-760	Strapping, Nonmetallic (and Connectors)
PPP-T-97	Tape, Pressure-sensitive, Adhesive, Filament Reinforced

MILITARY

MIL-P-116	Preservation, Methods of
MIL-P-11268K(EL)	Parts, Materials and Processes Used in Electronic Equipment
MIL-M-13231(EL)	Marking of Electronic Items
MIL-F-14072(EL)	Finishes for Ground Electronic Equipment
MIL-P-19644	Plastic Molding Material (Polystyrene Foam, Expanded Bead)
MIL-P-26514	Polyurethane Foam, Rigid or Plastic, for Packaging

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:03Z
Check the source to verify that this is the current version before use.

2.1 Issues of documents (Cont'd)

STANDARDS

MILITARY

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	Marking for Shipment and Storage
MIL-STD-147	Palletized Unit Loads, 40 Inch x 48 Inch Pallets, Skids, Runners, or Pallet Type Base
MIL-STD-252(EL)	Wired Equipment, Classification of Visual and Mechanical Defects
MIL-STD-454	Standard General Requirements for Electronic Equipment
MIL-STD-461A w/Notice 4(EL)	Electromagnetic Interference Characteristics, Requirements for Equipment
MIL-STD-462 w/Notice 3(EL)	Electromagnetic Interference Characteristics, Measurement of
MIL-STD-704B	Aircraft Electric Power Characteristics
MIL-STD-810C	Environmental Test Methods
MIL-STD-1472	Human Engineering Design Criteria for Military Systems, Equipment and Facilities

DRAWINGS

U.S. ARMY ELECTRONICS RESEARCH AND DEVELOPMENT COMMAND

SM-A-919708	Letter Code (Classified)
SM-A-919717	Attenuator
SM-A-920092	Acceptance Test Procedure for Test Set, Countermeasures Set TS-3614( )/ALQ-136(V)1
SM-A-920093	Acceptance Test Procedure for Antenna AS-3007( )/ALQ-136(V)1
SM-A-920182	Burn-in Procedure
DL-SM-B-919765	Test Set, Countermeasures Set TS-3614( )/ALQ-136(V)1

(Copies of specifications, standards, and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer. Both the title and number or symbol should be stipulated when requesting copies).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:03Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 First article. When specified in the contract or purchase order, the contractor shall furnish first article units in accordance with 4.4 (see 6.2 and 6.6).

3.2 Construction. The equipment shall be constructed in accordance with the requirements of this specification and the drawings listed in USAERADCOM Data List, DL-SM-B-919765, which describes the FLTS including the requirements for parts, materials and processes, thereon. The following listed items are all part of the FLTS:

DL-SM-B-919766	Transmitter Assembly
DL-SM-B-919768	Receiver Assembly
DL-SM-B-919767	Video Assembly
DL-SM-B-919771	Cable Assembly W1
DL-SM-B-919772	Cable Assembly W2
DL-SM-B-920040	Cable Assembly W3
DL-SM-B-920041	Cable Assembly W4

3.3 Parts, materials and processes; general. In addition to the requirements of this specification, the general requirements of MIL-P-11268K(EL), including the selection requirements therein, shall apply.

3.3.1 Finish. The equipment shall be finished in accordance with MIL-F-14072(EL) and the equipment drawings.

3.4 Marking.

3.4.1 General. Marking shall conform to MIL-M-13231(EL)(see 4.5). Front panel marking shall be Group I as described in MIL-M-13231(EL). Location of marking shall be as specified on the equipment drawings.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:03Z
Check the source to verify that this is the current version before use.

3.4.2 Visibility. Wherever practicable, parts shall be so mounted that their identification markings will be readily visible with minimum disassembly of the equipment.

3.4.3 Serial numbers. The following items shall have serial numbers:

SM-D-919765	Test Set, Countermeasures Set
SM-D-919766	Transmitter Assembly
SM-D-919768	Receiver Assembly
SM-D-919767	Video Assembly
SM-D-919769	Circuit Card Assembly, Pulse Generator
SM-D-919770	Circuit Card Assembly, CS and Pulse Control
SM-D-920052	Power Level Detector Assembly

3.5 System performance. The FLTS tests the operation of the AN/ALQ-136(V)1 Countermeasures Set when the CMS is installed in a helicopter. It consists of a transmitter assembly, receiver assembly and video assembly. The transmitter assembly is attached to the CMS receive antenna mounted on the helicopter. The receiver assembly is attached to the CMS transmit antenna mounted on the helicopter. The video assembly interconnects with the transmitter assembly, the receiver assembly and the monitor connector on LRU-1 of the CMS. The FLTS interface with the CMS is effected by power cables and antennas. Primary power for the FLTS is provided from LRU-1 of the CMS by means of an interconnecting cable. Operational status signal information from the CMS is provided to the FLTS by means of the same cable. RF signals are transmitted by means of mounting the FLTS receive and transmit antennas flush to the helicopter mounted antennas of the CMS.

3.5.1 Primary power. The FLTS shall draw 196 watts maximum primary power from the aircraft through LRU-1 of the CMS. Primary power shall meet the characteristics of MIL-STD-704B at 24 to 29 Vdc.

3.5.1.1 Primary current. Primary input current to the FLTS shall not exceed 7 amperes at 28.0 $\pm$ 0.5 Vdc.

3.5.1.2 Power indicator light. When the PWR switch is turned to ON, the green PWR indicator shall light.

3.5.2 Transmitter characteristics.

3.5.2.1 Frequency. The transmitter shall transmit at a specific frequency within D + 0.75 $\pm$ 0.2 GHz (see SM-A-919708).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:03Z
Check the source to verify that this is the current version before use.

3.5.2.2 Power output. The transmitter shall provide a power output at connector 1A1J2 of W-3 to W+2 dBM(See SM-A-919708). This corresponds to an effective pulsed power at the transmit antenna connector of O to M+1 dBm. Power output is controlled by RF output level adjustment 1A2A2R25.

3.5.2.3 Transmit antenna characteristics. The transmit antenna shall meet the following requirements over the frequency range of D ± 0.1 to E + 0.5 ± 0.1 GHz (see SM-A-919708).

3.5.2.3.1 Polarization. The transmit antenna shall be horizontally, linearly polarized.

3.5.2.3.2 Voltage standing wave ratio (VSWR). The VSWR of the transmit antenna shall not exceed 1.5 to 1 over the entire frequency range.

3.5.2.3.3 Elevation beam width. The elevation beam width of the transmit antenna shall be a minimum of G^{O} (see SM-A-919708) at the 3 dB points.

3.5.2.3.4 Azimuth beamwidth. The azimuth beamwidth of the transmit antenna shall be a minimum of $5E^{O}$ (see SM-A-919708) at the 3 dB points.

3.5.2.3.5 Antenna gain. For a horizontally, linearly polarized signal, the transmit antenna shall provide a peak gain of not less than B + 1 dBi. The minimum gain at $\pm 45^{O}$ azimuth, 0° elevation shall be not less than A dBi (see SM-A-919708).

3.5.2.3.6 Power handling capability. The transmit antenna shall not be damaged, nor shall its characteristics be changed from handling peak powers up to + 33 dBw.

3.5.3 Receiver characteristics.

3.5.3.1 Frequency. The receiver shall operate at the frequency specified in 3.5.2.1.

3.5.3.2 Power handling capability. The receiver shall be capable of operating with a peak pulsed RF input power at the receive antenna connector of +38 dBm.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:03Z
Check the source to verify that this is the current version before use.

3.5.3.3 Receive antenna characteristics. The receive antenna characteristics shall be identical to those of the transmit antenna as stated in 3.5.2.3.

3.5.4 Video assembly.

3.5.4.1 Pulse modulation. Pulse modulation for simulating two threats shall be accomplished by generating two synchronized pulse trains with fixed PRI's of 350 ± 35 microseconds, one of which is delayed by 100 ± 10 microseconds. Pulse widths shall be 0.3 ± 0.1 microseconds.

3.5.4.2 Scan modulation. Con scan modulation circuitry shall provide a 45 ± 4 Hz since wave modulation on the RF output with a modulation depth of 4.0 ± 1 dB.

3.5.4.3 GO/NO-GO criterion. The criterion for a GO decision (lighting the GO/NO-GO lamp) shall be the presence of each of the following signals:

Origin	Signal
CMS, LRU-1	Sorter 1 loaded
CMS. LRU-1	Sorter 2 loaded
CMS, LRU-1	SLO 1 loaded
CMS, LRU-1	SLO 2 loaded
CMS, LRU-1	Con scan 1 recognition
CMS, LRU-1	Con scan 2 recognition
FLTS	RF threshold exceeded

3.5.4.4 JAM light. The JAM light shall be activated when the RF threshold exceeded signal of the FLTS exists, i.e., when the power into J2 of the FLTS receiver is -5 dBm or greater (more power).

3.5.5 Self test. The FLTS is provided with self test capabilities which check proper signal processing between the receiver, transmitter, and video assembly. The self test function is initiated by a momentary action switch. Transmit and receive antennas are not self tested. The self test bench mode requirement is used for Group A electrical acceptance and the self test environmental mode requirement is used for environmental acceptance.

3.5.5.1 Self test, bench mode. Depressing the self test switch shall light the JAM and GO/NO-GO indicators when the attenuated RF output of the transmitter assembly at J2 of the FLTS receiver is-2.0 ± 0.5 dBm, and these indicators shall not light when the attenuation is increased by 6 dB.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:03Z
Check the source to verify that this is the current version before use.

3.5.5.2 Self test, environmental mode. The JAM and GO/NO-GO indicators shall light when the self test switch is depressed momentarily.

3.5.6 Lamp test. All front panel lamps except the primary power PWR lamp shall be tested. The lamps shall light when the lamp test function is initiated by a momentary action switch.

3.6 Environmental requirements. The equipment shall meet the following service conditions without degradation in specified performance. Where a test is referenced, meeting the performance criteria shall be considered as compliance with the requirements.

3.6.1 Temperature.

3.6.1.1 Low temperature. The flight line test set shall be capable of operation at ambient temperatures as low as -40°F and of being stored at temperatures as low as -67°F. Before, during and after testing as specified in 4.9.1.1 the equipment shall meet the performance specified in 3.5.1.2 and 3.5.5.2.

3.6.1.2 High temperature. The flight line test set shall be capable of operation at ambient temperatures as high a 131°F and of being stored at temperatures as high as 160°F. Before, during, and after testing as specified in 4.9.1.2 the equipment shall meet the performance specified in 3.5.1.2 and 3.5.5.2.

3.6.2 Altitude. The flight line test set shall be capable of operation at 15,000 feet altitude and of being air transported at 40,000 feet. Before, during, and after testing as specified in 4.9.2 the equipment shall meet the performance specified in 3.5.1.2 and 3.5.5.2.

3.6.3 Humidity. The flight line test set shall be operable without degradation in specified performance during exposure to extreme high humidity levels (94% RH at 86°F) and shall sustain no physical damage after prolonged exposure to extreme high humidity levels (to be determined by cycling from 70°F to 149°F at 94% RH) as encountered in tropical areas. Before, during, and after testing as specified in 4.9.3 the equipment shall meet the performance specified in 3.5.1.2 and 3.5.5.2. The equipment shall exhibit no physical damage such as corrosion, rust, blistering, swelling, or deterioration of parts and materials.

3.6.4 Vibration cycling. The flight line test set shall be capable of operation and shall sustain no physical damage after being subjected to the vibrations normally encountered by equipment transported by rail, sea, truck, or semitrailer. Before and after testing as specified in 4.9.4, the equipment shall meet the performance specified in 3.5.1.2 and 3.5.5.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:03Z
Check the source to verify that this is the current version before use.

3.6.5 Loose cargo bounce. The flight line test set shall be capable of operation and shall sustain no major physical damage (cosmetic damage permitted) after being subjected to the shocks normally encountered during transportation as loose cargo. Before and after testing as specified in 4.9.5, the equipment shall meet the performance specified in 3.5.1.2 and 3.5.5.2.

3.6.6 Bench handling. The flight line test set shall be capable of operation and shall sustain no physical damage after exposure to the shock intensities normally encountered during servicing. Before and after testing as specified in 4.9.6, the equipment shall meet the performance specified in 3.5.1.2 and 3.5.5.2.

3.6.7 Rain. The flight line test set shall be capable of operation and shall show no appreciable leak in its enclosure after exposure to severe blowing rain conditions. Before and after testing as specified in 4.9.7, the equipment shall meet the performance specified in 3.5.1.2 and 3.5.5.2.

3.6.8 Dust. The flight line test set shall be capable of operation and shall sustain no physical damage (other than cosmetic) after exposure to fine, dry, blowing sand or dust. Before and after testing as specified in 4.9.8, the equipment shall meet the performance specified in 3.5.1.2 and 3.5.5.2.

3.6.9 Fungus. No materials or components of the FLTS shall be nutrient to fungus as demonstrated by the test of 4.9.9. No materials shall be used other than inherently fungus resistant grades per Requirement 4 of MIL-STD-454.

3.6.10 Salt fog. All materials, finishes, and coatings used in the FLTS shall be capable of exposure to a corrosive salt atmosphere without degradation. After the salt fog test of 4.9.10, the equipment, when examined visually with the aid of a 10-power magnifier, shall show no evidence of degradation, such as flaking, pitting, blistering or loosening of finish or metal surface, corrosion, clogging or exfoliation of metal (see 6.3.4). There shall be no clogging or binding of moving mechanical parts. Electrical operation is not required.

3.6.11 Explosive atmosphere. The FLTS shall be capable of operation within a potentially explosive atmosphere without causing ignition of the ambient explosive material. Before and during testing as specified in 4.9.11, the equipment shall meet the performance specified in 3.5.1.2 and 3.5.5.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:03Z
Check the source to verify that this is the current version before use.

3.7 Electromagnetic interference. The FLTS shall comply with the emission and susceptibility requirements of MIL-STD-461A, Notice 4(EL) listed below when tested as specified in 4.10 with the exceptions noted in a through d below.

CE04	CS01	RE02	RS02
	CS02	RE02.1	RS03
	CS06		

a. CE04. Both the broadband and narrowband limits shall be those of the military standard except as narrowband limits are modified below:

Line	Frequency (range)	dB above MIL-STD-461A limits
+ 28 Vdc high	.05 to .125 MHz	20 dB
+ 28 Vdc high	9.8 MHz	5 dB
+ 28 Vdc high	19.5 MHz	4 dB
+ 28 Vdc high	28.0 MHz	5 dB
+ 28 Vdc return	.050 to .125 MHz	20 dB
+ 28 Vdc return	19.5 MHz	8 dB
+ 28 Vdc return	28.0 MHz	10 dB

b. CS01. Equipment operation in the presence of an interfering signal is acceptable as follows:

Line	Frequency	Operation
+ 28 Vdc high	375 Hz	PWR, GO/NO GO and JAM lights flicker. minimum perceptible level = 2.2 V rms.
+ 28 Vdc return	375 Hz	PWR, GO/NO GO and JAM lights flicker. MPL = 2.45 V rms.

c. RE02, RE02.1. The broadband limit shall be as specified in the military standard over the 0.014 to 1000 MHz frequency range and shall be a constant 70 dB uV/m/MHz over the 1 to 20 GHz frequency range.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:03Z
Check the source to verify that this is the current version before use.

3.7 Electromagnetic interference (cont'd)

The narrowband limit shall be as specified in the military standard over the 0.014 to 10,000 MHz frequency range, except as indicated below, and shall be a constant 60 dB uV/m over the 10 to 20 GHz frequency range.

Frequency (range)		dB above MIL-STD-461A limits
.014 to .050 MHz		60 dB
.050 to .140 MHz		30 dB
.140 to .170 MHz		15 dB
2.3 MHz		15 dB
3.7 to 4.3 MHz		5 dB
7.6 to 9.4 MHz		12 dB
9.8 MHz		20 dB
10.8 MHz		10 dB
14.5 MHz		15 dB
16.0 to 25.0 MHz		35 dB
25.0 to 29.0 MHz	(horizontal)	15 dB
50.0 to 275 MHz, every 10 MHz	(horizontal)	20 dB
24.0 to 32.5 MHz	(vertical)	35 dB
35.0 to 50.0 MHz	(vertical)	15 dB
50 to 200 MHz, every 10 MHz	(vertical)	12 dB

d. RS03. Radiated field and modulation requirements are as follows:

Frequency	Field Intensity	Modulation
10 kHz - 1.9 MHz	1 Volt/meter	400 Hz square wave, 50% modulated
2 MHz - 75.9 MHz	20 Volt/meter	FM, + 8 kHz deviation, 1000 Hz tone
76 MHz - 399.9 MHz	20 Volt/meter	AM, 50% modulated, 1000 Hz tone
400 MHz - 1999 MHz	10 Volt/meter	Pulse, 0.1 usec width, 400 pps
2 GHz - 12.4 GHz	5 Volt/meter	Pulse, 0.1 usec width, 400 pps

3.8 Burn-in. Each FLTS to be delivered on contract, or to be subjected to first article tests in accordance with this specification, shall be subjected to a 48 hour burn-in to limit infant mortality. The last 24 hours of the burn-in period shall be failure free. This burn-in shall be prior to any or all tests herein specified.

3.9 Systems safety engineering.

3.9.1 Personnel hazards. Personnel hazards shall be kept to a minimum by control of configuration changes and parts selection to assure compliance with Requirement 1 of MIL-STD-454. Compliance with these requirements shall be verified through a visual inspection (see 4.5).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:03Z
Check the source to verify that this is the current version before use.

3.9.2 Edge rounding, exposed. Exposed edges shall be rounded to a minimum radius of 0.04 inch (1mm), and exposed corners to a minimum of 0.03 inch (0.75mm).

3.10 Human engineering. Configuration design criteria affecting human factors operation, maintainability and handling shall be maintained through compliance with MIL-STD-1472.

3.11 Interchangeability. Like units, assemblies, subassemblies and replaceable parts shall be physically and functionally interchangeable, without modification of such items or the system, and shall conform to Requirement 7 of MIL-STD-454 (see 4.11). Individual items shall not be selected for fit or performance, however, matched pairs or sets, when permitted, may be interchangeable as such. Reliance shall not be placed on any unspecified dimension, rating, or characteristic.

3.12 Workmanship. The equipment shall be manufactured and assembled in accordance with Requirement 9 of MIL-STD-454 and the applicable portions of the following paragraphs:

In MIL-P-11268K(EL)

General requirements for plastic material and plastic parts
Wiring and cabling, including:
  Slack
  Protection
  Clearance
  Splicing
Connections, general
Grounding
  Wire and cable shielding
Flux and cleaning agent for soldering
Process for soldering
Cleaning
Riveting
General requirements for securing of parts
Cleaning after welding
Mechanical operation of controls
Process for welding
Self-tapping screws

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may utilize his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:03Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspection. Inspection shall be classified as follows:

a. First article inspection (does not include packaging (see 4.4)).

b. Inspection covered by subsidiary documents (see 4.5).

c. Quality conformance inspection.

(1) Quality conformance inspection of equipment before packaging (see 4.6).

(2) Quality conformance inspection of packaging (see 4.12).

4.3 Burn-in. Prior to the start of any or all of the following tests, each FLTS shall be burned-in in accordance with SM-A-920182 and shall meet the requirements of that procedure and paragraph 3.8 herein.

4.4 First article. Unless otherwise specified in the contract or purchase order, the first article inspection shall be performed by the contractor.

4.4.1 First article units. The contractor shall furnish three first article units of the complete FLTS.

4.4.2 First article inspection. The first article inspection shall consist of inspections specified in Table I and shall be performed in the order specified therein.

4.4.3 First article data. The first article test plan and test report shall be as required in the contract or purchase order (see 6.5).

4.5 Inspection covered by subsidiary documents. The following shall be inspected under the applicable subsidiary documents as part of the inspection required by this specification and the inspection requirements specified in the contract or purchase order.

ITEM	WHERE REQUIRED
Parts, materials, and processes; general	3.3
Finish	3.3.1
Marking	3.4
Safety	3.9
Human engineering	3.10

4.6 Quality conformance inspection of equipment before packaging. The contractor shall perform the inspections specified in 4.5 and 4.6.1 through 4.6.4 in that order. This does not relieve the contractor of his responsibility for performing any additional inspection which is necessary to control the quality of the product and to assure compliance with all specification requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:03Z
Check the source to verify that this is the current version before use.

TABLE I. FIRST ARTICLE INSPECTION

INSPECTIONS	REQ. PARA.	TEST PARA.	UNIT 1	UNIT 2	UNIT 3
1. Inspection covered by subsidiary documents.	3.3 3.4	4.5	Inspections to be performed on all units.		
2. Group A inspection	See Table II		Inspections to be performed on all units.		
3. Group B inspection	See Table III		Inspections to be performed on all units.		
4. Group C inspection	As follows:				
Electrical					
Primary current	3.5.1.1	4.8.2	1	1	1
EMI	3.7	4.10		2	
Environmental					
Temperature	3.6.1	4.9.1	2		
Altitude	3.6.2	4.9.2	3		
Humidity	3.6.3	4.9.3	4		
Vibration	3.6.4	4.9.4			3
Loose cargo bounce	3.6.5	4.9.5			4
Bench handling	3.6.6	4.9.6			2
Rain	3.6.7	4.9.7		4	
Dust	3.6.8	4.9.8		3	
Fungus	3.6.9	4.9.9			5
Salt fog	3.6.10	4.9.10		6	
Explosive atmosphere	3.6.11	4.9.11		5	

NOTES:
a. The inspections 1 through 3, in the order shown, shall be performed on all first article units before subjecting these units to any other inspection requirements specified in the table.
b. The numbers in the unit columns in the table covered by inspection 4 specify the order of inspections for the indicated unit.
c. The equipment shall be thoroughly washed, cleaned, dried, and refurbished after the fungus and salt fog tests before proceeding with subsequent inspection, if required.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:03Z
Check the source to verify that this is the current version before use.

4.6.1 Group A inspection. Each unit on contract or purchase order shall be inspected for conformance to the inspections specified in Table II. Discrete lots shall be formed from units that pass this inspection. Factors of lot composition not defined herein, or in the contract or purchase order, shall be in accordance with MIL-STD-105. Each lot shall be subjected to sampling inspection, utilizing the procedures of MIL-STD-105, using general inspection level II, and AQL's indicated in Table II.

4.6.1.1 Order of inspection within Group A. Group A inspection shall be performed in an order satisfactory to the Government.

4.6.2 Group B inspection. Group B inspection shall normally be performed on inspection lots that have passed Group A inspection and on samples selected from units that have been subjected to an met the Group A inspection, except inspection for the interchangeability requirement. Interchangeability test samples may be separate units whose modules and replaceable parts were randomly selected and assembled prior to Group A testing. This inspection shall conform to Table III.

4.6.2.1 Sampling for Group B inspection. Three samples of the equipment shall be selected at random from every 30 sets or fraction thereof produced. Satisfactory Group B inspection of first article samples shall satisfy the Group B inspection requirement for the first 30 units produced. Failure of a Group B requirement in test fails the lot from which the Group B sample was taken.

4.6.2.2 Order of inspection within Group B. Group B inspection shall be performed in an order satisfactory to the Government.

4.6.3 Group C inspection. Group C inspection shall be performed on units that have passed Group A and Group B inspection. The inspection shall consist of the inspections specified in Table IV. Samples shall be selected in accordance with 4.6.3.1.

4.6.3.1 Sampling for Group C inspection. Three samples of equipment shall be selected at random from every 30 sets or fraction thereof produced. One different sample shall be used for each of the first three Subgroup inspections in Table IV and all three samples will be tested in Subgroup IV. Satisfactory Group C inspection of first article samples shall satisfy the Group C inspection requirement for the first 30 units produced. Unless otherwise specified in the contract, salt fog, fungus, and primary current tests shall not be repeated after the first production lot Group C inspection unless parts, materials, or processes are changed.

4.6.3.2 Order of inspection within Group C. Group C inspection shall be performed in the order specified in Table IV.

4.6.3.3 Group C failures. Action required relative to Group C failures shall be as specified in the contract or purchase order.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:03Z
Check the source to verify that this is the current version before use.

TABLE II. GROUP A INSPECTION

INSPECTION	REQ. PARA.	TEST PARA.	AQL MAJOR	AQL MINOR
Visual and mechanical	3.2, 3.3, 3.4 3.9, 3.10, 3.12	4.5, 4.7	1%	4%
Power indicator light	3.5.1.2	4.8.3	*1.5% for the Group	
Transmitter frequency	3.5.2.1	4.8.4		
Power output	3.5.2.2	4.8.5		
Power handling capability	3.5.3.2	4.8.8		
Pulse modulation	3.5.4.1	4.8.10		
Scan modulation	3.5.4.2	4.8.11		
GO/NO-GO criterion	3.5.4.3	4.8.12		
JAM light	3.5.4.4	4.8.13		
Self test	3.5.5.1	4.8.14		
Lamp test	3.5.6	4.8.15		

*All electrical defects are considered major

TABLE III. GROUP B INSPECTION

INSPECTION	REQ. PARA.	TEST PARA.
Interchangeability Receiver frequency	3.11 3.5.3.1	4.11 4.8.7

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:03Z
Check the source to verify that this is the current version before use.

4.6.4 Reinspection of conforming Group C sample units. Unless otherwise specified, sample units which have been subjected to and passed Group C inspection may be accepted on the contract provided all damage is repaired and the sample units are resubjected to and pass Group B and Group A inspection, in that order.

4.7 Visual and mechanical inspection. The equipment shall be visually and mechanically inspected to insure conformance to the construction requirements of 3.2 and the workmanship requirements of 3.12. Defects shall be classified in accordance with MIL-STD-252(EL).

TABLE IV. GROUP C INSPECTION

INSPECTION	REQ. PARA.	TEST PARA.
Subgroup I		
Temperature	3.6.1	4.9.1
Altitude	3.6.2	4.9.2
Humidity	3.6.3	4.9.3
Subgroup II		
EMI	3.7	4.10
Dust	3.6.8	4.9.8
Rain	3.6.7	4.9.7
Explosive atmosphere	3.6.11	4.9.11
Salt Fog*	3.6.10	4.9.10
Subgroup III		
Bench handling	3.6.6	4.9.6
Vibration	3.6.4	4.9.4
Loose cargo bounce	3.6.5	4.9.5
Fungus	3.6.9	4.9.9
Subgroup IV		
Primary current	3.5.1.1	4.8.2

NOTE: *The equipment shall be thoroughly washed, cleaned, dried, and refurbished after this inspection before proceeding with subsequent inspection, if required.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:03Z
Check the source to verify that this is the current version before use.

4.8 Performance tests.

4.8.1 Test conditions. Unless otherwise specified, the electrical tests shall be conducted under the following conditions:

a. *Temperature and humidity* .....*room ambient*
b. Input voltage .....28 ± 0.5 Vdc
c. Warm up time .....5 minutes

4.8.2 Primary current. When the FLTS is connected as shown in Fig. 5 of SM-A-920092, the ammeter of the ERA Power Supply, model RT 36-12M, shall be read under load conditions. The FLTS shall meet the requirements of 3.5.1.1.

4.8.3 Power indicator light. The FLTS shall meet the requirements of 3.5.1.2 by turning the PWR switch to ON and observing the indicator light.

4.8.4 Transmitter frequency. The FLTS shall meet the requirements of 3.5.2.1 when tested in accordance with 3.2 of SM-A-920092.

4.8.5 Transmitter power output. The FLTS shall meet the requirements of 3.5.2.2 when tested in accordance with 3.2 of SM-A-920092.

4.8.6 Transmitter antenna characteristics. The transmit antenna shall meet the requirements of 3.5.2.3 when tested in accordance with 4.1.2, 4.2, and 4.2.1 of SM-A-920093, as a component only, and not as part of the FLTS.

4.8.7 Receiver frequency. The FLTS shall meet the requirements of 3.5.3.1 when tested in accordance with 3.4 of SM-A-920092.

4.8.8 Receiver power handling capability. The FLTS attenuator shall meet the requirements of 3.5.3.2 when tested in accordance with 4.2.1 of SM-A-919717, as a component only, and not as a part of the FLTS.

4.8.9 Receiver antenna characteristics. The receive antenna shall meet the requirements of 3.5.3.3 when tested in accordance with 4.1.2, 4.2, and 4.2.1 of SM-A-920093, as a component only, and not as part of the FLTS.

4.8.10 Pulse modulation. The FLTS shall meet the requirements of 3.5.4.1 when tested in accordance with 3.3 of SM-A-920092.

4.8.11 Scan modulation. The FLTS shall meet the requirements of 3.5.4.2 when tested in accordance with 3.3 of SM-A-920092.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:03Z
Check the source to verify that this is the current version before use.

4.8.12 GO/NO-GO criterion. The FLTS shall meet the requirements of 3.5.4.3 when tested in accordance with 3.4 of SM-A-920092.

4.8.13 JAM light. The FLTS shall meet the requirements of 3.5.4.4 when tested in accordance with 3.4 of SM-A-920092.

4.8.14 Self test. The FLTS shall meet the requirements of 3.5.5.1 when tested in accordance with 3.4 of SM-A-920092.

4.8.15 Lamp test. The FLTS shall meet the requirements of 3.5.6 when tested in accordance with 3.1.2 of SM-A-920092.

4.9 Environmental tests. All environmental test methods, conditions, and procedures given below are contained in MIL-STD-810C. The equipment performance measurements shall be made under standard conditions as defined in MIL-STD-810C. Successful completion of any particular performance test shall be considered evidence of meeting the corresponding service condition.

4.9.1 Temperature. The equipment shall be tested according to the following test methods.

4.9.1.1 Low temperature. The equipment shall be tested in accordance with Method 502.1, Procedure I of MIL-STD-810C and shall meet the requirements of 3.6.1.1.

Storage temp (Step 2).....-67°F(-55°C)
Operating temp (Steps 4 & 5).....-40°F(-40°C)
Make measurements at Steps 1, 5, & 7.....

4.9.1.2 High temperature. The equipment shall be tested in accordance with Method 501.1, Procedure II of MIL-STD-810C, and shall meet the requirements of 3.6.1.2.

Storage temp (Steps 2, 3, & 5).....120°F(49°C)
Storage temp (Step 4).....160°F(71°C)
Operating temp (Steps 7 & 8).....131°F(55°C)
Make measurements at Steps 1, 8, & 10

4.9.2 Altitude. The equipment shall be tested in accordance with Method 500.1, Procedure I of MIL-STD-810C. A non-operating test shall be performed for one hour at 40,000 feet. The equipment shall meet the requirements of 3.6.2 when tested at Steps 1, 2, and 4.

Operating altitude.....15,000 feet
Non-operating altitude.....40,000 feet

4.9.3 Humidity. The equipment shall be tested in accordance with Method 507.1, Procedure II of MIL-STD-810C. The equipment shall be operated during the last 5 hours of the last cycle of Step 6, and shall meet the requirements of 3.6.3 when tested in Steps 4, 6, (last cycle only) and 8.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:03Z
Check the source to verify that this is the current version before use.

4.9.4 Vibration cycling. The equipment, in its combination case, shall be tested in accordance with Method 514.2, Procedure X of MIL-STD-810C, and shall meet the requirements of 3.6.4.

Equipment category.....g
Applicable table.....514.2-VII
Applicable figure.....514.2-7
Test curve.....AW

Make measurements before and after the test only. The frequency of applied vibration shall be swept logarithmically over the specified range.

4.9.5 Loose cargo bounce. The equipment shall be tested in accordance with Method 514.2, Procedure XI, Part 2 of MIL-STD-810C, and shall meet the requirements of 3.6.5.

4.9.6 Bench handling. The equipment shall be tested in accordance with Method 516.2, Procedure V of MIL-STD-810C, and shall meet the requirements of 3.6.6.

4.9.7 Rain. The equipment shall be tested in accordance with Method 506.1, Procedure I of MIL-STD-810C, with combination case cover off, and shall meet the requirements of 3.6.7. There shall be no accumulated water in the enclosure after the rain test exposure (5 milliliters maximum accumulation).

4.9.8 Dust. The equipment shall be tested in accordance with Method 510.1, Procedure I of MIL-STD-810C, with combination case cover off and shall meet the requirements of 3.6.8. The equipment shall be re-oriented in the test chamber every 1 1/2 hours during Step 1 so that all sides are exposed directly to the dust-laden air. The equipment need not be operated during this test. Step 3 of the test procedure shall immediately follow temperature stabilization in Step 2.

4.9.9 Fungus. The equipment in the assembled and as ready for delivery condition, or representative samples subject to approval of the procuring agency, shall be subjected to the test of MIL-STD-810C, Method 508.1, Procedure I, except that the temperature humidity conditions of paragraph 3.1.6a shall be changed to a constant 29°C (84°F) and 95% RH (minimum) during the life of the test. The equipment or samples shall not be specially cleaned for the fungus test, except for the cleaning it receives during or after production. All enclosed or gasketed assemblies shall be opened and the interior sprayed with the specified mixed spore suspension. After 28 days, based on visual examination, the equipment assembly or samples shall show no more than sparse microbial growth with restricted tuberal growth development in and area 10% or less of the total area and no more than six unrelated

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:03Z
Check the source to verify that this is the current version before use.

4.9.9 Fungus(Continued)

minute colonies with mycelial development in areas only in other than critical circuit portions, such as terminal spacing, printed circuit boards, etc., with sparse growth due to random contamination or traces of unmixed material ingredients. (For definitions, see 6.3.3). The equipment shall fail if it does not meet criteria of 3.6.9 or if it shows more than the growth specified above.

4.9.10 Salt fog. The equipment in the assembled and as ready for delivery condition, or selected component parts of the equipment and samples of all materials, finishes, and processes used in the manufacture of the equipment, subject to approval of the procuring agency, shall be tested in accordance with Method 509.1, Procedure I of MIL-STD-810C. The equipment shall meet the requirements of 3.6.10.

4.9.11 Explosive atmosphere. The equipment shall be tested in accordance with Method 511.1, Procedure I of MIL-STD-810C, and shall meet the requirements of 3.6.11. The test temperature shall be limited to 131°F (55°C) and the test altitude to 15,000 feet.

4.10 Electromagnetic interference. The equipment shall be tested in accordance with the test setups and measurement techniques of MIL-STD-462, Notice 3 (EL), as implemented by a contractor prepared, Government approved EMI test plan, and shall meet the requirements of 3.7. These measurements shall have a $\pm$ 3% frequency tolerance and a 4db amplitude tolerance.

4.11 Interchangeability. The equipment shall be inspected to insure the physical and functional interchangeability requirements of 3.11.

4.11.1 Electrical interchangeability. All like modules and replaceable parts shall be tested for functional interchangeability by assembly of randomly selected parts. The assembly shall be tested to and shall meet Group A acceptance requirements. Electrical retuning or realignment of modules during production assembly may be expected and are permissible. Random selection for this assembly shall be supervised by the Government.

4.11.2 Mechnical interchangeability. The dimensions listed below shall be gaged or measured to determine conformance to the physical interchangeability requirements of 3.11. When a listed dimension is not within specified or design limits, it shall be considered a major defect.

a. External and internal dimensions of case, cover, and insertable assemblies, when such dimensions affect mating of parts.

b. Dimensions of cavities, when such dimensions affect insertion of items.

c. Location of hinges and fasteners on separable parts or assemblies which must mate, such as case, covers and mountings.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:03Z
Check the source to verify that this is the current version before use.

4.11.2 Mechanical interchangeability (cont'd)

d. Location of connectors, locking pins, fasteners, slides, and mountings which receive mating parts of plug-in assemblies and major units; and location of the mating parts on the plug-in assembly or major unit.

e. Size and form of special threads.

4.12 Quality conformance inspection of packaging. Packaging shall be inspected in accordance with MIL-P-116 to determine conformance to the requirements of Section 5.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or B, as specified (see 6.2.b).

5.1.1 Level A.

5.1.1.1 Cleaning. Each FLTS shall be cleaned in accordance with process C-1 of MIL-P-116.

5.1.1.2 Drying. Each FLTS shall be dried in accordance with the applicable procedure of MIL-P-116.

5.1.1.3 Preservation application. No preservation required.

5.1.1.4 Unit packaging. Unit packing shall be in accordance with the methods prescribed in MIL-P-116 as specified herein.

5.1.1.4.1 Technical literature. Each item of technical literature shall be individually unit packed method IC-1.

5.1.1.4.2 FLTS. Each set shall be individually unit packed Method III as follows: Secure each major component in combination case. Place the ancillary equipment in the cover of the case. Close the cover and secure with latches provided. Each combination case shall be cushioned on all surfaces with cells or pads or both fabricated of fiberboard conforming to PPP-F-320, type CF, class weather-resistant, W5c, designed to protect the unit from shock and vibration hazards during handling and transit. As an alternate, cushioning material may be fabricated of plastic molding material conforming to MIL-P-19644 or polyurethane foam conforming to MIL-P-26514. The cushioned item shall be inclosed within a close-fitting fiberboard box conforming to PPP-B-636, W5c. Place the technical literature, unit packed as specified in 5.1.1.4.1, on top of the contents, directly under the lid of the box. Close the box in accordance with the appendix of the box specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:03Z
Check the source to verify that this is the current version before use.

5.1.2 Level B. Cleaning, drying, preservative application, and unit packing shall be as specified in 5.1.1.

5.2 Packing. Packing shall be Level A or B, as specified (see 6.2.b). Shipping containers for Level A and B shall be capable of stacking and supporting superimposed loads during shipment and storage without damaging the container(s) or its contents.

5.2.1 Level A. A quantity of FLTS unit packed as specified in 5.1, shall be packed within a close-fitting box conforming to PPP-B-601 overseas type; PPP-B-621 style 4, class 2; or PPP-B-585, style 2 or 3, class 3. When the gross weight exceeds 200 pounds, or the container length and width is 48 x 24 inches or more and the wight exceeds 100 pounds, 3 x 34 inch skids, laid flat, shall be applied in accordance with the requirements of the container specification, or if not specified in the specification, in a manner which will adequately support the item and facilitate the use of material handling equipment. Closure and strapping shall be in accordance with the applicable container specification or appendix thereto except that metal strapping shall conform to QQ-S-781, type I, finish A.

5.2.1.1 Unitization. Palletization shall be required when: containers specified in 5.2.1 do not require skids; quantities per destination exceed either a total of 250 pounds (excluding the pallet) or a volume of 20 cubic feet; and the container size permits use of one of the pallet patterns of MIL-STD-147. A quantity of containers, packed as specified in 5.2.1 except that container strapping may be omitted, shall be placed on a pallet, load type I, conforming to MIL-STD-147. The pallet shall conform to NN-P-71, type IV, group I or II woods. The load shall be "bonded" to the pallet by strapping conforming to QQ-S-781, type I, finish A, or shrink film conforming to L-P-378, type IV.

5.2.2 Level B. A quantity of FLTS, unit packed as specified in 5.1, shall be packed within a close-fitting box conforming to PPP-B-640, class 2, style E or PPP-B-636, type CF, class weather-resistant. The gross weight of boxes conforming to PPP-B-640 shall not exceed 250 pounds. Closure shall be in accordance with the appendix of the applicable box specification. Reinforcing shall be by pressure-sensitive filament tape banding or nonmetalic strapping conforming to PPP-T-97 and PPP-S-760, respectively; selection of the material and application shall be in accordance with the appendix of the applicable box specification. When the gross weight exceeds 200 pounds, or the container length and width is 48 x 24 inches or more and the weight exceeds 100 pounds, containers will be pallet-mounted on pallets conforming to NN-P-71 group I or II woods. The load shall be "bonded" to the pallet by strapping conforming to QQ-S-781, type I, finish A, or shrink film conforming to L-P-378, type IV. When a single unit is shipped to a single destination no packing is required; the unit container shall serve as the shipping container. Reinforcing shall be as specified above.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:03Z
Check the source to verify that this is the current version before use.

5.2.2.1 Unitization. Palletization shall be required when quantities per destination exceed either a total of 250 pounds (excluding the pallet) or a volume of 20 cubic feet, and the container size permits use of one of the pallet patterns of MIL-STD-147. A quantity of FLTS unit packed as specified in 5.1, shall be placed on a pallet, load type I, conforming to MIL-STD-147. The pallet shall conform to NN-P-71, type IV, group I or II woods. The load shall be "bonded" to the pallet by strapping conforming to QQ-S-781, type I, finish A, or shrink film conforming to L-P-378, type IV.

5.3 Marking. In addition to any special marking required by the contract or order, interior packs and exterior shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The FLTS is the test equipment which is used to test the operation of the CMS at the organizational level of maintenance (AVUM). The CMS is used aboard U.S. Army helicopters as protection against radar directed weapon systems.

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification and any amendment thereto.

b. Level A or B preservation and packing (see Section 5).

c. When rough handling is required.

d. First article inspection.

Three complete systems are required so that lengthy environmental tests can be conducted on sample units.

e. Place of final inspection

f. Technical literature required.

g. Quantity of spare parts required.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:03Z
Check the source to verify that this is the current version before use.

6.3 Definitions.

6.3.1 Temperature stabilization. Temperature stabilization will have been attained when the temperature of the part of the test item considered to have the longest thermal lag does not change more than 2.0°C(3.6°F) per hour.

6.3.2 Physical damage. Physical damage is defined as corrosion, rust, blistering, swelling, or other deterioration of parts and materials.

6.3.3 Fungus.

6.3.3.1 Growth colonization. Growth colonization is a mass of individual plants, generally of one species living together; or a group of hyphae which is formed from one spore or cell and may be one individual plant. Colonization which completely covers the surface of the nutrient material constitutes abundant growth.

6.3.3.2 Microbial growth. Microbial growth is the growth of very minute organisms. Such organisms when present in large numbers may provide a colony visible to the naked eye.

6.3.3.3 Tubular germination. Tubular germination is partial growth by the production of hyphae, which are tubular shaped fungal filaments. Tubular germination constitutes restricted individual spore growth not proceeding to colonization.

6.3.4 Exfoliation. Exfoliation is corrosion along the grain boundaries of the metal resulting in the peeling or separating or both of successive layers of the metal. The appearance resembles loose book pages or onion skin peeling.

6.4 Nomenclature. The parentheses in the nomenclature will be deleted or replaced by a letter identifying the particular design. The contractor should apply for nomenclature in accordance with the applicable clause in the contract.

6.5 Data requirements. Deliverable data required by this specification is cited in 4.4.3 entitled first article data.

6.6 First article. First articles are required for inspection and approval (see 3.1, 4.4, and 6.2).

6.7 Environmental. Environmental pollution prevention measures are contained in the packaging material specifications referenced herein. Refer to material specifications or preparing activity for recommended disposability methods.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:03Z
Check the source to verify that this is the current version before use.

6.8 Weight. For shipping purposes the weight of the FLTS is approximately 44 pounds.

6.9 Size. The size of the FLTS is approximately 16.12 inches wide by 14.62 inches deep by 12.25 inches high.

CUSTODIAN
ARMY - ER

PREPARING ACTIVITY
ARMY - ER
PROJECT NO. 5865-0002

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:03Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
US Army Electronics Research and
Development Command
ATTN: DELET-DP
Fort Monmouth, New Jersey 07703

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:03Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. *Fold on lines on reverse side, staple in corner, and send to* preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE
Specification MIL-T-49363(ER) 21 Mar. 80

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?
   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

S/N 0102-014-1802

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:03Z
Check the source to verify that this is the current version before use.