INCH-POUND
A-A-59126C
23 February 2023
SUPERSEDING
A-A-59126B
28 March 2012

COMMERCIAL ITEM DESCRIPTION SHEET

TERMINALS, FEEDTHRU (INSULATED) AND TERMINALS, STUD (INSULATED AND NONINSULATED)

The General Services Administration has authorized the use of this commercial item description (CID) as a replacement for MIL-T-55155 for all federal agencies.

1. SCOPE

1.1 Scope. This CID covers the requirements for insulated feedthru terminals and insulated and noninsulated stud terminals.

2. CLASSIFICATION. Items procured under this CID shall be identified by part numbers as follows:

AA59126/XX	0	H	01
CID Sheet Identifier	Insulation Color	Conductor Material and Finish	Item Number

2.1 CID Sheet Identifier. The CID sheet identifier shall consist of the number of the CID, a slash (/), and a two digit number denoting the CID sheet covering the item.

2.2 Insulation Color. The insulation color is indicated by a single digit in accordance with Table I. For noninsulated terminals or natural color (other than polytetrafluoroethylene) insulated terminals, the letter "X" shall be used in place of the single digit.

2.3 Conductor Material and Finish. The conductor material and finish is identified by a single letter (see 3.3.1). For example, "H" defines a brass terminal, tin-lead plated in accordance with SAE-AMS-P-81728, 0.0003 inch minimum thickness.

2.4 Item Number. The item number is indicated by a two-digit number.

Comments, suggestions, or questions on this document should be emailed to usarmy.apg.devcom-c5isr.mbx.standardization-crx@army.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil/.

AMSC N/A FSC 5940

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:02Z
Check the source to verify that this is the current version before use.

Table I. Insulation color.

Symbol	Insulation Color
0	Black
1	Brown
2	Red
3	Orange
4	Yellow
5	Green
6	Blue
7	Violet
8	Gray
9	White

3. SALIENT CHARACTERISTICS

3.1 CID Sheets. The individual item requirements shall be as described herein and in accordance with the applicable CID sheet. In the event of any conflict between the requirements of this CID and the CID sheet, the latter shall govern.

3.2 Materials. Unless otherwise specified herein, materials shall conform to the manufacturer's specifications/standards. The use of recycled or reclaimed materials is acceptable provided that all requirements of this CID are met (see 4.1). Materials shall be fungus inert.

3.3 Design and Construction. The terminals shall conform to the manufacturer's design and construction. The dimensions shall be in accordance with the individual CID sheet.

3.3.1 Conductor Material and Finish. The conductor material and finish shall be in accordance with one of the following. When so constructed and finished, the terminals shall be solderable.

3.3.1.1 Bronze. The conductor material shall be bronze and finished with one of the following. Copper underplate is not required.

B - Tin-lead plated in accordance with SAE-AMS-P-81728, 0.0003 inch minimum thickness

C - Hot solder dipped using Sn60/Pb40 Solder per IPC J-STD-006, 0.0001 inch minimum thickness

D - Tin-lead electrodeposited in accordance with ASTM B545, 0.0003 inch minimum thickness. The minimum lead content shall be 3 percent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:02Z
Check the source to verify that this is the current version before use.

3.3.1.2 Brass. The conductor material shall be brass and finished with one of the following. Copper underplate of 0.0001 inch minimum thickness is required.

H	-	Tin-lead plated in accordance with SAE-AMS-P-81728, 0.0003 inch minimum thickness
I	-	Hot solder dipped using Sn0/Pb40 Solder per IPC J-STD-006, 0.0001 inch minimum thickness
J	-	Tin-lead electrodeposited in accordance with ASTM B545, 0.0003 inch minimum thickness. The minimum lead content shall be 3 percent.

3.3.2 Mounting Bases. Mounting bases shall be constructed of brass and shall be plated with one of the following finishes (NOTE: Pure tin finish should not be used due to the potential for whiskering):

(a) Tin-lead plated, 0.0001 inch minimum thickness provided that the minimum lead content is 3 percent.

(b) Nickel plated in accordance with SAE-AMS-QQ-N-290, class I or II, 0.0001 inch minimum thickness.

3.3.3 Mounting Hardware. Mounting hardware shall have a finish that is electrolytically compatible with the finish on the mounting base to avoid dissimilar metal corrosion. Pure tin finish should not be used so as to avoid the potential for whiskering. Mounting hardware, including internal tooth lockwashers, shall be supplied with terminals.

3.3.4 Insulation Colors. Insulation colors shall be in accordance with Table I. Manufacturer's standard (equivalent) colors are acceptable.

3.4 Performance.

3.4.1 Solderability. When a tinned copper wire is wrapped around the terminal or run through the terminal (depending on the configuration of the terminal) the connection shall be easily solderable with a soldering iron and rosin-core solder. The soldered joint shall have a smooth fillet over 95 percent of the interface between the wire and the terminal with no visible voids or dewetting.

3.4.2 Pull. The insulated terminals when mounted and subjected to an axial pull as specified on the individual CID sheet for at least 30 seconds, shall show no evidence of separation of the conductor from the insulation, or mounting base by more than 0.005 inch or of terminals pulling out of the mounting.

3.4.3 Torque. The insulated terminals, when mounted and subjected to a torque as specified on the individual CID sheet for at least 30 seconds, shall show no evidence of turning of the conductor within the insulation, or mounting base, or of terminals turning within the mounting.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:02Z
Check the source to verify that this is the current version before use.

3.5 Workmanship. Terminals shall be processed in such a manner as to be uniform in quality and shall be free from any defects that affect life, serviceability or appearance.

4. REGULATORY REQUIREMENTS

4.1 Recovered Materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

5. QUALITY ASSURANCE PROVISIONS

5.1 Contractor Certification. The contractor shall certify and maintain substantiating evidence that the product offered meets the salient characteristics of this Commercial Item Description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices, and is the same product offered for sale in the commercial marketplace. The government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

5.2 Market acceptability (MA). The following market acceptability criteria are necessary to document the quality of the product to be provided under this CID.

5.2.1 The item offered must have been sold to the government or commercial market.

6. PACKAGING

6.1 The packaging requirements shall be as specified in the contract or order (see 7.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:02Z
Check the source to verify that this is the current version before use.

7. NOTES

7.1 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this CID and the required slash sheet, and part number.

b. Packaging requirement (see 6.1).

7.2 Source of Documents.

7.2.1 ASTM Standards are available from https://www.astm.org or ASTM International, 100 Barr Harbor Drive, P.O. Box C700, West Conshohocken, PA 19428-2959.

7.2.2 SAE Standards are available from https://www.sae.org or SAE International, 400 Commonwealth Drive, Warrendale, PA 15096.

7.2.3 IPC Standards are available from https://www.ipc.org or IPC, 3000 Lakeside Drive, 105 N, Bannockburn, IL 60015.

7.2.4 The Federal Acquisition Regulation (FAR) may be obtained from https://www.acquisition.gov/far.

Changes from previous issue. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only, and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

MILITARY INTERESTS:

Custodian:
Army - CR
Navy – EC
Air Force – 85

Reviewer:
DLA – GS

CIVIL AGENCY COORDINATING ACTIVITY

GSA-7FXE

Preparing activity:
Army – CR

(Project No. 5940-2023-002)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/ .

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:02Z
Check the source to verify that this is the current version before use.