INCH-POUND
A-A-59126 /22A
31 May 2011
SUPERSEDING
A-A-59126 /22
26 September 1997

COMMERCIAL ITEM DESCRIPTION SHEET

TERMINALS, STUD (INSULATED)
STYLE SE22

The General Services Administration has authorized the use of this commercial item description (CID) as a replacement for Style SE22 of MIL-T-55155/22 for all federal agencies.

The requirements for acquiring the product described herein shall consist of this sheet and CID A-A-59126.

REQUIREMENTS:

Dimensions and configuration: see Figure 1.



Figure 1. Configuration and Dimensions

Comments, suggestions, or questions on this document should be emailed to michael.g.williams31.civ@mail.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.daps.dla.mil/

AMSC N/A FSC 5940

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:03Z
Check the source to verify that this is the current version before use.

PART NUMBER	DIMENSIONS								
	A	B	C	D	E	F	G	H	J
AA59126/22--01	.398	.130	.082	2-56 UNC-2A	.125	.125	.047	.020	.110
AA59126/22--02						.187			
AA59126/22--03						.250			

Figure 1. Configuration and Dimensions

Insulation material: ceramic

Figure 1 Notes:

1. Dimensions are in inches.
2. Unless otherwise specified, tolerances are ±0.015 inch.
3. Hex nut, brass, No. 2-56 UNC-2B C x 0.06 inch thick x 0.19 inch across flats.
4. The washer and hex nut shall be plated with the same finish as that on the mounting base.
5. Drawing depicts only general design characteristics and is not intended to limit specific manufacturing processes.

Dielectric withstanding voltage: see Table I.

Table I. Dielectric withstanding voltage.

Pressure	Volts ac rms
Atmospheric	1,000
Reduced barometric	425

Pull: 8 pounds minimum.
Torque: 3 ounce-inches, minimum.
Type of mounting: threaded stud.

Table II. Substitutability data.

Part number in A-A-59126/22 1/	Part number in MIL-T-55155/22B 1/
AA59126/22--01	M55155/22--01
AA59126/22--02	M55155/22--02
AA59126/22--03	M55155/22--03

1/ The complete part number shall include the symbol for the insulation color (first dash) and symbol for the conductor material and finish (second dash).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:03Z
Check the source to verify that this is the current version before use.

MILITARY INTERESTS:

Custodian:
Army - CR
Navy – AS
Air Force – 85

Reviewer:
DLA - GS

CIVIL AGENCY COORDINATING ACTIVITY

GSA-7FXE

Preparing activity:
Army – CR

(Project No. 5940-2011-080)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.daps.dla.mil/ .

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:03Z
Check the source to verify that this is the current version before use.