
DETAIL SPECIFICATION SHEET

HOSE ASSEMBLY, POLYTETRAFLUOROETHYLENE, CONVOLUTED, PERMANENTLY ATTACHED FITTINGS, HIGH TEMPERATURE, MEDIUM PRESSURE, FLARELESS-TO-FLARELESS

This specification is approved for use by all
Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-32434.

Hose assembly dimensions for style A: See figure 1.



Fitting ends		Hose size	Dimensions			
1	2		A (ref)	B (max)	C (max)	F (max)
Straight	Straight	3/4	.191	1.282	.620	.580
		4	.222	1.222	.620	.654
		5	.235	1.340	.680	.726
		6	.230	1.469	.750	.798
		8	.310	1.640	.880	1.014
		10	.356	1.940	.967	1.158
		12	.393	1.913	1.122	1.447
		16Z	.429	2.298	1.480	1.736
		20Z	.393	2.577	1.750	2.328
		24Z	.398	2.800	2.150	2.621


FIGURE 1. Style A hose assembly dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:21Z
Check the source to verify that this is the current version before use.

NOTES:
1. Style A uses class 1 fittings which are made from corrosion resistant steel (CRES).
2. Dimensions “A” and “B” are based on end of MS8000 series seal.
3. Dimension “F” is measured across the corners.
4. Assembly length (see PIN) is based on ends of MS8000 series seal.
5. Apply NAS1760 in accordance with MIL-DTL-25579/1, see requirements.

FIGURE 1. Style A hose assembly dimensions - Continued.

Hose assembly dimensions for style B: See figure 2.




Fitting ends		Hose size	Dimensions							
1	2		A (ref)	B (max)	C (max)	D (max)	E (max)	F (max)	G (min)	G (max)
Straight	45°	3/4	.191	1.282	.620	1.240	.950	.580	.412	.537
		4	.222	1.222	.620	1.490	.970	.654	.404	.529
		5	.235	1.340	.680	1.495	1.017	.726	.428	.553
		6	.230	1.469	.750	1.610	1.122	.798	.506	.631
		8	.310	1.640	.880	1.722	1.426	1.014	.542	.789
		10	.356	1.940	.967	2.037	1.596	1.158	.631	.877
		12	.393	1.913	1.122	2.368	1.739	1.447	.631	.952
		16Z	.429	2.298	1.480	2.583	1.931	1.736	.741	1.069
		20Z	.393	2.577	1.750	2.946	2.084	2.328	.863	1.196
		24Z	.398	2.800	2.150	3.210	2.376	2.621	1.012	1.402

Notes:
1. Style B uses class 1 fittings which are made from CRES.
2. Dimensions “A” and “B” are based on end of MS8000 series seal.
3. Dimension “E (max)” is an installation dimension and not a design dimension.
4. Dimension “F” is measured across the corners.
5. Assembly length (see PIN) is based on ends of MS8000 series seal.
6. Apply NAS1760 in accordance with MIL-DTL-25579/1, see requirements.

FIGURE 2. Style B hose assembly dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:21Z
Check the source to verify that this is the current version before use.

Hose assembly dimensions for style C: See figure 3.




Fitting ends		Hose size	Dimensions							
1	2		A (ref)	B (max)	C (max)	F (max)	H (max)	J (max)	K (min)	K (max)
Straight	90°	3/4	.191	1.282	.620	.580	1.845	1.350	.721	.846
		4	.222	1.222	.620	.654	1.885	1.370	.705	.830
		5	.235	1.340	.680	.726	1.980	1.550	.788	.975
		6	.230	1.469	.750	.798	2.205	1.687	.895	1.082
		8	.310	1.640	.880	1.014	2.495	2.032	1.032	1.282
		10	.356	1.940	.967	1.158	2.955	2.437	1.357	1.607
		12	.393	1.913	1.122	1.447	3.705	2.795	1.591	1.841
		16Z	.429	2.298	1.480	1.736	4.100	3.160	1.741	1.991
		20Z	.393	2.577	1.750	2.328	4.835	3.664	2.021	2.396
		24Z	.398	2.800	2.150	2.621	5.480	4.251	2.403	2.778

NOTES:
1. Style C uses class 1 fittings which are made from CRES.
2. Dimensions “A” and “B” are based on end of MS8000 series seal.
3. Dimension “F” is measured across the corners.
4. Dimension “J (max)” is an installation dimension and not a design dimension.
5. Assembly length (see PIN) is based on end of MS8000 series seal to center line of 90° fitting.
6. Apply NAS1760 in accordance with MIL-DTL-25579/1, see requirements.

FIGURE 3. Style C hose assembly dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:21Z
Check the source to verify that this is the current version before use.

Hose assembly dimensions for style D: See figure 4.




Fitting ends		Hose size	Dimensions						
1	2		A (ref)	C (max)	D (max)	E (max)	F (max)	G (min)	G (max)
45°	45°	3/4	.191	.620	1.240	.950	.580	.412	.537
		4	.222	.620	1.490	.970	.654	.404	.529
		5	.235	.680	1.495	1.017	.726	.428	.553
		6	.230	.750	1.610	1.122	.798	.506	.631
		8	.310	.880	1.722	1.426	1.014	.542	.789
		10	.356	.967	2.037	1.596	1.158	.631	.877
		12	.393	1.122	2.368	1.739	1.447	.631	.952
		16Z	.429	1.480	2.583	1.931	1.736	.741	1.069
		20Z	.393	1.750	2.946	2.084	2.328	.863	1.196
		24Z	.398	2.150	3.210	2.376	2.621	1.012	1.402

NOTES:
1. Style D uses class 1 fittings which are made from CRES.
2. Dimensions “A” is based on end of MS8000 series seal.
3. Dimension “E (max)”is an installation dimensions and not a design dimension.
4. Dimension “F” is measured across the corners.
5. Assembly length (see PIN) is based on ends of MS8000 series seal.
6. Apply NAS1760 in accordance with MIL-DTL-25579/1, see requirements.

FIGURE 4. Style D hose assembly dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:21Z
Check the source to verify that this is the current version before use.

Hose assembly dimensions for style E: See figure 5.




Fitting ends		Hose size	Dimensions										
1	2		A (ref)	C (max)	D (max)	E (max)	F (max)	G (min)	G (max)	H (max)	J (max)	K (min)	K (max)
45°	90°	3/4	.191	.620	1.240	.950	.580	.412	.537	1.845	1.350	.721	.846
		4	.222	.620	1.490	.970	.654	.404	.529	1.885	1.370	.705	.830
		5	.235	.680	1.495	1.017	.726	.428	.553	1.980	1.550	.788	.975
		6	.230	.750	1.610	1.122	.798	.506	.631	2.205	1.687	.895	1.082
		8	.310	.880	1.722	1.426	1.014	.542	.789	2.495	2.032	1.032	1.282
		10	.356	.967	2.037	1.596	1.158	.631	.877	2.955	2.437	1.357	1.607
		12	.393	1.122	2.368	1.739	1.447	.631	.952	3.705	2.795	1.591	1.841
		16Z	.429	1.480	2.583	1.931	1.736	.741	1.069	4.100	3.160	1.741	1.991
		20Z	.393	1.750	2.946	2.084	2.328	.863	1.196	4.835	3.664	2.021	2.396
		24Z	.398	2.150	3.210	2.376	2.621	1.012	1.402	5.480	4.251	2.403	2.778

NOTES:
1. Style E uses class 1 fittings which are made from CRES.
2. Dimensions “A” is based on end of MS8000 series seal.
3. Dimensions “E (max)” and “J (max)” are installation dimensions and not design dimensions.
4. Dimension “F” is measured across the corners.
5. Assembly length (see PIN) is based on end of MS8000 series seal to center line of 90° fitting.
6. Apply NAS1760 in accordance with MIL-DTL-25579/1, see requirements.

FIGURE 5. Style E hose assembly dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:21Z
Check the source to verify that this is the current version before use.

Hose assembly dimensions for style F: See figure 6.




Fitting ends		Hose	Dimensions						
1	2	size	A (ref)	C (max)	F (max)	H (max)	J (max)	K (min)	K (max)
90°	90°	3/4	.191	.620	.580	1.845	1.350	.721	.846
		4	.222	.620	.654	1.885	1.370	.705	.830
		5	.235	.680	.726	1.980	1.550	.788	.975
		6	.230	.750	.798	2.205	1.687	.895	1.082
		8	.310	.880	1.014	2.495	2.032	1.032	1.282
		10	.356	.967	1.158	2.955	2.437	1.357	1.607
		12	.393	1.122	1.447	3.705	2.795	1.591	1.841
		16Z	.429	1.480	1.736	4.100	3.160	1.741	1.991
		20Z	.393	1.750	2.328	4.835	3.664	2.021	2.396
		24Z	.398	2.150	2.621	5.480	4.251	2.403	2.778

NOTES:
1. Style F uses class 1 fittings which are made from CRES.
2. Dimensions “A” is based on end of MS8000 series seal.
3. Dimension “F” is measured across the corners.
4. Dimension “J (max)” is an installation dimension and not a design dimension.
5. Assembly length (see PIN) is based on center lines of 90° fittings.
6. Apply NAS1760 in accordance with MIL-DTL-25579/1, see requirements.

FIGURE 6. Style F hose assembly dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:21Z
Check the source to verify that this is the current version before use.

Hose assembly dimensions for style G: See figure 7.




Fitting ends		Hose size	Dimensions			
1	2		A (ref)	B (max)	C (max)	F (max)
Straight	Straight	8	.310	1.640	.880	1.014
		10	.356	1.940	.967	1.158
		12	.393	1.913	1.122	1.447
		16Z	.429	2.298	1.480	1.736
		20Z	.393	2.577	1.750	2.328
		24Z	.398	2.800	2.150	2.621

NOTES:
1. Style G uses class 2 fittings which are made from a combination of aluminum and CRES.
2. Dimensions “A” and “B” are based on end of MS8000 seal.
3. Dimension “F” is measured across the corners.
4 Assembly length (see PIN) is based on ends of MS8000 series seal.
5. Apply NAS1760 in accordance with MIL-DTL-25579/1, see requirements.

FIGURE 7. Style G hose assembly dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:21Z
Check the source to verify that this is the current version before use.

Hose assembly dimensions for style H: See figure 8.




Fitting ends		Hose size	Dimensions							
1	2		A (ref)	B (max)	C (max)	D (max)	E (max)	F (max)	G (min)	G (max)
Straight	45°	8	.310	1.640	.880	1.722	1.426	1.014	.542	.789
		10	.356	1.940	.967	2.037	1.596	1.158	.631	.877
		12	.393	1.913	1.122	2.368	1.739	1.447	.631	.952
		16Z	.429	2.298	1.480	2.583	1.931	1.736	.741	1.069
		20Z	.393	2.577	1.750	2.946	2.084	2.328	.863	1.196
		24Z	.398	2.800	2.150	3.210	2.376	2.621	1.012	1.402

NOTES:
1. Style H uses class 2 fittings which are made from a combination of aluminum and CRES.
2. Dimensions “A” and “B” are based on end of MS8000 series seal.
3. Dimension “E (max)”is an installation dimension and not a design dimension.
4. Dimension “F” is measured across the corners.
5. Assembly length (see PIN) is based on ends of MS8000 series seal.
6. Apply NAS1760 in accordance with MIL-DTL-25579/1, see requirements.

FIGURE 8. Style H hose assembly dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:21Z
Check the source to verify that this is the current version before use.

Hose assembly dimensions for style J: See figure 9.




Fitting ends		Hose size	Dimensions							
1	2		A (ref)	B (max)	C (max)	F (max)	H (max)	J (max)	K (min)	K (max)
Straight	90°	8	.310	1.640	.880	1.014	2.495	2.032	1.032	1.282
		10	.356	1.940	.967	1.158	2.955	2.437	1.357	1.607
		12	.393	1.913	1.122	1.447	3.705	2.795	1.591	1.841
		16Z	.429	2.298	1.480	1.736	4.100	3.160	1.741	1.991
		20Z	.393	2.577	1.750	2.328	4.835	3.664	2.021	2.396
		24Z	.398	2.800	2.150	2.621	5.480	4.251	2.403	2.778

NOTES:
1. Style J uses class 2 fittings which are made from a combination of aluminum and CRES.
2. Dimensions “A” and “B” are based on end of MS8000 series seal.
3. Dimension “F” is measured across the corners.
4. Dimension “J (max)” is an installation dimension and not a design dimension.
5. Assembly length (see PIN) is based on end of MS8000 series seal to center line of 90° fitting.
6. Apply NAS1760 in accordance with MIL-DTL-25579/1, see requirements.

FIGURE 9. Style J hose assembly dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:21Z
Check the source to verify that this is the current version before use.

Hose assembly dimensions for style K: See figure 10.




Fitting ends		Hose size	Dimensions						
1	2		A (ref)	C (max)	D (max)	E (max)	F (max)	G (min)	G (max)
45°	45°	8	.310	.880	1.722	1.426	1.014	.542	.789
		10	.356	.967	2.037	1.596	1.158	.631	.877
		12	.393	1.122	2.368	1.739	1.447	.631	.952
		16Z	.429	1.480	2.583	1.931	1.736	.741	1.069
		20Z	.393	1.750	2.946	2.084	2.328	.863	1.196
		24Z	.398	2.150	3.210	2.376	2.621	1.012	1.402

NOTES:
1. Style K uses class 2 fittings which are made from a combination of aluminum and CRES.
2. Dimensions “A” is based on end of MS8000 seal.
3. Dimension “E (max)” is installation dimension and not a design dimension.
4. Dimension “F” is measured across the corners.
5. Assembly length (see PIN) is based on ends of MS8000 series seal.
6. Apply NAS1760 in accordance with MIL-DTL-25579/1, see requirements.

FIGURE 10. Style K hose assembly dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:21Z
Check the source to verify that this is the current version before use.

Hose assembly dimensions for style M: See figure 11.




Fitting ends		Hose size	Dimensions										
1	2		A (ref)	C (max)	D (max)	E (max)	F (max)	G (min)	G (max)	H (max)	J (max)	K (min)	K (max)
45°	90°	8	.310	.880	1.722	1.426	1.014	0.542	.789	2.495	2.032	1.032	1.282
		10	.356	.967	2.037	1.596	1.158	0.631	.877	2.955	2.437	1.357	1.607
		12	.393	1.122	2.368	1.739	1.447	0.631	.952	3.705	2.795	1.591	1.841
		16Z	.429	1.480	2.583	1.931	1.736	0.741	1.069	4.100	3.160	1.741	1.991
		20Z	.393	1.750	2.946	2.084	2.328	0.863	1.196	4.835	3.664	2.021	2.396
		24Z	.398	2.150	3.210	2.376	2.621	1.012	1.402	5.480	4.251	2.403	2.778

NOTES:
1. Style M uses class 2 fittings which are made from a combination of aluminum and CRES.
2. Dimensions “A” is based on end of MS8000 seal.
3. Dimensions “E (max)” and “J (max)” are installation dimensions and not design dimensions.
4. Dimension “F” is measured across the corners.
5. Assembly length (see PIN) is based on end of MS8000 series seal to center line of 90° fitting.
6. Apply NAS1760 in accordance with MIL-DTL-25579/1, see requirements.

FIGURE 11. Style M hose assembly dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:21Z
Check the source to verify that this is the current version before use.

Hose assembly dimensions for style N: See figure 12.



Fitting ends		Hose size	Dimensions						
1	2		A (ref)	C (max)	F (max)	H (max)	J (max)	K (min)	K (max)
90°	90°	8	.310	.880	1.014	2.495	2.032	1.032	1.282
		10	.356	.967	1.158	2.955	2.437	1.357	1.607
		12	.393	1.122	1.447	3.705	2.795	1.591	1.841
		16Z	.429	1.480	1.736	4.100	3.160	1.741	1.991
		20Z	.393	1.750	2.328	4.835	3.664	2.021	2.396
		24Z	.398	2.150	2.621	5.480	4.251	2.403	2.778

NOTES:
1. Style N uses class 2 fittings which are made from a combination of aluminum and CRES.
2. Dimensions “A” is based on end of MS8000 series seal.
3. Dimension “F” is measured across the corners.
4. Dimension “J (max)” is an installation dimension and not a design dimension.
5. Assembly length (see PIN) is based on center lines of 90° fittings.
6. Apply NAS1760 in accordance with MIL-DTL-25579/1, see requirements.

FIGURE 12. Style N hose assembly dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:21Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Hose: Hose shall be in accordance with MIL-DTL-32435.

Hose assembly size code: See table I.

TABLE I. Hose assembly size code.

Size code	Size	Reference tube OD
B	3/4	1/
E	4	.250
F	5	.313
G	6	.375
H	8	.500
J	10	.625
K	12	.750
M	16Z	1.000
N	20Z	1.250
P	24Z	1.500

1/ Size 3/4 hose assembly consists of a size 4 tube OD hose assembled with size 3 tube OD fittings.

Fittings: The swivel nut and nipple ends shall mate with SAE-AS33514 fitting. The swivel nut threads shall be in accordance with SAE-AS8879.

Flareless fitting, hose connector design: Use MIL-DTL-25579/1 for application of NAS1760 design or radius ball-nose design.

Elbow fittings: The ovality of the circular cross section within the angle of the bend of the end fitting elbow shall not exceed 7.5% of the nominal tubing OD, see table II.

TABLE II. Elbow fitting ovality. 1/


Assembly size	3/4	4	5	6	8	10	12	16	20	24
Ball diameter	.080	.119	.174	.230	.313	.391	.515	.750	.969	1.188

1/ The fitting elbow bend shall be examined for ovality by rolling a ball of applicable diameter through the elbow fitting. The ball shall pass freely through the fitting elbow bend.

Assembly classification: Class 1 and class 2 hose assemblies, as specified in MIL-DTL-32434, have been incorporated into the Part or Identifying Number (PIN) as a part of styles.

Angular alignment: Hose assemblies with elbow fittings on each end shall have the angular orientation between the elbows measured counter-clockwise from the centerline of the nearest fitting, positioned at six-o'clock, to the centerline of the other fitting (see figure 13). When applicable, the angular alignment shall be expressed in three digits and specified in the PIN.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:21Z
Check the source to verify that this is the current version before use.



NOTE: Angular alignment shall be measured in degrees with a tolerance of ±2°.

FIGURE 13. Measurement of angular alignment between elbow fittings.

Protective sleeve: If required, the hose assembly shall include a protective sleeve (see table III) and its code shall be included in the PIN. Fire protective sleeve shall be subjected to testing in accordance with MIL-DTL-32434.

TABLE III. Protective sleeve code.

Code	Type
Blank	None
A	SAE-AS1072 sleeve, fire protection, silicone covered, temperature ranging from -65°F to 450°F, and intermittently to 500°F, secured with CRES bands as required. 1/
B	SAE-AS1073 - code B sleeve, abrasion protection, heat shrinkable, black polyolefin, temperature ranging from -65°F to 250°F.
C	SAE-AS1291 - code A sleeve, chafe guard, extruded seamless white PTFE, temperature ranging from -65°F to 450°F, secured with CRES bands as required.
D	SAE-AS1291 - code C sleeve, chafe guard, extruded seamless transparent FEP, temperature ranging from -65°F to 350°F, secured with CRES bands as required.
E	SAE-AS1298 sleeve, heavy wall chafe guard, extruded seamless black PTFE, temperature ranging from -65°F to 450°F, secured with CRES bands as required.
L	Lock-wire hole
F	Code A + L
G	Code B + L
H	Code C + L
J	Code D + L
K	Code E + L


1/ To prevent wicking of fluids, the cut end of the fire protective sleeve (code A) shall be coated with room temperature vulcanized (RTV) silicone rubber prior to installation. After installation, cracks and voids in the fire protective sleeve shall be coated with RTV rubber to prevent exposure of asbestos or fiberglass.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:21Z
Check the source to verify that this is the current version before use.

Assembly length: Hose assembly shall be furnished in lengths as specified in the contract or purchase order (see figures 1 through 12); however, tolerances on the length of each hose assembly shall be as follows:

a. ±1/8 inch for lengths under 18 inches.
b. ±1/4 inch for lengths from 18 inches to 36 inches.
c. ±1/2 inch for lengths from 36 inches to 50 inches.
d. ±1% for lengths over 50 inches.

PIN: The PIN consists of letter M, specification sheet number, hose size code, hose length in inches and an eighths of an inch, hose assembly style, sleeve code, and angular alignment in degree between elbow fittings.



Example: M32434/7H082FA030 represents 1/2inch OD PTFE convoluted hose assembly, 8.25 inches long, flare-to-flare permanently attached fittings with fire protective sleeve and 30° angular alignment between elbows.

Referenced documents. In addition to MIL-DTL-32434, this document references the following:

MIL-DTL-25579/1	SAE-AS1073
MIL-DTL-32435	SAE-AS1291
MS8000	SAE-AS1298
NAS1760	SAE-AS8879
SAE-AS1072	SAE-AS33514

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:21Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - AV
Navy - AS
Air Force - 99
DLA - CC

Preparing activity:
DLA - CC

(Project 4720-2012-025)

Review activities:
Army - AR, AT, EA, MI
Navy - MC, SA, SH
Air Force - 70

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:21Z
Check the source to verify that this is the current version before use.