INCH-POUND

MIL-DTL-32434/8
23 January 2013


DETAIL SPECIFICATION SHEET

HOSE ASSEMBLY, POLYTETRAFLUOROETHYLENE, CONVOLUTED, PERMANENTLY ATTACHED FITTINGS, HIGH TEMPERATURE, MEDIUM PRESSURE, FLARE-TO-FLANGE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-32434.

Hose assembly dimensions for style A: See figure 1.




Fitting ends		Hose size	Dimensions					
1	2		A (ref)	B (max)	C (max)	F (max)	M (max)	P (max)
Straight	Straight	8	.438	1.465	.880	1.014	1.560	.875
		10	.515	1.680	.967	1.158	1.570	1.000
		12	.570	1.727	1.122	1.447	1.640	1.250
		16Z	.620	2.101	1.480	1.736	1.750	1.500
		20Z	.640	2.255	1.750	2.328	1.990	1.844
		24Z	.765	2.400	2.150	2.621	2.260	2.125

NOTES
1. Style A uses class 1 fittings which are made from corrosion resistant steel (CRES).
2. Dimension “F” is measured across the corners.

FIGURE 1. Style A hose assembly dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:22Z
Check the source to verify that this is the current version before use.

Hose assembly dimensions for style B: See figure 2.




Fitting ends		Hose size	Dimensions								
1	2		A (ref)	B (max)	C (max)	D (max)	F (max)	N (max)	P (max)	R (min)	R (max)
Straight	45°	8	.438	1.465	.880	1.722	1.014	.606	.875	.303	.428
		10	.515	1.680	.967	2.037	1.158	.658	1.000	.340	.465
		12	.570	1.727	1.122	2.368	1.447	.789	1.250	.433	.558
		16Z	.620	2.101	1.480	2.583	1.736	.929	1.500	.470	.657
		20Z	.640	2.255	1.750	2.946	2.328	1.020	1.844	.534	.721
		24Z	.765	2.400	2.150	3.210	2.621	1.186	2.125	.589	.839

NOTES:
1. Style B uses class 1 fittings which are made from CRES.
2. Dimension “F” is measured across the corners.
3. Dimension “N (max)” is an installation dimensions and not a design dimensions.

FIGURE 2. Style B hose assembly dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:22Z
Check the source to verify that this is the current version before use.

Hose assembly dimensions for style C: See figure 3.




Fitting ends		Hose size	Dimensions								
1	2		A (ref)	B (max)	C (max)	F (max)	P (max)	S (max)	T (max)	U (min)	U (max)
Straight	90°	8	.438	1.465	.880	1.014	.875	2.320	1.422	.857	.982
		10	.515	1.680	.967	1.158	1.000	2.875	1.499	.861	1.015
		12	.570	1.727	1.122	1.447	1.250	3.606	1.807	1.032	1.246
		16Z	.620	2.101	1.480	1.736	1.500	3.981	2.174	1.156	1.434
		20Z	.640	2.255	1.750	2.328	1.844	4.435	2.590	1.344	1.715
		24Z	.765	2.400	2.150	2.621	2.125	5.075	3.103	1.516	2.028

NOTES:
1. Style C uses class 1 fittings which are made from CRES.
2. Dimension “F” is measured across the corners.
3. Dimension “T (max)” is an installation dimensions and not a design dimensions.

FIGURE 3. Style C hose assembly dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:22Z
Check the source to verify that this is the current version before use.

Hose assembly dimensions for style D: See figure 4.




Fitting ends		Hose size	Dimensions										
1	2		A (ref)	C (max)	D (max)	E (max)	F (max)	G (min)	G (max)	N (max)	P (max)	R (min)	R (max)
45°	45°	8	.438	.880	1.722	1.332	1.014	.445	.632	.606	0.875	.303	.428
		10	.515	.967	2.037	1.488	1.158	.501	.688	.658	1.000	.340	.465
		12	.570	1.122	2.368	1.667	1.447	.564	.775	.789	1.250	.433	.558
		16Z	.620	1.480	2.583	1.879	1.736	.609	.857	.929	1.500	.470	.657
		20Z	.640	1.750	2.946	2.058	2.328	.697	1.017	1.020	1.844	.534	.721
		24Z	.765	2.150	3.210	2.400	2.621	.785	1.127	1.186	2.125	.589	.839

NOTES:
1. Style D uses class 1 fittings which are made from CRES.
2. Dimension “F” is measured across the corners.
3. Dimensions “E (max)”and “N (max)” are installation dimensions and not design dimensions.

FIGURE 4. Style D hose assembly dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:22Z
Check the source to verify that this is the current version before use.

Hose assembly dimensions for style E: See figure 5.




Fitting ends		Hose size	Dimensions											
1	2		A (ref)	C (max)	D (max)	E (max)	F (max)	G (min)	G (max)	P (max)	S (max)	T (max)	U (min)	U (max)
45°	90°	8	.438	.880	1.722	1.332	1.014	.445	.632	.875	2.320	1.422	.857	.982
		10	.515	.967	2.037	1.488	1.158	.501	.688	1.000	2.875	1.499	.861	1.015
		12	.570	1.122	2.368	1.667	1.447	.564	.775	1.250	3.606	1.807	1.032	1.246
		16Z	.620	1.480	2.583	1.879	1.736	.609	.857	1.500	3.981	2.174	1.156	1.434
		20Z	.640	1.750	2.946	2.058	2.328	.697	1.017	1.844	4.435	2.590	1.344	1.715
		24Z	.765	2.150	3.210	2.400	2.621	.785	1.127	2.125	5.075	3.103	1.516	2.028

NOTES:
1. Style E uses class 1 fittings which are made from CRES.
2. Dimension “F” is measured across the corners.
3. Dimensions “E (max)” and “T (max)” are installation dimensions and not design dimensions.

FIGURE 5. Style E hose assembly dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:22Z
Check the source to verify that this is the current version before use.

Hose assembly dimensions for style F: See figure 6.




Fitting ends		Hose size	Dimensions											
1	2		A (ref)	C (max)	F (max)	H (max)	J (max)	K (min)	K (max)	P (max)	S (max)	T (max)	U (min)	U (max)
90°	90°	8	.438	.880	1.014	2.495	1.938	.810	1.092	0.875	2.320	1.422	.857	.982
		10	.515	.967	1.158	2.955	2.340	1.056	1.341	1.000	2.875	1.499	.861	1.015
		12	.570	1.122	1.447	3.705	2.722	1.341	1.591	1.250	3.606	1.807	1.032	1.246
		16Z	.620	1.480	1.736	4.100	3.075	1.465	1.840	1.500	3.981	2.174	1.156	1.434
		20Z	.640	1.750	2.328	4.835	3.637	1.747	2.233	1.844	4.435	2.590	1.344	1.715
		24Z	.765	2.150	2.621	5.480	4.212	1.997	2.372	2.125	5.075	3.103	1.516	2.028

NOTES:
1. Style F uses class 1 fittings which are made from CRES.
2. Dimension “F” is measured across the corners.
3. Dimensions “J (max)” and “T (max)” are installation dimensions and not design dimensions.

FIGURE 6. Style F hose assembly dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:22Z
Check the source to verify that this is the current version before use.

Hose assembly dimensions for style G: See figure 7.




Fitting ends		Hose size	Dimensions								
1	2		A (ref)	C (max)	D (max)	E (max)	F (max)	G (min)	G (max)	M (max)	P (max)
45°	Straight	8	.438	.880	1.722	1.332	1.014	.445	.632	1.560	.875
		10	.515	.967	2.037	1.488	1.158	.501	.688	1.570	1.000
		12	.570	1.122	2.368	1.667	1.447	.564	.775	1.640	1.250
		16Z	.620	1.480	2.583	1.879	1.736	.609	.857	1.750	1.500
		20Z	.640	1.750	2.946	2.058	2.328	.697	1.017	1.990	1.844
		24Z	.765	2.150	3.210	2.400	2.621	.785	1.127	2.260	2.125

NOTES:
1. Style G uses class 1 fittings which are made from CRES.
2. Dimension “F” is measured across the corners.
3. Dimension “E (max)”is an installation dimensions and not design dimensions.

FIGURE 7. Style G hose assembly dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:22Z
Check the source to verify that this is the current version before use.

Hose assembly dimensions for style H: See figure 8.




Fitting ends		Hose size	Dimensions								
1	2		A (ref)	C (max)	F (max)	H (max)	J (max)	K (min)	K (max)	M (max)	P (max)
90°	Straight	8	.438	.880	1.014	2.495	1.938	.810	1.092	1.560	.875
		10	.515	.967	1.158	2.995	2.340	1.056	1.341	1.570	1.000
		12	.570	1.122	1.447	3.705	2.722	1.341	1.591	1.640	1.250
		16Z	.620	1.480	1.736	4.100	3.075	1.465	1.840	1.750	1.500
		20Z	.640	1.750	2.328	4.835	3.637	1.747	2.233	1.990	1.844
		24Z	.765	2.150	2.621	5.480	4.212	1.997	2.372	2.260	2.125

NOTES:
1. Style H uses class 1 fittings which are made from CRES.
2. Dimension “F” is measured across the corners.
3. Dimension “J (max)” is installation dimension and not a design dimension.

FIGURE 8. Style H hose assembly dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:22Z
Check the source to verify that this is the current version before use.

Hose assembly dimensions for style J: See figure 9.




Fitting ends		Hose size	Dimensions											
1	2		A (ref)	C (max)	D (max)	F (max)	H (max)	J (max)	K (min)	K (max)	N (max)	P (max)	R (min)	R (max)
90°	45°	8	.438	.880	1.722	1.014	2.495	1.938	.810	1.092	.606	.875	.303	.428
		10	.515	.967	2.037	1.158	2.955	2.340	1.056	1.341	.658	1.000	.340	.465
		12	.570	1.122	2.368	1.447	3.705	2.722	1.341	1.591	.789	1.250	.433	.558
		16Z	.620	1.480	2.583	1.736	4.100	3.075	1.465	1.840	.929	1.500	.470	.657
		20Z	.640	1.750	2.946	2.328	4.835	3.637	1.747	2.233	1.020	1.844	.534	.721
		24Z	.765	2.150	3.210	2.621	5.480	4.212	1.997	2.372	1.186	2.125	.589	.839

NOTES:
1. Style J uses class 1 fittings which are made from CRES.
2. Dimension “F” is measured across the corners.
3. Dimensions “J (max)”and “N (max)” are installation dimensions and not design dimensions.

FIGURE 9. Style J hose assembly dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:22Z
Check the source to verify that this is the current version before use.

Hose assembly dimensions for style K: See figure 10.




Fitting ends		Hose	Dimensions					
1	2	size	A (ref)	B (max)	C (max)	F (max)	M (max)	P (max)
		8	.438	1.465	.880	1.014	1.560	.875
		10	.515	1.680	.967	1.158	1.570	1.000
Straight	Straight	12	.570	1.727	1.122	1.447	1.640	1.250
		16Z	.620	2.101	1.480	1.736	1.750	1.500
		20Z	.640	2.255	1.750	2.328	1.990	1.844
		24Z	.765	2.400	2.150	2.621	2.260	2.125

NOTES:
1. Style K uses class 2 fittings which are made from a combination of aluminum and CRES.
2. Dimension “F” is measured across the corners.

FIGURE 10. Style K hose assembly dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:22Z
Check the source to verify that this is the current version before use.

Hose assembly dimensions for style M: See figure 11.




Fitting ends		Hose size	Dimensions								
1	2		A (ref)	B (max)	C (max)	D (max)	F (max)	N (max)	P (max)	R (min)	R (max)
Straight	45°	8	.438	1.465	.880	1.722	1.014	.606	.875	.303	.428
		10	.515	1.680	.967	2.037	1.158	.658	1.000	.340	.465
		12	.570	1.727	1.122	2.368	1.447	.789	1.250	.433	.558
		16Z	.620	2.101	1.480	2.583	1.736	.929	1.500	.470	.657
		20Z	.640	2.255	1.750	2.946	2.328	1.020	1.844	.534	.721
		24Z	.765	2.400	2.150	3.210	2.621	1.186	2.125	.589	.839

NOTES:
1. Style M uses class 2 fittings which are made from a combination of aluminum and CRES.
2. Dimension “F” is measured across the corners.
3. Dimension “N (max)” is an installation dimensions and not a design dimensions.

FIGURE 11. Style M hose assembly dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:22Z
Check the source to verify that this is the current version before use.

Hose assembly dimensions for style N: See figure 12.




Fitting ends		Hose size	Dimensions								
1	2		A (ref)	B (max)	C (max)	F (max)	P (max)	S (max)	T (max)	U (min)	U (max)
		8	.438	1.465	.880	1.014	.875	2.320	1.422	.857	.982
Straight	90°	10	.515	1.680	.967	1.158	1.000	2.875	1.499	.861	1.015
		12	.570	1.727	1.122	1.447	1.250	3.606	1.807	1.032	1.246
		16Z	.620	2.101	1.480	1.736	1.500	3.981	2.174	1.156	1.434
		20Z	.640	2.255	1.750	2.328	1.844	4.435	2.590	1.344	1.715
		24Z	.765	2.400	2.150	2.621	2.125	5.075	3.103	1.516	2.028

NOTES:
1. Style N uses class 2 fittings which are made from a combination of aluminum and CRES.
2. Dimension “F” is measured across the corners.
3. Dimension “T (max)” is an installation dimension and not a design dimension.

FIGURE 12. Style N hose assembly dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:22Z
Check the source to verify that this is the current version before use.

Hose assembly dimensions for style P: See figure 13.




Fitting ends		Hose size	Dimensions (see note 2)										
1	2		A (ref)	C (max)	D (max)	E (max)	F (max)	G (min)	G (max)	N (max)	P (max)	R (min)	R (max)
45°	45°	8	.438	.880	1.722	1.332	1.014	.445	.632	.606	.875	.303	.428
		10	.515	.967	2.037	1.488	1.158	.501	.688	.658	1.000	.340	.465
		12	.570	1.122	2.368	1.667	1.447	.564	.775	.789	1.250	.433	.558
		16Z	.620	1.480	2.583	1.879	1.736	.609	.857	.929	1.500	.470	.657
		20Z	.640	1.750	2.946	2.058	2.328	.697	1.017	1.020	1.844	.534	.721
		24Z	.765	2.150	3.210	2.400	2.621	.785	1.127	1.186	2.125	.589	.839

NOTES:
1. Style P uses class 2 fittings which are made from a combination of aluminum and CRES.
2. Dimension “F” is measured across the corners.
3. Dimensions “E (max)” and “N (max)” are installation dimensions and not design dimensions.

FIGURE 13. Style P hose assembly dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:22Z
Check the source to verify that this is the current version before use.

Hose assembly dimensions for style R: See figure 14.




Fitting ends		Hose size	Dimensions											
1	2		A (ref)	C (max)	D (max)	E (max)	F (max)	G (min)	G (max)	P (max)	S (max)	T (max)	U (min)	U (max)
45°	90°	8	.438	.880	1.722	1.332	1.014	.445	.632	.875	2.320	1.422	.857	.982
		10	.515	.967	2.037	1.488	1.158	.501	.688	1.000	2.875	1.499	.861	1.015
		12	.570	1.122	2.368	1.667	1.447	.564	.775	1.250	3.606	1.807	1.032	1.246
		16Z	.620	1.480	2.583	1.879	1.736	.609	.857	1.500	3.981	2.174	1.156	1.434
		20Z	.640	1.750	2.946	2.058	2.328	.697	1.017	1.844	4.435	2.590	1.344	1.715
		24Z	.765	2.150	3.210	2.400	2.621	.785	1.127	2.125	5.075	3.103	1.516	2.028

NOTES:
1. Style R uses class 2 fittings which are made from a combination of aluminum and CRES.
2. Dimension “F” is measured across the corners.
3. Dimensions “E (max)” and “T (max)” are installation dimensions and not design dimensions.

FIGURE 14. Style R hose assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:22Z
Check the source to verify that this is the current version before use.

Hose assembly dimensions for style S: See figure 15.




Fitting ends		Hose size	Dimensions											
1	2		A (ref)	C (max)	F (max)	H (max)	J (max)	K (min)	K (max)	P (max)	S (max)	T (max)	U (min)	U (max)
90°	90°	8	.438	.880	1.014	2.495	1.938	.810	1.092	.875	2.320	1.422	.857	.982
		10	.515	.967	1.158	2.955	2.340	1.056	1.341	1.000	2.875	1.499	.861	1.015
		12	.570	1.122	1.447	3.705	2.722	1.341	1.591	1.250	3.606	1.807	1.032	1.246
		16Z	.620	1.480	1.736	4.100	3.075	1.465	1.840	1.500	3.981	2.174	1.156	1.434
		20Z	.640	1.750	2.328	4.835	3.637	1.747	2.233	1.844	4.435	2.590	1.344	1.715
		24Z	.765	2.150	2.621	5.480	4.212	1.997	2.372	2.125	5.075	3.103	1.516	2.028

NOTES:
1. Style S uses class 2 fittings which are made from a combination of aluminum and CRES.
2. Dimension “F” is measured across the corners.
3. Dimensions “J (max)” and “T (max)” are installation dimensions and not design dimensions.

FIGURE 15. Style S hose assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:22Z
Check the source to verify that this is the current version before use.

Hose assembly dimensions for style T: See figure 16.




Fitting ends		Hose size	Dimensions								
1	2		A (ref)	C (max)	D (max)	E (max)	F (max)	G (min)	G (max)	M (max)	P (max)
45°	Straight	8	.438	.880	1.722	1.332	1.014	.445	.632	1.560	.875
		10	.515	.967	2.037	1.488	1.158	.501	.688	1.570	1.000
		12	.570	1.122	2.368	1.667	1.447	.564	.775	1.640	1.250
		16Z	.620	1.480	2.583	1.879	1.736	.609	0.857	1.750	1.500
		20Z	.640	1.750	2.946	2.058	2.328	.697	1.017	1.990	1.844
		24Z	.765	2.150	3.210	2.400	2.621	.785	1.127	2.260	2.125

NOTES:
1. Style T uses class 2 fittings which are made from a combination of aluminum and CRES.
2. Dimension “F” is measured across the corners.
3 Dimension “E (max)” is an installation dimension and not a design dimension.

FIGURE 16. Style T hose assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:22Z
Check the source to verify that this is the current version before use.

Hose assembly dimensions for style U: See figure 17.




Fitting ends		Hose size	Dimensions (see note 2)								
1	2		A (ref)	C (max)	F (max)	H (max)	J (max)	K (min)	K (max)	M (max)	P (max)
90°	Straight	8	.438	.880	1.014	2.495	1.938	.810	1.092	1.560	.875
		10	.515	.967	1.158	2.955	2.340	1.056	1.341	1.570	1.000
		12	.570	1.122	1.447	3.705	2.722	1.341	1.591	1.640	1.250
		16	.620	1.480	1.736	4.100	3.075	1.465	1.840	1.750	1.500
		20	.640	1.750	2.328	4.835	3.637	1.747	2.233	1.990	1.844
		24	.765	2.150	2.621	5.480	4.212	1.997	2.372	2.260	2.125

NOTES:
1. Style U uses class 2 fittings which are made from a combination of aluminum and CRES.
2. Dimension “F” is measured across the corners.
3. Dimension “J (max)” is an installation dimension and not a design dimension.

FIGURE 17. Style U hose assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:22Z
Check the source to verify that this is the current version before use.

Hose assembly dimensions for style V: See figure 18.



Fitting ends		Hose size	Dimensions											
1	2		A (ref)	C (max)	D (max)	F (max)	H (max)	J (max)	K (min)	K (max)	N (max)	P (max)	R (min)	R (max)
90°	45°	8	.438	.880	1.722	1.014	2.495	1.938	.810	1.092	.606	.875	.303	.428
		10	.515	.967	2.037	1.158	2.955	2.340	1.056	1.341	.658	1.000	.340	.465
		12	.570	1.122	2.368	1.447	3.705	2.722	1.341	1.591	.789	1.250	.433	.558
		16	.620	1.480	2.583	1.736	4.100	3.075	1.465	1.840	.929	1.500	.470	.657
		20	.640	1.750	2.946	2.328	4.835	3.637	1.747	2.233	1.020	1.844	.534	.721
		24	.765	2.150	3.210	2.621	5.480	4.212	1.997	2.372	1.186	2.125	.589	.839

NOTES:
1. Style V uses class 2 fittings which are made from a combination of aluminum and CRES.
2. Dimension “F” is measured across the corners.
3 Dimensions “J (max)” and “N (max)” are installation dimensions and not design dimensions.

FIGURE 18. Style V hose assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:22Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Hose shall be in accordance with MIL-DTL-32435.

Hose assembly size code: See table I.

TABLE I. Hose assembly size code.

Size code	Size	Reference tube OD
H	8	.500
J	10	.625
K	12	.750
M	16Z	1.000
N	20Z	1.250
P	24Z	1.500

Fittings: The swivel nut and cone seat shall mate with SAE-AS33514 fitting. The swivel nut threads shall be in accordance with SAE-AS8879. The swivel flange shall be in accordance MS20756.

Elbow fittings: The ovality of the circular cross section within the angle of the bend of the end fitting elbow shall not exceed 7.5% of the nominal tubing OD (see table II).

TABLE II. Elbow fitting ovality. 1/


Assembly size	8	10	12	16	20	24
Ball diameter	.313	.391	.515	.750	.969	1.188

1/ The fitting elbow bend shall be examined for ovality by rolling a ball of applicable diameter through the elbow fitting. The ball shall pass freely through the fitting elbow bend.

Assembly classification: Class 1 and class 2 hose assemblies, as specified in MIL-DTL-32434, have been incorporated into the Part or Identifying Number (PIN) as a part of styles.

Angular alignment: Hose assemblies with elbow fittings on each end shall have the angular orientation between the elbows measured counter-clockwise from the centerline of the nearest fitting, positioned at six-o'clock, to the centerline of the other fitting (see figure 19). When applicable, the angular alignment shall be expressed in three digits and specified in the PIN.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:22Z
Check the source to verify that this is the current version before use.



NOTE: Angular alignment shall be measured in degrees with a tolerance of ±2°.

FIGURE 19. Measurement of angular alignment between elbow fittings.

Protective sleeve: If required, the hose assembly shall include a protective sleeve (see table III) and its code shall be included in the PIN. Fire protective sleeve shall be subjected to testing in accordance with MIL-DTL-32434.

Protective sleeve code: See table III.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:22Z
Check the source to verify that this is the current version before use.

TABLE III. Protective sleeve code.

Code	Type
Blank	None
A	SAE-AS1072 sleeve, fire protection, silicone covered, temperature ranging from -65°F to 450°F and intermittently to 500°F, secured with CRES bands as required. 1/
B	SAE-AS1073 - code B sleeve, abrasion protection, heat shrinkable, black polyolefin, temperature ranging from -65°F to 250°F.
C	SAE-AS1291 - code A sleeve, chafe guard, extruded seamless white PTFE, temperature ranging from -65°F to 450°F, secured with CRES bands as required.
D	SAE-AS1291 - code C sleeve, chafe guard, extruded seamless transparent FEP, temperature ranging from -65°F to 350°F, secured with CRES bands as required.
E	SAE-AS1298 sleeve, heavy wall chafe guard, extruded seamless black PTFE, temperature ranging from -65°F to 450°F, secured with CRES bands as required.
L	Lock-wire hole
F	Code A + L
G	Code B + L
H	Code C + L
J	Code D + L
K	Code E + L


1/ To prevent wicking of fluids, the cut ends of the fire protective sleeve (code A) shall be coated with Room Temperature Vulcanized (RTV) silicone rubber prior to installation. After installation, cracks and voids in the fire protective sleeve shall be coated with RTV rubber to prevent exposure of fiberglass.

Assembly length: Hose assembly shall be furnished in lengths as specified in the contract or purchase order (see figures 1 through 18); however, tolerances on the length of each hose assembly shall be as follows:

a. ±1/8 inch for lengths under 18 inches.
b. ±1/4 inch for lengths from 18 inches to 36 inches.
c. ±1/2 inch for lengths from 36 inches to 50 inches.
d. ±1% for lengths over 50 inches.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:22Z
Check the source to verify that this is the current version before use.

PIN: The PIN consists of letter M, specification sheet number, hose size code, hose length in inches and an eighths of an inch, hose assembly style, sleeve code, and angular alignment in degree between elbow fittings.



Example: M32434/8H082FA030 represents 1/2inch OD PTFE convoluted hose assembly, 8.25 inches long, flare-to-flare permanently attached fittings with fire protective sleeve and 30° angular alignment between elbows

Changes from previous issue: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Referenced documents. In addition to MIL-DTL-32434, this document references the following:

MIL-DTL-32435	SAE-AS1291
MS20756	SAE-AS1298
SAE-AS1072	SAE-AS8879
SAE-AS1073	SAE-AS33514

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:22Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - AV
Navy - AS
Air Force - 99
DLA - CC

Preparing activity:
DLA - CC

(Project 4720-2012-026)

Review activities:
Army - AR, AT, EA, MI
Navy - MC, SA, SH
Air Force - 70

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:22Z
Check the source to verify that this is the current version before use.