MILITARY SPECIFICATION

CARTRIDGE, INITIATOR, M73

This amendment forms a part of Military Specification MIL-C-46618A(MU), dated 15 April 1964 and is approved for use within the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* 2.1 Delete: "MIL-E-5272 . . ." in its entirety.
Delete: "MIL-STD-639 . . ." in its entirety.
Add: "MIL-STD-810 Environmental Test Methods and Engineering Guidelines".

* Add: "2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the document which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

ANSI B46.1 Surface Texture (Surface Roughness, Waviness and Lay)

(Application for copies should be addressed to the American National Standards Institute (ANSI), 1430 Broadway, NY 10018)

(Nongovernment standards and other publications are normally available from the organization which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)"

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer, Naval Ordnance Station, Standardization Branch (5241), Indian Head, MD 20640-5000.

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:28Z
Check the source to verify that this is the current version before use.

PAGE 2

3.4 Delete and substitute

"3.4 Primer. The 72M Primer shall be used. The primer shall conform to the applicable drawing and referenced specification, except that the sensitivity of the primer shall comply with the requirements of 3.4.1. Prior to assembly into a cartridge the primer shall be visually examined and x-rayed."

Add: "3.4.1 Primer sensitivity of primer lot. Prior to assembly into a cartridge, the primer sensitivity of the primer lot shall be such that: the average critical height (H) plus five standard deviations (5S) shall not exceed 12 inches. The average citical height (H) minus two standard deviations (2S) shall not be less that 2 1/2 inches."

* 3.5.1 Delete: ". . . MIL-E-5272, Procedure X11 . . ." and substitute ". . . MIL-STD-810, Method 514.3, Test Procedure I. Test Condition I - 3.2.5 . . .".

3.6.2.1 Delete and substitute

"3.6.2.1 Primer sensitivity. The primer shall fire when drop tested at an energy level of 46 inch ounces in a sectioned cartridge, void of igniter and propellant charge."

PAGE 3

4.2 Change sentence "the sample shall consist of 130 cartridges and . . ." to read "The sample shall consist of 80 cartridge and . . ."

* 4.3.2 Delete: "The Ordnance Standard Finish Blocks prescribed in MIL-STD-639" and substitute: "The roughness comparison standards prescribed in ANSI B46.1"

PAGE 4

4.3.3.2.1 Substitute "50" in place of "100"
Substitute "25" in place of "50"

Add: "4.3.3.2.2 Primer sensitivity of primer lot. The contractor shall provide complete rundown sensitivity test data and results for each lot of primers as objective evidence of compliance with 3.4.1."

PAGE 5

Add: "4.3.3.7 Sealant application. Five cartridges from each production lot shall be selected for this test. Failure of any cartridge to comply with the drawing requirements shall be cause for rejection of the lot cartridges."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:28Z
Check the source to verify that this is the current version before use.

4.4.2.1 Delete and substitute

"4.4.2.1 Primer sensitivity. Remove and discard all powder charges from the test cartridges by sectioning the cartridge around its periphery, 1/2 inch maximum, above the base of the cartridge. Drop test 50 sectioned cartridges from the initial production sample and 25 sectioned cartridges from each production lot sample (all void of powder charge) at 11 1/2 inches, using a steel ball 1 3/16 inches in diameter weighing 3.94 ± .02 ounces, in a primer sensitivity test machine with a cartridge holder approved by the procuring agency. Test shall be made with a drop test firing pin, whose pin contour radius shall be .078 inch minus .002 inch. All firing pin indent centers shall lie within .020 inch of the center of the primer."

* 4.4.4 Delete: ". . . MIL-E-5272, Procedure X11 . . ." and substitute ". . . MIL-STD-810, Method 514.3, Test Procedure I. Test Condition I - 3.2.5 . . .".

Add: "4.4.6 Sealant application. The cartridge shall be disassembled in such a manner that determination can be made that the sealant has been applied for the full length of the joining surfaces at the junction of the cartridge head and case sidewall and that the propellant cavity is free of sealant."

Changes from previous issue. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evalute the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue."

Preparing activity:
Navy - OS
Project No. 1377-N844

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:28Z
Check the source to verify that this is the current version before use.