MILITARY SPECIFICATION

DELAY ELEMENT, CARTRIDGE: M5 ASSEMBLY

This amendment forms a part of MIL-D-46634A(OS), dated 14 March 1974, and is approved for use by the Naval Sea Systems Command, Department of the Navy and is available for use by all department and agencies of the Department of Defense.

PAGE 1

Paragraph 2.1, under "SPECIFICATIONS", delete "MIL-E-5272", "MIL-P-46994" and their titles. Add "MIL-A-8625 Anodic Coatings, for Aluminum and Aluminum Alloys".

Paragraph 2.1, under "STANDARDS", add "MIL-STD-810C Environmental Test Methods".

PAGE 2

Paragraph 3.3, delete "MIL-E-5272, Procedure XII" and substitute "MIL-STD-810C, Method 514.2, Procedure I, Curve D, Sweep between 5-500H_z".

PAGE 10

Paragraph 4.3.3.1, line 3, delete "Table IV or V" and substitute "Table III or IV".

Paragraph 4.3.3.1, line 4, delete "MIL-C-60539" and substitute "MIL-A-8625".

Paragraph 4.3.3.2, last line, delete "MIL-E-5272, Procedure XII" and substitute "MIL-STD-810C, Method 514.2, Procedure I, Curve D, Sweep between 5-500H_z".

Preparing activity:

Navy - OS
(Project 1377-N942)

AMSC N/A FSC 1377

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:31Z
Check the source to verify that this is the current version before use.