INCH-POUND

MIL-P-46636D (AR)
14 September 1995

SUPERSEDING
MIL-P-46636C (AR)
26 September 1973

MILITARY SPECIFICATION

PROJECTILE, 20MM, HIGH PRESSURE TEST, M54A1

This specification is approved for use by the U.S. Army Armament, Research, Development, and Engineering Center, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements, examinations and high pressure test projectile for use in Cartridge, 20MM, HPT, M54A1.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

TT-C-490	-	Cleaning Methods and Pretreatment of Ferrous Surfaces for Organic Coatings

Benefical comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document, should be addressed to: Commander, U.S. Army ARDEC, ATTN: SMCAR-BAC-S, Picatinny Arsenal, New Jersey 07806-5000 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:32Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specifications for

STANDARDS

MILITARY

MIL-STD-651 - Visual Inspection Standards for 20MM Ammunition and Components
MIL-STD-1168 - Lot Numbering of Ammunition
MIL-STD-1169 - Packaging, Packing and Marking for Shipment of Inert Ammunition Components

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the DODSSP - Customer Service, Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS (see 6.4)

US ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

Product and Packaging Drawings

7258816 - Blank, Rotating Band
7258859 - Projectile, 20mm, High Pressure Test, M54A1
7258860 - Body, Projectile, 20mm, High Pressure Test, M54A1
7258861 - Carton, for Interplant Shipment of Projectiles, 20mm, Assemblies and Metal Parts Assemblies (200)
7259136 - Shipping Container for Inert Projectile, 20MM Assemblies and Metal Parts Assemblies (10,000)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:32Z
Check the source to verify that this is the current version before use.

Inspection Equipment Drawings

7259353	-	Go, Flat Plug Gage, Special
7259419	-	Band Tightness Tester
7259434	-	Scale
7259467	-	Comparator, Optical, Hand Type
7259536	-	Not Go, Flat Plug Gage, Special
7259545	-	Operating Instructions (Band Tester)
7259638	-	Gage, Indicator
7259678	-	Gage, Indicator
7259718	-	Optical Gaging Chart
8655592	-	Go, Ring Gage, Special
8657201	-	Optical Gaging Chart
11075045	-	Gage, Snap, Progressive
11075046	-	Block, Setting
11075092	-	Gage, Ring, Plain, Go, Special
11075094	-	Gage, Snap, Go, Special

(Copies of other Government documents, drawings, and publications required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

American Society for Testing and Materials (ASTM)
ASTM B117 - Standard Method of Salt Spray (Fog) Testing

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:32Z
Check the source to verify that this is the current version before use.

this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained. (See contract provisions for additional precedence criteria.)

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with the applicable drawings and specifications.

3.2 Components and assemblies. The components and assemblies shall comply with all requirements specified on Drawing 7258859, all associated drawings, and with all requirements specified in applicable specifications.

3.3 First article. When specified in the contract or purchase order (see 6.2), a sample shall be subjected to first article inspection in accordance with the technical provisions herein (see 4.3).

3.4 Banding. The rotating band blank and the rotating band seat shall be clean at the time of banding. Shot or sandblasting shall not be used to clean the rotating band seat after knurling. The rotating band blank shall fill the band seat.

3.5 Protective coating.

3.5.1 Phosphate coating. The pretreatment cleaning process shall be in accordance with the applicable requirements of Dwg. 7258859. The phosphate coating shall be in accordance with the requirements of TT-C-490 for appearance and minimum weight as applicable to the type of phosphate coating used. Test specimens (panels) shall be in accordance with the requirements of TT-C-490.

3.5.2 Paint coating. The exterior coating of the projectile shall be in accordance with applicable requirements of Dwg. 7258859. The exterior paint adhesion shall be in accordance with applicable requirements of TT-C-490.

3.5.3 Corrosion resistance. The exterior painted surface of the projectile shall show no evidence of corrosion (red rust) after exposure to a 5 percent solution of atomized salt spray for 24 hours.

3.6 Workmanship. The requirements for workmanship are as specified on the applicable drawings, referenced specifications and the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:32Z
Check the source to verify that this is the current version before use.

3.6.1 Processing defects. The projectile shall be free of defects, such as dents, deep scratches, cuts, excessive surface roughness, metal flaws, burrs, sharp edges, and other forms of substandard workmanship.

3.6.2 Cleanliness. The projectile shall be free of all foreign matter.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of Sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 General provisions. Unless otherwise specified herein, the provisions of MIL-A-48078 apply and form a part of this specification.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).

b. Quality conformance inspection (see 4.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:32Z
Check the source to verify that this is the current version before use.

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the assemblies, components and test specimens listed below in the quantities indicated.

Part Description	Drawings	Quantity	Method Para
Standard test panels		3	4.5.2
Rotating bands	7258816	32	4.4.2.1
Projectile bodies	7258860	125	4.4.2.2
Projectile (uncoated)	7258859	125	4.4.2.3
Projectile (painted)	7258859	170	4.4.2.4

Note: The projectile, Dwg. 7258859, shall be identified in accordance with MIL-STD-1168.

4.3.2 Inspections to be performed. As determined by the Government, the first article assemblies, components and test specimens may be subjected to any or all of the examinations and tests specified in Table I of this detail specification and be inspected for compliance with any or all requirements of the applicable drawings.

4.3.3 Rejection. If any assembly, component or test specimen fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate inspection upon any failure of an assembly, component or test specimen to comply with any of the requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:32Z
Check the source to verify that this is the current version before use.

TABLE I. First Article Inspection

CLASSIFICATION OF CHARACTERISTICS

MIL-P-46636D

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
	Projectile, 20MM, HPT, M54A1	1 OF 1	SEE BELOW
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Rotating Bands - Dwg. 7258816			
	Examination for defects	32	3.2	4.4.2.1
	Body, Projectile - Dwg. 7258860			
	Examination for defects	125	3.2	4.4.2.2
	Projectile (uncoated) - Dwg. 7258859			
	Examination for defects	125	3.2	4.4.2.3
	Phosphate Coating			
	Standard test panels (or specimens)	3	3.5.1	4.5.2
	Projectile (painted) - Dwg. 7258859			
	Examination for defects	170	3.2	4.4.2.4
	Band tightness	125	3.4	7259419/4.5.1
	Paint adhesion	13	3.5.2	4.5.3
	Corrosion resistance	32	3.5.3	4.5.4

NOTES:

AMSMC Form 1570b-E, 1 Jul 89 Replaces AMSMC Form 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:32Z
Check the source to verify that this is the current version before use.

4.4 Quality Conformance Inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examinations and tests.

a. Classification of characteristics. Quality conformance examinations and tests are specified in the following Classification of Characteristics paragraphs. The contractor's quality program or detailed inspection system shall provide assurance of compliance of all characteristics with the applicable drawing and specification requirements utilizing as a minimum the conformance criteria specified. When cited herein, attributes sampling inspection shall be conducted in accordance with Table II below, using the inspection levels stated in the Classification of Characteristics paragraphs.

TABLE II. Attributes sample inspection.

Lot Size	Inspection Levels			
	I	II	III	IV
2 to 8	*	*	*	*
9 to 15	*	*	*	13
16 to 25	*	*	*	13
26 to 50	*	*	32	13
51 to 90	*	*	32	13
91 to 150	*	125	32	13
151 to 280	*	125	32	32
281 to 500	*	125	32	32
501 to 1200	*	125	80	50
1201 to 3200	1250	125	80	50
3201 to 10000	1250	125	125	50
10001 to 35000	1250	315	125	80
35001 to 150000	1250	315	125	80
150001 to 500000	1250	500	200	125
500001 and over	1250	500	200	125

Numbers under inspection levels indicate sample size; asterisks (*) indicate one hundred percent inspection. If sample size exceeds lot size, perform one hundred percent inspection. Accept on zero and reject on one or more for all inspection levels.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:32Z
Check the source to verify that this is the current version before use.

b. Alternative quality conformance provisions. Unless otherwise specified herein or provided for in the contract, alternative quality conformance procedures, methods or equipment, such as statistical process control, tool control, other types of sampling plans, etc., may be used by the contractor when they provide, as a minimum, the level of quality assurance required by the provisions herein. Prior to applying such alternative procedures, methods or equipment, the contractor shall describe them in a written proposal submitted to the Government for evaluation (see 6.7). When required, the contractor shall demonstrate that the effectiveness of each proposed alternative is equal to or better than the specified quality conformance provisions(s) herein. In case of dispute as to whether the contractor's proposed alternative(s) provides equivalent assurance, the provisions of this specification shall apply. All approved alternative provisions shall be specifically incorporated into the contractor's quality program or inspection system, as applicable.

c. MIL-STD-651 shall apply in defining and evaluating visual defects.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:32Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-P-46636D

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	Rotating Band Blank	1 OF 1	7258816
			NEXT HIGHER ASSEMBLY: 7258859

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101.	Foreign matter	III	3.6.2	Visual
102.	Defective metal, including lamination	III	3.2	Visual
103.	Incomplete or deformed	III	3.2	Visual 1/
Minor				
201.	Width, max.	IV	3.2	11075094
202.	Evidence of poor workmanship	IV	3.6	Visual

NOTES:

1/ A rotating band blank which is deformed or is judged to lack sufficient metal in any part of its width or thickness to provide for complete band seat fill and minimum rotating band profile dimensions, shall be classed defective.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:32Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-P-46636D

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.2	Body, Projectile, 20mm, HPT, M54A1	1 OF 1	7258860
			NEXT HIGHER ASSEMBLY: 7258859

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101.	Knurling missing or incomplete	III	3.2	Visual
102.	Depth, knurling, min.	III	3.2	Visual/7259678 1/
103.	Foreign matter in rotating band seat	III	3.4	Visual
Minor				
201.	Width, rotating band seat	IV	3.2	7259353/7259536
202.	Diameter, rotating band seat (knurled)	IV	3.2	Gage 2/
203.	Width, knurling, min.	IV	3.2	Visual/7259467 1/
204.	Length, nose to rear edge of rotating band seat	IV	3.2	Gage
205.	Evidence of poor workmanship	IV	3.6, 3.6.1, 3.6.2	Visual

NOTES:

1/ Measurement of knurling for compliance with the minimum depth and width requirements shall apply where visual inspection indicates that the depth or width dimension is borderline.

2/ Gage, Snap - (Anvils, .170 min. width)
(Go .680) .6796 - .0004
(Not Go .662) .6620 + .0004

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:32Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.3	Projectile, 20mm, HPT, M54A1 (uncoated)	1 OF 2	7258859
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined.			
Major				
101.	Diameter, bourrelet, min.	III	3.2	Gage 1
102.	Diameter, body, rear of rotating band	III	3.2	11075092/Gage 2/
103.	Diameter, rotating band	III	3.2	Gage 3/
104.	Runout, rotating band with datum surface	III	3.2	Gage
105.	Runout, body, rear of rotating band, with datum surface	III	3.2	Gage
106.	Length, nose to rear edge of rotating band	III	3.2	7259638/11075046
107.	Location, crimp groove	III	3.2	Compar/20X/8657201
108.	Profile, crimp groove	III	3.2	Compar/20X/8657201
109.	Radius, rear edge of crimp groove, max.	III	3.2	Comparator/50X
110.	Width, rotating band	III	3.4	Compar/20X/8657201
111.	Void, junction rotating band and body	III	3.2	Visual
112.	Crack or split in body	III	3.2	Visual

NOTES:

1/ Snap gage - (Not Go .782) .7820 + .0001
2/ Snap gage - (Not go .765) .7650 + .0003
3/ Ring gage - (Go .828) .8278 - .00012
Snap gage - (Not Go .824) .8240 + .0002

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:32Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.3	Projectile, 20mm, HPT, M54A1 (uncoated)	2 OF 2	7258859
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Minor				
201.	Total length	IV	3.2	11075045
202.	Diameter, bourrelet, max.	IV	3.2	Gage 4/
203.	Mutilated	IV	3.2	Visual
204.	Depth and width of undercut, front and rear of rotating band, max.	IV	3.2	Comparator/31.25X/ 7259718
205.	Finish improper	IV	3.2	Visual
206.	Base radius missing	IV	3.2	Visual
207.	Evidence of poor workmanship	IV	3.6	Visual

NOTES:

4/ Ring gage - (Go .784) .78390 - .00007

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:32Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-P-46636D

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4	Projectile, 20mm, HPT, M54A1 (painted)	1 OF 1	7258859
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined.			
Major				
101.	Diameter, bourrelet, max.	III	3.2	8655592
102.	Weight	III	3.2	Balance/7259434
103.	Rotating band damaged	III	3.2	Visual
Minor				
201.	Paint not dry	IV	3.2	Manual
202.	Paint inadequate	IV	3.2	Visual
203.	Paint on rotating band	IV	3.2	Visual
204.	Marking incorrect, incomplete, illegible or missing	IV	3.2	Visual
205.	Foreign matter on exterior	IV	3.2	Visual
206.	Evidence of poor workmanship	IV	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:32Z
Check the source to verify that this is the current version before use.

4.4.3 Tests. The tests listed in Table III shall be conducted on each lot in compliance with the methods of inspection prescribed in 4.5. The samples shall be selected in such a manner as to be representative of the entire lot. The sample size and acceptance criteria for each test shall be as specified.

TABLE III

Test		Sample Size	Item	Rqmt Para
Band tightness/7259419	1/	315	Projectile, painted (See 4.5.1)	3.4
Phosphate coating (appearance & weight)	2/	3	Projectile, before painting/or standard panels TT-C-490 (See 4.5.2)	3.5.1
Paint adhesion	3/	13	Projectile, painted TT-C-490 (See 4.5.3)	3.5.2
Corrosion resistance	4/	32	Projectile, painted (See 4.5.4)	3.5.3

1/ If two or more units of the sample have an average radial void between the seated band and the band seat, greater than 0.004 inch, the lot shall be rejected. If one unit of the sample has an average radial void, greater than 0.004 inch, a second sample consisting of the same number of units as specified for the first sample shall be tested. If in the accumulated samples, two or more units have an average radial void greater than 0.004 inch, the lot shall be rejected.

2/ Failure of the phosphate coating on the sample projectiles or standard panels to comply with the applicable requirements shall cause rejection of all production projectile metal parts phosphated since the preceding test. (See 3.5.1)

3/ If two or more units of the sample fail to comply with the requirement for paint adhesion, the lot shall be rejected. If one unit of the sample fails to comply with the requirement, a second sample consisting of the same number of units as specified for the first sample shall be tested. If in the accumulated samples, two or more units fail to comply with the requirement for paint adhesion, the lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:32Z
Check the source to verify that this is the current version before use.

4/ If two or more units of the sample fail to comply with the corrosion resistance requirement, the lot shall be rejected. If one unit fails to comply with the same requirement, a second sample consisting of the same number of units as specified for the first sample shall be tested. If in the accumulated samples, two or more units fail to comply with the corrosion resistance requirement, the lot shall be rejected.

4.4.4 Packaging, packing and marking inspection. Inspection for packaging, packing and marking shall comply with Dwg. 7258861 or Dwg. 7259136 and MIL-STD-1169.

4.4.5 Inspection equipment. The inspection equipment required to perform the inspections specified herein is identified in the "Inspection Method Reference" column of the Classification of Characteristics listings starting with 4.4.2.1. Contractor inspection equipment designs shall be submitted for Government approval as specified in the contract. Designs which provide variable measurements instead of attributes data are preferred in order to facilitate the use of statistical process control. See MIL-A-48078 and 6.3 herein.

4.5 Methods of inspection.

4.5.1 Band tightness. The method of test shall comply with all requirements of the operating instructions for the band tightness tester Dwg. 7259419. The inspection sample shall be cycled through the tester to determine compliance with the rotating band tightness requirement. The total measurement of radial void registered on the tester indicator at final ram pressure, shall be divided by four (number of indentors) to determine the average radial void.

4.5.2 Phosphate coating. The method of test shall be as prescribed in TT-C-490 for the type of coating used (see Dwg. 7258859). The prescribed sample projectiles or standard panels shall be processed at the start of daily production and at 4-hour intervals, maximum thereafter. Appearance and weight of the coating shall be recorded.

4.5.3 Paint adhesion. The method of test shall be as prescribed in TT-C-490. The test shall be made on the exterior painted surface of each projectile metal part of the sample forward of the rotating band. Visible exposure of underlying phosphate coating or ferrous metal on any unit of the sample, as a result of the test, shall be recorded as a defect.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:32Z
Check the source to verify that this is the current version before use.

4.5.4 Corrosion resistance. The method of test shall be as prescribed in American Society for Testing and Materials (ASTM), ASTM B117. The paint shall not be disturbed, however, the rotating band and unpainted surfaces of the sample projectile metal part may be masked out by a wax coating or other suitable material. The salt spray solution and exposure time shall be as specified in 3.5.3.

5. PACKAGING

5.1 Preservation and packaging. The projectiles shall be preserved and packaged in accordance with Dwg. 7258861 or Dwg. 7259136, as directed by the procuring activity.

5.2 Packing. The projectiles shall be preserved and packaged as specified in 5.1. Each lot shall be packed for shipment in accordance with Dwg. 7258861 or Dwg. 7259136, as directed by the procuring activity.

5.3 Marking. Marking or labeling of packed cartons shall comply with applicable requirements of MIL-STD-1169.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The component covered by this specification is intended for use with Cartridge, 20MM, HPT, M54A1.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number and date of this specification.

b. Issue of DODISS to be cited in the solicitation, and, if required, the specific issue of individual documents referenced (see 2.1.1).

c. Requirements for submission of first article sample.

d. Applicable stock number.

e. Packaging requirements, if other than specified in Section 5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:32Z
Check the source to verify that this is the current version before use.

f. Serialization requirements, if applicable.

g. Certificate of conformance for each lot or shipment of product.

6.3 Submission of contractor inspection equipment designs for approval. Submit copies of designs as required to: Commander, U.S. Army ARDEC, ATTN: AMSTA-AR-QAC-C, Picatinny Arsenal, NJ 07806-5000. This address will be specified on the Contract Data Requirements List, DD Form 1423 in the contract.

6.4 Process deviation. A process deviation is defined as a change in the approved basic method of manufacture, or an operational change which alters the metallurgical or physical properties of the item.

6.5 Intermediate point inspection. The classification of defects identifies the defect characteristics (among other things) for acceptance inspection. It may be necessary to modify the sequence of inspection stations to best suit the manufacturing process. Inspection for defect characteristics which will be hidden or altered by subsequent processing operatons (including unrelated operations), should be scheduled to prevent premature acceptance which would be detrimental to the attainment of optimum product quality of the end item.

6.6 Drawings. Drawings listed in Section 2 of this specification under the heading U.S. Army Armament, Research, Development and Engineering Center (ARDEC) may also include drawings prepared by, and identified as U.S. Army Armament, Research and Development Command (ARRADCOM), Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under cognizance of ARDEC.

6.7 Submission of alternative quality conformance provisions. All contractor proposed alternative quality conformance provisions will be submitted to the Government for evaluation/approval as directed by the contracting activity.

6.8 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
Army-AR

Preparing Activity:
Army-AR

(Project 1305-0124)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:32Z
Check the source to verify that this is the current version before use.