MILITARY SPECIFICATION

PRIMER, PERCUSSION, M23A2
PARTS FOR

1. SCOPE

1.1 This specification covers the parts for one type of Percussion Primer designated as Percussion Primer, M23A2.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-2550 - Ammunition and Special Weapons; General Specification For

MIL-P-10025 - Packaging, Packing and Marking for Interplant Shipment of Inert Ammunition, General Specification For

MIL-I-45208 - Inspection Requirements, General Specification for

MIL-I-45607 - Inspection Equipment, Supply and Maintenance of

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.

MIL-STD-109 - Inspection Terms and Definitions.

Source: https://assist.dla.mil -- Downloaded: 2025-10-22T04:32Z
Check the source to verify that this is the current version before use.

DRAWINGS

ORDNANCE CORPS

8831162 - Disc, Closing
8831163 - Head
8838012 - Cup, Battery
8838015 - Plug, Firing

PUBLICATIONS

ORDNANCE CORPS

ORD-M608-11 - Procedures and Tables for Continuous Sampling by Attributes
IEL 7298944 - Index of Inspection Equipment Lists.

(Copies of specifications, standards, drawings and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

3. REQUIREMENTS

3.1 Material.-Materials shall be in accordance with applicable drawings and specifications.

3.2 Parts.-The parts shall comply with all requirements specified on Drawings (dwgs.) 8831162, 8831163, 8838012 and 8838015 as applicable and with all requirements specified in applicable specifications.

3.3 Workmanship.-All parts shall be free of chips, dirt, grease, rust and other foreign material. The cleaning method shall not be injurious to any of the parts nor shall the parts be contaminated by the cleaning agent. The onion skin closing discs shall be of the required diameter and thickness and shall be free from tears, wrinkles and perforations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:32Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 General quality assurance provisions.-The supplier is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. Inspection records of the examinations and tests shall be kept complete and available to the Government as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements. Reference shall be made to Standard MIL-STD-109 in order to define terms used herein. The provisions of Specification MIL-A-2550 shall apply.

4.1.1 Contractor quality assurance system.-The contractor shall provide and maintain an effective quality assurance system in compliance with the requirements of Specification MIL-I-45208.

4.1.2 Submission of product.-At the time the completed lot of product is submitted to the Government for acceptance the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all quality assurance provisions of the approved current written description of the system.
b. Number of units of product inspected.
c. Results obtained for all inspection performed.
d. Drawing, specification number and date, together with an identification and date of changes.
e. Certificates of analysis on all material procured directly by the contractor when such material is controlled by Government specifications referenced in any of the contractual documents.
f. Number of items in the lot.
g. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:32Z
Check the source to verify that this is the current version before use.

his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.1.3 Government verification.-Using the contractor's written quality assurance procedure, this detail specification, the applicable drawings and other contractual documents as a guide, the Government inspector shall verify at unscheduled intervals all quality assurance operations performed by the contractor. Verification will be in accordance with Specification MIL-I-45208 and will be performed to the extent necessary to assure compliance with the contractual requirements. Severity of Government inspection of individual characteristics will be directly related to the seriousness of the classification assigned. In no instance will a characteristic classified "critical" be accepted solely on the basis of the contractor's records.

4.2 Initial production.

4.2.1 Submission.-The contractor shall submit an initial production sample consisting of 20 consecutively produced complete sets of parts (i.e. 20 each of every individual component) which have been produced by the production process which the contractor will use in fulfilling the contract, to a Government-approved facility designated by the contracting officer. All parts and materials shall be obtained from the same source of supply as will be used in regular production. The initial production sample shall also be submitted whenever a change occurs in manufacturing process, material used, drawing, specification or source of supply such as to significantly affect product uniformity as determined by the Government.

4.2.2 Inspections to be performed.-Each component shall be inspected by the Government for all the inspections specified in 4.3 of this specification and for all requirements of the applicable drawings.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:32Z
Check the source to verify that this is the current version before use.

4.2.3 Rejection.-If any component fails to comply with the applicable requirements the initial production sample shall be rejected and the contractor shall take the necessary corrective action and submit a new initial production sample or portion thereof as specified by the contracting officer. The contractor shall continue to submit new or supplemental quantities as necessary until such time as the sample successfully passes the inspection specified, or until otherwise directed by the contracting officer.

4.3 Inspection provisions.

4.3.1 Lot formation.-A lot shall consist of parts produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification, and same specification revision. Drawing, specification, and process changes not affecting safety, performance or fit, as determined by the Government shall not necessitate changing the lot number.

4.3.2 Examination.-Sampling plans and procedures for the following classifications of defects shall be in accordance with Standard MIL-STD-105 except that inspection for critical defects, when listed, shall be 100 percent. Continuous sampling plans in accordance with Handbook ORD-M608-11 may be used if approved by the procuring activity. Also, at the option of the procuring activity, AQL's and sampling plans may be applied to the individual characteristics listed using an AQL of 0.25 percent for each major defect and an AQL of 0.40 percent for each minor defect. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.3.3.

4.3.2.1 Plug, firing (see dwg. 8838015)

Categories	Defects	Method of Inspection	Code No 01 (see 6.3)
Critical:	None defined		
Major:	AQL 0.40 percent		
101.	Large diameter minimum (min.)	Gage	01001
102.	Length and profile of point	Gage	01002
103.	Total length	Gage	01003
104.	Length of pilot (min.)	Gage	01004

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:32Z
Check the source to verify that this is the current version before use.

Minor:	AQL 2.50 percent		
201.	Large diameter maximum (max.)	Gage	01005
202.	Length of pilot (max.)	Gage	01006
203.	Diameter of pilot	Gage	01007
204.	Finish improper	Visual	01008
205.	Evidence of poor workmanship (see 3.3)	Visual	01009

4.3.2.2 Cup, Battery (see dwg. 8838012)

Categories	Defects	Method of Inspection	Code No 02
Critical:	None defined		
Major:	AQL 0.40 percent		
101.	Outside diameter (min.)	Gage	02001
102.	Thickness thru bottom (max.)	Gage	02002
103.	Length	Gage	02003
Minor:	AQL 2.50 percent		
201.	Diameter of hole	Gage	02004
202.	Thickness thru bottom (min.)	Gage	02005
203.	Inside diameter	Gage	02006
204.	Outside diameter (max.)	Gage	02007
205.	Flat missing from surface at open end	Visual	02008
206.	Evidence of poor workmanship (see 3.3)	Visual	02009

4.3.2.3 Head (see dwg. 8831163)

Categories	Defects	Method of Inspection	Code No 03
Critical:	None defined		
Major:	AQL 1.00 percent		
101.	Small outside diameter (max.)	Gage	03001
102.	Large outside diameter under flange	Gage	03002
103.	Diameter of battery cup cavity	Gage	03003
104.	Diameter of percussion element cavity	Gage	03004

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:32Z
Check the source to verify that this is the current version before use.

105.	Depth of percussion element cavity	Gage	03005
106.	Thickness of flange max	Gage	03006
107.	Crack or split	Visual	03007
108.	Flash hole missing or obstructed	Visual	03008
Minor:	AQL 6.50 percent		
201.	Diameter of flange	Gage	03009
202.	Depth of battery cup cavity	Gage	03010
203.	Small outside diameter (min.)	Gage	03011
204.	Concentricity between percussion element cavity and flash hole	Gage	03012
205.	Concentricity of percussion element cavity with outside diameter under flange	Gage	03013
206.	Concentricity of flange with outside diameter under flange	Gage	03014
207.	Diameter of chamfer at mouth of percussion element cavity	Gage	03015
208.	Diameter of flash hole	Gage	03016
209.	Length of small outside diameter	Gage	03017
210.	Total length	Gage	03018
211.	Depth of large (charge) interior cavity	Gage	03019
212.	Diameter of and profile of large (charge) interior cavity	Gage	03020
213.	Thickness of flange, min	Gage	03021
214.	Diameter of large (charge) interior cavity counterbore (prior to crimping 360 degrees)	Gage	03022
215.	Depth of large (charge) interior cavity counterbore after crimping 360 degrees	Gage	03023
216.	Inside diameter at crimped end (after crimping)	Gage	03024
217.	Any required radius missing	Visual	03025
218.	Finish improper	Visual	03026
219.	Evidence of poor workmanship (see 3.3)	Visual	03027

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:32Z
Check the source to verify that this is the current version before use.

4.3.3 Inspection equipment.-Index of inspection equipment lists number 7298944 identifies available approved inspection equipment designs. The contractor may however design alternate inspection equipment in order to facilitate his operation. Designs of any acceptance inspection equipment prepared by the contractor to support his approved written inspection plan (see 4.1.1) shall be approved by the Government prior to fabrication or procuring of such equipment (see 6.2). All acceptance inspection equipment shall be certified by the Government as complying with the approved design prior to its use. Supply and maintenance of inspection equipment shall be in accordance with Specification MIL-I-45607.

5. PREPARATION FOR DELIVERY

5.1 Packing

5.1.1 Packing and marking shall be in accordance with Specification MIL-P-10025.

5.2 Data cards.-Data card information shall be as specified in Specification MIL-A-2550.

6. NOTES

6.1 Ordering data.-Procurement documents should specify the title, number and date of this specification.

6.2 Submission of contractor developed equipment designs.-Documentation of contractor developed equipment designs shall be submitted in duplicate and identified with the associated examination or test required by the Specification to Picatinny Arsenal, Dover, New Jersey, ATTN: ORDBB-ND for approval. The documentation shall include special equipment designs and a complete description of the use and application of all standard devices and set-ups as well as special equipment designs. Design review will normally be accomplished within one month after receipt by Picatinny Arsenal. Partial submission of inspection equipment designs is permissable. However, the Arsenal completion date for design review will be based on the date of the final submission of designs.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:32Z
Check the source to verify that this is the current version before use.

6.3 Inspection code numbers.-The two and five digit code numbers assigned to the inspection herein are to facilitate data collection and analysis by the Government.

Notice.-When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Custodian:
Army-Ordnance Corps

Preparing activity:
Army-Ordnance Corps

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:32Z
Check the source to verify that this is the current version before use.