MIL-P-46651B (PA)
AMENDMENT I
28 December 1973

MILITARY SPECIFICATION

PROPELLANT M30E1
FOR USE IN PROPELLING CHARGE M85 AND XM121
FOR 105MM HOWITZER

This Amendment forms a part of Military Specification MIL-P-46651B (PA) dated 12 May 1966 and is approved for use by all Departments and Agencies of the Department of Defense.

Change "M30E1" to read "M30A1" wherever it appears.

Change "XM121" to read "M121" wherever it appears.

Page 1, Para. 2.1, Add the following:

"SPECIFICATIONS

MILITARY

MIL-A-2550 - Ammunition and Special Weapons; General Specification for

STANDARDS

MILITARY

MIL-STD-1171 - Acceptance and Description Sheets for Propellants and Explosives
MIL-STD-414 - Sampling Procedures and Tables for Inspection by Variables for Percent Defective
MIL-STD-286 - Propellants, Solid: Sampling, Examination and Testing"

Page 2, Para. 2.2, Delete in its entirety and substitute the following:

"2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply.

FSC: 1375

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:34Z
Check the source to verify that this is the current version before use.

CODE OF FEDERAL REGULATIONS

Title 49, Department of Transportation: Parts 0-199

AMC PAMPHLET 706-114

Experimental Statistics, Section 5, Tables

The Code of Federal Regulations is available from the Superintendent of Documents, Government Printing Office, Washington,D.C., 20402. Orders for the above publication should cite: 49 CFR 0-199 (latest revision)."

Page 2, Para 3.2.1, Table I, Delete in its entirety and substitute the following:

"TABLE I
VELOCITY AND PRESSURE

Zone	Charge	Velocity Ft. Per Sec (fps)	Piezo Equivalent Pressure (pep) Pounds Per Square Inch Minimum (min)	Maximum (max)
3	M85	640	4300	6100[1]
3	M121	640	4300	6500[1]
4	M85	804		
6	M85	1408		
6	M121	1408		
7	M121	1800		29000
8	M85	2200	42000	45000

[1] Zone 3 pressure (max) is waived when SP/MP are tested in matched pairs, loaded in matched pairs, and provided Zone 7 or Zone 8 pressures (as appropriate) are accepted.

Source: https://assist.dla.mil -- Downloaded: 202610-22T06:34Z
Check the source to verify that this is the current version before use.

SP=single perforated
MP=multi-perforated"

Page 3, Add the following:

"3.4 Graphite (Glaze). The graphite content shall not exceed 0.2 percent when determined as specified in paragraph 4.3.3."

Page 5, paragraph 4.2.2.1.3, line 3: Delete "four(4)" and substitute "three (3)".

Page 6, Paragraph 4.3.2.2: Delete in its entirety and substitute:

"4.3.2.2 Conditioned rounds (145°F minus 5°F). For information only,a seven round uniformity series shall be fired with rounds conditioned at 145°F. This test will be performed on the first five initial production lots which have been accepted. No more than five minutes shall elapse from the time the round is removed from the conditioning chamber until it is fired."

Page 6, Add the following:

"4.3.3 Graphite (Glaze) determination. The graphite content shall be determined in accordance with Method 308.1 of Standard MIL-STD-286."

Page 6, Para 6.3, Line 5: Delete " SMUPA-ND2" and SMUPA-DC8" and substitute "SARPA-QA-A-P" and "SARPA-ADEP-2."

Custodian:
Army-PA

Preparing Activity:
Army-PA

Project Number: 1375-A092

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:34Z
Check the source to verify that this is the current version before use.