MIL-R-46630B(MU)
23 June 1971
SUPERSEDING
MIL-R-46630A(MU)
9 October 1964

MILITARY SPECIFICATION
REMOVER, AIRCRAFT CANOPY, M1A3, METAL PARTS ASSEMBLY

1. SCOPE

1.1 This specification covers metal parts assembly for Remover, Aircraft Canopy, M1A3. Assembly will ultimately be loaded and used in conjunction with other propellant actuated devices in aircrew emergency escape systems.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids, or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Military

MIL-A-2550 - Ammunition and Special Weapons, General Specification for

STANDARDS

Military

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109 - Quality Assurance Terms and Definitions
MIL-STD-413 - Visual Inspection Guide for Rubber O-Rings

DRAWINGS

Munitions Command

F8593732 - Remover, Aircraft Canopy, M1A3, Metal Parts Assembly
F8797268 - Carton, Packing, Ammunition for Remover, Aircraft Canopy, M1A3
F8797269 - Box, Packing, Ammunition for Remover, Aircraft Canopy, M1A3
IEL-8593732 - Index to Inspection Equipment List for Remover, Aircraft Canopy, M1A3, Metal Parts Assembly

Source: https://assist.dla.mil -- Downloaded: 202610-22T06:31Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, and drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications - The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bid or request for proposal shall apply.

ASA B46.1 - Surface Texture

(Application for copies should be addressed to the American National Standards Institute, 1430 Broadway, New York, N.Y. 10018)

3. REQUIREMENTS

3.1 General - Material, parts and assemblies shall comply with the requirements specified on the applicable drawings and referenced specifications.

3.2 Physical properties - Physical properties required by the drawing shall be uniform throughout the part within specified tolerances. Requirements for all alloy steel parts shall be achieved by quenching and tempering.

3.3 Hydrostatic pressure - The components listed below shall withstand a constant internal pressure as indicated in Table I for 15 seconds, minimum, without application of any external load and shall show no evidence of leakage or mechanical failure (see 6.2).

Table I

Component	Hydrostatic Pressure (psi minimum)
Outside tube	2900
Telescoping tube	2000
Inside tube	2500

3.4 Torque - Torque requirements shall be as specified in Table II. No loosening or deformation shall occur upon application of the breakaway torque.

Table II

Components	A Run-ON (Inch Pounds)	B Seating or Bottoming Including A Inch Pounds	C Breakaway Inch Pounds
Base and outside tube	75 Min	500 + 50	400 Min
Firing head and inside tube	75 Min	---	---
Stop telescoping tube and outside tube			300 Min

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:31Z
Check the source to verify that this is the current version before use.

3.5 Protective finish - Protective finish shall be in accordance with the applicable specifications and drawings and shall apply to all surfaces of the component regardless of configuration.

3.6 Residual magnetism - The metal parts assembly shall not deflect the indicator of the compass more than 3 degrees in either direction when passed in front of the compass at a distance of 6 inches.

3.7 Workmanship - The requirements for workmanship are as specified on the applicable drawings, referenced specifications and the following:

3.7.1 Metal defects - The components shall be free from cracks, splits, cold shuts, inclusions, porosity or similar defects.

3.7.2 Burr - No part shall have a burr which might interfere with the assembly or function of the item or which might be injurious to personnel handling the item.

3.7.3 Foreign matter - No part or assembly shall contain chips, dirt, grease, rust, corrosion or toher foreign matter.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection - Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Quality assurance terms and definitions - Reference is made to MIL-STD-109 to define the quality assurance terms used.

4.1.2 Inspection - Inspection shall be in accordance with MIL-A-2550.

4.2 First Article Sample

4.2.1 Initial production sample - At the beginning of regular production, a sample shall be submitted in accordance with contract requirements and shall consist of 5 metal parts assemblies, 10 sets of unassembled components, for dimensional and visual examination and tests, 50 shear pins from the same lot of shear pins tested by the contractor. The sample shall be manufactured using the same materials, equipment, processes and procedures as used in regular production. All parts and materials including packaging and packing shall be the same as used for regular production and shall be obtained from the same source of supply.

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T06:31Z
Check the source to verify that this is the currentversion before use.

4.2.1.1 Examination and test - After inspection and provisional acceptance at source, the sample shall be inspected for all requirements of the drawings and specifications at a Government Laboratory or such other facility specified in the contract.

4.2.1.2 Initial production sample failure - Failure of the sample to comply with requirements of the drawings and specifications shall result in sample disapproval.

4.3 Inspection provisions

4.3.1 Lot

4.3.1.1 Submission of product - The product shall be submitted in accordance with MIL-STD-105.

4.3.1.2 Size of lot - The lot of metal parts assemblies shall consist of 1200 removers, maximum, provided the homogeneity requirements of inspection lots have been retained. A smaller lot may be shipped upon approval of the contracting officer.

4.3.2 Examination - One hundred percent examination shall be performed for all critical defects. Examination for major and minor defects shall be performed on a defect basis in accordance with the classification of defects contained herein, using the sampling plan and associated criteria in Tables III and IV. For an individual defect (single characteristic) the criteria in Table III shall be used. For total defects within a major or minor group, the criteria in Table IV shall be used. All nonconforming material shall be rejected. Inspection for rubber o-rings shall be in accordance with MIL-STD-413. The roughness comparison specimens prescribed in ASA B46.1 shall be used as a basis of comparison for surface roughness determination. Four power (4X) magnification may be used in performing visual examination for such defects as burr and foreign matter.

TABLE III

Lot Size	Number of Samples	Major		Minor	
		Accept	Reject	Accept	Reject
1 - 300	100% Examination	1	2	2	3
301 - 1,300	110	2	3	3	4
1,301 - 3,200	150	3	4	4	5
3,201 - 8,000	225	3	4	4	5
8,001 - 22,000	300	4	5	5	6

Source: https://assist.dla.mil -- Downloaded: 202610-22T06:31Z
Check the source to verify that this is the current version before use.

Table IV

Total Allowable Defects Per Sample Size				
Sample Sizes for Major Defects	110	150	225	300
No. of Defects in Class				
2 - 3	1	2	3	4
4 - 7	2	3	4	5
8 - 19	3	4	5	7
20 - 43	4	5	8	10
Over 43	6	8	11	14
Sample Sizes for Minor Defects	110	150	225	300
2 - 3	2	3	4	5
4 - 7	3	4	5	7
8 - 16	4	5	8	10
17 - 48	6	8	11	14
Over 48	8	11	17	20

4.3.2.1 Seal, Plain, Dwg. B8593658, a detail of Dwg. F8593732

Defect	Method of Inspection
CRITICAL	
None defined	
MAJOR	
101. Diameter of wire, max.	Measure
102. Outside diameter, min.	Measure
103. Locational variance of ends, max.	Visual
104. Number of coils incorrect	Visual
105. Metal defective	Visual
106. Protective finish inadequate or defective	Visual
107. Burr, sharp edge	Visual
108. Foreign matter	Visual
MINOR	
201. Outside diameter, max.	Measure
202. Length between coils, incorrect	Measure
203. Direction of turn incorrect	Visual
204. Radius or chamfer missing or incorrect	Visual

Source: https://assist.dla.mil -- Downloaded: 202610-22T06:31Z
Check the source to verify that this is the current version before use.

4.3.2.2 Spring, Firing Pin, Dwg. C8593729, a detail of Dwg. F8593732

Defect		Method of Inspection
CRITICAL		
None defined		
MAJOR		
101.	Load at specified heights	Gage
102.	Outside diameter	Gage
103.	Ends incorrect	Measure
104.	Metal defective	Visual
105.	Protective finish inadequate or defective	Visual
106.	Burr, sharp edges and slivers	Visual
107.	Foreign matter	Visual
MINOR		
201.	Closed length, max.	Gage
202.	Diameter of end coils, both ends	Measure

4.3.2.3 Tube, Telescoping, Dwg. D8593734, a detail of Dwg. F8593732

CRITICAL		
None defined		
MAJOR		
101.	Concentricity of body, large end, with datum location	Gage
102.	Diameter of body, large end, min.	Gage
103.	Diameter of body, small end, min.	Gage
104.	Diameter, inside, max.	Gage
105.	Depth of spiral groove	Gage
106.	Depth of spiral groove relief	Gage
107.	Total length, max.	Gage
108.	Variation in wall thickness	Gage
109.	Straightness	Gage
110.	Metal defective	Visual
111.	Protective finish inadequate or defective	Visual
112.	Burr	Visual
113.	Foreign matter	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:31Z
Check the source to verify that this is the current version before use.

4.3.2.3 (Cont'd)

Defect	Method of Inspection
MINOR	
201. Diameter of body, large end, max.	Gage
202. Diameter of body, small end, max.	Gage
203. Diameter, inside, min.	Gage
204. Total length, min.	Gage
205. Length of spiral groove relief, max.	Measure
206. Length of body, large end	Measure
207. Width of spiral groove relief, max.	Measure
208. Location of spiral groove	Measure
209. Number of turns of spiral groove, incorrect	Visual
210. Direction of turn of spiral groove, incorrect	Visual
211. Profile of spiral groove, incorrect	Visual
212. Marking missing, incorrect or illegible	Visual
213. Radius missing or incorrect	Visual
214. Surface finish, improper	Visual

4.3.2.4 Stop, Telescoping Tube, Dwg. C8593786, a detail of Dwg. F8593732

CRITICAL

None defined

MAJOR

101. Pitch diameter of large thread, max.	Gage
102. Minor diameter of large thread, max.	Gage
103. Pitch diameter of small thread, max.	Gage
104. Minor diameter of small thread, max.	Gage
105. Concentricity of bore with pitch diameter of large thread	Gage
106. Concentricity of counterbore with bore	Gage
107. Concentricity of hole on body with hole at flat	Gage
108. True position of threaded holes with hole at flat	Gage
109. True position of hole at flat with bore	Gage
110. Pitch diameter of set screw hole	Gage
111. Location of set screw hole	Gage
112. Diameter of thread undercut, max.	Gage
113. Diameter of hole on flat	Gage
114. Diameter of hole in body	Gage
115. Diameter of body, min.	Gage
116. Diameter of bore, max.	Gage
117. Diameter of counterbore, max.	Gage
118. Depth of thread cavity	Gage
119. Depth of counterbore, max.	Gage
120. Location of hole on flat	Gage
121. Location of flat, min.	Gage
122. Thread damaged or not full	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:31Z
Check the source to verify that this is the current version before use.

4.3.2.4 (Cont'd)

Defect	Method of Inspection
MAJOR (Cont'd)	
123. Metal defective	Visual
124. Protective finish inadequate or defective	Visual
125. Burr or sharp corner	Visual
126. Foreign matter	Visual
MINOR	
201. Pitch diameter of large thread, min.	Gage
202. Pitch diameter of small thread, min.	Gage
203. Diameter of bore, min.	Gage
204. Diameter of body, max.	Gage
205. Diameter of counterbore, min.	Gage
206. Diameter of car seal hole	Gage
207. Depth of flat	Gage
208. Depth of counterbore, min.	Gage
209. Total length	Gage
210. Location of flat, max.	Gage
211. Angular location of car seal hole	Gage
212. Width of thread undercut, max.	Measure
213. Marking missing, incorrect or illegible	Visual
214. Radius and/or chamfer missing or incorrect	Visual
215. Surface finish, improper, except as otherwise classified	Visual

4.3.2.5 Base, Dwg. C8593787, a detail of Dwg. F8593732

CRITICAL	
None defined	
MAJOR	
101. Pitch diameter of thread, max.	Gage
102. Minor diameter of thread, max.	Gage
103. Concentricity of body with pitch diameter of thread	Gage
104. True position of holes with pitch diameter of thread	Gage
105. Diameter of thread undercut, max.	Gage
106. Diameter of body, min.	Gage
107. Thickness of base, min.	Gage
108. Thread damaged or not full	Visual
109. Metal defective	Visual
110. Protective finish inadequate or defective	Visual
111. Burr	Visual
112. Foreign matter	Visual

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T06:31Z
Check the source to verify that this is the currentversion before use.

4.3.2.5 (Cont'd)

Defect	Method of Inspection
MINOR	
201. Pitch diameter of thread, min.	Gage
202. Diameter of body, max.	Gage
203. Diameter of holes	Gage
204. Length of body	Gage
205. Thickness of base, max.	Gage
206. Diameter of flange	Measure
207. Total length	Measure
208. Width of thread undercut, max.	Measure
209. Marking missing, incorrect or illegible	Visual
210. Radius or chamfer missing or incorrect	Visual
211. Surface finish improper	Visual
212. Foreign matter	Visual

4.3.2.6 Tube, Inside, Dwgs. D8593788 and C8593789 covering a detail of Dwg. F8543732

CRITICAL

None defined

MAJOR

101. Pitch diameter of thread, min.	Gage
102. Major diameter of thread, min.	Gage
103. Concentricity of pitch diameter of thread with inside diameter at datum location	Gage
104. Diameter, inside, max.	Gage
105. Diameter of body, large end	Gage
106. Diameter of body, midsection, min.	Gage
107. Depth of spiral groove	Gage
108. Depth of spiral groove relief	Gage
109. Total length, max.	Gage
110. Length of effective thread, min.	Gage
111. Thickness of wall, min.	Gage
112. Thickness of wall under pellet, min.	Gage
113. Straightness	Gage
114. Pellet missing, loose or improperly inserted	Visual
115. Thread damaged or not full	Visual
116. Metal defective	Visual
117. Protective finish, inadequate or defective	Visual
118. Surface finish of body, large end, improper	Visual
119. Burr	Visual
120. Foreign matter	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:31Z
Check the source to verify that this is the current version before use.

4.3.2.6 (Cont'd)

	Defect	Method of Inspection
MINOR		
201.	Pitch diameter of thread, max.	Gage
202.	Diameter, inside, min.	Gage
203.	Diameter of body, midsection, max.	Gage
204.	Total length, min.	Gage
205.	Length of shoulder	Measure
206.	Length of spiral groove relief, max.	Measure
207.	Length of thread, max.	Measure
208.	Width of spiral groove relief, max.	Measure
209.	Location of spiral groove, max.	Measure
210.	Profile of spiral groove	Visual
211.	Direction of turn of spiral groove, incorrect	Visual
212.	Number of turns of spiral groove, incorrect	Visual
213.	Marking missing, incorrect or illegible	Visual
214.	Radius or chamfer missing or incorrect	Visual
215.	Surface finish, improper, except as otherwise Classified	Visual

4.3.2.7 Tube, Outside, Dwgs. D8593790 and C8593791 of Dwg. F8593732

CRITICAL		
	None defined	
MAJOR		
101.	Pitch diameter of thread, min. (both ends)	Gage
102.	Major diameter of thread, min. (both ends)	Gage
103.	Concentricity of pitch diameter of thread with inside diameter at datum location (both ends)	Gage
104.	Diameter, inside, max.	Gage
105.	Diameter of body, min.	Gage
106.	Total length, min.	Gage
107.	Thickness of wall, min.	Gage
108.	Length of effective thread, min. (both ends)	Measure
109.	Straightness	Gage
110.	Metal defective	Visual
111.	Protective finish inadequate or defective	Visual
112.	Burr	Visual
113.	Foreign matter	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:31Z
Check the source to verify that this is the current version before use.

4.3.2.7 (Cont'd)

	Defect	Method of Inspection
MINOR		
201.	Pitch diameter of thread, max.	Gage
202.	Diameter, inside, min.	Gage
203.	Diameter of body, max.	Gage
204.	Total length, max.	Gage
205.	Length of thread, max. (both ends)	Measure
206.	Marking missing, incorrect or illegible	Visual
207.	Radius or chamfer missing or incorrect	Visual
208.	Surface finish, improper	Visual

4.3.2.8 Head, firing, Dwg. D8593792, covering a detail of Dwg. F8593732

CRITICAL		
1.	Metal defective	Visual
MAJOR		
101.	Pitch diameter of thread, max.	Gage
102.	Minor diameter of thread, max.	Gage
103.	Concentricity of cavity with pitch diameter of thread	Gage
104.	Concentricity of body with pitch diameter of thread	Gage
105.	Concentricity of flange with body	Gage
106.	True position of safety pin hole with cavity including perpendicularity with hole in body	Gage
107.	True position of hole in body with cavity	Gage
108.	True position of flange holes with body, small end	Gage
109.	Diameter of cavity	Gage
110.	Diameter of safety pin hole	Gage
111.	Diameter of flange, min.	Gage
112.	Diameter of hole in body	Gage
113.	Diameter of body, min.	Gage
114.	Thickness of flange, min.	Gage
115.	Thickness of wall, min.	Gage
116.	Location of hole in body	Gage
117.	Location of safety pin hole	Gage
118.	Diameter of body, small end, min.	Measure
119.	Thread damaged or not full	Visual
120.	Protective finish inadequate or defective	Visual
121.	Surface finish of cavity, improper	Visual
122.	Burr or sharp corner	Visual
123.	Foreign matter	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:31Z
Check the source to verify that this is the current version before use.

4.3.2.8 (Cont'd)

	Defect	Method of Inspection
MINOR		
201.	Pitch diameter of thread, min.	Gage
202.	Diameter of seal hole in flange	Gage
203.	Diameter of flange, max.	Gage
204.	Diameter of body, max.	Gage
205.	Diameter of thread undercut, max.	Gage
206.	Depth to bottom of threaded cavity	Gage
207.	Depth to bottom of long cavity	Gage
208.	Thickness of flange, max.	Gage
209.	Height of boss	Gage
210.	Total length	Gage
211.	Length to top of flange	Gage
212.	Location and angle of seal hole in flange	Gage
213.	Diameter of body undercut, min.	Measure
214.	Diameter of body, small end, max.	Measure
215.	Diameter of boss flat	Measure
216.	Diameter of flange holes	Measure
217.	Diameter of drill point, max.	Measure
218.	Depth to drill point, max.	Measure
219.	Depth of flange holes	Measure
220.	Location of flange holes	Measure
221.	Angle of boss, incorrect	Measure
222.	Width of body undercut, max.	Visual
223.	Width of thread undercut, max.	Visual
224.	Marking missing, incorrect or illegible	Visual
225.	Radius or chamfer missing or incorrect	Visual
226.	Surface finish, improper, except as otherwise classified	Visual

4.3.2.9 Pin, Safety, Dwg. C8593793, a detail of Dwg. F8593732

CRITICAL

None defined

MAJOR

101.	Diameter of wire	Measure
102.	Profile incorrect	Visual
103.	Metal defective	Visual
104.	Protective finish inadequate or defective	Visual
105.	Burr	Visual
106.	Foreign matter	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:31Z
Check the source to verify that this is the current version before use.

4.3.2.9 (Cont'd)

	Defect	Method of Inspection
MINOR		
201.	Diameter of head, inside	Measure
202.	Total length	Measure
203.	Length of loop to end of twist	Measure
204.	Length to center of loop	Measure
205.	Length between high and low prongs	Measure
206.	Location of end bend	Measure
207.	Profile of end, incorrect	Visual
208.	Radius missing or incorrect	Visual
209.	Surface finish, improper	Visual

4.3.2.10 Pin, Firing, Dwg. C8593794, a detail of Dwg. F8593732

CRITICAL

None defined

MAJOR

101.	Concentricity of striker with body	Gage
102.	Concentricity of rear striker with body	Gage
103.	True position of pin hole with body	Gage
104.	True position of cross pin hole with body including perpendicularity with pin hole	Gage
105.	Diameter of body, min.	Gage
106.	Diameter of hole	Gage
107.	Length of striker	Gage
108.	Length between holes	Gage
109.	Location of hole	Gage
110.	Metal defective	Visual
111.	Protective finish inadequate or defective	Visual
112.	Surface finish of body, improper	Visual
113.	Burr or sharp corner	Visual
114.	Foreign matter	Visual

MINOR

201.	Diameter of striker	Gage
202.	Diameter of body, max.	Gage
203.	Diameter of chamfer at hole	Gage
204.	Total length	Gage
205.	Angle of chamfer on holes	Measure
206.	Marking missing, incorrect or illegible	Visual
207.	Radius or chamfer missing or incorrect	Visual
208.	Surface finish, improper, except as otherwise classified	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:31Z
Check the source to verify that this is the current version before use.

Defect	Method of Inspection
4.3.2.11 Assembly, Dwg. F8593732	
CRITICAL	
1. Firing pin not cocked	Manual/Visual
2. Firing pin spring missing	Manual/Visual
MAJOR	
101. Any part missing, except as otherwise classified	Visual
102. Cotter pin ends not spread	Visual
103. Improper assembly	Visual
104. Thread damaged or not full	Visual
105. Marking missing, incorrect or illegible	Visual
106. Burr	Visual
107. Foreign matter	Visual
MINOR	
201. Protective finish inadequate or defective	Visual
4.3.2.12 Packing in carton, Dwg. F8797268	
CRITICAL	
None defined	
MAJOR	
None defined	
MINOR	
201. Contents loose or missing	Manual/Visual
202. Carton damaged	Visual
203. Packing wet	Visual
204. Marking missing, incorrect or illegible	Visual
4.3.2.13 Packing in wooden box, Dwg. F8797269	
CRITICAL	
None defined	

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T06:31Z
Check the source to verify that this is the currentversion before use.

4.3.2.12 (Cont'd)

Defect	Method of Inspection
MAJOR	
None defined	
MINOR	
201. Contents loose	Manual
202. Hardware missing, loose, broken or improperly engaged	Manual/Visual
203. Strapping missing, loose, broken or improperly assembled	Manual/Visual
204. Contents of box exposed	Visual
205. Box damaged	Visual
206. Marking missing, incorrect or illegible	Visual
207. Number of units incorrect	Visual

4.3.3 Inspection testing - The following tests shall be performed in accordance with the provisions of 4.4.

4.3.3.1 Hardness - Fifty units from each heat treated lot of components shall be tested to determine compliance with the requirements on the applicable drawing. Failure of any unit to comply with the drawing requirements shall be cause for rejection of the lot of components.

4.3.3.2 Hydrostatic pressure - Each outside, telescoping and inside tube shall be subjected to an internal hydrostatic pressure test. Failure of any tube to comply with the requirements of 3.3 shall be cause for rejection of the tube.

4.3.3.3 Breakaway torque - A breakaway torque shall be applied to each sub-assembly threaded joint as listed in Table II. Failure of sub-assembly to comply with the requirements of Column C of Table II shall be cause for rejection of the assembly.

4.3.3.4 Protective finish - The number of specimens and acceptance criteria for protective finish tests shall be in accordance with the applicable Military Standard listed on the drawing.

4.3.3.5 Residual magnetism - Each metal parts assembly shall be tested for excessive residual magnetism. Failure of any assembly to comply with the requirements of 3.6 shall be cause for rejection of the assembly.

4.3.4 Inspection equipment - The examination and tests shall be made, using the equipment listed on IEL-8593732.

4.4 Test methods and procedures

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:31Z
Check the source to verify that this is the current version before use.

4.4.1 Hardness - Prior to the application of protective finish, a hardness tester shall be used to determine compliance with the hardness requirements specified on the detail drawing.

4.4.2 Hydrostatic pressure - Prior to application of protective finish, the outside, inside and telescoping tube shall be mounted, individually, in the device and subjected to an internal hydrostatic pressure to determine compliance with the requirement of 3.3. The testing device used shall internally seal the ends of the tubes within 1-½ inches of each end without applying any axial load other than that applied by the liquid pressure.

4.4.3 Breakaway torque - A torque wrench set at the torque requirements specified in 3.4 shall be used to determine the adequacy of the joints. The assembly shall be secured in the fixture prior to application of the torque.

4.4.4 Protective finish - Test procedures for protective finish shall be in accordance with the applicable Military Standard referenced on the drawing.

4.4.5 Residual magnetism - The metal parts assembly shall be tested with a compass type AN-5766 for excessive residual magnetism in an area free of local magnetic effects by placing the assembly 6 inches from and at the same height as the compass in a north-south horizontal position (firing head end at south) with the compass set in an east-west heading. The assembly shall be moved slowly past the compass in a longitudinal direction for its entire length, rotated 180 degrees in the horizontal position about its longitudinal axis and moved slowly back past the compass.

5. PREPARATION FOR DELIVERY

5.1 Packing and marking - Level A - Packing and marking shall be in accordance with Drawings F8797268 and F8797269.

6. NOTES

6.1 Ordering data - Procurement documents should specify the title, number and date of this specification.

6.2 A "mechanical failure" is defined as any deformation or breakage of a part, the occurrence of which is other than a design function.

Custodian:

Army - MU

Preparing activity:

Army - MU(FA)

Project No. 1377-A474

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:31Z
Check the source to verify that this is the current version before use.

Location of groove

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 202610-22T06:31Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
Department of the Army

OFFICIAL BUSINESS

Commanding Officer
Frankford Arsenal
ATTN: SMUFA-T1000
Philadelphia, Pa. 19137

FOLD

Source: https://assist.dla.mil -- Downloaded: 202610-22T06:31Z
Check the source to verify that this is the current version before use.