NOT MEASUREMENT SENSITIVE

MIL-DTL-14639/67
24 February 2023

DETAIL SPECIFICATION SHEET
INSIGNIA, GRADE, CHIEF MASTER SERGEANT OF THE U.S. SPACE FORCE (E-9), U.S. SPACE FORCE

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-14639.



MATERIAL: Red Brass 85/15 (UNS Alloy No. C-230)

FINISH: Epoxy resin, Nickel Plated, Mirror-like Polished, and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 16.

DIMENSIONS:
HEIGHT (Overall): 1-13/16 inches (REF)
WIDTH (Overall): 1-3/32 inches (REF)
THICKNESS (At edge): 0.074 ± 0.010 inch

ATTACHING DEVICE:
1: Attaching device shall be prong and clutch type.

2: Two prongs shall be located on a horizontal line 1 inch ± 1/64 inch above the base of the grade insignia and spaced 15/16 inch ± 1/64 inch apart.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:15Z
Check the source to verify that this is the current version before use.

EPOXY:

1. All epoxy shall be stoned epoxy.

2. Epoxy resin shall be applied to the Insignia as indicated below and shall match TIOH Color Chip Numbers listed below.

COLOR	LOCATION
Blue #20	Background, except center image (Shaded area)

NOTES:

1: The term (REF) refers to measurements taken from the Government furnished hub or die.

2: Hard cloisonné enamel may be used in lieu of epoxy. If hard cloisonné enamel is used, the required base material shall be Gilding Metal 95/5 (UNS Alloy C-210).

Custodians:
Army - IH
Air Force - 11

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2023-092)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:15Z
Check the source to verify that this is the current version before use.