MIL-I-14645B
29 January 1988
SUPERSEDING
MIL-I-14645A
30 SEPTEMBER 1976

MILITARY SPECIFICATION

INSIGNIA, RANK AND GRADE, SHOULDER MARK, AIR FORCE AND ARMY (EMBROIDERED)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for shoulder marks with embroidered insignia of rank and grade.

1.2 The shoulder marks shall be of the type, size and class as noted below (see 6.2).

Type I - Air Force, Officer
Type II - Army, Officer

Size 1 - Large
Size 2 - Small
Class 1 - General
Class 2 - Lieutenant General
Class 3 - Major General
Class 4 - Brigadier General
Class 5 - Colonel
Class 6 - Lieutenant Colonel
Class 7 - Major
Class 8 - Captain
Class 9 - First Lieutenant
Class 10 - Second Lieutenant
Class 11 - Chief Warrant Officer 4
Class 12 - Chief Warrant Officer 3
Class 13 - Chief Warrant Officer 2
Class 14 - Warrant Officer 1
Class 15 - General of the Army (type 2 only)

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: Director, The Institute of Heraldry, US Army, Cameron Station, Alexandria, VA 22304-5050, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:16Z
Check the source to verify that this is the current version before use.

Type III - Army, Enlisted Personnel

Size 1 - Large
Size 2 - Small
Class 1 - Sergeant Major of the Army
Class 2 - Command Sergeant Major
Class 3 - Sergeant Major
Class 4 - First Sergeant
Class 5 - Master Sergeant
Class 6 - Sergeant First Class
Class 7 - Staff Sergeant
Class 8 - Sergeant
Class 9 - Corporal

Type IV - Air Force, Enlisted Personnel

Size 1 - Large
Size 2 - Small
Class 1 - Chief Master Sergeant of the Air Force
Class 2 - Chief Master Sergeant with First Sergeant Device
Class 3 - Chief Master Sergeant
Class 4 - Senior Master Sergeant with First Sergeant Device
Class 5 - Senior Master Sergeant
Class 6 - master Sergeant with First Sergeant Device
Class 7 - Master Sergeant

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

V-T-285 - Thread, Polyester
NN-P- 71 - Pallet, Material Handling, Wood, Stringer Construction, 2-way and 4-way (partial)
PPP-B-636 - Boxes, Shipping Fiberboard
PPP-B-676 - Boxes, Setup

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:16Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-C-83448 - Cloth, Serge, Polyester, Texturized
MIL-E-17568 - Embroidery Materials, Metallic and Synthetic Metallic
MIL-P-15011 - Pallet, Material Handling, Wood, Post Construction, 4-way entry

STANDARDS

FEDERAL

FED-STD-191 - Textile; Test Methods
FED-STD-751 - Stitches, Seams, and Stitchings.

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized Unit Loads
MIL-STD-2073-1- DoD Materiel Procedures for Development and Application of Packaging Requirements.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS

THE INSTITUTE OF HERALDRY

B-3-86 - Insignia of Rank, Officer, Shoulder Mark, AF, Large
B-3-87 - Insignia of Rank, Officer, Shoulder Mark, AF, Large
B-3-86A - Insignia of Rank, Officer, Shoulder Mark, AF, Small
B-3-87A - Insignia of Rank, Officer, Shoulder Mark, AF, Small
B-3-92 - Insignia of Grade, Officer, Shoulder Mark, Army, Large Size
B-3-93 - Insignia of Grade, Officer, Shoulder Mark, Army, Large Size
B-3-94 - Insignia of Grade, Officer, Shoulder Mark, Army, Large Size
B-3-95 - Insignia of Grade, Officer, Shoulder Mark, Army, Small Size
B-3-96 - Insignia of Grade, Officer, Shoulder Mark, Army, Small Size

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:16Z
Check the source to verify that this is the current version before use.

B-3-97 - Insignia of Grade, Officer, Shoulder Mark, Army, Small Size
B-3-101 - Insignia of Grade, Enlisted Personnel, Shoulder Mark, Army, Large Size
B-3-101A - Insignia of Grade, Enlisted Personnel, Shoulder Mark, Army, Small Size
B-3-102 - Insignia of Grade, Enlisted Personnel, Shoulder Mark, Army, Large Size
B-3-102A - Insignia of Grade, Enlisted Personnel, Shoulder Mark, Army, Small Size
B-3-103 - Insignia of Grade, Enlisted Personnel, Shoulder Mark, Army, Large Size
B-3-103A - Insignia of Grade, Enlisted Personnel, Shoulder Mark, Army, Small Size
B-3-116 - Insignia of Grade, Noncommissioned Officers, Shoulder Mark, Air Force, Large Size
B-3-117 - Insignia of Grade, Noncommissioned Officers, Shoulder Mark, Air Force, Large Size
B-3-116A - Insignia of Grade, Noncommissioned Officers, Shoulder Mark, Air Force, Small Size
B-3-117A - Insignia of Grade, Noncommissioned Officers, Shoulder Mark, Air Force, Small Size

(Copies of specifications, standards, and other Governments documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer).

2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

THE COLOR ASSOCIATION OF THE UNITED STATES

The Standard Color Reference of America, Tenth Edition

United States Army Color Card, The Official Colors for Branches, Agencies, etc.

DOD Standard Shades for Heraldic Yarns for Embroidery and Ribbons 1974.

(Application for copies of the color cards should be addressed to the Color Association of the United States, 343 Lexington Ave. New York, NY 10016-0927).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:16Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM-D-3951 - Standard Practice for Commercial Packaging.

(Application for copies of ASTM publications should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pennsylvania 19103-1187).

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services).

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, (except for associated detail specifications, specification sheets or MS standards) the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Standard sample. Unless otherwise specified (see 6.2), samples shall be furnished by the contracting officer to be used for guidance, information and as a standard for design and workmanship. Variation from this specification may appear in the guide samples in which event the specification shall govern.

3.2 First article. Unless otherwise specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.4 and 6.4).

3.3 Material.

3.3.1 Cloth, laminated. The laminated cloth shall be composed of two layers of cloth bonded together with an adhesive by heat and pressure. One layer to be texturized polyester cloth (shell fabric) see paragraph 3.3.1.2 and the other to be a fusible cloth referenced in paragraph 3.3.1.1. The laminated cloth shall show good adhesion between the two fabrics and show no bubbles or puckering in the shell fabric before or after dry cleaning.

3.3.1.1 Cloth, fusible. The fusible cloth shall be a cotton or polyester/cotton cloth printed with a polyamide adhesive containing a minimum of 300 dots per square inch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:16Z
Check the source to verify that this is the current version before use.

3.3.1.1.1 Cloth, cotton or polyester/cotton. The weave for the cotton or polyester/cotton cloth shall be plain and weight shall be 4 to 5 ounces per square yard. The maximum shrinkage shall be 2 percent warp and filling. The color of the cotton cloth shall be white or greige.

3.3.1.2 Cloth, texturized polyester (shell fabric). The top layer of the laminated cloth shall be a texturized polyester material conforming to MIL-C-83448 and shall show good fastness to wet-dry cleaning, perspiration, light, laundry, and crocking. The color of the texturized polyester shall be as follows:

Type I - Air Force Shade 1578
Type II - Army Green 434
Type III - Black Cable No. 65018
Type IV - Air Force shade 1578

3.3.1.2.1 Color. Unless otherwise specified, the color of the embroidery yarns shall be as shown on the applicable cartoon or drawing. The use of sulphur dyes is prohibited.

3.3.1.2.2 Colorfastness. When tested as specified in 4.6.1, the dyed embroidered yarn and cloth shall show good fastness to wet-dry cleaning, bleaching, or light, and fair fastness to laundering except that for black, blue, and red shades, the fastness to bleaching shall be not less than fair as defined in FED-STD-191.

3.3.1.2.3 Matching. The color shall match the standard sample when viewed under filtered tungsten lamps which approximate artificial daylight having a correlated color temperature of 7000 plus or minus 500 K, with illumination of 100 plus or minus 20 foot candles, and shall be a good match to the sample under incandescent lamplight at 2300 plus or minus 100 K. The degree of luster shall be equal to the standards established in the DOD Standard Color Card of Official Standardized Shades for Heraldic Yarns for Embroidery and Ribbons, 1974.

3.3.2 Thread. The thread for hemming the shoulder mark shall be polyester and conform to type I, class 1, letter size AA, 2 ply of V-T-285. The thread shall match the color of the top layer of the laminated cloth.

3.3.3 Embroidery yarn.

3.3.3.1 Synthetic metallic embroidery yarn. The synthetic metallic yarn for embroidery shall conform to type III, class 8 or 9 of MIL-E-17568 with the following exceptions:

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:16Z
Check the source to verify that this is the current version before use.

a. The finished yarn size shall be 260 (plus or minus 15 denier).

b. The yarn shall have sufficient turns per inch to insure proper uniformity of the metallic ribbon wrapped around the core and can be used on any type of embroidery machine to meet specification requirements. The shade of the metallic yarn shall match the standard sample.

3.3.3.2 Rayon embroidery yarn. The rayon embroidery yarn shall be semi-dull, continuous filament, regenerated cellulose type rayon, two-ply schiffli type yarn. The yarn size and color shall be specified on the applicable cartoon or drawing. The yarn shall show good colorfastness to wet-dry cleaning, perspiration, laundering and light.

3.4 Design. The design of each shoulder mark shall be as shown on the applicable drawing.

3.5 Construction.

3.5.1 Embroidering. The device for each class of shoulder mark shall be schiffli embroidered on the face side of the texturized polyester cloth. The applicable yarn shall be as specified in 3.3.3.1 for type II insignia and as specified in 3.3.3.2 for type I and III insignia. The embroidered device shall conform to the applicable cartoon furnished by the Government and will become a part of this specification. The embroidery stitches shall be of the type, color, length, minimum number, and density specified by the applicable cartoon. Sufficient base cloth shall be allowed in all directions so shoulder marks can be properly hemmed and joined together.

3.5.2 Cutting. After insignia have been embroidered, material shall be cut so that the finished shoulder mark will conform to the measurements specified on applicable drawing.

3.5.3 Hemming. The hemming shall be executed at the location indicated on the applicable drawing. Each hem shall have a minimum of 10-12 stitches per inch using a type 301 stitch of FED-STD-751. All ends of stitching not caught in other seams or stitching shall be backstitched a minimum of 1/2 inch. Hems shall be 3/8 inch, plus 1/8, minus 0 inch wide and stitching shall be located 1/8 inch, plus 0, minus 1/32 inch from the turned edge.

3.5.4 Pressing. The finished shoulder mark shall be pressed so that the item has the shape shown on the applicable drawing.

3.6 Workmanship. The finished shoulder mark shall be clean, well-made and shall conform to the quality and grade of product established by this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:16Z
Check the source to verify that this is the current version before use.

3.7 Tolerances. Unless otherwise specified herein or on the applicable drawing, dimensions shall be within a tolerance of plus or minus 1/32 inch.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. all items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. The inspections specified herein are classified as follows:

a. First article inspection (see 4.4).

b. Quality conformance inspection (see 4.5).

4.3 Inspection conditions. Unless otherwise specified, all inspections shall be performed in accordance with the test conditions specified in applicable test method document or applicable paragraph(s) in the specification.

4.4 First article inspection. Inspection and testing of the first article sample shall be made on a completely finished item for all provisions of this specification applicable to the end product examination and test.

4.5 Quality conformance inspection. Inspection shall be in accordance with provisions set forth in MIL-STD-105, except where otherwise indicated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:16Z
Check the source to verify that this is the current version before use.

4.5.1 Quality assurance inspection. Inspection shall be in accordance with the provisions set forth in MIL-STD-105 except when otherwise specified hereafter.

4.6 Component and material inspection. In addition to the quality assurance provisions of the subsidiary specifications and drawings, inspection shall be performed on components and materials as specified herein.

4.6.1 Testing of components. Components shall be tested as specified in table I. The test methods listed in table I shall be in accordance with FED-STD-191, wherever applicable. The sample unit for testing shall be as follows:

1/4 continuous yard full width of the laminated cloth.
1-1/2 continuous yards full width of the fusible cloth.
1-1/2 continuous yards full width of the cotton cloth.
3-1/2 continuous yards full width of the texturized cloth.

The sample unit for thread and embroidery yarn shall be five continuous yards each. The lot shall be unacceptable if one or more units fail to meet any requirement specified. The sample size shall be as follows:

Lot size (yd)	Sample size (units)
Less than 800	2
801 to 22,000	3
22,001 and over	5

TABLE I. Component test.

Component characteristic	Rqm't para	Test method	#Determ per s/u	Results reported as
Laminated cloth				
Wet-dry cleaning	3.3.1	5622		Pass or fail
Fusible cloth				
Amount of adhesive	3.3.1.1	Visual 1/		Pass or fail
Cloth, cotton or polyester/cotton				
Material identification	3.3.1.1.1	1/		Pass or fail
Weave	3.3.1.1.1	Visual	1	Pass or fail
Weight	3.3.1.1.1	5041		Nearest 0.1 oz/sq yard
Shrinkage	3.3.1.1.1	5550		Nearest 0.1 oz/sq yard

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:16Z
Check the source to verify that this is the current version before use.

TABLE I. Component test - continued.

Component characteristic	Rqm't para	Test method	#Determ per s/u	Results reported as
Texturized polyester cloth (shell fabric)				
Material identification	3.3.1.2	1/		
Colorfastness to:				
Wet-dry cleaning	3.3.1.2	5622		Pass or fail
Perspiration	3.3.1.2	5680		Pass or fail
Light	3.3.1.2	5660 2/		Pass or fail
laundry	3.3.1.2	5610		Pass or fail
Crocking	3.3.1.2	5651		Pass or fail
Synthetic metallic embroidery yarn				
Material identification	3.3.3.1 1/			
Denier	3.3.3.1			Pass or fail
Turns	3.3.3.1			Pass or fail
Rayon embroidery yarn				
Material identification	3.3.3.2 2/			
Denier	3.3.3.2			Pass or fail
Colorfastness to:				
Wet-dry cleaning	3.3.1.2.2	5622		Pass or fail
Bleaching	3.3.1.2.2	5680		Pass or fail
Laundry	3.3.1.2.2	5610		Pass or fail
Light	3.3.1.2.2	5660 2/		Pass or fail

1/ Unless otherwise specified a contractor's certification of compliance may be accepted as evidence of conformance.

2/ In the event of a dispute resulting from the test with method 5660, or as a result of suspected anomalous behavior of certain dye types of formulations, the contracting officer may authorize the exposure to natural light in accordance with method 5662.

4.7 End item examination.

4.7.1 Visual examination of the end item. Defects found during this examination shall be classified in accordance with table II. The sample unit for this examination shall be one finished pair of shoulder marks. The acceptable quality level (AQL) for this examination shall be 6.5 defects per 100 units. The inspection level shall be level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:16Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of visual examination defects.

Examine	Defects
Material defects (Texturized polyester)	Material not as specified Manufacturing defects, such as hole, float, broken end or pick, slub, lump, knot, stain, streak, clearly visible.
Embroidery device	Any device missing or mispositioned affecting appearance. Not underlaid to show a well raised effect. Details or device incomplete. The device is not centered. Wrong color of cover stitches. Wrong type embroidery yarn. Loose tension or tight tension clearly noticeable or resulting in poorly defined design. Embroidered piping stripe not extending beyond the creased line when applicable. Stitching incomplete (miss). Ragged, broken or loose stiele stitching. Stitching missing. Any shift affecting appearance. Device appearing askew. Not in accordance with applicable cartoon. Device does not matched in pairs, e.g., different shades, sizes.
Laminated cloth	Visible bubbles and puckering seen on shell fabric before or after dry cleaning.
Thread	Thread not a good color match to polyester cloth.
Workmanship	Spot or stain clearly noticeable. Misshaped or distorted insignia, affecting appearance. Not packaged in left and right (type 1 & 2, class 5) Operation not as specified. Cutting mark shows on outside of insignia. Pairs not same dimensions
Seams and stitching	Loose ends not backstitched a minimum of 1/2 inch. Loose tension, noticeably affecting appearance. Basting stitch or cutting mark showing on face or back of insignia. Any open seam on hems and joining seam. Tight tension, i.e., fabric puckers excessively. Seams crooked or irregular, affecting appearance. Finished hem not 3/8 to 1/2 inch in width.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:16Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of visual examination defects - continued.

Examine	Defects
Pressing	Stitching on hems not 1/16 to 1/8 inch from turned edge. Less than 10 or more than 12 stitches per inch. Wrong stitch type. Singed or scorched. Clearly visible creases or gloss marks. Misshaped by pressing. Color change clearly noticeable. Not pressed flat.

4.7.2 Examination for shoulder marks for defects in dimensions. Any dimension that is not within the specified tolerances shall be classified as a defect. The AQL shall be 6.5 defects per 100 units and the inspection level shall be S-1. The sample unit shall be one finished pair of shoulder marks.

4.7.3 Examination of paired shoulder marks for compatible synthetic metallic yarn color match. Any paired shoulder marks in which the synthetic yarn is not a good color match to standard sample shall be classified as a defect. The AQL shall be 1.5 defects per hundred units and the inspection level shall be S-4. The sample unit shall be one finished pair of shoulder marks.

4.7.4 Examination for count shoulder marks in intermediate containers. Shoulder marks packaged for shipment shall be examined to determine conformance with package markings and specified quantity. The sample unit for this examination shall be one box (interior package). Any box containing less than specified or marked quantity of shoulder marks shall be classified as a defect. The inspection level shall be S-2 and the AQL shall be 2.5 defects per hundred units. The lot size shall be the number of intermediate containers offered for delivery.

4.7.5 Examination of preparation for delivery requirements. An examination shall be made to determine that the packaging, packing and marking requirements of section 5 of this specification are complied with. Defects shall be scored in accordance with table III. The sample unit shall be one shipping container fully prepared for delivery with the exception it need not be sealed. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and AQL shall be 4.0 defects for hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:16Z
Check the source to verify that this is the current version before use.

TABLE III. Classification of preparation for delivery defects.

Examine	Defect
Marking (exterior and interior)	Omitted, incorrect, illegible, of improper size, location, sequence or method of application.
Materials	Any component missing. Any component damaged.
Workmanship	Inadequate application of components, such as imcomplete closure of container flaps, improper taping, inadequate stapling.
Contents	Number of unit packages per intermediate box is more or less than required. 1/ Number of intermediate boxes per shipping container is more or less than required. Number of shoulder marks per unit package is more or less than required.

1/ For this defect, one intermediate box shall be examined from each shipping container in the sample.

4.7.6 Palletization examination. An examination shall be made to determine that the palletization is in compliance with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one palletized unit load fully packaged. The lot size shall be the number of palletized unit loads in the inspection lot. The inspection level shall be S-1 and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirements.
Palletization	Pallet pattern not as specified. Interlocking of loads not as specified. Load not bonded with required straps as specified.
Weight	Exceeds maximum load limits.
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:16Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Preservation. Preservation shall be levels A, C or Commercial as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Unit packaging. One pair of shoulder marks of one type size and class only, shall be placed in a snug-fitting polyethylene bag fabricated from film having a minimum thickness of 0.002 inch. In addition, the shoulder marks shall be paired to assure a good color match of shade and size. All seams and closures shall be effected by heat sealing. Prior to, or during the heat sealing operation, excess air within the bag shall be expelled. A pair of type I and II, class 5 shoulder marks shall consist of one left and one right hand insignia.

5.1.1.2 Intermediate packaging. Fifty pairs of one type, size and class as specified in 5.1.1.1, shall be preserved in a snug-fitting, set-up paperboard box conforming to type I, style 4 of PPP-B-676. Closure shall be in accordance with the appendix of the container specification.

5.1.2 Level C. Shoulder marks shall be preserved to the MIL-STD-2073-1 requirements for this level.

5.1.3 Commercial. Shoulder marks shall be preserved in accordance with the applicable requirements of ASTM-D-3951.

5.2 Packing. Packing shall be level B, C or commercial as specified (see 6.2).

5.2.1 Level B. Shoulder marks preserved as specified in 5.1.1.2, shall be packed in a snug-fitting shipping container conforming to type CF or SF, class domestic, grade 275, style RSC of PPP-B-636. Closure shall be in accordance with appendix of the container specification. Maximum gross weight shall not exceed 65 pounds.

5.2.2 Level C. Shoulder marks, preserved as specified in 5.1, shall be packed in accordance with the applicable requirements of MIL-STD-2073-1.

5.2.3 Commercial. Shoulder marks shall be preserved as specified in 5.1, shall be packed in accordance with the applicable requirements of ASTM-D-3951.

5.3 Palletization. Items packed as specified shall be palletized on a 4-way entry pallet in accordance with load type 1A of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance bonding means C, K and L, O or P. Pallet pattern shall be in accordance with the appendix of MIL-STD-147. The pallet shall be 4-way, type I, class 1, style 1,

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:16Z
Check the source to verify that this is the current version before use.

size A, wood group I, II, III, or IV of MIL-P-15011, or 4-way, type IV, V or VIII, class 1, style A, size 2, wood group I, II, III or IV, grade A of NN-P-71. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the patterns specified in MIL-STD-147, the pallet pattern used shall be approved by the contracting officer.

5.4 Marking. In addition to any special marking required by the contract or purchase order, unit packs, intermediate boxes, shipping containers, and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM-D-3951, as applicable.

5.4.1 Polyethylene bagged packages. Polyethylene bagged packages shall have the required information legibly printed or stamped in black directly on the bag across the center face or on a white paper label inserted within the bag so as to permit ready identification. The white paper label shall contain the following information:

STOCK NUMBER
NOMENCLATURE
MANUFACTURER'S NAME
CONTRACT NUMBER

6. NOTES

6.1 Intended use. The embroidered shoulder marks covered by this specification are intended to be worn by personnel of the Army and Air Force to indicate their ranks or grade.

6.2 Ordering data.

6.2.1 Ordering data. Procurement documents should specify the following:

a. Title, number and date of this specification.
b. Type, size and class required (see 1.2).
c. When a standard sample will not be furnished (see 3.1).
d. When first article samples are not required (see 3.2).
e. Selection of applicable levels of packaging and packing (see 5.1 and 5.2).
f. When palletization is required (see 5.3).

6.3 Samples. For access to samples, address the contracting activity issuing the invitation to bids.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:16Z
Check the source to verify that this is the current version before use.

6.4 First article. When a first article inspection is required, the item should be a first article sample or it may be a standard production item from the contractor's current inventory as specified in 4.4. The first article should consist of one completed shoulder mark. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations approval of first article test results and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract.

6.5 Subject term (key word) listing.

Embroidered
Enlisted
Grade
Insignia
Officer
Rank
Shoulder marks

6.6 Changes from previous issue. Asterisks or vertical lines are not used in this revision to identify changes because of the numerous changes.

Custodians:
Army - IH
Air Force - 11

Review activities:
Air Force - 82,99
DLA - CT

User activities:
Air Force - 45

Preparing activity:
Army - IH

(Project No. 8455 - 0291)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:16Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements All users of military standardization documents are invited to provide suggestions This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems Enter in block 6 any remarks not related to a specific paragraph of the document If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered

NOTE This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

The Institute of Heraldry, US Army
Cameron Station, 5010 Duke Street
Alexandria, Virginia 22304-5050

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12062 WASHINGTON D C
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

Director
The Institute of Heraldry, US Army
ATTN: DAPC-PDH-T
Cameron Station, 5010 Duke Street
Alexandria, Virginia 22304-5050

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:16Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1 DOCUMENT NUMBER	2 DOCUMENT TITLE
MIL-I-14645B	Insignia, Rank and Grade, Shoulder Mark, Air Force and Army (Embroidered)

3a. NAME OF SUBMITTING ORGANIZATION	4 TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)* _____
b ADDRESS *(Street, City, State, ZIP Code)*	

5 PROBLEM AREAS

a. Paragraph Number and Wording

b Recommended Wording

c Reason/Rationale for Recommendation

6 REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8 DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE

Source: https://assist.dla.mil – Downloaded: 2026-10-18T04:16Z
Check the source to verify that this is the current version before use.