MIL-F-14648A
30 April 1986
SUPERSEDING
MIL-F-14648
31 December 1982

MILITARY SPECIFICATION

FLAGS, ORGANIZATIONAL AND STATUTORY, GENERAL SPECIFICATION FOR

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the general requirements for military flags used by Department of Defense which shall utilize Schiffli embroidered components to make up the designs. The detailed requirements for a given flag shall be covered by the drawing for that specific flag.

1.2 Classification. Flags shall be of the following types, classes, and styles.

Type I - Army
Class 1 - Organizational Flag - (Blank without unit designation motto shield).

Style 1 - Yellow
Style 2 - Maroon
Style 3 - Scarlet
Style 4 - National Flag Blue
Style 5 - Green
Style 6 - Crimson
Style 7 - Buff
Style 8 - Orange
Style 9 - Brick Red
Style 10 - Teal Blue
Style 11 - Oriental Blue
Style 12 - Ultramarine Blue
Style 13 - Bottle Green

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Director, The Institute of Heraldry, US Army, Cameron Station, Alexandria, VA 22304-5050, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 8345

AMSC N/A
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:17Z
Check the source to verify that this is the current version before use.

Type II - Air Force
Class 1 - Organizational Flag
Style 1 - Organizational blank (without unit shield and scroll)
Style 2 - Provisional Units
Style 3 - Ceremonial Flag
Class 2 - Statutory Flags
Style 1 - Secretary of the Air Force
Style 2 - Under Secretary of the Air Force
Style 3 - Assistant Secretary of the Air Force
Style 4 - Chief of Staff, Air Force
Style 5 - Assistant Chief of Staff, Air Force

Type III - Marine Corps
Class 1 - Command Battle Standard (without designation scroll)
Class 2 - Organizational Standard, USMC
Class 3 - Organizational Standard, USMCR

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

V-T-276 - Thread, Cotton
V-T-295 - Thread, Nylon
V-T-301 - Thread, Silk
KK-L-2004 - Leather, Cattlehide, Deerskin and Horsehide Chrome Tanned
UU-P-268 - Paper, Kraft, Wrapping
UU-P-553 - Paper, Wrapping; Tissue
CCC-C-430 - Cloth, Sheeting, Cotton and Polyester and Cotton
CCC-C-476 - Cloth, Bunting, Nylon; and Nylon and Wool
DDD-L- 20 - Label, for Clothing, Equipage, and Tentage (General Use)
PPP-B-636 - Boxes, Shipping, Fiberboard

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:17Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-C-606 - Cloth, Banner, Rayon
MIL-F-2310 - Fringe, Ornamental, Rayon
MIL-F-2692 - Flags and Pennants
MIL-I-14653 - Insignia, Embroidered Flag Components, General Specification for
MIL-L-40051 - Leather, Cattlehide, for Glove Leather

STANDARDS

FEDERAL

FED-STD-191 - Textile, Test Methods
FED-STD-751 - Stitches, Seams and Stitching

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized Unit Loads
MIL-STD-794 - Parts and Equipment, Procedures for Packaging of

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS

THE INSTITUTE OF HERALDRY, US ARMY

5-1-45E - Flag Headings, Type II
5-1-149 - Flags and Plates, Chief of Staff, United States Air Force
5-1-150 - Flags and Plates, Secretary, Under Secretary and Assistant Secretaries, United States Air Force
5-1-480 - Flags and Plates, Vice Chief of Staff, United States Air Force
5-6-2 - Base Drawing for Organizational Colors with Color Specification (Army)
5-100-1 - Base Drawing, Air Force Organizational Flags
5-100-1, Sheet 2 - Base Drawing, Air Force Organizational Flags Components on Base Cloth.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:17Z
Check the source to verify that this is the current version before use.

5-100-1B - Flags Organizational and Provisional, Star Arrangement
5-101-1 - Base Drawing, Coat of Arms, United States Air Force
5-101-1A - Ceremonial Flag, United States Air Force
5-101-3 - Base Drawing for United States Air Force, Provisional Flag
5-101-3A - Flag, U.S. Air Force Provisional, Device
5-MC-1, Sheet 1 of 5 - Organizational Flag for United States Marine Corps.
5-MC-1, Sheet 2 of 5 - Device for Organizational Flag for United States Marine Corps.
5-MC-1, Sheet 3 of 5 - Scroll for Organizational Flags for United States Marine Corps.
5-MC-1, Sheet 4 of 5 - Base Cloth for Components, Organizational Flags for United States Marine Corps.
5-MC-1, Sheet 5 of 5 - Base Cloth for Embroidered Scrolls, Organizational Flags for United States Marine Corps.

(Copies of specifications, standards, and other Governments documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

THE COLOR ASSOCIATION OF THE UNITED STATES

The Standard Color Reference of America, Tenth Edition.
United States Army Color Card, The Official Colors for Branches, Agencies, etc.
DOD Standard Shades for Heraldic Yarns for Embroidery and Ribbons, 1974.

(Application for copies of the color card should be addressed to The Color Association of the United States, 343 Lexington Avenue, New York, New York 10016.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS

ASTM-D-3951 - Standard Practice for Commercial Packaging

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:17Z
Check the source to verify that this is the current version before use.

(Application for copies of ASTM publications should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pennsylvania 19103.)

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, (except for associated detail specifications, specification sheets or MS standards) the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Guide samples. Unless otherwise specified (see 6.2), samples shall be furnished by the contracting officer to be used for guidance, information and as a standard for colorfastness. Variation from this specification may appear in the guide samples in which event the specification shall govern.

3.2 First article. Unless otherwise specified (see 6.2), before production is commenced, a sample of the finished item shall be submitted or made available to the contracting officer or his representative for inspection or testing as specified in 4.4. Approval of the first article sample authorizes the commencement of production but does not relieve the contractor of responsibility for compliance with all provisions of the specification. The samples shall be manufactured in the same facilities to be used for the manufacture of the production items.

3.3 Materials. Materials shall conform to the referenced specifications and the requirements specified herein.

3.3.1 Flag base material. Unless otherwise specified, the base material for type I; type II, style 1, class 1 and 2; and type III shall be lightweight nylon. The base material for type II, style 1, class 3 and style 2 shall be rayon banner cloth.

3.3.1.1 Rayon banner cloth. The rayon banner cloth shall conform to MIL-C-606.

3.3.1.2 Lightweight nylon bunting. Lightweight nylon bunting shall conform to type I, class A of CCC-C-476.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:17Z
Check the source to verify that this is the current version before use.

3.3.1.3 Color. The color of the base cloth shall be as specified on the applicable drawing. Care should be taken to ensure the color of the embroidered areas connecting the arrows and olive branches on components for type I flags matches the color of the base fabric. The shade of the base cloth for type II flags shall be an acceptable match to the base material extending from the eagle and cloud.

3.3.2 Thread.

3.3.2.1 Cotton. The cotton thread shall conform to mercerized cotton thread IC1 or IC2 ticket number 000 of V-T-276.

3.3.2.2 Nylon. The nylon thread shall conform to type II, letter size AA or B of V-T-295.

3.3.2.3 Silk. The silk thread for hand embroidery shall conform to type IV of V-T-301 with the following exceptions to the requirements:

Commercial Designation	Minimum average length per ounce (yard)	Minimum average breaking strength (pound)
A	1000	3.0
FF	233	11.0

As an alternate a ss mercerized and gassed cotton yarn may be used in lieu of the silk thread and shall show good colorfastness to wet dry cleaning, water, light and crocking. The cotton yarn may be substituted as follows:

Silk thread	Cotton size
A type	20/2
FF type	10/2

3.3.2.4 Color. The color of the thread shall be specified on the applicable drawing or as specified herein.

3.3.3 Fringe. The fringe shall conform to class 2 of MIL-F-2310. The color of the fringe shall be as specified on applicable drawing.

3.3.4 Cotton sheeting. The cotton sheeting used for lining the tube heading shall conform to type I or II, class 1, style A or B, of CCC-C-430.

3.3.5 Leather. Leather for the tabs in the heading shall conform to type I, class 2 of KK-L-2004 or type II of MIL-L-40051.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:17Z
Check the source to verify that this is the current version before use.

3.4 Design. The design and size of the flags shall be as specified on the applicable drawing. Unless otherwise specified on the drawing, a tolerance of plus or minus 5 percent shall be allowed for dimensions exceeding 2 inches, except that maximum and minimum measurement of dimensions on a single flag may not differ more than 2 percent of the required dimensions and both be within 5 percent. For dimensions 2 inches or under, a tolerance of plus or minus 1/8 inch will be allowed.

3.4.1 Embroidered components. Schiffli embroidered components shall be in accordance with MIL-I-14653. The base cloth shall be as specified in MIL-I-14653 and extend beyond the embroidery the distance specified on the applicable drawing. Type II components of MIL-I-14653 will be utilized for 3' x 4' Air Force flags and type III components will be used for 4'4" x 5'6" Air Force flags. The base material of the component shall be the same fabric as the base material of the flag.

3.4.1.1 Army Organizational Flags. Schiffli embroidered components for the eagle, arrows and olive branch shall be in accordance with MIL-I-14653. Care should be taken to insure the color of the embroidered areas connecting the arrows and olive branches in the eagle's claw matches the color of the base fabric to which it is to be appliqued. The base cloth shall be as specified in MIL-I-14653 and shall extend beyond the embroidery the distance specified on sheet 2 of "DRAWING" 5-6-1B.

3.4.1.2 Air Force Organizational Flags. Schiffli embroidered components for the Air Force Organizational shall be embroidered as specified in MIL-I-14653 and the applicable cartoon. The base cloth shall be as specified and the base cloth shall extend beyond the embroidery the distance specified on sheet 2 of "DRAWING" 5-100-1 or 5-101-1A, as applicable.

3.5 Construction. Flags shall be constructed in accordance with applicable drawing (see 2.1) and the requirements specified herein. Embroidered components shall be evenly trimmed to insure no raw edges are visible after being appliqued. Seams, stitching and stitches shall be in accordance with FED-STD-751 and as indicated in table II of MIL-F-2692.

3.5.1 Stitching of fringe. When fringe is specified for flags, a continuous length of the fringe conforming to 3.3.3 shall be stitched to the front side of the flag at the top, fly, and bottom edges of the flag and completely around each end of the heading. The fringe shall be neatly turned under and caught under the heading stitching. On single thickness flags, selvage edges at the top, fly and bottom shall be hemmed with seam type EFa-1 and cut edges with stitch type EFb-1. On double thickness flags, selvage or cut edges at the top, fly and bottom shall be hemmed with seam type SSc-1. The stitching used to attach the fringe may be incorporated in the formation of the hem. As an alternative, hemming may be completed with seam type indicated above and the fringe superimposed on the hem and evenly attached around the flag with a single row of stitching through the center of the fringe using seam type LSa-1.

Source: https://assist.dla.mil -- Downloaded: 202640-18T04:17Z
Check the source to verify that this is the currentversion before use.

3.5.2 Flags.

3.5.2.1 Type I, class 1 flags. All type I, class 1 flags, (blanks only) shall be fabricated on one thicknesse of base material. Components shall be closely trimmed and appliqued to base material on both sides of flag and shall appear as if printed through in the location indicated on drawings 5-6-1B and 5-6-2. The applique thread specified in 3.3.2 shall match the edge color of the component being appliqued. When two thicknesses of base material are used, the flag shall be joined so that no excessive puckering occurs. The blank shield shall be aligned and stitched through both thicknesses of material around the outside edge and shield. The shield portion of flag shall not be askew on either single or double thickness flags. A tolerance of +0, -1/8 inch will be allowed in both vertical and horizontal measurements of shield. Single thickness flags components shall be aligned with applique stitching catching the outside edge of embroidered components with no stitching showing on base material or within embroidery areas other than outside edge. For double thickness flags, components shall be aligned and stitched on each thickness of material and then the two pieces of base cloth stitched together. For completion of flags see applicable drawing or painting for unit designation, Coat of Arms or Crest.

3.5.2.2 Type II, class 1, style 1 flags. All type II, class 1, style 1 flags (blanks only) shall be fabricated of one thickness of material. The embroidered Coat of Arms shall be aligned and appliqued to both sides of base material and shall appear as if printed through. A maximum of 1/2 inch of applique material shall extend from embroidery edge. The white stars shall be appliqued back to back on both sides of base cloth using the same type fabric as the base material. The thread shall match the color of the applique material. The shield and scroll shall be indicated on the front side with a white stamping paste dotted line. The location of the eagle, stars, shield and scroll shall be as indicated on drawings 5-100-1 and 5-100-1B. For completion of flags, see applicable drawing for Organizational Coat of Arms and unit designation.

3.5.2.3 Type II, class 1, style 2 flags. All type II, class 1, style 2 flags shall be fabricated on one thickness of material. The embroidered components shall be located on both sides of base material and when appliqued shall appear as if printed through. The embroidered eagle shall be appliqued so that a maximum of 1/2 inch of applique material extend from the edge of the embroidery. The white stars shall be appliqued back to back on both sides of base cloth using the same type fabric as the base material. The color of the thread shall match the color of the applique material. The applique stitching for the shield nebula, and scroll shall completely cover the running stitching. The width and color of the applique stitching shall be as specified on drawing. The details for finishing Style 2 flags shall be as indicated as drawings 5-101-3, 5-101-3A and 5-100-1B.

Source: https://assist.dla.mil -- Downloaded: 202610-18T04:17Z
Check the source to verify that this is the current version before use.

3.5.2.4 Type II, class 1, style 3 flags. All type II, class 1, style 3 flags shall be fabricated on one thickness of material. The embroidered components shall be located on both sides of the base cloth and shall appear as if printed through. A maximum of 1/2 inch of base material may extend beyond the edge of the embroidery, when the embroidered eagle is appliqued to the base material. The white stars shall be appliqued back to back on both side of base material using the same type fabric as the base material. The color of the applique thread shall match the color of the appliqued material. The applique stitching for the shield nebula and scroll shall completely cover the running stitching. The width and color of the applique stitching shall be as specified on the drawing. The details for finishing the flags shall be as indicated on drawings 5-101-1 and 5-101-1A.

3.5.2.5 Type II, class 2 flags. All type II, class 2 flags shall be fabricated of one thickness of material. The embroidered components shall be located on both sides, as shown on the applicable drawing (see 2.1), and shall appear as printed-through. The stars shall be white or blue banner cloth appliqued as indicated on the applicable drawing. Except for diagonal stitching required on the style 4 and 5 flags, the color of thread shall match the color of the base material, either white or blue. The applique stitching used for appliqueing the shield, nebula and scroll shall completely cover the running stitching in the width specified on the drawing. For the diagonal seam in style 4 and 5 flags, the ultramarine blue and white base cloth shall be joined using seam type LSc-2, with stitch type 301. The thread color shall match the color of the base fabric sewn. Finishing details for complete flag shall be as shown on the applicable individual flag drawing.

3.5.2.6 Type III. All type III flags shall be fabricated on one or two thickness of base material. Components shall be closely trimmed to the embroidered edge and appliqued to base material on both sides of the flag and shall appear on the reverse as if printed through in the location indicated on drawing 5-MC-1, sheet 1, except the landmasses and lettering shall appear as illustrated on drawing 5-MC-1, sheet 2, on both sides of the flag. The color of the applique thread specified in 3.3.2 shall match the embroidery edge of the component being appliqued. Single thickness component flags shall be aligned with no applique stitching showing on base material or within embroidery areas other than the outside edge. For double thickness flags, components shall be aligned as required by the design and stitched on each thickness of material and then the two pieces of base cloth stitched together. The border and folds of the scrolls will be formed by using an applique stitch and form the design as indicated on drawing 5-MC-1, sheet 3. The design of both scrolls will appear as if printed through on the reverse with the lettering reading from left to right on both sides. The ends of the bottom scroll shall be formed using the same fabric as the component with lettering and joined with an applique stitch at the fold indicated on the drawing. The upper shaded area on the fold of the bottom scroll will be hand embroidered.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:17Z
Check the source to verify that this is the current version before use.

3.5.3 Heading. The heading of all flags shall be the tube or tunnel type for insertion of a flagstaff, and shall be made with cotton sheeting specified in 3.3.4. The construction and dimensions shall be as specified for type II headings on drawing 5-1-45E, stitch type 301 shall be used with 12 stitches per inch. The sheeting shall be 6 inches wide and 5 inches longer than the hoist of the flag. Each end shall be folded under 2-1/2 inches. The sheeting shall be fitted with a tab of leather specified in 3.3.5 at each end. Each tab shall be 3/4 inches, plus or minus 1/16 inch wide, and not less than 2 inches long. Each tab shall have a slit and eyelet 3/4 inch, plus or minus 1/16 inch long, for fastening over a knob or a button on the flagstaff. The slit and eyelet shall be centered on the width of the tab shown on the applicable drawing. The tab shall be placed within the heading and centered opposite the stitching of the hem. The tab shall be secured through the two thicknesses of lining by box stitching, as shown on the applicable drawing. As an alternate, the leather tabs may be secured by stitching through both lining and heading material. Stitching shall be securely backstitched. The contractor's label specified in 3.5.4, shall be affixed at the same time the tabs are placed on the sheeting. The sheeting strip shall be placed on the back of the flag at the hoist end with the folded ends of the strip flush with the hemmed or selvage edges of the flag at the top and attached thereto by a single row of stitching across each folded end of the strip. The raw edge side of the stitching shall be placed 1/2 inch from the raw edge of the flag. The tube or tunnel shall then be formed by hemming the hoist end of the flag with the sheeting strip inside. Sheeting may also be seamed separately with a 1/2 inch seam to form a tunnel. Turn under hoist edge of flag 1/2 inch and insert under the folded side edge of sheeting strip. Turn under and stitch with a single or double row of stitching (3/16 inch margin), which shall pass through both the turned edge of the flag and both edges of the unseamed or seamed lining strip. The flat width of the finished hem shall not be less than 2-3/4 inches.

3.5.4 Marking. The contractor shall affix a label conforming to type VI, class 5 of DDD-L-20, adjacent to top leather strap, on all flags having a type II heading.

3.6 Workmanship. Flags shall be clean, well made, and shall meet the acceptable quality levels established by this specification. All stitching which is not caught up by a seam or other stitching shall be backstitched a minimum of one inch. Thread tension shall be maintained throughout and all thread ends shall be trimmed.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:17Z
Check the source to verify that this is the current version before use.

requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Certificate of compliance. Where certificate of compliance are submitted, the Government reserves the right to check test such items to determine the validity of the certificate.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4).
b. Quality conformance inspection (see 4.5).

4.3 Inspection conditions. Unless otherwise specified, all inspections shall be performed in accordance with the test conditions specified in (applicable test method document or applicable paragraph(s) in the specification).

4.4 First article inspection. When a first article is required, examination shall be made on a completely fabricated flag for all provisions of this specification applicable to end product examination and tests.

4.5 Quality conformance inspection. Inspection shall be in accordance with the provisions set forth in MIL-STD-105, except where otherwise indicated.

4.5.1 Inspection of component.

4.5.1.1 Testing of component. In addition to the quality assurance provisions of the subsidiary specifications and standards, inspection shall be performed on components and materials listed in table I. The inspection level shall be S-1 and the acceptable quality level (AQL) shall be 6.5 defects per hundred units. The sample unit for the inspection shall be one cone or spool.

Source: https://assist.dla.mil -- Downloaded: 202640-18T04:17Z
Check the source to verify that this is the currentversion before use.

TABLE I. Testing of component.

Component and lot expressed in terms of	Character-istic	Rqm't ref	Test method 1/	Rqm't indi vidual unit	Appl to lot aver-age	#determ per sample unit	Results reported as
Silk or cotton em-broidery thread	Breaking strength	3.3.2.3	4102	-	x	-	-
(1 cone or spool)	Length weight	3.3.2.3	4010	-	x	-	-

1/ Test will be in accordance with FED-STD-191.

4.5.2 Inspection of the end item.

4.5.2.1 Visual examination of flags. The defects found during examination shall be classified in accordance with 4.5.2.1.1 and 4.5.2.1.2. The lots shall be inspected in accordance with 4.5.2.1.1 or 4.5.2.1.2, when applicable. The unit of product for these examinations shall be one flag.

4.5.2.1.1 Examination of flags for defects in material, design, construction, workmanship and marking. Examination shall be made at a distance of 18 to 40 inches with good illumination except for functional defects which by their nature, require closer examination. Defects designated by an asterisk (*) shall be classified as major when seriously affecting serviceability or appearance and minor when affecting serviceability or appearance, but not seriously.

TABLE II. Classification of defects.

Examine	Defects	Classification Major	*	Minor
Quality of cloth:				
Type	Any component not fabricated of specified material	-	*	-
Color	Basic color other than specified. . .	x	-	-
	Off shade	-	*	-
Material	Hole, cut, tear, smash or weak place.	-	*	-
	Spot, stains, streaks or shade bars (considering the use position) . . .	-	*	-
	Two or more contiguous broken, missing ends or picks in flag base material.	x	-	-
	Double pick, course pick or mispick .	-	*	-
	Slub, slough-off, float or skip . . .	-	*	-

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:17Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of defects - Continued.

Examine	Defects	Classification		
		Major	*	Minor
Quality of embroidered components	Color not as specified.	-	*	-
	Design not as specified	x	-	-
	Area of missing or incomplete stitching	x	-	-
	Defect in base material surrounding embroidery	-	*	-
	Stain or spots.	-	*	-
	Area of base cloth around embroidered component not as specified	x	-	-
Schiffli embroidery components (emblem, insignia, lettering, etc.)	Broken stitches	-	*	-
	Not applied as specified.	x	-	-
	Design or parts of design, reversed or inverted.	x	-	-
	Lettering does not read from right to left on both sides (unless otherwise specified)	x	-	-
	Design not oriented on each side of flag, as specified	x	-	-
	Pattern marks used for location of design clearly visible and in accordance with applicable drawing	-	*	-
	Design or insignia not neatly trimmed	-	*	-
	Evidence that sizing or stiffening agent, used as an aid in sewing, has deleterious effect	-	*	-
	No visible pattern marks showing on finished flag.	-	*	-
Quality of leather components	Not fabricated of specified leather .	-	-	x
	Hole (other than required), cut, tear or weak place.	x	-	-
Quality of fringe	Material, type construction, color or color combination, not as specified.	-	*	-
	Frayed edges.	-	*	-
	Spotted, stained or soiled.	-	*	-
	Cut or tear	-	*	-
Construction and workmanship general:	Operation omitted or not accomplished as specified	-	*	-
	Flag pieced where piecing is prohibited	x	-	-
	Component is not the required type, class, or size	-	*	-
	Warp threads of the base material of the flag in other than fly direction of the flag, except as permitted in 3.4	-	*	-

Source: https://assist.dla.mil -- Downloaded: 202640-18T04:17Z
Check the source to verify that this is the currentversion before use.

TABLE II. Classification of defects - Continued.

Examine	Defects	Classification		
		Major	*	Minor
	Components not aligned as required. .	x	-	-
	Puckering serious by affecting appearance or serviceability	x	-	-
	Puckering affecting appearance or serviceability but not seriously . .	-	-	x
	Embroidered components not trimmed as required	-	*	-
Stitches, seams and stitching	Wrong type of seam, stitches or stitching.	-	*	-
	Wrong color of thread	-	*	-
	Row of stitches partially or completely missing	-	*	-
	Wrong stitching gauge or margin . . .	-	*	-
	Seams improperly formed, material caught in unrelated stitching operations. .	-	*	-
	Ends of stitching not backstitched at least 1 inch (when not caught in other seams or stitching).	-	*	-
	Run-offs resulting in open seam . . .	-	*	-
	Needle chews.	-	*	-
	Any raw edge exceeding 1/2 inch in length	-	-	x
	Loose stitch tension resulting in a loosely secured seam	x	-	-
	Tight stitch tension (stitches break when normal pull is exerted in length-wise direction of seam or stitching.	x	-	-
	Stitches per inch for seams and hems: Four or more stitches less than specified	x	-	-
	One to three stitches less than specified	-	-	x
	Stitches per inch for Appliqueing: Five or more stitches less than specified	x	-	-
	One to four stitches less than specified	-	-	x
	Seams twisted, pleated or puckered. .	-	*	-
	More than two continuous skipped stitches	-	*	-
	Broken stitches in heading seam causing an unstitched length of one inch or more	x	-	-

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:17Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of defects - Continued.

Examine	Defects	Classification Major	*	Minor
	Broken stitches in heading seam causing an unstitched length of less than 1 inch	-	-	*
	Broken stitches in any other seam causing an unstitched length of less than 1/2 inch.	-	-	x
Hems	Nylon flags not hemmed on all edges .	x	-	-
	Hem uneven.	-	*	-
	Hem on wrong side of flag	-	-	x
Fringe	Not completely attached as specified.	x	-	-
Heading (type II)	Sheeting all or partially missing . .	x	-	-
	Heading improperly formed, e.g., both edges of the sheeting or hoist end of flag not caught entire length by heading seam	-	-	x
	Leather tabs not positioned and attached as shown on drawings. . . .	-	-	x
Marking	Missing, incorrect, illegible, text incomplete; marking in wrong location, size of lettering not as specified or color or marking, not as specified .	-	-	x
Label	Text incomplete or incorrect, not attached as specified, not in location specified or not in position specified.	-	-	x

4.5.2.1.3 Inspection levels. One hundred percent inspection shall be performed on the end item flag. A flag shall be rejected if over five major defects are found or if any major defect cannot be repaired.

4.5.2.1.4 Examination of count of flags in intermediate containers. Flags packaged for shipment shall be examined to determine conformance with package markings and specified quantity. The sample unit for this examination shall be one box (interior package). Any box containing less than the specified or marked quantity of flags shall be classified as defect. The inspection level shall be S-2 and the AQL shall be 4.0 defects per hundred units.

4.5.3 Examination of preparation for delivery requirements. An examination shall be made to determine that packaging, packing and marking requirements of section 5 of this specification are complied with. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping contai-

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:17Z
Check the source to verify that this is the current version before use.

ner fully prepared for delivery with the exception that it need not be sealed. Defects of closure listed below shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and the AQL shall be 4.0 defects per hundred units.

Examined	Defects
Marking (exterior and interior)	Omitted, incorrect, illegible, of improper size, location, sequence or method application.
Materials	Any component missing. Any component damaged, affecting serviceability.
Workmanship	Inadequate application of components, such as incomplete closure of case liners, container flaps, loose strapping, or inadequate strapping. Bulging or distortion of containers.
Weight	Net weight exceeds requirements.

4.5.4 Palletization examination. An examination shall be made to determine that the palletization complies with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one palletized unit load fully packaged. The lot size shall be the number of palletized unit loads in the inspection lot. The inspection level shall be S-1 and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirements.
Palletization	Pallet pattern not as specified. Interlocking of loads not as specified. Load not bonded with required straps as specified.
Weight	Exceeds maximum load limits.
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.

5. PACKAGING

5.1 Preservation. Preservation shall be levels A, C, or commercial as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 202610-18T04:17Z
Check the source to verify that this is the current version before use.

5.1.1 Level A.

5.1.1.1 Unit packaging. Each flag shall be laid out flat on two thicknesses of tissue paper conforming to type I, grade A, class 1 of UU-P-553. Tissue paper shall overlap all edges of flag a minimum of two inches. Each flag combined with overlaping tissue paper, shall be rolled, open width, on a chipboard tube. The tissue paper overlapping the tube ends shall be tucked inside the tube ends. Each flag shall be tightly wrapped with 50-pound minimum basis weight kraft paper conforming to grade B of UU-P-268. The closure shall be sealed with 2 inch minimum width gummed paper tape. Each wrapped flag shall then be individually packaged in an applicable paperboard folding, or set-up box, fiberboard box or metal stay paperboard box.

5.1.1.2 Intermediate packaging. Unless otherwise specified, flags preserved as specified in 5.1.1.1, shall be packaged in multiples of 10 within a snug fitting intermediate fiberboard container conforming to class domestic, grade 275 of PPP-B-636. The net weight of contents in each container shall not exceed 65 pounds. Closure shall be in accordance with the appendix of the specification. The use of Scotch Brand box closing filament tape no. 898 or equal, 1/2 inch, using a minimum of two 1/2 inch x 4 inch ("L" clips) on each edge, may be utilized as an alternate method for effecting closure of set-up boxes.

5.1.2 Level C. Assembled flags shall be preserved and packaged in a manner which will afford adequate protection against corrosion, deterioration and physical damage during shipment from the supply source to the first receiving activity.

5.1.3 Commercial. Flags shall be preserved in accordance with the applicable requirements of ASTM-D-3951.

5.2 Packing. Packing shall be level A, C or Commercial as specified (see 6.2).

5.2.1 Level A. Flags preserved as specified in 5.1, shall be packed in a snug-fitting shipping container conforming to type CF, grade V3c or W5c or type SF, grade V3c or W5s of PPP-B-636. Closure shall be in accordance with the applicable container specification.

5.2.2 Level B. Flags preserved as specified in 5.1.1.3, shall be acceptable as level B pack.

5.2.3 Level C. Flags preserved as specified in 5.1, shall be packed to the MIL-STD-794 requirements for this level.

5.2.4 Commercial. Flags shall be preserved in accordance with the applicable requirements of ASTM-D-3951.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:17Z
Check the source to verify that this is the current version before use.

5.3 Marking. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with MIL-STD-129 or ASTM-D-3951 as applicable.

5.4 Palletization. Unitized loads, commensurate with the level of packing specified in the contract or order, shall be palletized in accordance with MIL-STD-147. Palletized loads shall be uniform in size and quantities to the greatest extent possible. If the container is of a size which does not conform to any of the pallet patterns specified in MIL-STD-147, the pallet pattern used shall first be approved by the contracting officer.

6. NOTES

6.1 Intended use. The flags covered by this specification are intended to be used by individuals and Military organizations for identification.

6.2 Ordering data.

6.2.1 Ordering data. Procurement documents should specify the following:

a. Title, number and date of this specification.
b. Type, class and style (see 1.2).
c. When a first article is required (see 1.2).
d. Title of flag required (see 1.2).
e. Applicable drawings (see 2.1).
f. Type of base material if other than specified (see 3.3.1).
g. Selection of applicable levels of packaging and package (see 5.1 and 5.2).

6.3 Samples. For access to samples, address the contracting activity issuing the invitation for bids.

6.4 First article. When a first article inspection is required, the item should be a first article sample or it may be a standard production item from the contractor's current inventory as specified in 4.2. The first article should consist of one completed flag. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, approval of first article test results and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract.

Source: https://assist.dla.mil -- Downloaded: 202640-18T04:17Z
Check the source to verify that this is the current version before use.

6.5 Changes from previous issue. Asterisks or vertical line are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:
Army - IH
Air Force - 11
Navy - NU

Review activities:
Air Force - 82,99
Navy - MC

User activities:
Air Force - 45

Preparing activity:
Army - IH

(Project No. 8345 - 0164)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:17Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY
The Institute of Heraldry,
US Army
Cameron Station
Alexandria, VA 22314

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Director
The Institute of Heraldry, US Army
ATTN: DAAG-HDT
5010 Duke Street
Alexandria, VA 22314

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:17Z
Check the source to verify that this is the current version before use.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-F-14648A	Flags, Organizational and Statutory, General Specification for

3a. NAME OF SUBMITTING ORGANIZATION

b. ADDRESS *(Street, City, State, ZIP Code)*

4. TYPE OF ORGANIZATION *(Mark one)*

- ☐ VENDOR
- ☐ USER
- ☐ MANUFACTURER
- ☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:17Z
Check the source to verify that this is the current version before use.