MIL-I-14647A
20 January 1987
SUPERSEDING
MIL-S-14647(USAF)
15 November 1979

MILITARY SPECIFICATION

INSIGNIA, RANK AND GRADE, SHOULDER MARKS, ROTC CADETS, ARMY AND AIR FORCE (EMBROIDERED)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification establishes the requirements for shoulder marks worn by Army and Air Force ROTC Cadets to indicate rank or grade.

1.2 Classification. The shoulder marks covered by this specification shall be of the following types, sizes and classes (see 6.2).

Type I - Army Cadet, Officers
Type II - Air Force Cadet, Officers
- Size 1 - Large
- Size 2 - Small
- Class 1 - Colonel
- Class 2 - Lieutenant Colonel
- Class 3 - Major
- Class 4 - Captain
- Class 5 - First Lieutenant
- Class 6 - Second Lieutenant

Type III - Army Cadet Noncommisioned Officer
- Size 1 - Large
- Size 2 - Small
- Class 1 - Command Sergeant Major
- Class 2 - Sergeant Major
- Class 3 - First Sergeant
- Class 4 - Master Sergeant

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: Director, The Institute of Heraldry, US Army, Cameron Station, Alexandria, VA 22304-5050, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:17Z
Check the source to verify that this is the current version before use.

Class 5 - Sergeant First Class
Class 6 - Staff Sergeant
Class 7 - Sergeant
Class 8 - Corporal

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

V-T-285 - Thread, Polyester
NN-P- 71 - Pallet, Material Handling, Wood, Stringer Construction, 2-way and 4-way (partial)
PPP-B-636 - Boxes, Shipping Fiberboard
PPP-B-676 - Boxes, Setup

MILITARY

MIL-C-83448(USAF) - Cloth, Serge, Polyester, Texturized
MIL-E-17568 - Embroidery Materials, Metallic and Synthetic Metallic
MIL-P-15011 - Pallet, Material Handling, Wood, Post Construction, 4-way entry

STANDARDS

FEDERAL

FED-STD-191 - Textile; Test Methods
FED-STD-751 - Stitches, Seams, and Stitchings.

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized unit loads
MIL-STD-794 - Part and Equipment, Procedures for Packaging and Packing of

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:17Z
Check the source to verify that this is the current version before use.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS

THE INSTITUTE OF HERALDRY

B-3- 99 - Air Force ROTC Shoulder Marks - Male
B-3- 100 - Air Force ROTC Shoulder Marks - Female
B-3- 112 - Army ROTC Shoulder Marks Cadet Officers - Large
B-3-112A - Army ROTC Shoulder Marks Cadet Officers - Small
B-3- 113 - Army ROTC Shoulder Marks Cadet Officers - Large
B-3-113A - Army ROTC Shoulder Marks Cadet Officers - Small
B-3- 114 - Army ROTC Shoulder Marks Cadet Noncommissioned Officer - Large
B-3-114A - Army ROTC Shoulder Marks Cadet Noncommissioned Officer - Small
B-3- 115 - Army ROTC Shoulder Marks Cadet Noncommissioned Officer - Large
B-3-115A - Army ROTC Shoulder Marks Cadet Noncommissioned Officer - Small

(Copies of specifications, standards, and other Governments documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

THE COLOR ASSOCIATION FOR THE UNITED STATES

The Standard Color Reference of America, Tenth Edition

United States Army Color Card, The Official Colors for Branches, Agencies, etc.

DOD Standard Shades for Heraldic Yarns for Embroidery and Ribbons 1974.

(Application for copies of the color cards should be addressed to the Color Association of the United States, Inc., 343 Lexington Ave. New York, NY 10016.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:17Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM-D-3951 - Standard Practice for Commercial Packaging.

(Application for copies of ASTM publications should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pennsylvania 19103.)

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, (except for associated detail specifications, specification sheets or MS standards) the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Standard sample. Unless otherwise specified (see 6.2), samples shall be furnished by the contracting officer to be used for guidance, information and as a standard for design and workmanship. Variation from this specification may appear in the guide samples in which event the specification shall govern.

3.2 First article. Unless otherwise specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.4 and 6.4).

3.3 Material.

3.3.1 Cloth, laminated. The laminated cloth shall be composed of two layers of cloth bonded together with an adhesive by heat and pressure. One layer to be texturized polyester cloth (shell fabric) see paragraph 3.3.1.2 and the other to be a fusible cloth referenced in paragraph 3.3.1.1. The laminated cloth shall show good adhesion between the two fabrics and show no bubbles or puckering in the shell fabric before or after dry cleaning.

3.3.1.1 Cloth, fusible. - The fusible cloth shall be a cotton cloth printed with a polyamide adhesive containing a minimum of 300 dots per square inch.

3.3.1.1.1 Cloth, cotton. The weave for the cotton cloth shall be plain and weight shall be 4 to 5 ounces per square yard. The maximum shrinkage shall be 2 percent warp and filling. The color of the cotton cloth shall be white or greige.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:17Z
Check the source to verify that this is the current version before use.

3.3.1.2 Cloth, texturized polyester (shell fabric). The top layer of the laminated cloth shall be a texturized polyester material conforming to MIL-C-83448 (USAF) and shall show good fastness to wet-dry cleaning, perspiration, light, laundry, and crocking. The color of the texturized polyester shall be Black, Cable No. 65018 for type II and III shoulder marks and shall be Army Green AG344 for type I shoulder marks.

3.3.1.2.1 Color. Unless otherwise specified, the color of the embroidery yarns shall be as shown on the applicable cartoon or drawing. The use of sulphur dyes is prohibited.

3.3.1.2.2 Colorfastness. When tested as specified in 4.6.1, the dyed embroidered yarn shall show good fastness to wet-dry cleaning, bleaching, or light, and fair fastness to laundering except that for black, blue, and red shades, the fastness to bleaching shall be not less than fair as defined in FED-STD-191.

3.3.1.2.3 Matching. The color shall match the standard sample when viewed under filtered tungsten lamps which approximate artificial daylight having a correlated color temperature of 7000 plus or minus 500 K, with illumination of 100 plus or minus 20 foot candles, and shall be a good match to the sample under incandescent lamplight at 2300 plus or minus 100 K. The degree of luster shall be equal to the standards established in the DOD Standard Color Card of Official Standardized Shades for Heraldic Yarns for Embroidery and Ribbons, 1974.

3.3.2 Thread. The thread for hemming the shoulder mark shall be polyester and conform to type I, class 1, letter size AA, 2 ply of V-T-285. The thread shall match the color of the top layer of the laminated cloth.

3.3.3 Embroidery yarn.

3.3.3.1 Synthetic metallic embroidery yarn. The synthetic metallic yarn for embroidery shall conform to type III, class 8 or 9 of MIL-E-17568 with the following exceptions:

a. The finished yarn size shall be 260 (plus or minus) 15 denier.

b. The yarn shall have sufficient turns per inch to insure proper uniformity of the metallic ribbon wrapped around the core and can be used on any type of embroidery machine to meet specification requirements.

3.3.3.2 Rayon embroidery yarn. The rayon embroidery yarn shall be semi-dull, continuous filament, regenerated cellulose type rayon, two-ply yarn. The yarn size and color shall be specified on the applicable cartoon or drawing. The yarn shall show good colorfastness to wet-dry cleaning, perspiration, laundering and light.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:17Z
Check the source to verify that this is the current version before use.

3.4 Design. The design of each shoulder mark shall be as shown on the applicable drawing.

3.5 Construction.

3.5.1 Embroidering. The device for each class of shoulder mark shall be machine embroidered on the face side of the texturized polyester cloth. The applicable yarn shall be as specified in 3.3.3.1 for type II insignia and as specified in 3.3.3.2 for type I and III insignia. The embroidered device shall conform to the applicable cartoon furnished by the Government and will become a part of this specification. The embroidery stitches shall be of the type, color, length, minimum number, and density specified by the applicable cartoon. Sufficient base cloth shall be allowed in all directions so shoulder marks can be properly hemmed and joined together.

3.5.2 Cutting. After insignia have been embroidered, material shall be cut so that the finished shoulder mark will conform to the measurements specified on applicable drawing.

3.5.3 Hemming. The hemming shall be executed at the location indicated on the applicable drawing. Each hem shall have a minimum of 10-12 stitches per inch using a type 301 stitch of FED-STD-751. All ends of stitching not caught in other seams or stitching shall be backstitched a minimum of 1/2 inch. Hems shall be 3/8 inch, plus 1/8, minus 0 inch wide and stitching shall be located 1/8 inch, plus 0, minus 1/16 inch from the turned edge.

3.5.4 Pressing. The finished shoulder mark snall be pressed so that the item has the shape shown on the applicable drawing.

3.6 Workmanship. The finished shoulder mark shall be clean, well-made and shall conform to the quality and grade of product established by this specification.

3.7 Tolerances. Unless otherwise specified herein or on the applicable drawing, dimensions shall be within a tolerance of plus or minus 1/32 inch.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:17Z
Check the source to verify that this is the current version before use.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. The inspections specified herein are classified as follows:

a. First article inspection (see 4.4).

b. Quality conformance inspection (see 4.5).

4.3 Inspection conditions. Unless otherwise specified, all inspections shall be performed in accordance with the test conditions specified in applicable test method document or applicable paragraph(s) in the specification.

4.4 First article inspection. Inspection and testing of the first article sample shall be made on a completely finished item for all provisions of this specification applicable to the end product examination and test.

4.5 Quality conformance inspection. Inspection shall be in accordance with provisions set forth in MIL-STD-105, except where otherwise indicated.

4.5.1 Quality assurance inspection. Inspection shall be in accordance with the provisions set forth in MIL-STD-105 except when otherwise specified hereafter.

4.6 Component and material inspection. In addition to the quality assurance provisions of the subsidiary specifications and drawings, inspection shall be performed on components and materials as specified herein.

4.6.1 Testing of components. Components shall be tested as specified in table I. The test methods listed in table I shall be in accordance with FED-STD-191, wherever applicable. The sample unit for testing shall be as follows:

1/4 continuous yard full width of the laminated cloth.
1-1/2 continuous yards full width of the fusible cloth.
1-1/2 continuous yards full width of the cotton cloth.
3-1/2 continuous yards full width of the texturized cloth.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:17Z
Check the source to verify that this is the current version before use.

The sample unit for thread and embroidery yarn shall be five continuous yards each. The lot shall be unacceptable if one or more units fail to meet any requirement specified. The sample size shall be as follows:

Lot size (yd)	Sample size (units)
Less than 800	2
801 to 22,000	3
22,000 and over	5

TABLE I Component test.

Component characteristic	Rqm't para	Test method	#Determ per s/u	Results reported as
Laminated cloth				
Wet-dry cleaning	3.3.1	5622		Pass or fail
Fusible cloth				
Amount of adhesive	3.3.1.1	Visual 1/		Pass or fail
Cotton cloth				
Material identification	3.3.1.1.1	1/		Pass or fail
Weave	3.3.1.1.1	Visual	1	Pass or fail
Weight	3.3.1.1.1	5041		Nearest 0.1 oz/sq yard
Shrinkage	3.3.1.1.1	5550		Nearest 0.1 oz/sq yard
Texturized polyester cloth (shell fabric)				
Material identification	3.3.1.2	1/		
Colorfastness to:				
Wet-dry cleaning	3.3.1.2	5622		Pass or fail
Perspiration	3.3.1.2	5680		Pass or fail
Light	3.3.1.2	5660 2/		Pass or fail
Laundry	3.3.1.2	5610		Pass or fail
Crocking	3.3.1.2	5651		Pass or fail
Synthetic metallic embroidery yarn				
Material identification	3.3.3.1 1/			
Denier	3.3.3.1			Pass or fail
Turns	3.3.3.1			Pass or fail
Rayon embroidery yarn				
Material identification	3.3.3.2 2/			
Denier	3.3.3.2			Pass or fail

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:17Z
Check the source to verify that this is the current version before use.

TABLE I Component test - continued.

Component characteristic	Rqm't para	Test method	#Determ per s/u	Results reported as
Colorfastness to:				
Wet-dry cleaning	3.3.1.2.2	5622		Pass or fail
Perspiration	3.3.1.2.2	5680		Pass or fail
Laundry	3.3.1.2.2	5610		Pass or fail
Light	3.3.1.2.2	5660 2/		Pass or fail

1/ Unless otherwise specified a contractor's certification of compliance may be accepted as evidence of conformance.

2/ In the event of a dispute resulting from the test with method 5660, or as a result of suspected anomalous behavior of certain dye types of formulations, the contracting officer may authorize the exposure to natural light in accordance with method 5662.

4.7 End item examination.

4.7.1 Visual examination of the end item. Defects found during this examination shall be classified in accordance with table II. The sample unit for this examination shall be one finished pair of shoulder marks. The acceptable quality level (AQL) for this examination shall be 6.5 defects per 100 units. The inspection level shall be level II.

TABLE II. Classification of visual examination defects

Examine	Defects
Material defects (Texturized polyester)	Manufacturing defects, such as hole, float, broken end or pick, slub, lump, knot, stain, streak, clearly visible.
Embroidery device	Any device missing or mispositioned affecting appearance. Not underlaid to show a well raised effect. Details or device incomplete. The device is not centered. Wrong color of cover stitches. Wrong type embroidery yarn. Loose tension or tight tension clearly noticeable or resulting in poorly defined design. Embroidered device not extending beyond the creased line for type II and III shoulder marks. Stitching incomplete (miss).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:17Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of visual examination defects - continued.

Examine	Defects
	Ragged, broken or loose stiele stitching.
	Stitching missing.
	Any shift affecting appearance.
	Device appearing askew.
	Not in accordance with applicable cartoon.
Laminated cloth	Visible bubbles and puckering seen on shell fabric before or after dry cleaning.
Thread	Thread not a good color match to polyester cloth.
Workmanship	Spot or stain clearly noticeable.
	Misshaped or distorted insignia, affecting appearance.
Seams and stitching	Loose ends not backstitched a minimum of 1/2 inch.
	Loose tension, noticeably affecting appearance.
	Basting stitch or cutting mark showing on face or back of insignia.
	Any open seam on hems and joining seam.
	Tight tension, i.e., fabric puckers excessively.
	Seams crooked or irregular, affecting appearance.
	Finished hem not 3/8 to 1/2 inch in width.
	Stitching on hems not 1/16 to 1/8 inch from turned edge.
	Less than 10 or more than 12 stitches per inch.
	Wrong stitch type.
Pressing	Singed or scorched.
	Clearly visible creases or gloss marks.
	Misshaped by pressing.
	Color change clearly noticeable.

4.7.2 Examination for shoulder marks for defects in dimensions. Any dimension that is not within the specified tolerances shall be classified as a defect. The AQL shall be 6.5 defects per 100 units and the inspection level shall be S-1. The sample unit shall be one finished pair of shoulder marks.

4.7.3 Examination of paired shoulder marks for compatible synthetic metallic yarn color match. Any paired shoulder marks in which the synthetic yarn is not a good color match shall be classified as a defect. The AQL shall be 1.5 defects per hundred units and the inspection level shall be S-4. The sample unit shall be one finished pair of shoulder marks.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:17Z
Check the source to verify that this is the current version before use.

4.7.4 Examination for count shoulder marks in intermediate containers. Shoulder marks packaged for shipment shall be examined to determine conformance with package markings and specified quantity. The sample unit for this examination shall be one box (interior package). Any box containing less than specified or marked quantity of shoulder marks shall be classified as a defect. The inspection level shall be S-2 and the AQL shall be 2.5 defects per hundred units. The lot size shall be the number of intermediate containers offered for delivery.

4.7.5 Inspection of packaging. An examination shall be made to determine that packaging, packing and marking requirements of section 5 of this specification are complied with. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully prepared for delivery with the exception that it need not be sealed. Defects of closure listed below shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lots. The inspection level shall be S-2 and the acceptable quality level (AQL) shall be 2.5 defects per hundred units.

4.7.6 Examination of preparation for delivery requirements. An examination shall be made to determine that the packaging, packing and marking requirements of section 5 of this specification are complied with. Defects shall be scored in accordance with table III. The sample unit shall be one shipping container fully prepared for delivery with the exception it need not be sealed. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and AQL shall be 4.0 defects for hundred units.

TABLE III. Classification of preparation for delivery defects.

Examine	Defect
Marking (exterior and interior)	Omitted, incorrect, illegible, of improper size, location, sequence or method of application.
Materials	Any component missing. Any component damaged.
Workmanship	Inadequate application of components, such as incomplete closure of container flaps, improper taping, inadequate stapling.
Contents	Number of unit packages per intermediate box is more or less than required. 1/ Number of intermediate boxes per shipping container is more or less than required. Number of shoulder marks per unit package is more or less than required.

1/ For this defect, one intermediate box shall be examined from each shipping container in the sample.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:17Z
Check the source to verify that this is the current version before use.

4.7.7 Palletization examination. An examination shall be made to determine that the palletization is in compliance with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one palletized unit load fully packaged. The lot size shall be the number of palletized unit loads in the inspection lot. The inspection level shall be S-1 and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirements.
Palletization	Pallet pattern not as specified. Interlocking of loads not as specified. Load not bonded with required straps as specified.
Weight	Exceeds maximum load limits.
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.

5. PACKAGING

5.1 Preservation. Preservation shall be levels A, C or Commercial as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Unit packaging. One pair of shoulder marks of one type size and class only, shall be placed in a snug-fitting polyethylene bag fabricated from film having a minimum thickness of 0.002 inch. In addition, the shoulder marks shall be paired to assure a good color match of the synthetic metallic yarn. All seams and closures shall be effected by heat sealing. Prior to, or during the heat sealing operation, excess air within the bag shall be expelled.

5.1.1.2 Intermediate packaging. Fifty pairs of one type, size and class as specified in 5.1.1.1, shall be preserved in a snug-fitting, set-up paperboard box conforming to type I, style 4 of PPP-B-676. Closure shall be in accordance with the appendix of the container specification.

5.1.2 Level C. Shoulder marks shall be preserved to the MIL-STD-794 requirements for this level.

5.1.3 Commercial. Shoulder marks shall be preserved in accordance with the applicable requirements of ASTM-D-3951.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:17Z
Check the source to verify that this is the current version before use.

5.2 Packing. Packing shall be level B, C or commercial as specified (see 6.2).

5.2.1 Level B. Shoulder marks preserved as specified in 5.1.1.2, shall be packed in a snug-fitting shipping container conforming to type CF or SF, class domestic, grade 275, style RSC of PPP-B-636. Closure shall be in accordance with appendix of the container specification. Maximum gross weight shall not exceed 65 pounds.

5.2.2 Level C. Shoulder marks preserved as specified in 5.1, shall be packed in a manner to assure carrier acceptance and safe delivery at destination at the lowest transportation rates for such supplies. Containers shall be in accordance with the rules and regulations of the carriers applicable to the mode of transportation.

5.2.3 Commercial. Shoulder marks shall be preserved in accordance with the applicable requirements of ASTM-D-3951.

5.3 Palletization. Items packed as specified shall be palletized on a 4-way entry pallet in accordance with load type 1A of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance bonding means C, K and L, O or P. Pallet pattern shall be in accordance with the appendix of MIL-STD-147. The pallet shall be 4-way, type I, class 1, style 1, size A, wood group I, II, III, or IV of MIL-P-15011, or 4-way, type IV, V or VIII, class 1, style A, size 2, wood group I, II, III or IV, grade A of NN-P-71. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the patterns specified in MIL-STD-147, the pallet pattern used shall be approved by the contracting officer.

5.4 Marking. In addition to any special marking required by the contract or purchase order, unit packs, intermediate boxes, shipping containers, and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM-D-3951, as applicable.

5.4.1 Polyethylene bagged packages. Polyethylene bagged packages shall have the required information legibly printed or stamped in black directly on the bag across the center face or on a white paper label inserted within the bag so as to permit ready identification. The white paper label shall contain the following information:

STOCK NUMBER
NOMENCLATURE
MANUFACTURER'S NAME
CONTRACT NUMBER

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:17Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The embroidered shoulder marks are intended for use by male and female Army and Air Force ROTC cadets.

6.2 Ordering data.

6.2.1 Ordering data. Procurement documents should specify the following:

a. Title, number and date of this specification.
b. Type, size and class required (see 1.2).
c. When a standard will not be furnished (see 3.1).
d. When first article samples are not required (see 3.2).
e. Selection of applicable levels of packaging and packing (see 5.1 and 5.2).
f. When palletization is required (see 5.3).

6.3 Samples. For access to samples, address the contracting activity issuing the invitation to bids.

6.4 First article. When a first article inspection is required, the item should be a first article sample or it may be a standard production item from the contractor's current inventory as specified in 4.4. The first article should consist of one completed shoulder mark. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, approval of first article test results and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract.

6.4 Changes from previous issue. Asterisks or vertical lines are not used in this revision to identify changes because of the numerous changes.

6.5 Subject term (key word) listing.

Insignia
Rank and grade
Shoulder marks
ROTC cadets
Embroidered
Army cadet, officers
Air Force cadet, officers
Army cadet noncommisioned officer

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:17Z
Check the source to verify that this is the current version before use.

Custodians:
Army - IH
Air Force - 11

Review activities:
Air Force - 82,99
Other - CT

User activities:
Air Force - 45

Preparing activity:
Army - IH

(Project No. 8455 - 0228)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:17Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements All users of military standardization documents are invited to provide suggestions This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems Enter in block 6 any remarks not related to a specific paragraph of the document If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered

NOTE This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

The Institute of Heraldry, US Army
Cameron Station,
Alexandria, Virginia 22304-5050

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12062 WASHINGTON D C
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Director
The Institute of Heraldry, US Army
ATTN: DAPC-PDH-T
Cameron Station,
Alexandria, Virginia 22304-5050

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:17Z
Check the source to verify that this is the current version before use.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1 DOCUMENT NUMBER	2 DOCUMENT TITLE
MIL-I-14647A	Insignia, Rank and Grade, Shoulder Marks, ROTC Cadets, Army and Air Force (Embroidered)

3a. NAME OF SUBMITTING ORGANIZATION	4 TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)* _____
b ADDRESS *(Street, City, State, ZIP Code)*	

5 PROBLEM AREAS

a. Paragraph Number and Wording

b. Recommended Wording

c Reason/Rationale for Recommendation

6 REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:17Z
Check the source to verify that this is the current version before use.