MIL-C-10320E
2 December 1982

SUPERSEDING
MIL-C-10320D(ME)
1 February 1977

MILITARY SPECIFICATIONS

COVER, LEVEL ROD, PHILADELPHIA: CANVAS

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a canvas cover for the Philadelphia-type level rod.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified, the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

T-R-571	- Rope, Cotton, or Cotton and Polyester.
V-T-276	- Thread, Cotton.
KK-L-154	- Leather, Cattlehide, (Bag and Case).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Mobility Equipment Research and Development Command, ATTN: DRDME-DS, Fort Belvoir, VA 22060 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 6675

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:55Z
Check the source to verify that this is the current version before use.

CCC-C-419	- Cloth, Duck, Cotton, Unbleached, Plied-Yarns Army and Numbered.
CCC-D-950	- Dyeing and Aftertreating Processes for Cotton Cloths.
PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-636	- Boxes, Shipping, Fiberboard.
PPP-B-640	- Boxes, Fiberboard, Corrugated,Triple-Wall.

MILITARY

MIL-P-116	- Preservation, Methods of.
MIL-T-3530	- Thread and Twine; Mildew Resistant or Water Repellent Treated.

STANDARDS

FEDERAL

FED. STD. No. 751	- Stitches, Seams, and Stitching.

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-130	- Identification Marking of US Military Property.
MIL-STD-1188	- Commercial Packaging of Supplies and Equipment.

(Copies of specifications and standards required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Description. The cover shall consist of a canvas sleeve having one end open and flared to allow insertion of the Philadelphia-type level rod, with attached target.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:55Z
Check the source to verify that this is the current version before use.

3.2 Material. Material shall be as specified herein. Material not specified shall be selected by the contractor and shall be subject to all provisions of this specification (see 6.3).

3.2.1 Cotton duck. Cotton duck shall conform to CCC-C-419, type I hard texture No. 10, weight 14.35 ounces per square yard and finished in accordance with CCC-D-950, type I, class B, inhibitor f, olive drab No. 7.

3.2.2 Thread. Thread shall conform to V-T-276, type I, IA1, for both needle and bobbin. Thread shall be fungus resistant in accordance with MIL-T-3530, type I, class 1.

3.2.3 Tie rope. The tie rope shall conform to T-R-571, class 2, 3/4-inch nominal circumference.

3.2.4 Leather. Leather shall conform to KK-L-154, type II, class 1, style A, and shall be not less than 3/32 inch in thickness.

3.3 Design. The cover shall be canvas duck and shall be 1-3/4 inches square, plus or minus 1/8 inch, and 8-1/2 feet long, plus or minus 1/2 inch. The cover shall be flared at the open end to a width of 8 inches, plus or minus 1/2 inch. The flare shall start not less than 2 feet 5 inches from the open end. The flared portion shall be designed to allow a closing fold over the rod and to be fastened below the target with a tie rope.

3.3.1 Longitudinal seam. A 1/2 inch longitudinal seam conforming to FED. STD. No. 751, type SSe-3(b), shall join the edges of the cotton duck to form the cover.

3.3.2 Binding at open end. The edges of the cover at the open end shall be double-lapped not less than 1 inch wide. Stitching shall conform to FED. STD. No. 751, stitching type EFb-2.

3.3.3 Stitches. All stitches shall conform to FED. STD. No. 751, stitch type 301 or 401, 6 to 9 stitches per inch. All ends of stitching shall be back-stitched not less than 1/2 inch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:55Z
Check the source to verify that this is the current version before use.

3.3.4 Leather boot. A protective leather boot shall be sewed to the bottom end of the cover and up the sides to a height of not less than 4 inches.

3.4 Identification marking. The cover shall be identified in accordance with MIL-STD-130.

3.5 Workmanship. Finished covers shall be clean, free from abrasion marks, permanently embedded creases, tackiness (sticky to touch), and visible crystallization of mildew inhibitors. Stitched seams shall be free from twists, puckers, exposed raw edges, and loose, crowded, or poorly formed stitches, or any other defect which would prevent the cover from performing its intended function.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Component and material inspection. The contractor is responsible for insuring that components and materials used are manufactured, examined, and tested in accordance with referenced specifications and standards, as applicable.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. Quality conformance inspection (see 4.3).

b. Inspection of packaging (see 4.5).

4.3 Quality conformance inspection.

4.3.1 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.3.2 Examination. Samples selected in accordance with 4.3.1 shall be examined for the major and minor characteristics for possible defects as specified in 4.4.1. AQL shall be 2.5 percent defective for major defects and 4.0 percent defective for minor defects.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:55Z
Check the source to verify that this is the current version before use.

4.4 Inspection procedure.

4.4.1 Examination. The sample covers shall be examined as specified herein for the following defects:

Major

101. Cotton duck not as specified.
102. Thread not as specified.
103. Tie rope not as specified.
104. Leather not as specified.
105. Design not as specified.
106. Longitudinal seam not as specified.
107. Binding at open end not as specified.
108. Stitches not as specified.
109. Leather boot not as specified.
110. Workmanship not as specified.

Minor

201. Identification marking not as specified.

4.5 Inspection of packaging.

4.5.1 Quality conformance inspection of pack.

4.5.1.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

4.5.1.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.5.1.3 Examination. Samples selected in accordance with 4.5.1.2 shall be examined for the following defects. AQL shall be 2.5 percent defective.

111. Materials, methods and containers not as specified for level A or B. Each incorrect material, method, or container shall be considered one defect.
112. Quantities consolidated together exceed the weight limitation of the box level A.
113. Preservation and packaging not in accordance with the referenced document as specified for commercial.
114. Quantities packed together exceed 200 pounds for level A.
115. Quantities packed together exceed the weight or size limitation of the box for level B.
116. Marking missing, illegible, incorrect or incomplete for level A, B, or commercial.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:55Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or commercial, as specified (see 6.2).

5.1.1 Level A. Each cover shall be folded to form a neat and compact bundle and shall be preserved in accordance with MIL-P-116, method IC-1 or IC-3.

5.1.1.1 Consolidation. The preserved covers shall be consolidated together in a close-fitting box conforming to PPP-B-636, W5c or W6c, style optional, in quantities not to exceed the weight limitation of the box specification.

5.1.2 Commercial. Covers shall be preserved in accordance with MIL-STD-1188.

5.2 Packing. Packing shall be level A, level B, or commercial, as specified (see 6.2).

5.2.1 Level A. The covers, preserved as specified in 5.1, shall be packed together in a close-fitting box conforming to PPP-B-601, overseas type, style optional, in quantities not to exceed 200 pounds gross weight. Box closure and strapping shall be in accordance with the appendix to the box specification.

5.2.2 Level B. The covers, preserved as specified in 5.1, shall be packed together in a close-fitting box conforming to PPP-B-636, V3c, or V3s, style optional, or PPP-B-640, class 2, style optional. The gross weight or size shall not exceed the limitation of the applicable box specification.

5.2.3 Commercial. The covers, preserved as specified in 5.1, shall be packed in accordance with MIL-STD-1188.

5.3 Marking.

5.3.1 Military. Marking for military levels of protection (level A or B) shall be in accordance with MIL-STD-129.

5.3.2 Commercial. Marking for commercial packaging shall be in accordance with MIL-STD-1188.

6. NOTES

6.1 Intended use. The cover is intended to protect Philadelphia-type level rods during storage, shipment, and field use.

6.2 Ordering data. Aquisition documents should specify the following:

a. Title, number, and date of this specification.

b. Degree of preservation and degree of packing required (see 5.1 and 5.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:55Z
Check the source to verify that this is the current version before use.

6.3 Recycled material. It is encouraged that recycled material be used, when practical, as long as it meets the requirements of this specification (see 3.2).

Custodian:
Army - ME

Review activity:
DLA - GS

User activity:
Navy - MC

Preparing activity:
Army - ME

Project 6675-0725

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:55Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE
MIL-C-10320E Cover, Level Rod, Philadelphia: Canvas

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:55Z
Check the source to verify that this is the current version before use.