MIL-P-10334B(EA)
19 January 1984
SUPERSEDING
MIL-P-10334A(EA)
18 July 1980

MILITARY SPECIFICATION

POT, SMOKE, FLOATING, HC, M4A2 COMPONENTS FOR

This specification is approved for use by US Army Armament, Munitions and Chemical Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one type of smoke pot.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. Unless otherwise specified, the following specifications, standards, and handbooks of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification for

: Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed: to: Commander, Armament Research and Development Center, US Army Armament, Munitions and Chemical Command, ATTN: DRSMC-TSC-S(A), Aberdeen Proving Ground, MD 21010 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter. :

FSC 1365

Source: https://assist.dla.mil -- Downloaded: 202610-17T13:56Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

DRAWING AND TECHNICAL DATA PACKAGE LIST (TDPL)

US ARMY ARMAMENT, MUNITIONS AND CHEMICAL COMMAND

CHEMICAL RESEARCH AND DEVELOPMENT CENTER

TDPL 36-1-26 - Pot, Smoke, Floating, HC, M4A2.

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.1.3 Other publications. The following documents form a part of this specification to the extent specified herein. The issues of the documents which are indicated as DoD adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

ASTM STANDARDS

D 3951 - Commercial Packaging

(Application for copies should be addressed to ASTM, 1916 Race Street, Philadelphia, PA 19103.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Materials and components. All materials for components cited on the applicable drawings, which is listed on TDPL 36-1-26 shall conform to the specifications listed thereon and to the specific characteristics set forth on the drawings.

Source: https://assist.dla.mil -- Downloaded: 202610-17T13:56Z
Check the source to verify that this is the current version before use.

3.2 Leakage. The container (Drawing 36-2-226) shall not leak when subjected to an internal air pressure of 15 pounds per square inch gauge (psig) and tested in accordance with 4.5.2. The cover, outer (Drawing 36-2-128) and the cover, inner (Drawing 36-2-227) shall not leak when subjected to an air pressure of 5 pounds per square inch gauge (psig) and tested in accordance with 4.5.1 and 4.5.3, respectively.

3.3 Handle lug separation. The lugs (Drawing 36-2-193) shall not separate from the outer cover assembly (Drawing 36-2-128) nor from the inner cover assembly (Drawing 36-2-227) when subjected to a 50 pound load per lug when tested in accordance with 4.5.4.

3.4 Preproduction. Prior to the start of regular production, a preproduction lot of components shall be produced in accordance with this specification for examination and tests.

3.5 Workmanship. The components shall be free from contamination (foreign matter) and damage such as dents, cracks and deformation which would impair their intended use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.

4.1.1 Contractor's responsibility. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.2 Objective evidence. The contractor shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.1.3 Inspection equipment. For inspection equipment required to perform the examination and tests prescribed herein; the contractor shall submit for approval, inspection equipment designs in accordance with the terms of the contract. (See section 6 of MIL-A-48078 and 6.3 herein).

4.2 Classification of inspections. The inspection requirements are classified as follows:

(a) Preproduction inspection (see 4.3)
(b) Quality conformance inspection (see 4.4).

Source: https://assist.dla.mil -- Downloaded: 202640-17T13:56Z
Check the source to verify that this is the currentversion before use.

4.3 Preproduction inspection.

4.3.1 Lot. A preproduction lot of components shall be produced using the same methods, materials, equipment and processes as will be used in regular production.

4.3.2 Sampling.

4.3.2.1 For examination and nondestructive test. Sampling shall be conducted in accordance with MIL-STD-105, except the cup, starter (Drawing 36-2-63) shall meet the requirements of 4.4.3.1. For the tool controlled cup, starter (Drawing 36-2-63) dimensionally examine five each parts from each cavity for conformance to all dimensions on Drawing 36-2-63 to qualify the process and the tooling.

4.3.2.2 For destructive test. Sample inner covers and outer covers shall be tested in accordance with 4.5.4. Sampling shall be conducted in accordance with MIL-STD-105, level S-4 with an AQL of 1.0 percent.

4.3.3 Acceptance/rejection criteria. The preproduction sample shall comply with the examinations and tests specified in 4.4.3.2 to be acceptable. The acceptance number is zero. The contractor shall obtain written approval from the contracting officer prior to proceeding with regular production.

4.4 Quality conformance inspection.

4.4.1 Lotting. A lot shall consist of the components of one interfix number, produced by one manufacturer, at one plant, from the same materials, and under essentially the same manufacturing conditions.

4.4.2 Sampling.

4.4.2.1 For examination and nondestructive tests. Sampling shall be conducted in accordance with MIL-STD-105, except the cup, starter (Drawing 36-2-63) shall be tool controlled.

4.4.2.2 For destructive test. Sample inner covers and outer covers shall be tested in accordance with 4.5.4. Sampling shall be conducted in accordance with MIL-STD-105, inspection level S-4 with an AQL of 1.0 percent defective.

4.4.3 Inspection procedure.

4.4.3.1 For examination and nondestructive tests. The sample components shall be examined and tested in accordance with the classification of defects and with MIL-STD-105. For the tool controlled cup, starter (Drawing 36-2-63), dimensionally examine 5 each parts from each cavity for conformance to all dimensions on Drawing 36-2-63 to qualify the process and the tooling. To maintain process and tool qualification, one starter cup from each cavity shall be dimensionally examined for conformance to all drawing dimensions at the beginning and end of each eight hour shift. In the event a defective starter cup is

Source: https://assist.dla.mil -- Downloaded: 202610-17T13:56Z
Check the source to verify that this is the current version before use.

found, all starter cups produced since the last acceptable cup was inspected, shall be lotted, randomly sampled and dimensionally inspected using MIL-STD-105 level II, AQL 0.65%. If the lot is rejected, the lot shall be screened and all defective cups removed.

4.4.3.2 Classification of defects.

(a) Adapter, fuze (Dwg 36-2-67).

Categories		Defects
Critical:		None defined
Major:	AQL 1.0 percent defective	
101		Threads incorrect
102		Slot incorrect
103		Inside diameter incorrect
104		Hole missing or incorrect
105		Finish missing or incorrect

(b) Clamp (Dwg 36-2-127).

Categories		Defects
Critical:		None defined
Major:	AQL 1.0 percent defective	
101		Protective coating missing or incorrect
102		Cut out in flange missing
103		Component missing or incorrect

(c) Disc, closure (Dwg 36-2-61).

Categories		Defects
Critical:		None defined
Major:	AQL 1.0 percent defective	
101		Hole diameter incorrect
102		Diameter incorrect
103		Thickness incorrect
104		Contamination (3.5)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:56Z
Check the source to verify that this is the current version before use.

(d) Cover, outer (Dwg 36-2-128).

Categories	Defects	Acceptance standards
Critical:	None defined	
Major:	AQL 1.0 percent defective	
101	Leakage	4.5.1
102	Handle location incorrect	
103	Outside diameter incorrect	
104	Welding incorrect	
105	Gasket missing or incorrect	
106	Lip configuration incorrect	
107	Forming incorrect	
108	Finish missing or incorrect	

(e) Card, instruction (Dwg 36-4-9).

Categories	Defects
Critical:	None defined
Major:	AQL 2.5 percent defective
101	Dimensions incorrect
102	Instruction incorrect
103	Print type incorrect
104	Ink color incorrect
105	Acrylic coating missing or incorrect
106	Paper color or type incorrect

(f) Tube, igniter (Dwg 36-2-106).

Categories	Defects
Critical:	None defined
Major:	AQL 1.0 percent defective
101	Threads incorrect
102	Inside diameter incorrect
103	Outside diameter incorrect
104	Length incorrect
105	Finish missing, incomplete or incorrect

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:56Z
Check the source to verify that this is the current version before use.

(g) Container (Dwg 36-2-226).

Categories	Defects	Acceptance standards
Critical:	None defined	
Major:	100 percent inspection	
101	Leakage	4.5.2
Major:	AQL 1.0 percent defective	
102	Inside diameter incorrect	
103	Outside diameter of lip incorrect	
104	Lip thickness incorrect (.250 ± .020)	
105	Bottom diameter incorrect (11.00 ± .06)	
106	Height incorrect	
107	Finish missing or incorrect	

(h) Disc, retainer (Dwg 36-2-124).

Categories	Defects
Critical:	None defined
Major:	AQL 1.0 percent defective
101	Hole locations incorrect
102	Finish incorrect
103	Press fit incorrect

(i) Cover, inner (Dwg 36-2-228).

Categories	Defects
Critical:	None defined
Major:	AQL 1.0 percent defective
101	Outside diameter incorrect
102	Handle recess (Section B-B and C-C) dimensions incorrect
103	Center well depth incorrect
104	Center well position incorrect
105	Location of holes incorrect

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:56Z
Check the source to verify that this is the current version before use.

(j) Cover, inner assembly (Dwg 36-2-227).

Categories	Defects	Acceptance standards
Critical:	None defined	
Major:	AQL 1.0 percent defective	
101	Leakage	4.5.3
102	Welding incorrect	
103	Gasket missing or incorrect	
104	Handle lugs incorrectly located	
105	Finish incorrect	

4.5 Test.

4.5.1 Outer cover leakage test. The outer cover shall be placed in a contractor designed fixture and test set-up (see 4.1.3 and 6.3) so that a pressure of 5 pounds per square inch gauge is maintained against one side of the cover. The fixture with the cover shall be immersed in water for at least 30 seconds. Leakage is indicated by a steady stream or a recurring succession of bubbles from the surface of the cover, especially the areas of the lug handle welds.

4.5.2 Container leakage test. The container shall be placed in a contractor designed fixture and test set-up (see 4.1.3 and 6.3) so that an internal air pressure of 15 pounds per square inch gauge is maintained. The fixture with the container shall be immersed in water for at least 30 seconds. Leakage is indicated by a steady stream or a recurring succession of bubbles from any surface of the container.

4.5.3 Inner cover leakage test. The inner cover, with the holes covered or plugged, shall be placed in a contractor designed fixture and test set-up (see 4.1.3 and 6.3) so that a pressure of 5 pounds per square inch gauge is maintained against one side of the cover. The fixture with the cover shall be immersed in water for at least 30 seconds. Leakage is indicated by a steady stream or a recurring succession of bubbles from the surface of the cover, especially the areas of the lug handle welds.

4.5.4 Handle lug separation test. The lugs shall be subjected to a direct pull of 50 pounds or the handle held by the lugs shall be subjected to a direct pull of 100 pounds. Any weld separation shall be cause for rejection.

5. PACKAGING

5.1 Industrial. Commercial/industrial packaging, which is normally used to support production line operations, shall be in accordance with ASTM D 3951.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:56Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The items covered by this specification are used in assembling the M4A2 floating smoke pot.

6.2 Ordering data. Acquisition documents should specify the following:

(a) Title, number, and date of this specification.
(b) The shipment group size and marking (when required).
(c) Contract data requirements cited in section 6 of MIL-A-48078 and applicable to this specification (reference 4.1.3 and 6.3).

6.3 Submission of inspection equipment design for approval. Refer to MIL-A-48078. Submit designs to Commander, DRSMC-QAC-T(A), Aberdeen Proving Ground, MD 21010.

Custodians:

Army - EA

Preparing activity:

Army - EA

Project No. 1365-A078

☆U.S. GOVERNMENT PRINTING OFFICE: 1984—705-040/A1853

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:56Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for submitting comments and suggestions for improvements. All users of military standardization documents are invited to p suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)* mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorizati to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

NO P
NEC
IF M
IN
UNITE

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON, D.C.

POSTAGE WILL BE PAID BY DEPARTMENT OF THE ARMY

Commander
Armament Research and Development Center
US Army Armament, Munitions and Chemical Command
ATTN: DRSMC-TSC-S(A)
Aberdeen Proving Ground, MD 21010

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:56Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-P-10334B(EA)	POT, SMOKE, FLOATING, HC, M4A2 COMPONENTS FOR

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*:

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426

EDITION OF 1 OCT 76 IS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 202610-17T13:56Z
Check the source to verify that this is the current version before use.