NOTE: The document identifier and heading have been changed on this page to reflect that this is a performance specification. There are no other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised.

INCH POUND

MIL-PRF-83504/11C
27 OCTOBER 1993
SUPERSEDING
MIL-S-83504/11B
10 March 1989

PERFORMANCE SPECIFICATION SHEET

SWITCHES, DUAL IN-LINE PACKAGE (DIP), SIDE TOGGLE ACTUATOR, LOW PROFILE SINGLE POLE, SINGLE THROW STATIONS, SEALED BASE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-S-83504.




FIGURE 1. Dimensions and configuration.


denotes changes.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:22Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm
.003	0.08	.040	1.02
.005	0.13	.090	2.29
.010	0.25	.100	2.54
.012	0.30	.160	4.06
.015	0.38	.240	6.10
.020	0.51	.300	7.62
.021	0.53	.380	9.65
.030	0.76		

(C)



TYPICAL CONTACT CIRCUIT ARRANGEMENT 10 STATION SWITCH
(CONTACTS SHOWN IN OPEN POSITION)

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Each switch station is shown in the "ON" position.
4. Each switch position shall be numbered as shown.
5. Exact shape of switch is optional provided outline dimensions are not exceeded.
6. Design of terminals and standoffs are optional.

FIGURE 1. Dimensions and configuration - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:22Z
Check the source to verify that this is the current version before use.

REQUIREMENTS

Material:

Body and actuator rocker: Molded plastic.

(C) Terminals: Gold plated or solderable. See table I. The solderable terminals shall be solder over nickel over copper over brass Both gold plated and solderable must meet solderability requirements

(C) Terminal sealing and solderability: The terminal potting material meniscus may extend to .030 inch maximum beyond the solder standoff.

Dimensions and configuration: See figure 1 and table I

(C) Seal: Sealed base. Temporary tape top seal.

Switch position and setting identification: See figure 1.

Orientation. See figure 1.

Operating force 2.5 to 13 ounces

Electrical ratings:

10 mA maximum at 50 mV, switching (resistive load)
100 mA maximum at 6 V dc, switching (resistive load).
25 mA maximum at 24 V dc, switching (resistive load)

Application note: In applications where the switch will mate with sockets or with panel boards, the user should consider the compatibility of the mating terminals with respect to finishes and mechanical configuration.

Part or Identifying Number (PIN). M83504/11- (dash number from table I).

(C) TABLE I. Dash numbers and characteristics.

Dash number		Number of stations	Dimension "A" inches (mm)
Terminal finish			
Gold 1/ 2/	Solderable		
002	022	2	.280 (7.11)
003	023	3	.380 (9.65)
004	024	4	.480 (12.19)
005	025	5	.580 (14.73)
006	026	6	.680 (17.27)
007	027	7	.780 (19.81)
008	028	8	.880 (22.35)
009	029	9	980 (24.89)
010	030	10	1.080 (27.43)

1/ PIN's for switches equipped with gold terminations are inactive for new design
2/ PIN'S 011, 012, 031 and 032 have been canceled without replacement

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:22Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - AR, AV
Navy - AS
Air Force - 99
DLA - ES

Preparing activity:
Air Force - 85

Agent:
DLA - ES

(Project 5930-1503-08)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:22Z
Check the source to verify that this is the current version before use.