A-A-1914
August 8, 1983

COMMERCIAL ITEM DESCRIPTION

ROLLER FRAME, PAINT

The General Services Administration has authorized the use of this commercial item description in preference to Federal Specification H-R-550.

This description covers paint roller frames of the slip-off design.

Type I - Professional

Class A - To accommodate 9-inch roller covers

Type II - Consumer

Class A - To accommodate 9-inch roller covers
Class B - To accommodate 7-inch roller covers

Salient characteristics:

The type I frame shall be fabricated of 5/16-inch ± 0.0025-inch diameter corrosion resistant steel wire, so formed as to permit mounting the roller cage at 90° ± 5° to the handle, and having the center of the roller cage within 1/2-inch ± 1/32-inch of the center line of the handle. The type II frame shall be constructed to the same requirements as the type I, except that the wire shall be 1/4-inch ± 0.0025-inch diameter.

The cage shall be free turning on the wire which is at 90° to the handle, and so constructed of 0.135-inch diameter spanning wires, as to accommodate covers having a nominal inside core diameter of 1-1/2 inches. The spanning wires shall be made of corrosion resistant metal or metal made corrosion resistant by plating. The type I cage shall have a minimum of five spanning wires and the type II shall have a minimum of four spanning wires. A force of not less than six pounds shall be required to remove the cover from the cage.

The handle shall be made of a molded low density polyethylene or polypropylene plastic. It shall be a minimum of 5-1/8 inch in length from the point of insertion to the outer end. The grip shall be pressure bonded to the frame so as to allow no movement, lateral or rotational, between it and the wire. The outer end shall contain a threaded hole for securely attaching an extension pole with 3/4-inch 5 pitch acme thread. The grip end nearer the cage shall be molded so as to allow hooking the roller frame over the rim of a paint pail or roller tray. The type I grip shall have a minimum weight of 1.5 ounces and the type II shall have a minimum weight of 0.8 ounces.

The roller frame shall not discolor, wrinkle, blister or otherwise deteriorate when submerged for one hour in a solvent mixture, by volume, of:

Normal butyl acetate	15 ± 1 percent
Normal butyl alcohol	15 ± 1 percent
Methyl ethyl ketone	10 ± 1 percent
Toluene	Remainder

Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable.

Preservation, packaging, packing, labeling, and marking. Preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order.

Notes: When this commercial item description is used for procurement the commercial item certification clause must appear in the solicitation.

CIVIL AGENCIES COORDINATING ACTIVITIES:

COMMERCE - CPS, NBS
DC GOV'T - DCG
GPO - GPO
JUS - FPI
POSTAL - POS
VA - DMS

PREPARING ACTIVITY:

GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:17Z
Check the source to verify that this is the current version before use.

FSC 8020