MILITARY SPECIFICATION

ANTI-TANK MINE DISPENSING SYSTEM,

PACKAGING OF

1. SCOPE

1.1 This specification covers the requirements for methods, materials, and procedures for the preservation, packaging, packing and marking of the anti-tank mine dispensing system (SC 1095-97-CL-E03) and individually procured components of the system.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

QQ-S-781	- Strapping, Steel, Flat and Seals.
PPP-B-566	- Boxes, Folding, Paperboard.
PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-621	- Boxes, Wood, Nailed and Lock-Corner.
PPP-C-650	- Crates, Wood, Open and Covered.
PPP-P-40	- Packaging and Packing of Hand Tools.

Military

MIL-P-116	- Preservation, Methods of

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:32Z
Check the source to verify that this is the current version before use.

STANDARDS

Military

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.

(Copies of specifications and standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, ATTN: Tariff Publishing Officer, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., ATTN: Tariff Order Section, 1616 P Street, NW, Washington, DC 20036.)

3. REQUIREMENTS

3.1 Materials. Materials shall be as specified herein and in applicable specifications and standards. Materials not specified shall be selected by the supplier and shall be subject to all provisions of this specification. Material shall be free of defects.

3.2 First article (preproduction pack). The supplier shall furnish a preproduction pack for examination within the time frame specified (see 6.2) to prove, prior to starting production packaging and packing, that

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:32Z
Check the source to verify that this is the current version before use.

the applied preservation, packaging, packing and marking comply with the requirements of this specification. Examination shall be as specified in section 4 and shall be subject to surveillance and approval by the Government (see 6.3). The preproduction pack may be accomplished utilizing either the preproduction model anti-tank mine dispensing system or a production dispensing system. If the preproduction model dispensing system is utilized, any preservation, packaging, and packing shall be removed by the supplier at no expense to the Government, when requested by the Government to facilitate comparison between the preproduction model dispensing system and production dispensing systems.

3.3 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.2).

3.3.1 Level A.

3.3.1.1 Unprotected surfaces. Unpainted and unprotected exterior metal surfaces of components requiring the application of a contact preservative in accordance with MIL-P-116 shall be coated with type P-1 preservative. The preservative shall conform to the applicable specification listed in and shall be applied in accordance with MIL-P-116.

3.3.1.2 Tools. Tools shall be preserved and packaged in accordance with the level A requirements of PPP-P-40.

3.3.1.3 Technical manuals. Technical manuals shall be preserved in accordance with MIL-P-116, method IC-1 or IC-3 and placed in the maintenance case.

3.3.1.4 Incandescent lamps. Incandescent lamps, furnished as part of the overpack kit, shall be individually preserved in accordance with MIL-P-116, method IC-2, using the supplier's box or a box conforming to PPP-B-566.

3.3.1.5 Gaskets and seals. Gaskets and seals shall be individually preserved in accordance with MIL-P-116, method III.

3.3.1.6 Whistles. Whistles shall be individually preserved in accordance with MIL-P-116, method IC-1 or IC-3.

3.3.1.7 Consolidated packaging. Small components that do not have securing provisions provided on the dispenser shall be consolidated packaged together

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:32Z
Check the source to verify that this is the current version before use.

in the toolboxes as space permits. Components such as lamps, gaskets, and seals shall be placed and secured in the boxes in a manner to prevent damage. The toolbox lids shall be closed and secured in a manner to prevent accidental opening or pilferage of contents. If sufficient space is not provided in the toolboxes , the remainder of the components shall be consolidated packaged together in a close-fitting box conforming to PPP-B-601, overseas type, grade B, style optional or PPP-B-621, class 2, style optional.

3.3.2 Level C. The components of the anti-tank mine dispensing system shall be preserved and packaged in a manner to assure protection against deterioration and damage from the supplier to the initial destination. The toolboxes shall be utilized to the greatest extent and the lids closed and secured to prevent accidental opening or pilferage of contents.

3.4 Packing. Packing shall be level A or C as specified (see 6.2).

3.4.1 Level A.

3.4.1.1 Dispenser. The dispenser, prepared as required for travel shall not require packing. Components designed for attachment to the dispenser while in the travel position shall be secured by the provisions provided. The tires shall be inflated to 10 pounds above the pressure recommended for maximum load. The box containing components that will not fit in the toolbox (see 3.3.1.7) shall be secured to the dispenser in the most convenient location that will not increase cubage or interfere with the towing of the dispenser. Securing shall be with strapping conforming to QQ-S-781, type I or IV, finish B, grade 2, size as applicable.

3.4.1.2 Mine containers. The corner posts, spacers, braces, restraint rod, and web strap shall be removed. The eight spacers shall be placed on the base and secured with three metal straps conforming to QQ-S-781, type I or IV, finish B, size 3/4 inch. Two straps shall be placed lengthwise between the skids, the other strap shall be around the width. The removed nuts, bolts and web strap required for each pallet shall be preserved together in accordance with MIL-P-116, method IC-1. The required quantity of corner posts, braces, center poles, and the preserved nuts, bolts and web straps needed to completely assemble eighteen complete mine containers shall be packed together in a close-fitting box conforming to PPP-B-601, overseas type, grade B, style optional or PPP-B-621, class 2, style optional. The contents shall be secured in a manner to prevent free movement. Box closure and strapping shall be in accordance with the appendix to the applicable box specification. Strapping shall be zinc coated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:32Z
Check the source to verify that this is the current version before use.

3.4.1.3 Conveyor sections and stands.

3.4.1.3.1 Conveyor sections. Ten conveyor sections shall be packed together in a close-fitting open wood crate conforming to PPP-C-650, type III, style B. The sections shall be secured within the crate in a manner to prevent movement or damage.

3.4.1.3.2 Stands. Twelve conveyor stands shall be packed together as specified in 3.4.1.3.1 for conveyor sections.

3.4.1.4 Lifting fork, can opener stands, and mine cache toolbox. The lifting fork, can opener stands, and mine cache tool box shall be packed together in a close-fitting box conforming to PPP-B-601, overseas type, grade B, style optional or PPP-B-621, class 2, style optional. The contents shall be secured within the box in a manner to prevent movement or damage. Box closure and strapping shall be in accordance with the appendix to the applicable box specification. Strapping shall be zinc coated.

3.4.1.5 Components procured as replacements or spares. Components, of like description, procured as replacements or spares shall be packed together in close-fitting boxes conforming to PPP-B-601, overseas type, grade B, style optional; PPP-B-621; class 2, style optional or in crates conforming to PPP-C-650, type III, style B; as applicable. The contents shall be secured within the container in a manner to prevent movement or damage. Closure and strapping shall be in accordance with the appendix to the applicable box or crate specification. Strapping shall be zinc coated.

3.4.2 Level C. The components comprising a complete anti-tank mine dispensing system or individually procured components, preserved and packaged as specified in 3.3, shall be prepared for shipment in a manner to assure carrier acceptance and safe delivery to destination at lowest ratings in compliance with Uniform Freight Classification rules or National Motor Freight Classification rules.

3.5 Marking. Packages, shipping containers, and mobile dispensers shall be marked in accordance with MIL-STD-129.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:32Z
Check the source to verify that this is the current version before use.

of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Material inspection. The supplier is responsible for insuring that supplies and materials used are manufactured, examined, and tested in accordance with referenced specifications and standards.

4.2 Classification of inspection. Inspection shall be classified as follows:

(a) Preproduction pack inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).

4.3 Preproduction pack inspection.

4.3.1 Examination. The preproduction pack shall be examined for the defects specified in table I. Presence of one or more defects shall be cause for rejection.

4.4 Quality conformance inspection.

4.4.1 Inspection stages. Inspection shall be in three stages as follows:

(a) The first stage shall include inspection of procedures, methods, materials, containers and packaging marking prior to placing the packaged and unpackaged components into the consolidated containers.
(b) The second stage shall include inspection of closure and marking of the consolidated containers, and the arrangement, blocking, bracing and anchoring of the components within the consolidated container, shipping container, or to the wheel mounted dispenser.
(c) The third stage shall include inspection of the closed, strapped and marked shipping container or the wheel mounted dispenser as prepared for shipment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:32Z
Check the source to verify that this is the current version before use.

4.4.2 Unit of product. For the purpose of inspection, all packages or packs prepared for any applicable inspection stage that will comprise a complete dispensing system or components, as applicable, shall be considered a unit of product.

4.4.3 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.4.4 Examination. Samples selected in accordance with 4.4.3 shall be examined for the defects marked "X" for the applicable level in table I. Acceptable quality level (AQL) shall be 2.5 percent defective.

Table I. Classification of defects

No.	Defect	Level	
		A	C
101.	Materials, methods, or containers not as specified. Each incorrect material, method, or container shall constitute one defect.	X	-
102.	Surfaces requiring a contact preservative in accordance with the referenced document not coated with preservative.	X	-
103.	Tools not preserved in accordance with the referenced document.	X	-
104.	Technical manuals not preserved and placed in the maintenance case.	X	-
105.	Consolidated packaging not as specified.	X	-
106.	Tool box lids not secured in a manner to prevent accidental opening or pilferage	X	X
107.	Tires not inflated as specified.	X	-
108.	Boxes secured to the dispenser in a manner that increases cubage or interferes with towing.	X	-
109.	Mine containers not disassembled and components not secured together as specified.	X	-
110.	Conveyor sections not packed together in the quantities specified.	X	-
111.	Conveyor stands not packed together in the quantities specified.	X	-
112.	Lifting fork, can opener stands and mine cache toolbox not packed together as specified.	X	-

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:32Z
Check the source to verify that this is the current version before use.

No.	Defects	Level	
		A	C
113.	Components procured as replacements or spares not packed as specified.	X	-
114.	Strapping not zinc coated.	X	-
115.	Marking missing, illegible, incorrect or incomplete	X	X

5. PREPARATION FOR DELIVERY

(This section is not applicable to this specification).

6. NOTES

6.1 Intended use. It is intended that this specification be used for preservation, packaging, packing, and marking of the anti-tank mine dispensing systems (SC 1095-97-CL-E03) or for procurement of components of the system and shall be referenced in section 5 of commodity specifications or direct reference in contracts or orders.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Time frame required for submission of the preproduction pack (see 3.2).
(c) Level of preservation and packaging and level of packing required (see 3.3 and 3.4).

6.3 Preproduction pack. Any changes or deviations of production packs from the approved preproduction pack will be subject to the approval of the contracting officer. Approval of the preproduction pack will not relieve the supplier of his obligation to preserve, package, pack and mark the anti-tank mine dispensing system or individually procured components of the system in accordance with this specification.

Custodian:

Army - ME

Preparing activity:

Army - ME

Project No. 1095-A068

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:32Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION MIL-A-52759(ME) Anti-Tank Mine Dispensing System, Packaging Of

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1426
11 Oct 72 (Rev)

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:32Z
Check the source to verify that this is the current version before use.