MILITARY SPECIFICATION

BAGS, DYE, PROPELLANT AND BASE CHARGE, FOR ANTI-PERSONNEL ARTILLERY PROJECTILES

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the fabrication of polyethylene bags for use in loading various anti-personnel artillery projectiles.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposals form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-2550 - Ammunition and Special Weapons, General Specification for.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105).
MIL-STD-109 - Quality Assurance Terms and Definitions
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

DRAWINGS

ARMY

9211482 - Base Charge Parts Arrangement
9216493 - Bag, Propellant
9218978 - Bag, Dye
9226364 - Bag, Dye

FSC: 1315

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:16Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material.- Material and parts shall be in accordance with applicable drawings and specifications.

3.2 Bags.- The bags shall comply with all requirements specified on the drawing (dwg.) for the bag specified in the invitation for bid or request for proposal and with all requirements specified in applicable specifications. The bags covered by this specification are as follows:

Torroidal
Dwg. 9211482 - Base charge parts arrangement
Dwg. 9216493 - Bag, propellant

Rectangular
Dwg. 9218978 - Bag, Dye
Dwg. 9226364 - Bag, Dye

3.3 Pressure test of torroidal bags.- The bags shall withstand an internal pressure of 1.4 pounds per square inch gage minimum (min) (39 inches of water) without evidence of peelback of the seams and without leakage when tested as specified in 4.4.1 and 4.4.2.

3.4 Strength of heat seal for rectangular bags.- The specimen shall withstand application of a static load of .86 pounds per lineal inch, minimum, without peelback of the heat seal and without tensile failure of the area adjacent the heat seal when tested as specified in 4.4.1 and 4.4.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:16Z
Check the source to verify that this is the current version before use.

3.5 Workmanship.- The fabricated bag shall be free from cuts, tears, creases or cracks. They shall be clean and free from dirt, grease and other foreign matter.

3.6 First article inspection.- This specification makes provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for Inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to Standard MIL-STD-109 in order to define terms used herein. The provisions of Specification MIL-A-2550 shall apply.

4.1.1 Submission of product.- At the time the completed lot of product is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all of the quality assurance provisions specified within this specification.

b. Drawing and specification number and date, together with an identification and date of changes thereto.

c. A statement that all material purchased by the contractor meets requirements, when such material is controlled by Government or commercial specifications referenced in any of the contractual documents, and that certificates of conformance are on file and available for review.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:16Z
Check the source to verify that this is the current version before use.

d. Number of items in the lot.

e. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.2 First Article Inspection

4.2.1 Submission.- The contractor shall submit a first article sample as designated by the contracting officer for evaluation in accordance with the provisions of 4.2.2. The first article sample shall consist of 25 pieces and finished bags which have been produced by the contractor or furnished by a supplier and which have been manufactured using the same production processes, procedures and equipment which will be used in fulfilling the contract. All parts and materials, including packaging and packing, shall be obtained from the same source of supply as will be used in regular production. Prior to submission, the contractor shall inspect the sample to the degree necessary to assure that it conforms to the requirements of the contract and submit a record of this inspection with the sample, including statements of findings for materials, processes and tests. A sample containing known defects will not be submitted unless specifically authorized by the Contracting Officer. A first article sample, or portion thereof, as directed by the contracting officer, shall also be submitted whenever there is a lapse in production for a period in excess of 90 days or whenever a change occurs in manufacturing process, material used, drawing or specification such as to significantly affect product uniformity as determined by the Government.

4.2.2 Inspections to be performed.- Assemblies and components will be subjected by the Government to any or all the examinations or tests specified in 4.3.2 and 4.3.3 of this specification and any or all requirements of the applicable drawings.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:16Z
Check the source to verify that this is the current version before use.

4.2.3 Rejection.- If any assembly or component fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate its inspection upon any failure of an assembly or component to comply with any of the stated requirements.

4.3 Quality Conformance Inspection

4.3.1 Lot Formation.- The term "inspection lot", as used in this specification, is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer, in one unchanged process, using the same materials and methods, in accordance with the same drawings, same drawing revisions, same specifications and same specification revisions, and complies with the provisions for submission of product as specified in Standard MIL-STD- 105. Changes to the process, specifications or drawings, not affecting safety, performance, interchangeability or storage, as determined by the Government, shall not be deemed to alter the homogeneity of an inspection lot. All material submitted for inspection shall comply with the homogeneity criteria specified herein, regardless of the type of sampling procedure which is being applied to determine conformance with requirements.

4.3.2 Examination.- The examinations listed in the following subparagraphs shall be performed on inspection lots (see 4.3.1) of the components or assemblies designated in the applicable paragraph headings. Sampling plans for Major and Minor Defects shall be in accordance with MIL-STD-105 except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the Government. Instead of applying the AQL's designated herein to the groups of Major and Minor Defects listed, the contractor may elect to apply AQL's to individual defects using an AQL of 0.40 percent for each Major Defect and an AQL of 0.65 percent for each Minor Defect. When this method is elected, it shall be applied to all of the major and minor defects listed in the applicable subparagraph of this section and be documented as part of the contractor's inspection system. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.3.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:16Z
Check the source to verify that this is the current version before use.

4.3.2.1 Base charge parts arrangement (see dwg. 9211482 and dwg. 9211542 which covers a detail of dwg. 9211482.)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	None defined.		
Minor:	AQL 2.5 percent		
201.	Outside diameter	Gage	01001
202.	Inside diameter	Gage	01002
203.	Length from center of hole to end of neck	Gage	01003
204.	Width of neck	Gage	01004
205.	Material thickness	Gage	01005
206.	Width of heat seal	Gage	01006
207.	Evidence of poor workmanship (see 3.5)	Visual	01007

4.3.2.2 Bag, propellant (see dwg. 9216493 and dwg. 9216494 which covers a detail of dwg. 9216493).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	None defined		
Minor:	AQL 2.5 percent		
201.	Outside diameter	Gage	02001
202.	Inside diameter	Gage	02002
203.	Length from center of hole to end of neck	Gage	02003
204.	Width of neck	Gage	02004
205.	Material thickness	Gage	02005
206.	Width of heat seal	Gage	02006
207.	Evidence of poor workmanship (see 3.5)	Visual	02007

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:16Z
Check the source to verify that this is the current version before use.

4.3.2.3 Bag, Dye (see dwg. 9218978 or dwg. 9226364)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	None defined		
Minor:	AQL 2.5 percent		
201.	Length	Gage	03001
202.	Width	Gage	03002
203.	Material thickness	Gage	03003
204.	Width of heat seal	Gage	03004
205.	Evidence of poor workmanship (see 3.5)	Visual	03005

4.3.3 Testing

4.3.3.1 Pressure test of torroidal bags (see 3.3) - Major defect, Code No. 04001.- Twenty sample bags shall be selected from each lot for this test. If any sample fails to comply with the applicable requirement, the lot shall be rejected. Testing shall be in accordance with 4.4.1 and 4.4.2. The method of inspection shall be by an appropriate pressure test fixture.

4.3.3.2 Strength of heat seal of rectangular bags (3.4) - Major defect, Code No. 05001.- Twenty sample bags shall be selected from each lot for this test. If any sample fails to comply with the applicable requirement, the lot shall be rejected. Testing shall be in accordance with 4.4.1 and 4.4.3. The method of inspection shall be by an appropriate test fixture.

4.3.4 The inspection equipment required to perform the examinations and tests prescribed in this section is identified under the "Method of Inspection" headings in 4.3.2 and 4.3.3, see 6.3.

4.4 Test Methods and Procedures

4.4.1 Conditioning.- The test samples shall be conditioned for 48 hours prior to testing at a temperature of 73.4 degrees

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:16Z
Check the source to verify that this is the current version before use.

Fahrenheit (F) plus or minus 3.6 degrees F at 50 plus or minus 5 percent relative humidity, and shall be tested under these conditions, unless otherwise specified.

4.4.2 Pressure test of torroidal bags.- The bags shall be subjected to the internal pressure specified in 3.3 for a period of not less than 15 seconds. Observation shall be made for water leakage and peelback of the heat seal.

4.4.3 Strength of heat seal of rectangular bags.- One specimen one inch wide shall be cut perpendicular to the line of the seam, from each seam, of each sample bag. One leg of the specimen shall be clamped so that the specimen hangs freely. The required load (see 3.4) shall be applied to the free end in such a manner as to avoid impact loading the seam. The load shall be allowed to act for one minute after which the seam shall be examined for peelback of the heat seal.

5. PREPARATION FOR DELIVERY

5.1 Packaging

5.1.2 Level C.- Bags of one type only shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies.

5.2 Marking.- Marking of the packages and shipping containers shall be in accordance with MIL-STD-129.

6. NOTES

6.1 Ordering data.- Procurement documents shall specify the following:

a. Title, number and date of this specification.
b. Drawing number of bag.
c. Provisions for the submission of first article sample.

6.2 Inspection code numbers.- The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:16Z
Check the source to verify that this is the current version before use.

6.3 Inspection Equipment Designs.- Inspection equipment designs are of two types - Government Special Inspection Equipment (SIE) designs and contractor designs. SIE designs are designated by drawing numbers under the "Method of Inspection" headings in Section 4. Design responsibility for all other inspection equipment is assigned to the contractor. The contractor need not furnish any design when a complete Government SIE design is provided. Unless otherwise specified, however, the contractor may submit alternate or modified contractor designs of SIE in accordance with 6.3.2 and 6.3.3 should be elect to do so.

6.3.1 SIE designs.- SIE designs may consist of any of the following:

a. Detailed drawings which completely depict all information necessary for the fabrication and use of the item of inspection equipment.

b. A source control drawing or a specification control drawing as defined in MIL-STD-100.

c. An envelope drawing, as defined in MIL-STD-100, which establishes the criteria which a detail design shall meet. When envelope drawings are specified, the contractor shall prepare designs which comply with the criteria therein.

6.3.2 Contractor designs.- Contractor designs are required for all inspection equipment for which SIE designs are not specified and may include commercial equipment which the contractor proposes to use. (Commercial equipment is defined as unmodified equipment which is cataloged and available for purchase by the general public.) Contractor designs shall include appropriate operating instructions, calibration procedures and maintenance procedures. Commercial equipment shall be fully described by catalog listings or other means which provide sufficient information to permit identification and evaluation by the Government and may include illustrations and engineering data. Designs shall be prepared for any special fixture(s) required to be used with commercial equipment, or with SIE designs if not otherwise covered thereby (see 6.3.1c). Designs shall be of the category and form (per MIL-D-1000) specified in the Contract Data Requirements Lists (DD Form 1423).The contractor is referred to MIL-HDBK-204, "Inspection Equipment Design" for guidance. The specification number and the applicable five-digit defect code number (or other specific identifying information) from Section 4 of this specification shall be referenced on each contractor design together with the component or assembly drawing number and revision letter to which the specific design applies.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:16Z
Check the source to verify that this is the current version before use.

6.3.3 Submission of designs for approval.- Contractor designs shall be approved by the Government prior to fabricating or procuring the equipment. Designs shall be submitted for approval in accordance with the stipulations, time frame and distribution specified in the Contract Data Requirements List (DD Form 1423) or in the contract. Partial submission of inspection equipment designs is permissible and encouraged. However, the completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will normally be accomplished within one month after receipt.

6.4. Supersession data.- This specification includes the requirements of Purchase Description PA-PD-2887 dated 5 October 1966.

Custodian:
Army - PA

Preparing Activity
Army - PA

Project Number: 1315 - A021

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:16Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:16Z
Check the source to verify that this is the current version before use.