# MILITARY SPECIFICATION

# CONNECTOR, ELECTRICAL

## 1. SCOPE

1.1 This specification covers requirements, quality assurance provisions, and the preparation for delivery criteria for one type of connector, electrical used on M454, M455 and T5123E1 projectiles.

## 2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-P-116 - Preservation, Methods of

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1168 - Lot Numbering of Ammunition
MIL-STD-1169 - Packaging, Packing, and Marking for Shipments of Inert Ammunition Components

DRAWINGS

PICATINNY ARSENAL

8808362 - Packing and Marking for Storage and Shipments
8883535 - Bag, Packing, for Repair Parts

FSC 1110



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:10Z
Check the source to verify that this is the current version before use.

9220308 - Connector, Electrical
9220312 - Contact, Connector
9220310-2 - Screw, Connector
9220311 - Screw, Guide
9220309 - Connector Body Assembly
9220313 - Insulator, Top
9220314 - Body, Connector
9220315 - Seal, Lower
9220322 - Adhesive Sealant
ET9220308 - Equipment Tabulation

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

## 3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The connector shall comply with all requirements specified on the drawing (dwg) 9220308, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3.3 Tool manufacturing control (T.M.C.). When T.M.C. is specified herein, five consecutive parts which comply with drawing dimensions will constitute proper initial tool control acceptance. During normal production, five parts shall be selected at the start and at the end of each day's production (for a minimum of 10 parts) and examined as specified in the applicable paragraph in 4.3.2.1 In addition, five consecutive parts shall be examined as specified in the applicable paragraph in 4.3.2.1 whenever the manufacturing tool requires maintenance. Failure of any part to comply with any of the examinations specified in 4.3.2.1 shall reject the lot of production under consideration.

3.4 Workmanship.

3.4.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristics.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:10Z
Check the source to verify that this is the current version before use.

3.4.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.4.3 Burrs. Parts shall be free from burrs.

3.4.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.4.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

## 4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection. Not applicable.

4.3 Quality conformance inspection.

4.3.1 Lot formation.

4.3.1.1 Production lot. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting safety, performance, storage, or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

4.3.1.2 Inspection lot. A lot or batch and its formation, size, and presentation is described in MIL-STD-105, Section 5. Accordingly, a lot shall mean an inspection lot and a batch shall mean an inspection batch for the purpose of this specification. The manner in which each inspection lot or batch is to be presented and identified by the contractor, shall be designated or approved by the Government representative.

4.3.2 Product inspection examination. Critical characteristics shall require 100 percent inspection of all items in the inspection lot. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table (see Table I, II, III, and Table IV), and inspected for all characteristics in the applicable classification. Any characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.



Source: https://assist.dla.mil -- Downloaded: 202610-22T19:10Z
Check the source to verify that this is the current version before use.

Table I

Major Characteristics for War Reserve Items

| Lot Size | Sample Size | Lot Size | Sample Size | Lot Size | Sample Size | Lot Size | Sample Size |
|---|---|---|---|---|---|---|---|
| 1-72 | all | 140-141 | 124 | 256-259 | 177 | 541-549 | 230 |
| 73 | 72 | 142 | 125 | 260-262 | 178 | 550-559 | 231 |
| 74 | 73 | 143-144 | 126 | 263-265 | 179 | 560-569 | 232 |
| 75 | 74 | 145 | 127 | 266-268 | 180 | 570-579 | 233 |
| 76 | 75 | 146-147 | 128 | 269-271 | 181 | 580-590 | 234 |
| 77 | 76 | 148-149 | 129 | 272-275 | 182 | 591-601 | 235 |
| 78 | 77 | 150 | 130 | 276-278 | 183 | 602-613 | 236 |
| 79 | 78 | 151-152 | 131 | 279-282 | 184 | 614-625 | 237 |
| 80 | 79 | 153-154 | 132 | 283-285 | 185 | 626-637 | 238 |
| 81-82 | 80 | 155-156 | 133 | 286-289 | 186 | 638-649 | 239 |
| 83 | 81 | 157 | 134 | 290-293 | 187 | 650-662 | 240 |
| 84 | 82 | 158-159 | 135 | 294-296 | 188 | 663-676 | 241 |
| 85 | 83 | 160-161 | 136 | 297-300 | 189 | 677-690 | 242 |
| 86 | 84 | 162-163 | 137 | 301-304 | 190 | 691-704 | 243 |
| 87 | 85 | 164-165 | 138 | 305-308 | 191 | 705-719 | 244 |
| 88-89 | 86 | 166-167 | 139 | 309-312 | 192 | 720-735 | 245 |
| 90 | 87 | 168 | 140 | 313-316 | 193 | 736-751 | 246 |
| 91 | 88 | 169-170 | 141 | 317-320 | 194 | 752-768 | 247 |
| 92 | 89 | 171-172 | 142 | 321-324 | 195 | 769-785 | 248 |
| 93 | 90 | 173-174 | 143 | 325-329 | 196 | 786-804 | 249 |
| 94-95 | 91 | 175-176 | 144 | 330-333 | 197 | 805-823 | 250 |
| 96 | 92 | 177-178 | 145 | 334-338 | 198 | 824-842 | 251 |
| 97 | 93 | 179-180 | 146 | 339-342 | 199 | 843-863 | 252 |
| 98 | 94 | 181-182 | 147 | 343-347 | 200 | 864-884 | 253 |
| 99-100 | 95 | 183-184 | 148 | 348-352 | 201 | 885-907 | 254 |
| 101 | 96 | 185-187 | 149 | 353-356 | 202 | 908-930 | 255 |
| 102 | 97 | 188-189 | 150 | 357-361 | 203 | 931-955 | 256 |
| 103 | 98 | 190-191 | 151 | 362-366 | 204 | 956-981 | 257 |
| 104-105 | 99 | 192-193 | 152 | 367-372 | 205 | 982-1008 | 258 |
| 106 | 100 | 194-195 | 153 | 373-377 | 206 | 1009-1036 | 259 |
| 107 | 101 | 196-197 | 154 | 378-382 | 207 | 1037-1066 | 260 |
| 108-109 | 102 | 198-200 | 155 | 383-388 | 208 | 1067-1098 | 261 |
| 110 | 103 | 201-202 | 156 | 389-393 | 209 | 1099-1131 | 262 |
| 111 | 104 | 203-204 | 157 | 394-399 | 210 | 1132-1166 | 263 |
| 112-113 | 105 | 205-207 | 158 | 400-405 | 211 | 1167-1204 | 264 |
| 114 | 106 | 208-209 | 159 | 406-411 | 212 | 1205-1243 | 265 |
| 115 | 107 | 210-212 | 160 | 412-417 | 213 | 1244-1285 | 266 |
| 116-117 | 108 | 213-214 | 161 | 418-424 | 214 | 1286-1330 | 267 |
| 118 | 109 | 215-217 | 162 | 425-430 | 215 | 1331-1378 | 268 |
| 119 | 110 | 218-219 | 163 | 431-437 | 216 | 1379-1429 | 269 |
| 120-121 | 111 | 220-222 | 164 | 438-443 | 217 | 1430-1483 | 270 |
| 122 | 112 | 223-224 | 165 | 444-450 | 218 | 1484-1542 | 271 |
| 123-124 | 113 | 225-227 | 166 | 451-457 | 219 | 1543-1605 | 272 |
| 125 | 114 | 228-230 | 167 | 458-465 | 220 | 1606-1673 | 273 |
| 126-127 | 115 | 231-232 | 168 | 466-472 | 221 | 1674-1747 | 274 |
| 128 | 116 | 233-235 | 169 | 473-480 | 222 | 1748-1827 | 275 |
| 129-130 | 117 | 236-238 | 170 | 481-488 | 223 | 1828-1914 | 276 |
| 131 | 118 | 239-241 | 171 | 489-496 | 224 | 1915-2010 | 277 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:10Z
Check the source to verify that this is the current version before use.

Table I (Cont)
Major Characteristics for War Reserve Items

| Lot Size | Sample Size | Lot Size | Sample Size | Lot Size | Sample Size | Lot Size | Sample Size |
|---|---|---|---|---|---|---|---|
| 132-133 | 119 | 242-243 | 172 | 497-504 | 225 | 2011-2115 | 278 |
| 134 | 120 | 244-246 | 173 | 505-513 | 226 | 2116-2232 | 279 |
| 135-136 | 121 | 247-249 | 174 | 514-521 | 227 | 2233-2361 | 280 |
| 137 | 122 | 250-252 | 175 | 522-530 | 228 | over 2361 | 298 |
| 138-139 | 123 | 253-255 | 176 | 531-540 | 229 | | |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:10Z
Check the source to verify that this is the current version before use.

Table II
Minor Characteristics for War Reserve Items

| Lot Size | Sample Size | Lot Size | Sample Size | Lot Size | Sample Size | Lot Size | Sample Size |
|---|---|---|---|---|---|---|---|
| 1-16 | all | 28-29 | 23 | 52-56 | 31 | 132-156 | 39 |
| 17 | 16 | 30-31 | 24 | 57-62 | 32 | 157-191 | 40 |
| 18 | 17 | 32-34 | 25 | 63-69 | 33 | 192-244 | 41 |
| 19-20 | 18 | 35-36 | 26 | 70-76 | 34 | 245-334 | 42 |
| 21 | 19 | 37-40 | 27 | 77-86 | 35 | 335-519 | 43 |
| 22-23 | 20 | 41-43 | 28 | 87-97 | 36 | 520-1120 | 44 |
| 24-25 | 21 | 44-47 | 29 | 98-112 | 37 | over 1120 | 45 |
| 26-27 | 22 | 48-51 | 30 | 113-131 | 38 | | |

Table III
Major Characteristics for Training and Test Items

| Lot Size | Sample Size | Lot Size | Sample Size | Lot Size | Sample Size | Lot Size | Sample Size |
|---|---|---|---|---|---|---|---|
| 1-16 | all | 28-29 | 23 | 52-56 | 31 | 132-156 | 39 |
| 17 | 16 | 30-31 | 24 | 57-62 | 32 | 157-191 | 40 |
| 18 | 17 | 32-34 | 25 | 63-69 | 33 | 192-244 | 41 |
| 19-20 | 18 | 35-36 | 26 | 70-76 | 34 | 245-334 | 42 |
| 21 | 19 | 37-40 | 27 | 77-86 | 35 | 335-519 | 43 |
| 22-23 | 20 | 41-43 | 28 | 87-97 | 36 | 520-1120 | 44 |
| 24-25 | 21 | 44-47 | 29 | 98-112 | 37 | over 1120 | 45 |
| 26-27 | 22 | 48-51 | 30 | 113-131 | 38 | | |

Table IV
Minor Characteristics for Training and Test Items

| Lot Size | Sample Size | Lot Size | Sample Size | Lot Size | Sample Size | Lot Size | Sample Size |
|---|---|---|---|---|---|---|---|
| 1-9 | all | 14-16 | 12 | 28-33 | 16 | 77-121 | 20 |
| 10 | 9 | 17-18 | 13 | 34-41 | 17 | 122-273 | 21 |
| 11 | 10 | 19-22 | 14 | 42-54 | 18 | over 273 | 22 |
| 12-13 | 11 | 23-27 | 15 | 55-76 | 19 | | |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:10Z
Check the source to verify that this is the current version before use.

4.3.2.1 Classification of characteristics (see 3.2). Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Adhesive, sealant (see dwg. 9220322 covering a detail of dwg. 9220309).

| Categories | Characteristics | Method of Inspection |
|---|---|---|
| Critical: None defined. | | |
| Major: | | |
| | 101. Objective evidence (see 6.2) for adhesive in accordance with dwg. 9220322 | Visual |
| Minor: None defined. | | |

4.3.2.1.2 Seal, lower (see dwg. 9220315 covering a detail of dwg. 9220309).

| Categories | Characteristics | Method of Inspection |
|---|---|---|
| Critical: None defined. | | |
| Major: | | |
| | 101. Thickness | T.M.C. (see 3.3) |
| | 102. Large radius | T.M.C. (see 3.3) |
| | 103. Small radius | T.M.C. (see 3.3) |
| | 104. Location of large hole | T.M.C. (see 3.3) |
| | 105. Diameter of large hole | T.M.C. (see 3.3) |
| | 106. Diameter of small holes | T.M.C. (see 3.3) |
| | 107. Location of small holes | T.M.C. (see 3.3) |
| | 108. Diameter of counterbores | T.M.C. (see 3.3) |
| | 109. Concentricity of counterbores with small hole diameter | T.M.C. (see 3.3) |
| | 110. Depth of counterbores | T.M.C. (see 3.3) |
| | 111. No tear, split, or crack | Visual |
| | 112. Flash removed | Visual |
| | 113. Correct Material (see 3.1) | Visual |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:10Z
Check the source to verify that this is the current version before use.

| Categories | Characteristics | Method of Inspection |
|---|---|---|

Minor:

201. Radius, countersink present.....Visual
202. Workmanship (see 3.4).....Visual/Manual

4.3.2.1.3 Body, connector (see dwg. 9220314 covering a detail of dwg. 9220309).

| Categories | Characteristics | Method of Inspection |
|---|---|---|

Critical: None defined.

Major:

101. Total length.....T.M.C.(see 3.3)
102. Diameter of end bosses.....T.M.C.(see 3.3)
103. Diameter of center boss.....T.M.C.(see 3.3)
104. Height of bosses.....T.M.C.(see 3.3)
105. Total thickness.....T.M.C.(see 3.3)
106. Large radius.....T.M.C.(see 3.3)
107. Small radius.....T.M.C.(see 3.3)
108. Diameter of center hole.....T.M.C.(see 3.3)
109. Location of center hole.....T.M.C.(see 3.3)
110. Diameter of 2 end holes.....T.M.C.(see 3.3)
111. Location of 2 end holes.....T.M.C.(see 3.3)
112. Diameter of small holes.....T.M.C.(see 3.3)
113. Location of small holes.....T.M.C.(see 3.3)
114. Diameter of top counterbores.....T.M.C.(see 3.3)
115. Concentricity of top counterbores with small holes.....T.M.C.(see 3.3)
116. Depth of top counterbores.....T.M.C.(see 3.3)
117. Depth of bottom counterbores.....T.M.C.(see 3.3)
118. Diameter of bottom counterbores.....T.M.C.(see 3.3)
119. Concentricity of bottom counterbores with small holes.....T.M.C.(see 3.3)
120. Radius, countersink or chamfer missing.....Visual
121. Mold flash removed.....Visual/Manual
122. No crack, split or tear.....Visual
123. Material (see 3.1).....Visual

Minor:

201. Workmanship (see 3.4).....Visual/Manual



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:10Z
Check the source to verify that this is the current version before use.

4.3.2.1.4 Insulator, top (see dwg. 9220313 covering a detail of dwg. 9220309).

| Categories | Characteristics | Method of Inspection |
|---|---|---|
| Critical: None defined. | | |
| Major: | | |
| 101. | Total length | T.M.C. (see 3.3) |
| 102. | Thickness | T.M.C. (see 3.3) |
| 103. | Large radius | T.M.C. (see 3.3) |
| 104. | Small radius | T.M.C. (see 3.3) |
| 105. | Diameter of center hole | T.M.C. (see 3.3) |
| 106. | Location of center hole | T.M.C. (see 3.3) |
| 107. | Diameter of 10 small holes | T.M.C. (see 3.3) |
| 108. | Location of 10 small holes | T.M.C. (see 3.3) |
| 109. | No tear, split or crack | Visual |
| 110. | Flash removed | Visual |
| 111. | Material (see 3.1) | Visual |
| Minor: | | |
| 201. | Workmanship (see 3.4) | Visual/Manual |

4.3.2.1.5 Connector body assembly (see dwg. 9220309 covering a detail of dwg. 9220308).

| Categories | Characteristics | Method of Inspection |
|---|---|---|
| Critical: None defined. | | |
| Major: | | |
| 101. | Properly assembled | Visual |
| Minor: | | |
| 201. | Workmanship (see 3.4) | Visual/Manual |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:10Z
Check the source to verify that this is the current version before use.

4.3.2.1.6 Screw guide (see dwg. 9220311 covering a detail of dwg. 9220308).

| Categories | Characteristics | Method of Inspection |
|---|---|---|
| Critical: None defined. | | |
| Major: | | |
| 101. | Diameter of head | Gage |
| 102. | Width of slot | Gage |
| 103. | Depth of slot | Gage |
| 104. | Length of pilot diameter | Gage |
| 105. | Length from right of head to right end, min | Gage |
| 106. | Total length | Gage |
| 107. | Length of right diameter | Gage |
| 108. | Depth of chamfer | Gage |
| 109. | Right diameter | Gage |
| 110. | Pilot diameter | Gage |
| 111. | Pitch diameter of thread | Gage |
| 112. | Major diameter of thread, min | Gage |
| 113. | Inside diameter | Gage |
| 114. | Depth of inside diameter | Gage |
| 115. | Material (see 3.1) | Gage |
| Minor: | | |
| 201. | Shoulder or thread clearance present | Visual |
| 202. | Workmanship (see 3.4) | Visual/Manual |

4.3.2.1.7 Screw, connector (see dwg. 9220310-2 covering a detail of dwg. 9220308.)

| Categories | Characteristics | Method of Inspection |
|---|---|---|
| Critical: None defined. | | |



Source: https://assist.dla.mil -- Downloaded: 202610-22T19:10Z
Check the source to verify that this is the current version before use.

| Categories | Characteristics | Method of Inspection |
|---|---|---|
| Major: | | |
| | 101. Pitch diameter of thread | Gage |
| | 102. Major diameter of thread, min | Gage |
| | 103. Thread clearance, max | Gage |
| | 104. Pilot diameter | Gage |
| | 105. Distance from left fact to left shoulder | Gage |
| | 106. Total length | Gage |
| | 107. Length of head | Gage |
| | 108. Width of slot | Gage |
| | 109. Depth of slot | Gage |
| | 110. Pilot shoulder clearance missing | Visual |
| | 111. Diameter of head | Gage |
| | 112. Material(see 3.1) | Visual |
| Minor: | | |
| | 201. Location of screw slot | Gage |
| | 202. Chamfer present | Visual |
| | 203. Proper finish | Visual |
| | 204. Workmanship (see 3.4) | Visual/Manual |

4.3.2.1.8 Contact, connector (see dwg. 9220312 covering a detail of dwg. 9220308).

| Categories | Characteristics | Method of Inspection |
|---|---|---|
| Critical: None defined. | | |
| Major: | | |
| | 101. Objective evidence (see 6.2) for contact in accordance with dwg. 9220312 | Visual |
| Minor: | | |
| | 201. Workmanship (see 3.4) | Visual/Manual |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:10Z
Check the source to verify that this is the current version before use.

4.3.2.1.9 Connector, electrical (see dwg. 9220308).

| Categories | Characteristics | Method of Inspection |
|---|---|---|

Critical: None defined.

Major:

| | | |
|---|---|---|
| 101. | All parts present | Visual |
| 102. | Proper assembly | Visual |
| 103. | Distance from ends of pins to body of connector | Gage |

Minor:

| | | |
|---|---|---|
| 201. | Workmanship (see 3.4) | Visual/Manual |

4.3.2.1.10 Bag, Packing, for Repair Parts (see dwg. 8883535 covering dwg. part number 8883535-2 and 5.2).

| Categories | Characteristics | Method of Inspection |
|---|---|---|

Critical: None defined.

Major:

| | | |
|---|---|---|
| 101. | Material (see 3.1) | Visual |
| 102. | Length before packing, min | Measure* |
| 103. | Width before packing, min | Measure* |
| 104. | Objective evidence (see 6.2) for heat seal test in accordance with MIL-P-116 | Visual |
| 105. | Properly packed | Visual |
| 106. | No tear, split, or crack in bag | Visual |
| 107. | Proper heat seal | Visual |

*Measure with suitable scale.

Minor:

| | | |
|---|---|---|
| 201. | Marking | Visual |
| 202. | Workmanship (see 3.4) | Visual/Manual |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:10Z
Check the source to verify that this is the current version before use.

4.3.2.1.11 Packing and Marking for Storage and Shipments (see dwg. 8808362 and 5.2).

| Categories | Characteristics | Method of Inspection |
|---|---|---|

Critical: None defined.

Major:

| | | |
|---|---|---|
| 101. | Gross load weight, max. | Measure* |
| 102. | Contents tight in package. | Manual |
| 103. | Correctly packed | Visual/Manual |
| 104. | Package material (see 3.1). | Visual |

*Determine weight with a suitable scale.

Minor:

| | | |
|---|---|---|
| 201. | Marking. | Visual |
| 202. | Workmanship (see 3.4). | Visual/Manual |

4.3.2.1.12 Preparation for delivery (see 5.1).

| Categories | Characteristics | Method of Inspection |
|---|---|---|

Critical: None defined.

Major:

| | | |
|---|---|---|
| 101. | Preservation, packaging, packing and marking in accordance with MIL-STD-1169. | Visual/Manual |

Minor: None defined.

4.3.3 Testing. Not applicable.

4.3.4 Acceptance inspection equipment.

4.3.4.1 Critical and major characteristics and tests. Inspection and testing shall be performed with the acceptance inspection equipment, operating instructions, and calibration instructions specified on the Equipment Lists (EL). EL's for assemblies are listed on the Equipment



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:10Z
Check the source to verify that this is the current version before use.

Tabulation, ET-9220308. When either of the conditions listed below exist, the contractor shall design required equipment or specify suitable commercial equipment and obtain approval prior to use on the contract.

a. Any deviation from equipment or procedures specified on the EL is desired (see 6.3).
b. The code "CD" is listed in the "Part or Identifying Number" column on the EL (see 6.1.2).

4.3.4.2 Minor characteristics and tests. Acceptance inspection equipment for minor characteristics is not specified on ELs. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for minor classification inspection shall be approved by the Government representative authorized by the procuring agency.

4.4 Test methods. Not applicable.

## 5. PREPARATION FOR DELIVERY

5.1 Production items.

5.1.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.1.1.1 Level A. The connector shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169 (MU).

5.1.1.2 Level C. The connector shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169 (MU).

5.1.2 Packing.

5.1.2.1 Levels A and C. The connector shall be packed in accordance with the applicable instructions contained in MIL-STD-1169 (MU).

5.1.3 Marking. Marking shall be in accordance with MIL-STD-1169 (MU).

5.2 Repair parts.

5.2.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.2.1.1 Level A. The connector shall be packaged in accordance with dwg. 8883535 and 8808362 using the specified moisture barrier.

5.2.1.2 Level C. The connector shall be packaged in accordance with dwg. 8808362 except that the moisture barrier may be omitted.

5.2.2 Packing.

5.2.2.1 Level A and C. The connector shall be packed in accordance with dwg. 8883535 and 8808362.

5.2.3 Marking. Marking shall be as specified in accordance with dwg. 8883535 and 8808362 as applicable.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:10Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

6.1.1 Procurement requirements.

a. Title, number, and date of this specification.
b. Production or Repair Parts.
c. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).
d. Part used for War Reserve, Training or Test Projectile.

6.1.2 Contract data requirements (see 4.3.4.1). Data specified in 4.3.4.1 will be delivered as identified on a numbered DD Form 1664 or specification when specified on a DD Form 1423 incorporated in the contract.

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment (see 4.3.4.1). The contractor shall obtain approval from the Commanding Officer, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SMUPA-QA-I.

Custodian:
Army - MU

Preparing activity:
Army - MU

Project No. 1110-A030



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:10Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS

Commanding Officer
Picatinny Arsenal
ATTN: SMUPA-NR
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:10Z
Check the source to verify that this is the current version before use.

# SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

MIL-C48019(MU) Connector, Electrical

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:10Z
Check the source to verify that this is the current version before use.