MILITARY SPECIFICATION

CONTAINER, SHIPPING AND STORAGE MARK 300 MOD 0

(For Torpedo Mk 46 Mod 0)

This specification has been approved by the Bureau of Naval Weapons, Department of the Navy

1. SCOPE

1.1 Scope.- This specification covers the Shipping and Storage Container Mark 300 Mod 0, herein referred to as the "Container." (See 6.1 for the intended use of the Container.)

2. APPLICABLE DOCUMENTS

2.1 Government documents.- The following documents, of the issue in effect on date of invitation for bids, form a part of this specification, to the extent specified herein.

SPECIFICATIONS

Military

MIL-W-21927	Weapons, Handling and Preparation for Delivery of; General requirements for

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:58Z
Check the source to verify that this is the current version before use.

STANDARDS

Military

MIL-STD-129	Marking for Shipment and Storage

DRAWINGS

Bureau of Naval Weapons

BuWeps LD 541201 (List of Drawings)	Container, Shipping and Storage Mk 300 Mod 0 and all documents listed thereon

(Copies of specifications, standards, drawings, and publications required by the supplier in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Preproduction sample.- Unless otherwise specified in the contract or order, the preproduction sample shall:

(a) Be manufactured using the procedures proposed for production

(b) Consist of one Container

(c) Be tested as specified in section 4 herein and is for the purpose of determining that, prior to starting production, the supplier's production methods are capable of yielding items that comply with the technical requirements of the contract

3.2 Basic requirements.-

3.2.1 Materials and treatments of materials and parts.- Unless otherwise specified in the contract or order, all materials and treatments

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:58Z
Check the source to verify that this is the current version before use.

of materials and parts used in the manufacture of the Container shall be in accordance with the requirements specified herein, and with the applicable documents listed in BuWeps LD 541201. No fungus nutrient materials shall be used.

3.2.2 Gages.- The supplier shall provide whatever gages are necessary and adequate to assure that the material and parts of the Container will meet dimensions and requirements shown on applicable documents. When requested by the supplier, the procuring activity will furnish existing drawings of pertinent Naval final inspection gages for use only in the designing of the supplier's gages. This action does not relieve the supplier of the responsibility for designing and manufacturing the gages needed for satisfactory fulfillment of the contract requirements.

3.2.3 Inspection and test equipment and facilities.- The supplier shall furnish and maintain all necessary inspection and test equipment and facilities and provide personnel for performing all tests. The test equipment shall be adequate in quantity to permit performance of the required tests for the Container.

3.3 Performance requirement.-

3.3.1 Airtightness.- The Container shall not leak air at a rate greater than 1.0 pound per square inch, gage (psig) per hour when pressurized to 1.25 $\pm$ .25 psig (above ambient).

3.4 Environmental requirements.-

3.4.1 Vibration.- The Container, in its normal shipping attitude, with one Torpedo Main Assembly or Gas Generator (see 6.1), shall withstand vibration through the following frequencies (3.4.1.1 and 3.4.1.2) and thereafter show no evidence of damage to Container or contents and meet the performance requirement of this specification.

3.4.1.1 Variable frequency.- The Container shall withstand vibration of 5 to 60 cps at 1 inch double amplitude or a multiple of gravitational acceleration (g's) of 1.3, whichever is less.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:58Z
Check the source to verify that this is the current version before use.

3.4.1.2 Natural frequency.- The Container shall withstand vibration at the resonant frequency of the packaged-article cushioning system at 1.3 g's or 1 inch double amplitude, whichever is less, for a period of not less than 30 minutes.

3.4.2 Rough handling.- The Container, with one Torpedo Main Assembly or Gas Generator enclosed, shall withstand the following shock loading and thereafter show no evidence of structural damage to Container or contents or shifting of contents; and thereafter meet the performance requirements of this specification.

3.4.2.1 Cornerwise drop.- The Container shall withstand shock loading as induced by a cornerwise drop of not less than 24 inches on a steel or concrete surface on each of the 4 base corners.

3.4.2.2 Impact.- The Container shall withstand impact on all four vertical surfaces against a rugged unyielding surface at a velocity of 7.6 feet per second.

3.4.2.3 Roll-over.- The Container shall withstand being tipped slowly from its base to fall freely on each side on a steel or concrete surface.

3.4.2.4 Pushing and towing.- The Container shall withstand being pushed or towed a distance not less than 5 feet in line with longitudinal axis and not less than 5 feet normal to the longitudinal axis.

3.5 Workmanship.- The workmanship and finish shall be of sufficiently high grade to assure satisfactory operation consistent with the requirements of this specification. All parts used in the assembly shall be thoroughly clean and free of excess material, chips, and loose or splattered foreign materials. The standards of workmanship exhibited in any approved preproduction sample, subject to any qualification stated in the Government's notice of approval, shall be determinative of the requirements of the contract relative to workmanship insofar as not specifically covered by applicable specifications.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:58Z
Check the source to verify that this is the current version before use.

commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection.- Inspection of the Container shall be classified as follows:

(a) Preproduction inspection

(1) Preproduction sample (see 4.3.1)

(2) Preproduction tests (see 4.5)

(b) Periodic production inspection

(1) Periodic production sampling (see 4.3.2)

(2) Periodic production tests (see 4.6)

(c) Acceptance inspection

(1) Acceptance sampling (4.3.3)

(2) Acceptance tests and examinations (see 4.7)

4.3 Sampling.-

4.3.1 Preproduction sample.- A preproduction sample of one Container manufactured in accordance with 3.1, shall be subjected to the preproduction tests detailed in 4.5 at a facility designated by the procuring activity. Acceptance of the preproduction sample shall be based on no defects in the sample. Further production of the Container by the supplier, prior to approval of the preproduction sample, shall be at the supplier's risk.

4.3.2 Periodic production sampling.- Periodic production tests detailed in 4.6 shall be performed at a facility designated by the procuring activity. Samples shall consist of units that have satisfactorily passed the acceptance tests and examinations detailed in 4.7; selected as follows:

(a) Step 1.- Upon initiation of production, randomly select 1 unit from each group of 10 units. Upon satisfactory compliance of samples selected from three consecutive groups, proceed to step 2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:58Z
Check the source to verify that this is the current version before use.

(b) Step 2.- Randomly select 1 unit from each group of 25 units. Upon satisfactory compliance of samples selected from three consecutive groups, proceed to step 3.

(c) Step 3.- Randomly select 1 unit from each group of 50 units. Continue with step 3 for the balance of the contract or until a defective unit is found.

4.3.2.1 Defective units.- When a defective unit is found in any group the supplier shall:

(a) Determine the cause of the defect

(b) Determine if the defect is an isolated case

(c) Take the necessary action to eliminate the defects from units on hand and, if so directed by the procuring activity, from those units previously shipped.

(d) Submit to the procuring activity for approval, the proposed corrective action to prevent recurrence of the defect.

(e) Return to step 1 (4.3.2(a)) and proceed as indicated for inspection of units subsequently produced.

4.3.3 Acceptance sampling.- The tests and examinations detailed in 4.7 shall be conducted on each Container to be delivered; therefore, there shall be no sampling plan for acceptance. Defective units shall be rejected.

4.4 Test conditions.- Unless otherwise specified, the Container shall be subjected to tests under the following conditions:

(a)	Temperature	Ambient (20 to 110 degrees F)
(b)	Humidity (Relative)	Ambient, up to 95 percent
(c)	Altitude	Normal ground atmospheric pressure

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:58Z
Check the source to verify that this is the current version before use.

4.5 Preproduction tests.- The preproduction sample Container, with the Torpedo Main Assembly or Gas Generator (see 6.1) or simulated contents of equal weight distribution enclosed, shall be subjected to the following tests (4.5.2 through 4.5.3.4). With approval of the procuring activity, testing shall be at ambient temperature only. The preproduction sample shall be subjected to and satisfactorily pass the acceptance tests and examinations both prior to and after completion of the preproduction tests. Certified inspection data covering the results of preproduction tests shall be forwarded to the Bureau of Naval Weapons. Certified inspection data shall consist of the following:

(a) Date of tests and names of persons conducting tests

(b) Run or test plan used

(c) Serial number of the Container

(d) Test results of preproduction tests (4.5.2 through 4.5.3.4)

4.5.1 Preproduction test equipment.- The following items of test equipment are required to perform the preproduction tests specified herein.

(a) A compressor or pressurized tank capable of pressurizing the Container to 1.0 psig, minimum. The compressor or pressurized tank shall have a pressure gage, accurate within ± 0.1 psig

(b) Vibration test equipment capable of applying and monitoring the magnitude and direction of vibration specified in 4.5.2

(c) A hoist or fork-lift truck capable of lifting and moving the Container as specified in 4.5.3

4.5.2 Vibration.- Subject the Container to the vibration test for cushioned items as specified in Specification MIL-W-21927. Evidence of damage to the contents or the inability of the Container to pass the acceptance tests and examinations (4.7) constitutes a failure.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:58Z
Check the source to verify that this is the current version before use.

4.5.3 Rough handling.- Immediately after the following tests (4.5.3.1 through 4.5.3.4) examine the Container. Evidence of load shifting or binding as the contents are removed from the Container constitute a failure.

4.5.3.1 Cornerwise drop.- Subject the Container to the cornerwise drop test as specified in Specification MIL-W-21927.

4.5.3.2 Impact.- Subject the Container to the impact test as specified in Specification MIL-W-21927, except that the impact velocity shall be 7.6 feet per second.

4.5.3.3 Roll-over.- Subject the Container to the roll-over test as specified in Specification MIL-W-21927.

4.5.3.4 Pushing and towing.- Subject the Container to the pushing and towing test as specified in Specification MIL-W-21927.

4.6 Periodic production tests.- The periodic production sample, selected in accordance with 4.3.2, shall be subjected to the following tests (4.6.2). Certified inspection data covering the test results shall be forwarded to the Bureau of Naval Weapons. Certified inspection data shall consist of the following:

(a) Items 4.5(a) through 4.5(c)

(b) Test results of periodic production tests (4.6.2(a) through (f)

4.6.1 Periodic production test equipment.- The following items of test equipment are required to perform the periodic production tests specified herein:

(a) A compressor or pressurized tank (see 4.5.1(a))

(b) Vibration test equipment (see 4.5.1(b))

(c) A hoist or fork lift truck (see 4.5.1(c))

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:58Z
Check the source to verify that this is the current version before use.

4.6.2 Periodic production test schedule.- Subject the Container to the following tests in the order indicated:

(a) Vibration (see 4.5.2)

(b) Cornerwise drop (see 4.5.3.1)

(c) Impact (see 4.5.3.2)

(d) Roll-over (see 4.5.3.3)

(e) Pushing and towing (see 4.5.3.4)

(f) Acceptance tests and examinations (see 4.7)

4.7 Acceptance tests and examinations.- The following tests and examinations (4.7.2 and 4.7.3) shall be conducted on each Container to be delivered. Failure to pass any test or examination specified herein shall be considered cause for rejection of the unit.

4.7.1 Acceptance test equipment.- The only item of test equipment required to perform the acceptance tests specified herein is a compressor or pressurized tank (see 4.5.1(a)).

4.7.2 Airtightness.- Pressurize the Container to 1.25 $\pm$ 0.25 psig and seal the inlet. Allow the Container to stand for 30 $\pm$ 5 minutes. A pressure drop in excess of 0.5 psig constitutes a failure.

4.7.3 Examination of product.- The Container shall be examined for conformance to the requirements specified herein and on drawings listed on BuWeps LD 541201. The presence of any one of the following defects shall constitute a failure:

(a) Container not complete; component parts missing

(b) Component parts not new; evidence of reclaimed, used, or salvaged components.

(c) Evidence of use of unauthorized repairs

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:58Z
Check the source to verify that this is the current version before use.

(d) Shock mounts not correctly installed

(e) Rubber surfaces of saddles and straps missing, damaged, or deteriorated

(f) Evidence of shock mount deterioration

(g) Use of unauthorized materials

(h) Evidence of substandard weld procedures

(i) Loose mechanical connections

(j) Paint damaged or coverage not complete

(k) Identification plate and markings not attached or not located as specified; not legible; data incomplete

(l) Packing not as specified in section 5

5. PREPARATION FOR DELIVERY

5.1 Packing.-

5.1.1 Level A.- Not applicable

5.1.2 Level B.- Not applicable

5.1.3 Level C.- Unless otherwise specified, packing for domestic shipment shall be in accordance with commercial packing methods, to protect the Container and finish from damage. The method used shall be commensurate with shipping at the lowest practical commercial rates.

5.2 Labeling and marking.- Unless otherwise specified, labeling and marking of all shipments shall be in accordance with Standard MIL-STD-129. Any special marking required by the contract or order shall be provided.

5.2.1 Marking shall be applied only to the packing material, as specified. Carload or truck load shipments do not require marking.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:58Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use.- The Container is intended as a reusable Container for use in both foreign and domestic shipment and indeterminate storage of one Torpedo Main Assembly Mk 46 Mod 0, or one Propellant Actuated Gas Pressure Generator, Mk 8 Mod 0, loaded or unloaded.

6.2 Ordering data.- Procurement documents should specify the following:

(a) Title, number, and date of this specification

(b) Facility assigned to perform preproduction and product verification tests

(c) Serialization requirements

(d) All additional samples required shall be provided and inspected at the expense of the supplier, when such additional samples are required because of failure of any Container(s) to pass the prescribed periodic production inspections

(e) Any exceptions to this specification

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:58Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

SPECIFICATION
MIL-C-81084(Wep) CONTAINER, SHIPPING AND STORAGE MK 300 MOD 0 (For Torpedo Mk 46 Mod 0)

ORGANIZATION *(Of submitter)*	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 APR 63 1426

C-6279

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:58Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY

Bureau of Naval Weapons
Washington, D. C. 20360

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

BUREAU OF NAVAL WEAPONS (RREN-5)
DEPARTMENT OF THE NAVY
WASHINGTON, D. C. 20360

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:58Z
Check the source to verify that this is the current version before use.