MILITARY SPECIFICATION

CART, CORROSION CONTROL, JET ENGINE

This Specification has been approved by the Naval Air Systems Command, Department of the Navy, Washington, D. C.

1. SCOPE

1.1 This specification covers a trailer mounted self-contained mobile unit that provides a convenient and safe method of applying fresh water as a rinsing agent and a preservative compound under low pressure spray action to the compressor section of aircraft jet engines.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Federal

L-P-378	Plastic Film, Polyethylene, Thin Gauges

Military

MIL-C-104	Crates, Wood, Lumber and Plywood Sheathed, Nailed and Bolted
MIL-P-116	Preservation, Methods of
MIL-L-7808	Lubricating Oil, Aircraft Turbine Engine, Synthetic Base

STANDARDS

Military

MIL-STD-129	Marking for Shipment and Storage
MIL-STD-1186	Cushioning, Anchoring, Bracing, Blocking, and Water Proofing, with Appropriate Test Methods

Source: https://assist.dla.mil -- Downloaded: 202610-23T05:57Z
Check the source to verify that this is the current version before use.

DRAWINGS

Navy Department, Bureau of Naval Weapons

65A102J1 Corrosion Control Cart, Jet Engine

3. REQUIREMENTS

3.1 Preproduction.- This specification makes provisions for preproduction testing.

3.2 Design and Construction.- The Corrosion Control Cart shall be designed and constructed in accordance with Bureau of Naval Weapons Drawing 65A102J1. In the event of conflict, this specification shall govern.

4. QUALITY ASSURANCE PROVISIONS

4.1 Supplier's Responsibility.- The supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own or any other facilities and services acceptable to the government. Inspection records of the examination and tests shall be kept complete and available to the government as specified in the contract or order. The government reserves the right to perform any of the inspections set forth in the specifications where such inspections are deemed necessary to assure supplies and services conforming to prescribed requirements.

4.2 Classification of Tests.- The inspection and testing of the cart shall be classified as follows:

a. Preproduction testing..... Sec. 4.4, 4.5
b. Production tests..... Sec. 4.6

4.3 Test Conditions.-

4.3.1 Standard Atmosphere Conditions.- Unless otherwise specified, tests shall be conducted at atmospheric pressure (approximately 29.92 inches Hg) and at room temperature (approximately 70 degrees F).

4.3.2 Fluid Flow.- The calibrations and performance checks of the displaced fluid shall be determined by containers calibrated in gallons and tenths of gallons.

4.3.3 Apparatus.- Apparatus used in conjunction with testing specified herein shall be furnished by supplier except for the water and preservative applicators which shall be supplied by the government.

4.4 Preproduction Testing.-

4.4.1 Preproduction Test Sample.- One cart shall be subjected to the preproduction tests specified in 4.5.

Source: https://assist.dla.mil -- Downloaded: 202610-23T05:57Z
Check the source to verify that this is the current version before use.

4.4.2 Preproduction Test Report.- After completion of the preproduction tests, a preproduction test report shall be prepared and three copies furnished to the procuring activity.

4.5 Preproduction Tests.- Preproduction tests shall consist of all tests described under 4.5.

4.5.1 Examination.- The cart shall be examined for conformance to requirements described herein and in the contract or order.

4.5.2 Hydrostatic Test.- The solution tank shall be hydrostatically tested to 200 PSI with all ports blocked. The water and preservative compartments shall be tested separately. Any leaks shall be cause for rejection.

4.5.3 Operational Test.- The cart shall be operated under the following conditions:

a. Air cylinder charged to 3000 PSIG

b. Pressure regulator set to 60 PSIG

c. 20 gallons of water and 5 gallons of preservative in the respective tank compartments

d. The water supply hose connected to a water applicator (General Electric P/N 21C2217 or equal) and the preservative supply hose to a preservative applicator (General Electric P/N 21C2216 or equal).

A leak check shall be made of all joints and connections while the tank is under pressure of 60 PSIG. Any leaks shall be cause for rejection. The delivery rates shall be checked and shall be a minimum of 10 GPM for the water and 1 GPM for the preservative. (Preservative shall be oil per MIL-L-7808 or "Rust-Lick, Incorporated, Boston, Massachusetts".)

4.5.4 Brake Test.- With the foot brakes set, the Corrosion Control Cart shall be towed over a level smooth concrete surface. Rotation of the rear wheels shall be cause for rejection.

4.6 Production Tests.- The production tests shall consist of tests specified in 4.5.2, 4.5.3, and 4.5.4.

5. PRESERVATION, PACKAGING, PACKING, AND MARKING

5.1 Preservation and Packaging.- Preservation and packaging shall be Level A or Level C as specified in the contract (see 6.2).

5.1.1 Level A.- The Corrosion Control Cart and all components thereof shall be cleaned in accordance with Procedure C-1 of Specification MIL-P-116. Exterior surfaces subject to corrosion shall be preserved in acoordance with Method I or MIL-P-116 or covered with a suitable barrier material.

Source: https://assist.dla.mil -- Downloaded: 202610-23T05:57Z
Check the source to verify that this is the currentversion before use.

5.1.2 Level C.- Preservation and Packaging shall be in accordance with the manufacturer's commercial practice.

5.2 Packing.- Packing shall be Level A or C as specified in the contract or order (see 6.2). Insofar as practicable shipping containers shall effect a close fit, contain identical quantities and be of uniform configuration.

5.2.1 Level A.- Each cart packaged as specified shall be securely braced within a MIL-C-104 crate, export type. The blocking and bracing shall be generally in accordance with MIL-STD-1186. The cart within the crate shall be provided with a waterproof shroud, material conforming to L-P-37B, 3 mils, thick, which shall cover the top and sides of the cart.

5.2.1.1 The cart shall be shipped without compressed air, water, or preservative.

5.2.1.2 The hoses shall be coiled on the mounting bracket and tied in three places with cotton tape.

5.2.1.3 All openings shall be covered with plastic or metal caps.

5.2.1.4 The rear tires shall be inflated to 60 p.si.i.g. and the front tires to 35 p.s.i.g.

5.2.2 Level C.- The carts shall be packaged for domestic shipment in accordance with the manufacturer's commercial practice. The packaging shall be adequate to afford protection from damage during direct shipment from the supply source to the first receiving activity. The shipment containers shall comply with the carrier rules and regulations applicable to the mode of transportation used.

5.2.2.1 The requirements of 5.2.1.1 through 5.2.1.4 shall apply.

5.3 Marking.- All carts and shipping containers shall be marked in accordance with MIL-STD-129. All items preserved and packaged Level C, must be marked in addition with: -

"Not Preserved For Long Term Storage"

6. NOTES

6.1 Intended Use.- The Corrosion Control Cart is intended for use with aircraft jet engines subjected to environmental conditions contributing to the corrosion of the internal rotating components. The cart is used to perform a fresh water rinse

Source: https://assist.dla.mil -- Downloaded: 202610-23T05:57Z
Check the source to verify that this is the currentversion before use.

operation for removal of surface deposits of salt and to apply a preservative compound to the internal rotating components of aircraft jet engines.

6.2 Ordering Data.- Procurement document shall specify the following: -

a. Title, number, and date of this specification.

b. Selection of applicable level of preservation and packaging.

(See 5.1). Level A shall be used for overseas shipment. Level C shall be used for domestic shipment.

c. Selection of applicable level of packing (see 5.2). Level A shall be used for overseas shipment. Level C shall be used for domestic shipment where the cart is intended for immediate use upon receipt.

Source: https://assist.dla.mil -- Downloaded: 202610-23T05:57Z
Check the source to verify that this is the currentversion before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:57Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity (as indicated on reverse hereof).

SPECIFICATION

MIL-C-81707(AS) CART, CORROSION CONTROL JET ENGINE

ORGANIZATION (Of submitter)	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS (Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)

SUBMITTED BY (Printed or typed name and activity)	DATE

DD, FORM 1 APR 63 1426

C-8979

Source: https://assist.dla.mil -- Downloaded: 202610-23T05:57Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY
Naval Air Systems Command
Washington, D.C. 20360

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

NAVAL AIR SYSTEMS COMMAND (AIR-52021)
DEPARTMENT OF THE NAVY
WASHINGTON, D. C. 20360

FOLD

☆ U. S. GOVERNMENT PRINTING OFFICE: 1969-341-515/A-3814

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:57Z
Check the source to verify that this is the current version before use.