MILITARY SPECIFICATION

KIT, MODIFICATION FOR 14XPM15 BATTERY FILLING KIT

1. SCOPE

1.1 This specification covers special requirements, quality assurance provisions, and the preparation for delivery criteria for one type of Modification Kit for 14XPM15 Battery Filling Kit used with Atomic Demolition Charge.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-B-22205 - Bag, Transparent, Flexible, Heat Sealable for Packaging Application
MIL-B-43014 - Hymnody Set Tape
MIL-P-116 - Preservation, Methods of

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1168 - Lot Numbering of Ammunition

DRAWINGS

ORDNANCE CORPS

8880602 - Marking and Sealing for Unit Packages
8883534 - Bag, Packing for Repair Parts
9242109 - Cover, Battery
9242110 - Activator, Toluene
9242111 - Absorbing, Sponges
9242112 - Tape
9242114 - Label
9242704 - Modification Kit for 14XPM15 Battery Filling Kit

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

9243146 - Carton Packing Ammunition for Modification Kit 14XPM15 Battery Filling Kit
9243147 - Bag, Packing, Ammunition for Battery Cover
9243171 - Box Set-up Packing Ammunition for Activator, Toluene
9243172 - Bag Packing Ammunition for Label
9243234 - Cellulose
9243437 - Gasket
9243438 - Bottle, Activator
9252250 - Case, Battery, Polyethylene
ET-9242704 - Equipment Tabulation

(Copies of specifications, standards, drawings, and publication required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The modification kit shall comply with all requirements specified on Drawing (dwg.) 9242704, with all requirements specified herein, and with the requirements of applicable specifications to the extent specified on the drawing and herein.

3.3 Workmanship.

3.3.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.3.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.3.3 Burrs. Parts shall be free from burrs.

3.3.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.3.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agents.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

4.2 First article inspection. Not applicable.

4.3 Product acceptance inspection.

4.3.1 Lot formation. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting safety, performance, storage, or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

4.3.1.1 Inspection lot. An inspection lot shall be the quantity of parts, subassemblies, or assemblies from the same lot, which are submitted to inspection for Government acceptance.

4.3.2 Product inspection examination. Critical characteristics shall require 100 percent inspection of all items in the spection lot. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table and inspected for all characteristics in the applicable classification. Any characteristic in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

Table I
Major Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-72	all	140-141	124	256-259	177	541-549	230
73	72	142	125	260-262	178	550-559	231
74	73	143-144	126	263-265	179	560-569	232
75	74	145	127	266-268	180	570-579	233
76	75	146-147	128	269-271	181	580-590	234
77	76	148-149	129	272-275	182	591-601	235
78	77	150	130	276-278	183	602-613	236
79	78	151-152	131	279-282	184	614-625	237
80	79	153-154	132	283-285	185	626-637	238
81-82	80	155-156	133	286-289	186	638-649	239
83	81	157	134	290-293	187	650-662	240
84	82	158-159	135	294-296	188	663-676	241
85	83	160-161	136	297-300	189	677-690	242
86	84	162-163	137	301-304	190	691-704	243
87	85	164-165	138	305-308	191	705-719	244
88-89	86	166-167	139	309-312	192	720-735	245
90	87	168	140	313-316	193	736-751	246
91	88	169-170	141	317-320	194	752-768	247
92	89	171-172	142	321-324	195	769-785	248
93	90	173-174	143	325-329	196	786-804	249
94-95	91	175-176	144	330-333	197	805-823	250
96	92	177-178	145	334-338	198	824-842	251
97	93	179-180	146	339-342	199	843-863	252
98	94	181-182	147	343-347	200	864-884	253
99-100	95	183-184	148	348-352	201	885-907	254
101	96	185-187	149	353-356	202	908-930	255
102	97	188-189	150	357-361	203	931-955	256
103	98	190-191	151	362-366	204	956-981	257
104-105	99	192-193	152	367-372	205	982-1008	258
106	100	194-195	153	373-377	206	1009-1036	259
107	101	196-197	154	378-382	207	1037-1066	260
108-109	102	198-200	155	383-388	208	1067-1098	261
110	103	201-202	156	389-393	209	1099-1131	262
111	104	203-204	157	394-399	210	1132-1166	263
112-113	105	205-207	158	400-405	211	1167-1204	264
114	106	208-209	159	406-411	212	1205-1243	265
115	107	210-212	160	412-417	213	1244-1285	266
116-117	108	213-214	161	418-424	214	1286-1330	267
118	109	215-217	162	425-430	215	1331-1378	268
119	110	218-219	163	431-437	216	1379-1429	269
120-121	111	220-222	164	438-443	217	1430-1483	270
122	112	223-224	165	444-450	218	1484-1542	271
123-124	113	225-227	166	451-457	219	1543-1605	272
125	114	228-230	167	458-465	220	1606-1673	273
126-127	115	231-232	168	466-472	221	1674-1747	274
128	116	233-235	169	473-480	222	1748-1827	275
129-130	117	236-238	170	481-488	223	1828-1914	276
131	118	239-241	171	489-496	224	1915-2010	277
132-133	119	242-243	172	497-504	225	2011-2115	278
134	120	244-246	173	505-513	226	2116-2232	279
135-136	121	247-249	174	514-521	227	2233-2361	280
137	122	250-252	175	522-530	228	2362- ∞	298
138-139	123	253-255	176	531-540	229		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

Table II
Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	1121-∞	45
26-27	22	48-51	30	113-131	38		

4.3.2.1 Classification of characteristics. Critical, major, and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Cellulose (see dwg 9243234); bottle activator (see dwg 9243438); label (see dwg 9242114) covering details of dwgs 9242110 and 9242704 as applicable.

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Objective evidence (see 6.2) for parts in accordance with applicable drawing	Visual
Minor:		
201.	Workmanship (see 3.3)	Visual-Manual

4.3.2.1.2 Activator, toluene (see dwg 9242110) covering a detail of dwg 9242704.

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Material (see 3.1)	Visual
102.	Label present	Visual
Minor: None defined.		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

4.3.2.1.3 Tape (see dwg 9242112) covering a detail of dwg 9242704.

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Material (see 3.1)	Visual
102.	Diameter max	*Measure
103.	Width of tape roll	*Measure

* Measure with suitable scale

Minor: None defined.

4.3.2.1.4 Absorbing, sponges (see dwg 9242111) covering a detail of dwg 9242704.

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Location of holes sponge No. 1 and 2	*Measure
102.	Length sponge No. 1,2,3,4 and 5	*Measure
103.	Width sponge No. 1,2,3,4, and 5	*Measure
104.	Thickness sponge No. 1,2,3,4, and 5	*Measure
105.	Diameter of holes sponge No. 1 and 2	*Measure
106.	Material (see 3.1)	Visual
107.	Properly stacked and wrapped	Visual
108.	No tear or split in sponge	Visual

* Measure with suitable scale with material in its relaxed, undistorted configuration

Minor: None defined.

4.3.2.1.5 Gasket (see dwg 9243437) covering a detail of dwg 9242704.

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Outside diameter	Gage
102.	Thickness	Gage
103.	Hole present	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

104. Material (see 3.1).....Visual
105. No tear split or hole in gasket.....Visual

Minor:
201. Workmanship (see 3.3).....Visual-Manual

4.3.2.1.6 Cover Battery (see dwg 9242109 part Nos. 9242109-1 and 2) covering details of dwg 9252250.

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:
101. Functional check of all dimensions, except thickness, and location of all cavities.....Gage
102. Thickness.....Gage
103. Materials (see 3.1).....Visual
104. Proper bonding surface process.....Visual

Minor:
201. Workmanship (see 3.3).....Visual-Manual

4.3.2.1.7 Case, battery, polyethylene (see dwg 9252250).

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:
101. Part No. 1 and 2 present on dwg 9242109.....Visual

Minor: None defined.

4.3.2.1.8 Modification kit for 14XPM15 battery filling kit (see dwg 9242704).

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:
101. All items present.....Visual

Minor: None defined.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

4.3.2.1.9 Box set-up packing ammunition for activator, toluene (see dwg 9243171 and section 5).

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Close box in accordance with MIL-B-43014	Visual
102.	Marking	Visual
103.	Packaging material (see 3.1)	Visual
Minor: None defined.		

4.3.2.1.10 Bag packing ammunition for label (see dwg 9243172 and section 5).

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Seal in accordance with MIL-B-22205	Visual-Manual
102.	Packaging material (see 3.1)	Visual
Minor: None defined.		

4.3.2.1.11 Bag packing ammunition for battery cover (see dwg 9243147).

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Number of items in bag	Visual-Manual
102.	Sealing in accordance with 8880602	Visual-Manual
103.	Packaging material (see 3.1)	Visual
104.	No holes in bag	Visual
Minor: None defined.		

4.3.2.1.12 Bag, packing, for repair parts (see dwg 8883534 covering dwg. part number 8883534-1 & 3 and section 5).

Categories	Characteristics	Method of inspection
Critical: None defined.		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

Major:
101. Material (see 3.1).....Visual
102. Length before packing, min.....*Measure
103. Width before packing, min.....*Measure
104. Objective evidence (see 6.2) available for heat seal test in accordance with MIL-P-116.....Visual
105. Properly packed.....Visual
106. No tear, split, or crack in bag.....Visual

* Measure with suitable scale.

Minor:
201. Marking.....Visual
202. Workmanship (see 3.3).....Visual-Manual

4.3.2.1.13 Carton packing ammunition for modification kit 14XPM15 battery filling kit (see dwg 9243146).

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:
101. Bagged Part No. 9242109 on edge against side of carton.....Visual
102. Boxed part No. 9242110 upright in corner opposite of bag.....Visual
103. Packing of remaining items.....Visual
104. Contents tight in carton.....Manual
105. Carton sealed in accordance with 8880602.....Visual
106. Marking.....Visual
107. Packaging material (see 3.1).....Visual

Minor: None defined.

4.3.3 Testing. Not applicable.
4.3.4 Acceptance inspection equipment.
4.3.4.1 Critical and major characteristics and tests. Inspection and testing shall be performed with the acceptance inspection equipment, operating instructions, and calibration instructions specified on the Equipment Lists (EL). EL's for assemblies are listed on the Equipment Tabulation, ET-9242704. When either of the conditions listed below exist, the contractor shall design required equipment or specify suitable commercial equipment. The contractor shall obtain approval of such designs, operating instructions, and special calibration instructions as specified in 6.3 prior to use on the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

a. Any deviation from equipment or procedures specified on the EL is desired.
b. The code "CD" is listed in the "Part of Identifying Number" column on the EL.

4.3.4.2 Minor characteristics and tests. Acceptance inspection equipment for minor characteristics is not specified on EL's. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for minor classification inspection shall be approved by the Government representative authorized by the procuring agency.

4.4 Test methods. Not applicable.

5.0 PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.1.1 Level A. The modification kit shall be packaged in accordance with dwgs 8883534, 9243147, 9243171, 9243172, and 9243146, using the specified moisture barrier.

5.1.2 Level C. The modification kit shall be packaged in accordance with 9243171 and 9243146 except that the moisture barrier may be omitted.

5.2 Packing.

5.2.1 Level A and C. The modification kit shall be packed in accordance with dwgs 8883534, 9243147, 9243171, 9243172 and 9243146.

5.3 Marking. Marking shall be as specified in accordance with dwgs 8883534, 9243147, 9243171, 9243172, and 9243146, as applicable.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification.
b. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment. The contractor shall obtain approval of equipment designs, operating instructions, and calibration instructions from the Commanding Officer, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SMUPA-NR4.

Custodian:
Army - MU

Preparing Activity:
Army - MU

Project No. 1195-A056

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

MIL-K-50295(MU) Kit, Modification for 14XPM15 Battery Filling Kit

ORGANIZATION

CITY AND STATE	CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

   ☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*	DATE

DD FORM 1 JAN 66 1426 REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS

Commanding Officer
Picatinny Arsenal
ATTN: SMUPA-NR
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.