MIL-S-63385A (AR)
24 July 1981
SUPERSEDING
MIL-S-63385 (AR)
5 DECEMBER 1979

MILITARY SPECIFICATION

SABOT, 60MM PRACTICE: M3
ASSEMBLING AND PACKING

This specification is approved for use by the US Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification contains requirements not covered by the drawings and provides quality assurance provisions for the fabrication of parts, assembly and packing of one type of training round for the 60MM Mortar System.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids, or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables

MIL-STD-810 - Environmental Test Methods

FSC: 1315

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 202640-23T02:45Z
Check the source to verify that this is the current version before use.

DRAWINGS (see 6.4)

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND (ARRADCOM)

9328601	-	Sabot, 60MM, Practice, M3
9329479	-	Bag, Barrier
9329480	-	Box, Ammunition, Packing For Sabot, 60MM Practice M3, and 81MM, Practice M1 Metal Parts Assembly
9329481	-	Packing and Marking For Box Ammunition, Packing, for Sabot, 60MM, Practice, M3, and 81MM, Practice, M1, Metal Parts Assembly

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with the applicable drawings and specifications.

3.2 Assembly. The sabot assembly shall comply with all requirements specified on drawing (dwg.) 9328601 and associated drawings and with all requirements specified in applicable specifications and standards.

3.3 Proving ground ballistic test. The Sabot assembly shall impact within an area of five by fifteen meters placed two meters from the mortar tube, shall separate from the 22mm projectile, and shall be reuseable when test fired in the applicable equipment and subjected to temperature conditions of minus 25°F to plus 120°F.

3.3.1 Humidity test. The Sabot assembly shall withstand exposure to a humid atmosphere when tested per MIL-STD-810, procedure V (limited to three cycles).

3.4 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.5 Workmanship. The item of shipment, its components, and materials shall be free from dirt, chips, grease and other foreign matter. There shall be no cracks, scratches, dents, gouges, holes, porous areas, distortion, or undesirable characteristics which would in any way detract from the useability of the product for its intended purpose. Parts and assemblies shall be free from all contaminants and damage after cleaning.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

Source: https://assist.dla.mil -- Downloaded: 202640-23T02:45Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item:

a. First Article Inspection

b. Quality Conformance Inspection

4.3 First article inspection

4.3.1 Submission. The contractor shall submit a first article sample as designated by the contracting officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the components in the quantities indicated in Table 1.

4.3.2 Inspections to be performed. See MIL-A-48078 and Table 1 specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 202640-23T02:45Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-63385A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
	Sabot, 60MM, Practice, M3	1 OF 2	See Below
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Sabot, 60MM, Practice, M3				
	Dwg. 9328601				
	Examination for defects	5		3.2(a)	4.4.2.1/4.4.2.1.1
	Proving Ground Test (a)				
	Temperature humidity conditioning	10		3.3.1	4.5.2
	+70°F temperature conditioning	10		3.3	4.5.2
	+120°F temperature conditioning	10		3.3	4.5.2
	-20°F temperature conditioning	10		3.3	4.5.2
	Body				
	Dwg. 9328599				
	Examination for defects	5		3.2	4.4.2.2
	Tail Fin				
	Dwg. 9328600				
	Examination for defects	5		3.2	4.4.2.3
	Nose				
	Dwg. 9311187				
	Examination for defects	5		3.2	4.4.2.4
	Flange Nut				
	Dwg. 9311189				
	Examination for defects	5		3.2	4.4.2.5

NOTES: (a) The forty rounds to be tested and returned to the production lot after cleaning and alignment gaging in accordance with para. 4.4.2.1 Major 101 and Major 110 or para. 4.4.2.1.1 Major 101 and Major 107.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil - Downloaded: 2020-10-23T02:45Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-63385A(AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER / NEXT HIGHER ASSEMBLY
	Sabot, 60MM, Practice, XM3 Metal Parts Assembly				See Below
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Barrel No. 1 (If applicable) Dwg. 9311185 Examination for defects	5		3.2	4.4.2.6
	Barrel No. 2 (If applicable) Dwg. 9311186 Examination for defects	5		3.2	4.4.2.7
	Barrel (If applicable) Dwg. 9311196 Examination for defects	5		3.2	4.4.2.8

NOTES:

Source: https://assist.dla.mil - Downloaded: 2025-10-29T02:45Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination. See MIL-A-48078. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 202610-23T02:45Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-63385A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	Sabot, 60MM, Practice, M3	1 OF 1	9328601
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Inside profile and alignment of barrel or barrels (as applicable)		100%	3.2	Gage
102	Barrel No. 1 fully seated into barrel No. 2 (prior to assembly of sabot) (if applicable)		100%	3.2	Visual
103	Tail fin torque		0.40%	3.2	Gage
104	Nose torque		0.40%	3.2	Gage
105	Setscrew torque		0.40%	3.2	Gage
106	Rear barrel threads damaged		0.40%	3.2	Visual
107	Presence of adhesive on inside diameter (if applicable)		100%	3.2	Visual
108	Overall length of sabot, max.		0.40%	3.2	Gage
109	Runout of forward to rear inside diameter		0.40%	3.2	Gage
110	Profile and alignemnt of sabot with barrels		100%	3.2	Gage
Minor					
201	Presence of nicks or gouges on interior or exterior		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil - Downloaded: 2025-10-29T02:14:52Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-63385A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.2	Body		9328599
			NEXT HIGHER ASSEMBLY 9328601

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outside diameter, max.		0.40%	3.2	Gage
102	Forward inside diameter		0.40%	3.2	Gage
103	Rear inside diameter		0.40%	3.2	Gage
104	True position of rear inside diameter with forward inside diameter		0.40%	3.2	Gage
105	Length between gas checks (3 places)		0.40%	3.2	Gage
106	Depth of gas checks (4 places)		0.40%	3.2	Gage
107	Length from forward face to center of first gas check		0.40%	3.2	Gage
108	Overall length		0.40%	3.2	Gage
109	Runout of front face with bourrelet diameter		0.40%	3.2	Gage
110	Runout fo forward inside diameter with bourrelet diameter		0.40%	3.2	Gage
111	Runout of 9.755 radius with bourrelet diameter		0.40%	3.2	Gage
112	Runout of 30.0 radius with bourrelet diameter		0.40%	3.2	Gage
113	Runout of aft face with bourrelet diameter		0.40%	3.2	Gage
Minor					
201	Presence of burrs		0.65%	3.5	Visual
202	Surface finish improper		0.65%	3.2	Visual/Manual
203	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 202610-23T02:45Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-63385A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.3	Tail Fin	1 OF 1	9328600
			NEXT HIGHER ASSEMBLY: 9328601

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Forward inside diameter		0.40%	3.2	Gage
102	Set screw threads missing or damaged		0.40%	3.2	Gage
103	Diameter of fins		0.40%	3.2	Gage
104	Runout of fin diameter with forward inside dia.		0.40%	3.2	Gage
105	Pitch diameter of rear thread		0.40%	3.2	Gage
106	Minor diameter of rear thread		0.40%	3.2	Gage
107	Runout of the pitch diameter of rear thread with the forward inside diameter		0.40%	3.2	Gage
108	Width of fins		0.40%	3.2	Gage
109	True position of fins to forward inside diameter		0.40%	3.2	Gage
110	Perpendicularity of rear face with the forward inside diameter		0.40%	3.2	Gage
111	Pitch diameter of set screw threads		0.40%	3.2	Gage
112	Minor diameter of set screw threads		0.40%	3.2	Gage
113	True position of set screw threads		0.40%	3.2	Gage
114	Overall length		0.40%	3.2	Gage
Minor					
201	Surface finish improper		0.65%	3.2	Visual/Manual
202	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:45Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-63385A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9311187
4.4.2.4	Nose				NEXT HIGHER ASSEMBLY 9328601
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Rear inside diameter		0.40%	3.2	Gage
102	Threads missing or damaged		0.40%	3.2	Visual
103	Pitch diameter of threads		0.40%	3.2	Gage
104	Minor diameter of threads		0.40%	3.2	Gage
105	Runout of rear inside diameter with the pitch diameter of threads		0.40%	3.2	Gage
106	Overall length		0.40%	3.2	
Minor					
201	Presence of burrs		0.65%	3.5	Visual
202	Protective finish missing or inadequate		0.65%	3.1	Visual
203	Cut-out flat missing		0.65%	3.2	Visual
204	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:45Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-63385A(AR)

PARAGRAPH	TITLE		SHEET	DRAWING NUMBER
4.4.2.5	Flange Nut		1 OF 1	9311189
				NEXT HIGHER ASSEMBLY: 9328601

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pitch diameter of threads		0.40%	3.2	Gage
102	Minor diameter of threads		0.40%	3.2	Gage
103	Inside center cavity diameter		0.40%	3.2	Gage
104	Aft inside diameter		0.40%	3.2	Gage
105	Distance between forward face to aft surface of inside center cavity		0.40%	3.2	Gage
106	Runout of the pitch diameter of the thread with the rear inside diameter		0.40%	3.2	Gage
107	Knurl missing		0.40%	3.2	Visual
108	Overall length		0.40%	3.2	Gage
Minor					
201	Protective finish missing or inadequate		0.65%	3.1	Visual
202	Inside diameter of aft cavity		0.65%	3.2	Gage
203	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:45Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET	DRAWING NUMBER
4.4.2.6	Barrel No. 1 (If applicable)		1 OF 1	9311185
				NEXT HIGHER ASSEMBLY: 9328601

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pitch diameter of forward thread		0.40%	3.2	Gage
102	Major diameter of forward thread		0.40%	3.2	Gage
103	Pitch diameter of rear thread		0.40%	3.2	Gage
104	Major diameter of rear thread		0.40%	3.2	Gage
105	Outside diameter		0.40%	3.2	Gage
106	Runout of the pitch diameter of the forward thread with the outside diameter		0.40%	3.2	Gage
107	Runout of the pitch diameter of the rear thread with the outside diameter		0.40%	3.2	Gage
108	Inside diameter excluding stepped area		0.40%	3.2	Gage
109	Runout of inside diameter with outside diameter		0.40%	3.2	Gage
110	Overall length		0.40%	3.2	Gage
111	Rear inside diameter		0.40%	3.2	Gage
112	Distance from aft face to forward face of center inside step		0.40%	3.2	Gage
Minor					
201	Presence of burrs		0.65%	3.5	Visual
202	Protective finish missing		0.65%	3.2	Visual
203	Chamfered grooves missing		0.65%	3.2	Visual
204	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:45Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-63385A(AR)

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER
4.4.2.7	Barrel No 2. (If applicable)		9311186
			NEXT HIGHER ASSEMBLY 9328601

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Forward outside diameter		0.40%	3.2	Gage
102	Center inside diameter		0.40%	3.2	Gage
103	Outside diameter forward of set screw groove (1.510 dimension)		0.40%	3.2	Gage
104	Runout of central inside diameter with forward outside diameter and outside diameter forward of set screw groove		0.40%	3.2	Gage
105	Runout of forward outside diameter with outside diameter forward of set screw groove		0.40%	3.2	Gage
106	Rear inside diameter		0.40%	3.2	Gage
107	Runout of rear inside diameter with center inside diameter		0.40%	3.2	Gage
108	Pitch diameter of rear thread		0.40%	3.2	Gage
109	Major diameter of rear thread		0.40%	3.2	Gage
110	Runout of the pitch diameter of the rear of the set screw groove and the forward outside diameter		0.40%	3.2	Gage
111	Overall length		0.40%	3.2	Gage
112	Setscrew groove missing		0.40%	3.2	Gage
113	Pitch diameter of forward inside thread		0.40%	3.2	Gage
114	Minor diameter of forward inside thread		0.40%	3.2	Gage
115	Runout of pitch diameter of forward thread forward outside diameter and undercut of forward thread		0.40%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202610-23T02:45Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET		DRAWING NUMBER
4.4.2.7	Barrel No. 2 (If applicable)		2 OF 2		9311186
					NEXT HIGHER ASSEMBLY 9328601
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Minor					
201	Presence of burrs		0.65%	3.2	Visual
202	Protective finish missing		0.65%	3.2	Visual
203	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-01-28T07:45:22
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-63385A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER 9311196
4.4.2.8	Barrel (If applicable)				NEXT HIGHER ASSEMBLY 9328601
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pitch diameter of rear thread		0.40%	3.2	Gage
102	Major diameter of rear thread		0.40%	3.2	Gage
103	Pitch diameter of forward thread		0.40%	3.2	Gage
104	Major diameter of forward thread		0.40%	3.2	Gage
105	Forward outside diameter		0.40%	3.2	Gage
106	Central outside diameter		0.40%	3.2	Gage
107	Runout of central outside diameter with forward outside diameter		0.40%	3.2	Gage
108	Outside diameter forward of set screw groove (1.510 dimension)		0.40%	3.2	Gage
109	Runout of 1.510 dimension with forward outside diameter		0.40%	3.2	Gage
110	Runout of front thread with forward outside dia.		0.40%	3.2	Gage
111	Runout of rear thread with forward outside diameter and 1.510 dimension		0.40%	3.2	Gage
112	Forward inside diameter		0.40%	3.2	Gage
113	Runout of inside diameter with outside diameter and 1.510 dimension		0.40%	3.2	Gage
114	Runout of forward inside diameter with center inside diameter		0.40%	3.2	Gage
115	Center inside diameter		0.40%	3.2	Gage
116	Runout of center inside diameter with forward outside diameter and 1.510 dimension		0.40%	3.2	Gage
117	Rear inside diameter		0.40%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202610-23T02:45Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-63385A(AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER 9311196
4.4.2.8	Barrel (If applicable)				NEXT HIGHER ASSEMBLY 9328601
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
118	Runout of rear inside diameter with .9465 dimension		0.40%	3.2	Gage
119	Length from aft face to aft end of last inside central step		0.40%	3.2	Gage
120	Length from aft face to forward end of middle inside central step		0.40%	3.2	Gage
121	Inside surface finish improper		0.40%	3.2	Gage
Minor					
201	Protective finish missing		0.65%	3.1	Visual
202	Overall length		0.65%	3.2	Gage
203	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-04-27T02:44:58Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection Tables.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

4.5 Methods of inspection.

PRECAUTION - This specification covers sampling and testing of chemical, toxic or explosive materials which are potentially hazardous to personnel. Accordingly, it is emphasized that all applicable safety rules, regulations and procedures must be followed in handling and processing these materials.

4.5.1 Materials, components and processes. Compliance with all requirements of Section 3 of this specification shall be ascertained by current and continuing examination of inspection and test data to determine that all components (parts, subassemblies, and materials) have been inspected and tested and found to comply with their respective drawing and specification requirements, and that all specified manufacturing processes have been followed.

4.5.1.1 Visual and mechanical inspections. The visual, manual and mechanical inspections and tests shall verify compliance with the requirements of Sections 3 and 5 of this specification in accordance with 4.4.2 herein and Table 1.

4.5.2 Proving ground test. The test area should not be rocky or hard-packed ground surface. The impact area shall use a tarpaulin or canvas covering with the required size and placed centrally two meters from the mortar tube. The Sabot assembly shall be assembled with a production accepted charge cartridge, conditioned a minimum of six (6) hours at the required temperature and test fired within two (2) minutes after removal from the conditioning chamber. Units conditioned at minus 25°F shall utilize charge one and shall be test fired at an elevation of 1416 mils. Units conditioned at plus 70°F and plus 120°F shall utilize charge four and shall be test fired at an elevation of 852 mils. Observation and notation shall be made of the Sabot impact point and of any damage condition.

4.5.2.1 Humidity test. The Sabot assembly (inert loaded) shall be subjected to the required test. Observation shall be made as to whether the flange nut can be readily disassembled and the Sabot can be properly assembled. This test is for information only.

Source: https://assist.dla.mil -- Downloaded: 202640-23T02:45Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging requirements. Packaging shall be as specified on dwg. 9329480.

5.2 Packing and marking. Packing and marking shall be as specified on dwg. 9329481.

6. NOTES

6.1 Intended use. The Sabots covered by this specification are intended for use on the 60MM Mortar Training Device.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection equipment for design approval. See MIL-A-48078. Submit designs as required to Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAT-I, Dover, NJ 07801.

6.4 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research and Development Command (ARRADCOM) may also include drawings prepared by, and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARRADCOM.

6.5 Proving Ground test data. First article and lot acceptance proving ground test data shall be submitted to Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAT-A, Dover, NJ 07801 after each test has been completed.

CUSTODIAN:
Army-AR

PREPARING ACTIVITY:
Army-AR

Project Number: 1315-A433

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:45Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-S-63385A SABOT, 60MM PRACTICE; M3 ASSEMBLING AND PACKING

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:45Z
Check the source to verify that this is the current version before use.