MIL-W-51255C(EA)
17 March 1981
SUPERSEDING
MIL-W-51255B(EA)
13 September 1977

MILITARY SPECIFICATION

WINTERIZATION KIT, CHEMICAL-BIOLOGICAL MASK: M4

This specification is approved for use by US Army Armament Research and Development Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers a chemical-biological mask winterization kit (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

QQ-S-781	-	Strapping, Steel, Flat and Seals.
PPP-B-26	-	Bag, Plastic (General Purpose).
PPP-B-601	-	Boxes, Wood, Cleated-Plywood.
PPP-B-621	-	Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636	-	Boxes, Shipping, Fiberboard.
PPP-F-320	-	Fiberboard, Corrugated and Solid, Sheet Stock (Container Grade), and Cut Shapes.

FSC 4240

: Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed: to: Commander, US Army Armament Research and Development Command, ATTN: DRDAR-TSC-S, Aberdeen Proving Ground, MD 21010 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter. :

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:54Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-1188 - Commercial Packaging of Supplies and Equipment.

DRAWINGS AND TECHNICAL DATA PACKAGE LIST (TDPL)

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

CHEMICAL SYSTEMS LABORATORY

TDPL 5-77-944 - Winterization Kit, Chemical-Biological Mask: M4.

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. All materials shall conform to the applicable specifications listed on Drawing TDPL 5-77-944.

3.2 Stitching. All rows of stitching shall be regular lines free from loose stitches or thread loops. All stitching shall be of continuous thread. All seams shall be backstitched at the ends with two or three stitches.

3.3 Fasteners. The nylon tape fasteners shall function smoothly and efficiently.

3.4 Preproduction. Prior to the start of regular production, a preproduction sample of kits shall be produced in accordance with this specification for examination as specified in 4.3.

3.5 Workmanship. The kit shall be free from damage (cuts, tears, or punctures) and foreign matter (dirt, grease, or oil). Plastic parts shall be clean-cut and free from rough edges.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.

4.1.1 Contractor's responsibility. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:54Z
Check the source to verify that this is the current version before use.

the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to specified requirements.

4.1.2 Objective evidence. The contractor shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5, for which specific inspection has not been provided in this specification have been satisfied.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) Preproduction inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).

4.3 Preproduction inspection.

4.3.1 Sample. A preproduction sample of 15 kits shall be manufactured using the same methods, materials, equipment, and processes as will be used during regular production.

4.3.2 Inspection procedure. The 15 sample kits shall be inspected in accordance with the classification of defects.

4.3.3 Acceptance/rejection criteria. The preproduction sample shall meet the inspection specified in 4.3.2 to be acceptable. The contractor shall obtain written approval from the contracting officer before proceeding with regular production.

4.4 Quality conformance inspection.

4.4.1 Lotting. A lot shall consist of the winterization kits produced by one manufacturer, at one plant, from the same materials, under essentially the same manufacturing conditions, and submitted for acceptance at one time.

4.4.2 Sampling. Sampling shall be conducted in accordance with MIL-STD-105.

4.4.3 Inspection procedure. Sample winterization kits and the level A preparation for delivery shall be inspected in accordance with the classification of defects and MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:54Z
Check the source to verify that this is the current version before use.

4.4.3.1 Classification of defects.

(a) Winterization kit, chemical-biological mask: M4 (Dwg D5-77-944).

Categories		Defects
Critical:		None defined
Major:	AQL 1.0 percent defective	
	101	Stitching (3.2)
	102	Fasteners nonfunctionable (3.3)
	103	Component missing, incorrect, or incomplete
	104	Workmanship (3.5)
	105	Marking missing, inadequate, or incorrect

(b) Packaging (section 5).

Categories		Defects
Critical:		None defined
Major:	AQL 4.0 percent defective	
	101	Package method incorrect
	102	Container incorrect
	103	Filler pads, if required, missing
	104	Quantity incorrect
	105	Marking incorrect, missing, or illegible

5. PACKAGING

5.1 Packaging, level A.

5.1.1 Unit packaging. The cheek flaps shall be folded in toward the center of the kit, and the kit shall then be unit packaged in a bag conforming to PPP-B-26, type II, style 1, film thickness 0.002 inch. The included air volume shall be kept to a minimum by removal of excess air prior to heat sealing the bag. The bag shall be heat sealed in accordance with the bag or material contractor's recommendations for dwell, pressure, and temperature.

5.1.2 Intermediate packaging. Ten kits, unit-packaged as specified in 5.1.1, shall be intermediately packaged in a box conforming to W6c, style RSC of PPP-B-636 and having inside dimensions approximately 4 by 4 by 9 inches.

Source: https://assist.dla.mil -- Downloaded: 20261O-22T20:54Z
Check the source to verify that this is the current version before use.

Filler pads of the same material as the box shall be used as necessary to make a tight pack. The box shall be closed and sealed with tape in accordance with the appendix of the box specification.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. Ten intermediate packages conforming to 5.1.2 (100 kits) shall be packed in a nailed wooden box conforming to class 2, overseas, style 2 of PPP-B-621 or an overseas type, style A, grade A, cleated-plywood box conforming to PPP-B-601 and having inside dimensions approximately 9-1/2 by 8-3/4 by 22 inches. Filler pads of material conforming to W6c of PPP-F-320 shall be used as necessary to make a tight pack. The box shall be closed and strapped in accordance with the appendix to its specification, using strapping and seals conforming to QQ-S-781; the strapping shall be class 1, type I, regular duty, finish B, grade 2, and the seals shall be type D, style I or IV, class R, finish B, grade 2.

5.2.2 Level B. Ten intermediate packages conforming to 5.1.2 (100 kits) shall be packed in a box conforming to V3c, style RSC of PPP-B-636 and having inside dimensions approximately 9-1/2 by 8-3/4 by 22 inches. Filler pads of material conforming to W6c of PPP-F-320 shall be used as necessary to make a tight pack. The box shall be closed and sealed with tape in accordance with the appendix of the box specification.

5.2.3 Commercial packing. Commercial packing shall be in accordance with MIL-STD-1188.

5.3 Marking. In addition to any special marking required by the contract or order, unit packages, intermediate packages, and shipping containers shall be marked in accordance with MIL-STD-129. However, commercial shipping containers (5.2.3) shall be marked in accordance wiht MIL-STD-1188.

6. NOTES

6.1 Intended use. The M4 winterization kit is intended for use with the M17 and M17A1 chemical-biological masks to insure operation of the masks under extremely cold conditions.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Level of packing required (A, B, or commercial).
(c) Preproduction:

(1) Time allowed for contractor submission of samples for Government test and evaluation after award of contract.
(2) Name and address of test facility and shipping instructions when testing is performed by the Government.
(3) Time required for the Government to notify the contractor whether or not to proceed with production.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:54Z
Check the source to verify that this is the current version before use.

Custodian:

Army - EA

Preparing activity:

Army - EA

Project No. 4240-A754

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:54Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-W-5125C

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*	TELEPHONE NO.
	DATE

DD FORM 1426 1 OCT 76 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:54Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Armament Research
and Development Command
ATTN: DRDAR-TSC-S
Aberdeen Proving Ground, MD 21010

FOLD

☆ U.S. GOVERNMENT PRINTING OFFICE 1981—703-023/3150 2-1

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:54Z
Check the source to verify that this is the current version before use.